THE CITY OF TEA TREE GULLY

› Technical Specifications

FENCING

DESCRIPTION: FENCING - FARM RURAL GATE TIMBER POSTS

CODE: FEN24 23/06/2026

APPLICATIONS	
	Regional
	District
	Neighbourhood
	Local
	Main Roads
	Local Roads

PERFORMANCE CRITERIA

durable and weather resistant, safe, provide clear visibility, structural integrity, low maintenance, visually appealing, robust locking mechanism, appropriate size, easy to use



IMAGE/S

Images are indicative of the style, not a specific brand. Council's procurement policy must be followed when selecting and purchasing items.

CITY OF TEA TREE GULLY

MATERIALS	Gate - steel Posts - hardwood timber
FINISHES	Gate - galvanised (unless otherwise specified) Posts - coated with Natural Timber Decking Oil All in-ground posts to be treated with Eco In-Ground Timber Protecta or similar
COLOURS	NA
SIZE (INDICATIVE)	Posts - 100mm round x 2 Gate - DN25 H1200 x W2400-4800mm Gate Wire - 5mm galvanised, 200mm horizontal x 100mm vertical aperture
VARIATIONS	As specified in a design brief
OPTIONS	
INSTALLATION INSTRUCTIONS	Footings - posts - D600 x W 300mm
DDA (Universal design principles)	NA
MAINTENANCE	As required
ENVIRONMENTAL	
EXPECTED LIFESPAN / END OF LIFE REPLACEMENT	Expected lifespan 15-20 years
FURTHER INFORMATION	Fixings: Screw-in 12mm latch and catch Top hinge - through post strap 16mm x 400mm thread length including back plate Bottom hinge - through post gudgeon 16mm x 400mm thread
OTHER INFORMATION	Refer D21/50514
RELEVANT STANDARDS	