THE CITY OF TEA TREE GULLY

› Technical Specifications

FENCING

DESCRIPTION: FENCING - BOLLARD SAFETY (SINGLE)

CODE: FEN32 23/06/2026

APPLICATIONS

Regional	●
District	●
Neighbourhood	●
Local	●
Main Roads	●
Local Roads	●

PERFORMANCE CRITERIA

highly visible, does not obstruct access or create hazards, durable, safe with minimal injury risk, load bearing capacity, low maintenance

IMAGE/S

Images are indicative of the style, not a specific brand. Council's procurement policy must be followed when selecting and purchasing items.



Single Safety Bollard

CITY OF TEA TREE GULLY

MATERIALS	Galvanised Steel (circular hollow section)
FINISHES	Powder coated with Class 1 Red Reflective Tape
COLOURS	Yellow
SIZE (INDICATIVE)	Bollard height - 1600mm (1300mm above ground) Bollard size 90 - 125NB x 3.0mm (specify in RFQ)
VARIATIONS	Bollard Height - 1500mm (900mm above ground) Any other variations as specified in a design brief
OPTIONS	
INSTALLATION INSTRUCTIONS	Footings 1500mm bollard - D 600 x W 450mm Footings 1600mm bollard - D 300 x W 350mm
DDA (Universal design principles)	AS 3845.1
MAINTENANCE	As required
ENVIRONMENTAL	
EXPECTED LIFESPAN / END OF LIFE REPLACEMENT	Expected lifespan 15-20 years
FURTHER INFORMATION	
OTHER INFORMATION	
RELEVANT STANDARDS	