THE CITY OF TEA TREE GULLY

› Technical Specifications

SURFACES

DESCRIPTION: COMPACTED QUARRY RUBBLE

CODE: SUR05 29/10/2024

APPLICATIONS

Regional	●
District	●
Neighbourhood	●
Local	●
Main Roads	●
Local Roads	●

PERFORMANCE CRITERIA	complies to compaction standards, stable surface, suitable for its application, facilitates drainage, reistant to weathering, minimal maintenance, flexibility in design



IMAGE/S

Images are indicative of the style, not a specific brand. Council's procurement policy must be followed when selecting and purchasing items.

MATERIALS	Pathways - compacted quarry rubble Medians / Decorative Areas - compacted quarry sand
FINISHES	
COLOURS	
SIZE (INDICATIVE)	100mm compacted standard compaction to AS 1289.5.4.1:95% (unless otherwise stated by engineer)
VARIATIONS	Non cement based “Soilbond” binder to manufacturers specifications where requied for additional stabilsation Any other variation as specified in a design brief
OPTIONS	Main Roads and Local Streets - general use in medians and verges in and along roads Green Corridors and Local Parks - pathway treatment for secondary footpaths and in seating and picnic areas (path widthe min 1.5m, 2m preferred) Civic Park - for use in the Reconciliation Garden only
INSTALLATION INSTRUCTIONS	Edge restraints on all sides (as determined)
DDA (Universal design principles)	Compliance with Disability Discrimination Act and universal design principles.
MAINTENANCE	Repairs to match exiting as required
ENVIRONMENTAL	NA
EXPECTED LIFESPAN / END OF LIFE REPLACEMENT	50 years
FURTHER INFORMATION	
OTHER INFORMATION	
RELEVANT STANDARDS	