THE CITY OF TEA TREE GULLY

› Technical Specifications

FENCING

DESCRIPTION: FENCING - FARM RURAL GATE STEEL POSTS

CODE: FEN23 23/06/2026

APPLICATIONS

Regional	○
District	●
Neighbourhood	●
Local	●
Main Roads	○
Local Roads	●

PERFORMANCE CRITERIA

durable and weather resistant, safe, provide clear visibility, structural integrity, low maintenance, visually appealing, robust locking mechanism, appropriate size, easy to use



IMAGE/S

Images are indicative of the style, not a specific brand. Council's procurement policy must be followed when selecting and purchasing items.

MATERIALS	Steel
FINISHES	Galvanised (unless otherwise specified)
COLOURS	NA
SIZE (INDICATIVE)	Posts - DN80 x 3.2mm (2 ea) - Circular Hollow Section Gate - DN25 H1200 x W2400-4800mm Gate Wire - 5mm galvanised, 200mm horizontal x 100mm vertical aperture
VARIATIONS	As specified in a design brief
OPTIONS	
INSTALLATION INSTRUCTIONS	Footings - posts - D600 x W 300mm
DDA (Universal design principles)	NA
MAINTENANCE	As required
ENVIRONMENTAL	
EXPECTED LIFESPAN / END OF LIFE REPLACEMENT	Expected lifespan 15-20 years
FURTHER INFORMATION	Fixings: Two part interlocking hinges Long plate gudgeon - fixed pin - bolt on (suit DN32 gate frame) 8mm galvanised chain x 600mm Welded latch and catch
OTHER INFORMATION	Refer D21/50514
RELEVANT STANDARDS	