8 WELLINGTON CT GREENWITH SA 5125

Address:

Click to view a detailed interactive SAILIS in SAILIS

To view a detailed interactive property map in SAPPA click on the map below



Property Zoning Details

Local Variation (TNV)

Concept Plan (81)

Gradient Minimum Frontage (Detached) (Minimum frontage for detached dwellings where the site gradient is less than 1-in-8 is 24m; 1-in-8 to 1-in-4 is 24m; greater than 1-in-4 is 24m)

Gradient Minimum Frontage (Semi-detached) (Minimum frontage for semi-detached dwellings where the site gradient is less than 1-in-8 is 24m; 1-in-8 to 1-in-4 is 24m; greater than 1-in-4 is 24m)

Gradient Minimum Site Area (Detached) (Minimum site area for detached dwellings where the site gradient is less than 1-in-8 is 1860sqm; 1-in-8 to 1-in-4 is 1860sqm; greater than 1-in-4 is 1860sqm)

Gradient Minimum Site Area (Semi-detached) (Minimum site area for semi-detached dwellings where the site gradient is less than 1-in-8 is 1860sqm; 1-in-8 to 1-in-4 is 1860sqm; greater than 1-in-4 is 1860sqm)

Overlay

Affordable Housing

Defence Aviation Area (All structures over 15 metres)

Hazards (Flooding)

Hazards (Bushfire - Urban Interface)

Hazards (Flooding - Evidence Required)

Prescribed Wells Area

Regulated and Significant Tree

Stormwater Management

Urban Tree Canopy

Water Resources

Zone

Hills Neighbourhood

Selected Development(s)

Detached dwelling

This development may be subject to multiple assessment pathways. Please review the document below to determine which pathway may be applicable based on the proposed development compliances to standards.

If no assessment pathway is shown this mean the proposed development will default to performance assessed. Please contact your local council in this instance. Refer to Part 1 - Rules of Interpretation - Determination of Classes of Development

Page 1 of 36 Printed on 22/11/2021

Property Policy Information for above selection

Detached dwelling - Code Assessed - Performance Assessed

Part 2 - Zones and Sub Zones

Hills Neighbourhood Zone

Assessment Provisions (AP)

Desired Outcome DO 1 Development provides a complementary transition to adjacent natural and rural landscapes. Low density housing minimises disturbance to natural landforms and existing vegetation to mitigate the visible extent of buildings, earthworks and retaining walls.

Performance Outcomes (PO) and Deemed to Satisfy (DTS) / Designated Performance Feature (DPF) Criteria

Performance Outcome Deemed-to-Satisfy Criteria / **Designated Performance Feature** Land Use and Intensity PO 1.1 DTS/DPF 1.1 Predominantly low density residential development with Development comprises one or more of the following: complementary non-residential uses compatible with natural Ancillary accommodation (a) landforms and a low density residential character. (b) Consulting room (c) Dwelling (d) Office (e) Open space (f) Shop (g) Recreation area. Site Dimensions and Land Division

PO 2 1

Allotments/sites created for residential purposes are of suitable size and dimension to accommodate residential development that is sensitive to the natural topography and compatible with the housing pattern in the locality.

DTS/DPF 2.1

Development will not result in more than 1 dwelling on an existing allotment

Allotments/sites for residential purposes accord with the following:

site areas (or allotment areas in the case of land division) are not less than the following (average site area per dwelling, including common areas, applies for group dwellings or dwellings within a residential flat building):

Gradient Minimum Site Area (Detached)

Minimum site area for detached dwellings where the site gradient is less than 1-in-8 is 1860sqm; 1-in-8 to 1-in-4 is 1860sqm; greater than 1-in-4 is 1860sqm

Page 2 of 36 Printed on 22/11/2021

Gradient Minimum Site Area (Semi-detached)

Minimum site area for semi-detached dwellings where the site gradient is less than 1-in-8 is 1860sqm; 1-in-8 to 1-in-4 is 1860sqm; greater than 1-in-4 is 1860sqm

and

(b) site frontages (or allotment frontages in the case of land division) are not less than:

Gradient Minimum Frontage (Detached)

Minimum frontage for detached dwellings where the site gradient is less than 1-in-8 is 24m; 1-in-8 to 1-in-4 is 24m; greater than 1-in-4 is 24m

Gradient Minimum Frontage (Semi-detached)

Minimum frontage for semi-detached dwellings where the site gradient is less than 1-in-8 is 24m; 1-in-8 to 1-in-4 is 24m; greater than 1-in-4 is 24m

In relation to DTS/DPF 2.1, in instances where:

- (c) more than one value is returned in the same field, refer to the relevant Technical and Numeric Variation layer in the SA planning database to determine the applicable value relevant to the site of the proposed development
- (d) no value is returned in DTS/DPF 2.1(a) or (b) (i.e. there is a blank field or the relevant dwelling type is not listed), then none are applicable and the relevant development cannot be classified as deemed-to-satisfy.

PO 2.2

Development creating new allotments/sites in conjunction with retention of an existing dwelling ensures the site of the existing dwelling remains fit for purpose.

DTS/DPF 2.2

Where the site of a dwelling does not comprise an entire allotment:

- (a) The balance of the allotment accords with site area and frontage requirements specified in DTS/DPF 2.1
- (b) If there is an existing dwelling on the allotment that will remain on the allotment after completion of the development it will not contravene:
 - (i) Private open space requirements specified in Design in Urban Areas Table 1 - Private Open Space
 - (ii) Car parking requirements specified in Transport, Access and Parking Table 1 - General Off-Street Car Parking Requirements or Table 2 - Off-Street Car Parking Requirements in Designated Areas to the nearest whole number.

Site coverage

PO 3.1

Building footprints consistent with the character and pattern of a low-density suburban neighbourhood and provide sufficient space around buildings to limit visual impact, provide an attractive outlook and access to light and ventilation.

DTS/DPF 3.1

The development does not result in site coverage exceeding:

- (a) On sites with a gradient more than 1-in-8, 40%
- (b) On sites with a gradient less than 1-in-8, 50%.

Building Height

PO 4.1 DTS/DPF 4.1

Page 3 of 36 Printed on 22/11/2021

Buildings contribute to a low-rise suburban character and complement the height of nearby buildings.

Building height (excluding garages, carports and outbuildings) is no greater than:

- (a) the following:
- (b) in all other cases (i.e. there are blank fields for both maximum building height (metres) and maximum building height (levels)) - 2 building levels up to a height of 9m.

In relation to DTS/DPF 4.1, in instances where:

- (c) more than one value is returned in the same field, refer to the Maximum building Height (Levels) Technical and Numeric Variation layer or Maximum Building Height (Meters) Technical and Numeric Variation layer in the SA planning database to determine the applicable value relevant to the site of the proposed development.
- (d) only one value is returned for DTS/DPF 4.1(a) (i.e. there is one blank field), then the relevant height in metres or building levels applies with no criteria for the other.

Primary Street Setback

PO 5.1

Buildings are set back from primary street boundaries consistent with the existing streetscape.

DTS/DPF 5.1

The building line of a building set back from the primary street boundary:

- (a) at least the average setback to the building line of existing buildings on adjoining sites which face the same primary street (including those buildings that would adjoin the site if not separated by a public road or a vacant allotment)
- (b) where there is only one existing building on adjoining sites which face the same primary street (including those that would adjoin if not separated by a public road or a vacant allotment), not less than the setback to the building line of that building

or

(c) not less than 8m where no building exists on an adjoining site with the same primary street frontage.

Secondary Street Setback

PO 6.1

Buildings are set back from secondary street boundaries to maintain a pattern of separation between buildings and public streets and reinforce streetscape character.

DTS/DPF 6.1

Building walls are set back from the boundary of the allotment with a secondary street frontage:

- (a) no less than:
 - (i) on sites with a site gradient greater than 1-in-8: 1900mm
 - (ii) on sites with a site gradient less than 1-in-8: at least 900mm

or

(b) if a dwelling on any adjoining allotment is closer to the secondary street, the distance of that dwelling from the boundary with the secondary street

(being, if relevant, the lesser of the 2 distances).

Boundary Walls

PO 7.1

Boundary walls are limited in height and length to manage impacts

DTS/DPF 7.1

Except where the dwelling is located on a central site within a row

Page 4 of 36 Printed on 22/11/2021

on adjoining properties. dwelling or terrace arrangement, side boundary walls occur on only one side boundary and satisfy (a) or (b) below: side boundary walls adjoin or abut a boundary wall of a building on adjoining land for the same or lesser length and height (b) side boundary walls do not: (i) exceed 3.2m in height from the lower of the natural or finished ground level (ii) exceed 8m in length (iii) when combined with other walls on the boundary of the subject development site, exceed a maximum 45% of the length of the boundary (iv) encroach within 3m of any other existing or proposed boundary walls on the subject land. PO 7.2 DTS/DPF 7.2 Dwellings in a semi-detached, row or terrace arrangement maintain Dwelling walls in a semi-detached, row or terrace arrangement are space between buildings consistent with a low density suburban set back from side boundaries shared with allotments outside the streetscape character. development site at least the minimum distance identified in DTS/DPF 8.1. Side Boundary Setback PO 8.1 DTS/DPF 8 1 Buildings are set back from side boundaries to provide: Building walls not sited on side boundaries set back from the side boundary at least: (a) separation between dwellings in a way that complements the established character of the locality on sites with a site gradient greater than 1-in-8: (b) access to natural light and ventilation for neighbours. Other than a wall facing a southern boundary, 1900mm (ii) For walls facing a southern boundary, at least 1900mm plus 1/3 of the wall height above 3m measured from the top of the footings (b) on sites with a site gradient less than 1-in-8, and other than walls located on a side boundary: at least 900mm where the wall is up to 3m measured from the top of the footings other than for a wall facing a southern side boundary, at least 900mm plus 1/3 of the wall height above 3m measured from the top of the footings for walls facing a southern side boundary, at least 1900mm plus 1/3 of the wall height above 3m measured from the top of the footings. Rear Boundary Setback PO 9.1 DTS/DPF 9.1 Buildings are set back from rear boundaries to provide: Buildings are set back from the rear boundary at least: (a) separation between dwellings in a way that complements (a) 4m for the first building level the established character of the locality (b) 6m for any second building level. (b) access to natural light and ventilation for neighbours (c) private open space

Page 5 of 36 Printed on 22/11/2021

(d) space for landscaping and vegetation.

Policy24 - Enquiry			
	Built Form and Character		
PO 10.1		DTS/DPF 10.1	
Development that would be prominently visible from the Adelaide plains or urban areas within regional cities and townships:		None are applicable.	
(a)	achieves a profile that blends with the topography of the land		
(b)	avoids the use of bright and highly reflective external materials and finishes		
(c)	incorporates existing vegetation wherever possible and additional landscaping to assist in reducing the apparent bulk and scale.		
PO 10.2		DTS/DPF 10.2	
Development of more than 1 building level in height takes account of its height and bulk relative to adjoining dwellings by:		None are applicable.	
(a)	incorporating stepping in the design in accordance with the slope of the land		
(b)	where appropriate, setting back the upper level a greater distance from front and side boundaries than the lower level.		
	Earthworks and retaining		
PO 11.1		DTS/DPF 11.1	
topogra	s sited and designed to integrate with the natural phy of the land using measures such as split level building ction and other approaches that minimise the extent of cut	None are applicable.	
PO 11.2		DTS/DPF 11.2	
Vegetat view.	ion is used to screen buildings and excavation or filling from	None are applicable.	
-			

Table 5 - Procedural Matters (PM) - Notification

The following table identifies, pursuant to section 107(6) of the *Planning, Development and Infrastructure Act 2016*, classes of performance assessed development that are excluded from notification. The table also identifies any exemptions to the placement of notices when notification is required.

Interpretation

A class of development listed in Column A is excluded from notification provided that it does not fall within a corresponding exclusion prescribed in Column B. In instances where development falls within multiple classes within Column A, each clause is to be read independently such that if a development is excluded from notification by any clause, it is, for the purposes of notification excluded irrespective of any other clause.

Class of Development (Column A)	Exceptions (Column B)
A kind of development which, in the opinion of the relevant authority, is of a minor nature only and will not unreasonably impact on the owners or occupiers of land in the locality of the site of the development	None specified.

Page 6 of 36 Printed on 22/11/2021

- 2. All development undertaken by:
 - (a) the South Australian Housing Trust either individually or jointly with other persons or hodies

or

(b) a provider registered under the Community Housing National Law participating in a program relating to the renewal of housing endorsed by the South Australian Housing Trust. Except development involving any of the following:

- 1. residential flat building(s) of 3 or more building levels
- 2. the demolition of a State or Local Heritage Place
- 3. the demolition of a building (except an ancillary building) in a Historic Area Overlay.
- 3. Any development involving any of the following (or of any combination of any of the following):
 - (a) air handling unit, air conditioning system or exhaust fan
 - (b) ancillary accommodation
 - (c) building work on railway land
 - (d) carport
 - (e) deck
 - (f) dwelling
 - (g) dwelling addition
 - (h) fence
 - (i) outbuilding
 - (j) pergola
 - (k) private bushfire shelter
 - (I) residential flat building
 - (m) shade sail
 - (n) solar photovoltaic panels (roof mounted)
 - (o) swimming poor or spa pool
 - (p) verandah
 - (q) water tank.

Except development that:

- exceeds the maximum building height specified in Hills Neighbourhood Zone DTS/DPF 4.1
- involves a building wall (or structure) that is proposed to be situated on a side boundary (not being a boundary with a primary street or secondary street) and:
 - (a) the length of the proposed wall (or structure) exceeds 8m (other than where the proposed wall abuts an existing wall or structure of greater length on the adjoining allotment)
 - (b) the height of the proposed wall (or post height) exceeds 3.2m measured from the lower of the natural or finished ground level (other than where the proposed wall abuts an existing wall or structure of greater height on the adjoining allotment).

- 4. Any development involving any of the following (or of any combination of any of the following):
 - (a) consulting room
 - (b) office
 - (c) shop.

Except development that:

- exceeds the maximum building height specified in Hills Neighbourhood Zone DTS/DPF 4.1
- does not satisfy any Hills Neighbourhood Zone DTS/DPF
 1.2
 or
- involves a building wall (or structure) that is proposed to be situated on a side boundary (not being a boundary with a primary street or secondary street) and:
 - (a) the length of the proposed wall (or structure) exceeds 8m (other than where the proposed wall abuts an existing wall or structure of greater length on the adjoining allotment)
 - (b) the height of the proposed wall (or post height) exceeds 3.2m measured from the lower of the natural or finished ground level (other than where the proposed wall abuts an existing wall or structure of greater height on the adjoining allotment).

Page 7 of 36 Printed on 22/11/2021

-		
5.	Any development involving any of the following (or of any combination of any of the following):	None specified.
	(a) internal building works	
	(b) land division	
	(c) recreation area	
	(d) replacement building	
	(e) temporary accommodation in an area affected by bushfire	
	(f) tree damaging activity.	
6.	Demolition.	Except any of the following:
		the demolition of a State or Local Heritage Place
		 the demolition of a building (except an ancillary building) in a Historic Area Overlay.
7.	Retaining wall.	Except retaining wall that does not satisfy Hills Neighbourhood Zone DTS/DPF 11.3.

Placement of Notices - Exemptions for Performance Assessed Development

None specified.

Placement of Notices - Exemptions for Restricted Development

None specified.

Part 3 - Overlays

Affordable Housing Overlay

Assessment Provisions (AP)

Desired Outcome		
DO 1	Affordable housing is integrated with residential and mixed use development.	
DO 2	Affordable housing caters for a variety of household structures.	

Performance Outcomes (PO) and Deemed-to-Satisfy (DTS) Criteria / Designated Performance Feature (DPF)

Performance Outcome	Deemed-to-Satisfy Criteria / Designated Performance Feature
Land	Division
PO 1.1	DTS/DPF 1.1
Development comprising 20 or more dwellings / allotments incorporates affordable housing.	Development results in 0-19 additional allotments / dwellings.

Page 8 of 36 Printed on 22/11/2021

PO 1.2 DTS/DPF 1.2 Development comprising 20 or more dwellings or residential Development comprising 20 or more dwellings / or residential allotments provides housing suited to a range of incomes including allotments includes a minimum of 15% affordable housing except households with low to moderate incomes. where: (a) it can be demonstrated that any shortfall in affordable housing has been provided in a previous stage of development or (b) it can be demonstrated that any shortfall in affordable housing will be accommodated in a subsequent stage or stages of development. PO 1.3 DTS/DPF 1.3 Affordable housing is distributed throughout the development to None are applicable. avoid an overconcentration. **Built Form and Character** PO 2.1 DTS/DPF 2.1 Affordable housing is designed to complement the design and None are applicable. character of residential development within the locality. Affordable Housing Incentives DTS/DPF 3.1 PO 3.1 The minimum site area specified for a dwelling can be reduced by To support the provision of affordable housing, minimum allotment up to 20%, or the maximum density per hectare increased by up to sizes may be reduced below the minimum allotment size specified 20%, where it is to be used to accommodate affordable housing in a zone while providing allotments of a suitable size and dimension except where the development is located within the Character Area to accommodate dwellings with a high standard of occupant Overlay or Historic Area Overlay. amenity. PO 3.2 DTS/DPF 3.2 To support the provision of affordable housing, building heights may Where a building incorporates dwellings above ground level and be increased above the maximum specified in a zone. includes at least 15% affordable housing, the maximum building height specified in any relevant zone policy can be increased by 1 building level in the: (a) Business Neighbourhood Zone (b) City Living Zone (c) Established Neighbourhood Zone (d) General Neighbourhood Zone (e) Hills Neighbourhood Zone (f) Housing Diversity Neighbourhood Zone (g) Neighbourhood Zone (h) Master Planned Neighbourhood Zone (i) Master Planned Renewal Zone (j) Master Planned Township Zone (k) Rural Neighbourhood Zone (I) Suburban Business Zone (m) Suburban Neighbourhood Zone (n) Township Neighbourhood Zone (o) Township Zone (p) Urban Renewal Neighbourhood Zone (q) Waterfront Neighbourhood Zone

Page 9 of 36 Printed on 22/11/2021

and up to 30% in any other zone, except where:

- the development is located within the Character Area Overlay or Historic Area Overlay or
- (b) other height incentives already apply to the development.

Movement and Car Parking

PO 4.1

Sufficient car parking is provided to meet the needs of occupants of affordable housing.

DTS/DPF 4 1

Dwellings constituting affordable housing are provided with car parking in accordance with the following:

- (a) 0.3 carparks per dwelling within a building which incorporates dwellings located above ground level within either:
 - 200 metres of any section of road reserve along which a bus service operates as a high frequency public transit service⁽²⁾
 - (ii) is within 400 metres of a bus interchange⁽¹⁾
 - (iii) is within 400 metres of an O-Bahn interchange⁽¹⁾
 - (iv) is within 400 metres of a passenger rail station⁽¹⁾
 - (v) is within 400 metres of a passenger tram station⁽¹⁾
 - (vi) is within 400 metres of the Adelaide Parklands.

or

(b) 1 carpark per dwelling for any other dwelling.

[NOTE(S): (1) Measured from an area that contains any platform(s), shelter(s) or stop(s) where people congregate for the purpose waiting to board a bus, tram or train, but does not include areas used for the parking of vehicles. (2) A high frequency public transit service is a route serviced every 15 minutes between 7.30am and 6.30pm Monday to Friday and every 30 minutes at night, Saturday, Sunday and public holidays until 10pm.]

Procedural Matters (PM) - Referrals

The following table identifies classes of development / activities that require referral in this Overlay and the applicable referral body. It sets out the purpose of the referral as well as the relevant statutory reference from Schedule 9 of the Planning, Development and Infrastructure (General) Regulations 2017.

Class of Development / Activity	Referral Body	Purpose of Referral	Statutory Reference
Development for the purposes of the provision of affordable housing (applying the criteria determined under regulation 4 of the South Australian Housing Trust Regulations 2010).	Minister responsible for administering the South Australian Housing Trust Act 1995.	To provide direction on the conditions required to secure the provision of dwellings or allotments for affordable housing.	Development of a class to which Schedule 9 clause 3 item 20 of the Planning, Development and Infrastructure (General)

Page 10 of 36 Printed on 22/11/2021

	Regulations
	2017 applies.

Defence Aviation Area Overlay

Assessment Provisions (AP)

	Desired Outcome
DO 1	Management of potential impacts of buildings on the operational and safety requirements of Defence Aviation Areas.

Performance Outcomes (PO) and Deemed-to-Satisfy (DTS) Criteria / Designated Performance Feature (DPF)

Performance Outcome	Deemed-to-Satisfy Criteria / Designated Performance Feature
Built Form	
PO 1.1	DTS/DPF 1.1
Building height does not pose a hazard to the operations of Defence Aviation Areas.	Building height does not exceed the relevant height specified by the Defence Aviation Area Overlay.

Procedural Matters (PM) - Referrals

The following table identifies classes of development / activities that require referral in this Overlay and the applicable referral body. It sets out the purpose of the referral as well as the relevant statutory reference from Schedule 9 of the Planning, Development and Infrastructure (General) Regulations 2017.

Class of Development / Activity	Referral Body	Purpose of Referral	Statutory Reference
None	None	None	None

Hazards (Flooding) Overlay

Assessment Provisions (AP)

Desired Outcome		
DO 1	Impacts on people, property, infrastructure and the environment from high flood risk are minimised by retaining areas free from development, and minimising intensification where development has occurred.	

Performance Outcomes (PO) and Deemed-to-Satisfy (DTS) Criteria / Designated Performance Feature (DPF)

Performance Outcome	Deemed-to-Satisfy Criteria / Designated Performance Feature
Flood Re	esilience

Page 11 of 36 Printed on 22/11/2021

Policy24 - Eriquity			
PO 3.1	DTS/DPF 3.1		
Development avoids the need for flood protection works.	None are applicable.		
PO 3.2	DTS/DPF 3.2		
Development does not cause unacceptable impacts on any adjoining property by the diversion of flood waters or an increase in flood velocity or flood level.	None are applicable.		
PO 3.3	DTS/DPF 3.3		
Development does not impede the flow of floodwaters through the allotment or the surrounding land, or cause an unacceptable loss of flood storage.	None are applicable.		
PO 3.4	DTS/DPF 3.4		
Development avoids frequently flooded or high velocity areas, other than where it is part of a flood mitigation scheme to reduce flood impact.	Other than a recreation area, development is located outside of the 5% AEP principal flow path.		
PO 3.5	DTS/DPF 3.5		
Buildings are sited, designed and constructed to prevent the entry of floodwaters in a 1% AEP flood event where the entry of floodwaters is likely to result in undue damage to, or compromise ongoing activities within, buildings.	Buildings comprise one of the following: (a) a porch or portico with at least 2 open sides (b) a verandah with at least 3 open sides (c) a carport or outbuilding with at least 2 open sides (whichever elevations face the direction of the flow) (d) any post construction with open sides (e) a building with a finished floor level that is at least 300mm above the height of a 1% AEP flood event.		
Environmen	tal Protection		
PO 4.2	DTS/DPF 4.2		
Development does not create or aggravate the potential for erosion or siltation or lead to the destruction of vegetation during a flood.	None are applicable.		
Site Ea	rthworks		
PO 5.1	DTS/DPF 5.1		
The depth and extent of filling required to raise the finished floor level of a building does not cause unacceptable impact on any adjoining property by diversion of flood waters, an increase in flood velocity or flood level, or an unacceptable loss of flood storage.	None are applicable.		
PO 5.2	DTS/DPF 5.2		
Driveways, access tracks and parking areas are designed and constructed to minimise excavation and filling.	Filling for ancillary purposes: (a) does not exceed 300mm above existing ground level (b) is no more than 5m wide.		
Acc	cess		
PO 6.1	DTS/DPF 6.1		
Development does not occur on land:	None are applicable.		

Page 12 of 36 Printed on 22/11/2021

(a)	from which evacuation to areas not vulnerable to flood risk is not possible during a 1% AEP flood event	
(b)	which cannot be accessed by emergency services vehicles or essential utility service vehicles during a 1% AEP flood event.	
PO 6.2		DTS/DPF 6.2
dwelling	driveways and tracks to significant development (i.e. gs, places of work, etc.) consist of a safe, all-weather ble surface that is accessible during a 1% AEP flood event.	None are applicable.

Procedural Matters (PM) - Referrals

The following table identifies classes of development / activities that require referral in this Overlay and the applicable referral body. It sets out the purpose of the referral as well as the relevant statutory reference from Schedule 9 of the Planning, Development and Infrastructure (General) Regulations 2017.

Class of Development / Activity	Referral Body		Statutory Reference
None	None	None	None

Hazards (Flooding - Evidence Required) Overlay

Assessment Provisions (AP)

Desired Outcome
Development adopts a precautionary approach to mitigate potential impacts on people, property, infrastructure and the environment from potential flood risk through the appropriate siting and design of development.

Performance Outcomes (PO) and Deemed-to-Satisfy (DTS) Criteria / Designated Performance Feature (DPF)

Performance Outcome	Deemed-to-Satisfy Criteria / Designated Performance Feature	
Flood R	esilience	
PO 1.1 Development is sited, designed and constructed to minimise the risk of entry of potential floodwaters where the entry of flood waters is likely to result in undue damage to or compromise ongoing activities within buildings.	DTS/DPF 1.1 Habitable buildings, commercial and industrial buildings, and buildings used for animal keeping incorporate a finished floor level at least 300mm above: (a) the highest point of top of kerb of the primary street or (b) the highest point of natural ground level at the primary street boundary where there is no kerb	

Procedural Matters (PM) - Referrals

The following table identifies classes of development / activities that require referral in this Overlay and the applicable referral body. It sets out the purpose of the referral as well as the relevant statutory reference from Schedule 9 of the Planning, Development and Infrastructure (General) Regulations 2017.

Page 13 of 36 Printed on 22/11/2021

Class of Development / Activity	Referral Body	Purpose of Referral	Statutory Reference
None	None	None	None

Stormwater Management Overlay

Assessment Provisions (AP)

	Desired Outcome
DO 1	Development incorporates water sensitive urban design techniques to capture and re-use stormwater.

Performance Outcome				isfy Criteri erformanc ure	
PO 1.1	DTS/DPF 1.1	1			
Residential development is designed to capture and re-use stormwater to:		ngs, or less	s than 5 group o	detached, semi-detach Iwellings or dwellings w	
(a) maximise conservation of water resources	(a) in	oludos rai	nwatar tank ata	rago:	
 (b) manage peak stormwater runoff flows and volume to ensure the carrying capacities of downstream systems ar 			nwater tank stor nnected to at lea	-	
not overloaded (c) manage stormwater runoff quality.		F	in relation a battle-a detached of the roo	to a detached dwelling xe arrangement), semi- dwelling or row dwelling f area	g, 60%
		E	3. in all othe	er cases, 80% of the roo	of area
		out		r a toilet, laundry cold v r service for sites less tl	
		(iii) cor wa	nnected to one t	coilet and either the laur t water service for sites	•
			h a minimum to ble 1	tal capacity in accordar	nce with
		dia		required, includes a 20 ase orifice at the botton ent of the tank	
	(b) incorporates dwelling roof area comprising at least 80% of the site's impervious area				
	Table 1: Rainwater Tank				
	5	Site size	Minimum retention volume (Litres)	Minimum detention volume (Litres)	
	<	<200	1000	1000	

Page 14 of 36 Printed on 22/11/2021

2	2000	Site perviousness <30%: 1000
		Site perviousness ≥30%: N/A
4	4000	Site perviousness <35%: 1000
		Site perviousness ≥35%: N/A

Procedural Matters (PM) - Referrals

The following table identifies classes of development / activities that require referral in this Overlay and the applicable referral body. It sets out the purpose of the referral as well as the relevant statutory reference from Schedule 9 of the Planning, Development and Infrastructure (General) Regulations 2017.

Class of Development / Activity	Referral Body	Purpose of Referral	Statutory Reference
None	None	None	None

Urban Tree Canopy Overlay

Assessment Provisions (AP)

	Desired Outcome
DO 1	Residential development preserves and enhances urban tree canopy through the planting of new trees and retention of existing mature trees where practicable.

Performance Outcome	Deemed-to-Satisfy Criteria / Designated Performance Feature			
PO 1.1	DTS/DPF 1.1			
Trees are planted or retained to contribute to an urban tree canopy.	Tree planting is provided in accordance with the following:			
	Site size per dwelling (m ²)	Tree size* and number required per dwelling		
	<450	1 small tree		
	450-800	1 medium tree or 2 small trees		
	>800	1 large tree or 2 medium trees or 4 small trees		
	*refer Table 1 Tree Size			

Page 15 of 36 Printed on 22/11/2021

Table 1 Tree Size			
Tree size	Mature height (minimum)	Mature spread (minimum)	Soil area around tree within development site (minimum)
Small	4 m	2m	10m ² and min. dimension of 1.5m
Medium	6 m	4 m	30m ² and min. dimension of 2m
Large	12 m	8m	60m ² and min. dimension of 4m

The discount in Column D of Table 2 discounts the number of trees required to be planted in DTS/DPF 1.1 where existing tree(s) are retained on the subject land that meet the criteria in Columns A, B and C of Table 2, and are not a species identified in Regulation 3F(4)(b) of the Planning Development and Infrastructure (General) Regulations 2017.

Table 2 Tree Discounts			
Retained tree height (Column A)	Retained tree spread (Column B)	Retained soil area around tree within development site (Column C)	Discount applied (Column D)
4-6m	2-4m	10m ² and min. dimension of 1.5m	2 small trees (or 1 medium tree)
6-12m	4-8m	30m ² and min. dimension of 3m	2 medium trees (or 4 small trees)
>12m	>8m	60m ² and min. dimension of 6m	2 large trees (or 4 medium trees, or 8 small trees)

Note: In order to satisfy DTS/DPF 1.1, payment may be made in accordance with a relevant off-set scheme established by the Minister under section 197 of the Planning, Development and Infrastructure Act 2016, provided the provisions and requirements of that scheme are satisfied. For the purposes of section 102(4) of

Page 16 of 36 Printed on 22/11/2021

the Planning, Development and Infrastructure Act 2016, an
applicant may elect for any of the matters in DTS/DPF 1.1 to be
reserved.

Procedural Matters (PM) - Referrals

The following table identifies classes of development / activities that require referral in this Overlay and the applicable referral body. It sets out the purpose of the referral as well as the relevant statutory reference from Schedule 9 of the Planning, Development and Infrastructure (General) Regulations 2017.

Class of Development / Activity	Referral Body	Purpose of Referral	Statutory Reference
None	None	None	None

Water Resources Overlay

Assessment Provisions (AP)

	Desired Outcome
DO 1	Protection of the quality of surface waters considering adverse water quality impacts associated with projected reductions in rainfall and warmer air temperatures as a result of climate change.
DO 2	Maintain the conveyance function and natural flow paths of watercourses to assist in the management of flood waters and stormwater runoff.

Performance Outcomes (PO) and Deemed-to-Satisfy (DTS) Criteria / Designated Performance Feature (DPF)

Performance Outcome	Deemed-to-Satisfy Criteria / Designated Performance Feature
Water C	atchment
PO 1.1	DTS/DPF 1.1
Watercourses and their beds, banks, wetlands and floodplains (1% AEP flood extent) are not damaged or modified and are retained in their natural state, except where modification is required for essential access or maintenance purposes.	None are applicable.
PO 1.2	DTS/DPF 1.2
Development avoids interfering with the existing hydrology or water regime of swamps and wetlands other than to improve the existing conditions to enhance environmental values.	None are applicable.
PO 1.5	DTS/DPF 1.5
Development that increases surface water run-off includes a suitably sized strip of vegetated land on each side of a watercourse to filter runoff to:	A strip of land 20m or more wide measured from the top of existing banks on each side of the watercourse is free from development, livestock use and revegetated with locally indigenous vegetation.
(a) reduce the impacts on native aquatic ecosystems (b) minimise soil loss eroding into the watercourse.	

Page 17 of 36 Printed on 22/11/2021

PO 1.6	DTS/DPF 1.6
Development resulting in the depositing or placing of an object or solid material in a watercourse or lake occurs only where it involves any of the following:	None are applicable.
(a) the construction of an erosion control structure	
(b) devices or structures used to extract or regulate water flowing in a watercourse	
(c) devices used for scientific purposes	
(d) the rehabilitation of watercourses.	
PO 1.7	DTS/DPF 1.7
Watercourses, floodplains (1% AEP flood extent) and wetlands protected and enhanced by retaining and protecting existing native vegetation.	None are applicable.
PO 1.8	DTS/DPF 1.8
Watercourses, floodplains (1% AEP flood extent) and wetlands are protected and enhanced by stabilising watercourse banks and reducing sediments and nutrients entering the watercourse.	None are applicable.

Procedural Matters (PM) - Referrals

The following table identifies classes of development / activities that require referral in this Overlay and the applicable referral body. It sets out the purpose of the referral as well as the relevant statutory reference from Schedule 9 of the Planning, Development and Infrastructure (General) Regulations 2017.

Class of Development / Activity	Referral Body	Purpose of Referral	Statutory Reference
None	None	None	None

Part 4 - General Development Policies

Clearance from Overhead Powerlines

Assessment Provisions (AP)

	Desired Outcome
DO 1	Protection of human health and safety when undertaking development in the vicinity of overhead transmission powerlines.

Performance Outcome	Deemed-to-Satisfy Criteria / Designated Performance Feature
PO 1.1	DTS/DPF 1.1
Buildings are adequately separated from aboveground powerlines to minimise potential hazard to people and property.	One of the following is satisfied: (a) a declaration is provided by or on behalf of the applicant to

Page 18 of 36 Printed on 22/11/2021

Design in Urban Areas

Assessment Provisions (AP)

		Desired Outcome
DO 1	Develo	pment is:
	(a)	contextual - by considering, recognising and carefully responding to its natural surroundings or built environment and positively contributing to the character of the locality
	(b)	durable - fit for purpose, adaptable and long lasting
	(c)	inclusive - by integrating landscape design to optimise pedestrian and cyclist usability, privacy and equitable access and promoting the provision of quality spaces integrated with the public realm that can be used for access and recreation and help optimise security and safety both internally and within the public realm, for occupants and visitors
	(d)	sustainable - by integrating sustainable techniques into the design and siting of development and landscaping to improve community health, urban heat, water management, environmental performance, biodiversity and local amenity and to minimise energy consumption.

Performance Outcome

Deemed-to-Satisfy Criteria / Designated Performance Feature

All Development

On-site Waste Treatment Systems

PO 6.1

Dedicated on-site effluent disposal areas do not include any areas to be used for, or could be reasonably foreseen to be used for, private open space, driveways or car parking.

DTS/DPF 6.1

Effluent disposal drainage areas do not:

- encroach within an area used as private open space or result in less private open space than that specified in Design in Urban Areas Table 1 - Private Open Space
- (b) use an area also used as a driveway
- (c) encroach within an area used for on-site car parking or result in less on-site car parking than that specified in Transport, Access and Parking Table 1 - General Off-Street Car Parking Requirements or Table 2 - Off-Street Car Parking Requirements in Designated Areas.

Earthworks and sloping land

PO 8.1

Development, including any associated driveways and access tracks, minimises the need for earthworks to limit disturbance to natural topography.

DTS/DPF 8.1

Development does not involve any of the following:

- (a) excavation exceeding a vertical height of 1m
- (b) filling exceeding a vertical height of 1m
- (c) a total combined excavation and filling vertical height of 2m or more.

Page 19 of 36 Printed on 22/11/2021

Policy24 - Enquiry	
PO 8.2	DTS/DPF 8.2
Driveways and access tracks designed and constructed to allow safe and convenient access on sloping land.	Driveways and access tracks on sloping land (with a gradient exceeding 1 in 8) satisfy (a) and (b): (a) do not have a gradient exceeding 25% (1-in-4) at any point along the driveway (b) are constructed with an all-weather trafficable surface.
PO 8.3	DTS/DPF 8.3
Driveways and access tracks on sloping land (with a gradient exceeding 1 in 8):	None are applicable.
 (a) do not contribute to the instability of embankments and cuttings (b) provide level transition areas for the safe movement of 	
people and goods to and from the development (c) are designed to integrate with the natural topography of the land.	
PO 8.4	DTS/DPF 8.4
Development on sloping land (with a gradient exceeding 1 in 8) avoids the alteration of natural drainage lines and includes on site drainage systems to minimise erosion.	None are applicable.
PO 8.5	DTS/DPF 8.5
Development does not occur on land at risk of landslip or increase the potential for landslip or land surface instability.	None are applicable.
Overlooking / Visual Pr	ivacy (low rise buildings)
PO 10.1 Development mitigates direct overlooking from upper level windows to habitable rooms and private open spaces of adjoining residential uses in neighbourhood-type zones.	DTS/DPF 10.1 Upper level windows facing side or rear boundaries shared with a residential use in a neighbourhood-type zone: (a) are permanently obscured to a height of 1.5m above finished floor level and are fixed or not capable of being opened more than 125mm (b) have sill heights greater than or equal to 1.5m above finished floor level (c) incorporate screening with a maximum of 25% openings, permanently fixed no more than 500mm from the window surface and sited adjacent to any part of the window less than 1.5 m above the finished floor level.
PO 10.2 Development mitigates direct overlooking from balconies to habitable rooms and private open space of adjoining residential uses in neighbourhood type zones.	DTS/DPF 10.2 One of the following is satisfied: (a) the longest side of the balcony or terrace will face a public road, public road reserve or public reserve that is at least 15m wide in all places faced by the balcony or terrace or (b) all sides of balconies or terraces on upper building levels are permanently obscured by screening with a maximum 25% transparency/openings fixed to a minimum height of:

Page 20 of 36 Printed on 22/11/2021

(ii) 1.7m above finished floor level in all other cases

Policy24 - Enquiry	
All residentia	al development
Front elevations and	d passive surveillance
PO 17.1	DTS/DPF 17.1
Dwellings incorporate windows facing primary street frontages to encourage passive surveillance and make a positive contribution to	Each dwelling with a frontage to a public street:
the streetscape.	includes at least one window facing the primary street from a habitable room that has a minimum internal room dimension of 2.4m
	(b) has an aggregate window area of at least 2m ² facing the primary street.
PO 17.2	DTS/DPF 17.2
Dwellings incorporate entry doors within street frontages to address the street and provide a legible entry point for visitors.	Dwellings with a frontage to a public street have an entry door visible from the primary street boundary.
Outlook a	and Amenity
PO 18.1	DTS/DPF 18.1
Living rooms have an external outlook to provide a high standard of amenity for occupants.	A living room of a dwelling incorporates a window with an external outlook of the street frontage, private open space, public open space, or waterfront areas.
Residential Deve	lopment - Low Rise
External a	appearance
PO 20.1	DTS/DPF 20.1
Garaging is designed to not detract from the streetscape or appearance of a dwelling.	Garages and carports facing a street:
	(a) are situated so that no part of the garage or carport will be in front of any part of the building line of the dwelling
	(b) are set back at least 5.5m from the boundary of the primary street
	(c) have a garage door / opening width not exceeding 7m
	(d) have a garage door / opening width not exceeding 50% of the site frontage unless the dwelling has two or more building levels at the building line fronting the same public street.
PO 20.2	DTS/DPF 20.2
Dwelling elevations facing public streets and common driveways make a positive contribution to the streetscape and the appearance of common driveway areas.	Each dwelling includes at least 3 of the following design features within the building elevation facing a primary street, and at least 2 of the following design features within the building elevation facing any other public road (other than a laneway) or a common driveway:
	 (a) a minimum of 30% of the building wall is set back an additional 300mm from the building line (b) a porch or portico projects at least 1m from the building

Page 21 of 36 Printed on 22/11/2021

wall

of the front elevation

a balcony projects from the building wall

a verandah projects at least 1m from the building wall

eaves of a minimum 400mm width extend along the width

a minimum 30% of the width of the upper level projects

(c)

(d)

(e)

(f)

forward from the lower level primary building line by at least 300mm a minimum of two different materials or finishes are incorporated on the walls of the front building elevation, with a maximum of 80% of the building elevation in a single material or finish. PO 20.3 DTS/DPF 20.3 The visual mass of larger buildings is reduced when viewed from None are applicable adjoining allotments or public streets. Private Open Space DTS/DPF 21.1 PO 21.1 Dwellings are provided with suitable sized areas of usable private Private open space is provided in accordance with Design in Urban open space to meet the needs of occupants. Areas Table 1 - Private Open Space. PO 21.2 DTS/DPF 21.2 Private open space is positioned to provide convenient access from Private open space is directly accessible from a habitable room. internal living areas. Landscaping PO 22.1 DTS/DPF 22.1 Soft landscaping is incorporated into development to: Residential development incorporates soft landscaping with a minimum dimension of 700mm provided in accordance with (a) and (a) minimise heat absorption and reflection (b): (b) contribute shade and shelter (a) a total area as determined by the following table: provide for stormwater infiltration and biodiversity (c) (d) enhance the appearance of land and streetscapes. Dwelling site area (or in the case Minimum of residential flat building or group percentage of dwelling(s), average site area) (m²) site <150 10% 150-200 15% >200-450 20% >450 25% at least 30% of any land between the primary street (b) boundary and the primary building line. Car parking, access and manoeuvrability PO 23.1 **DTS/DPF 23.1** Enclosed car parking spaces are of dimensions to be functional, Residential car parking spaces enclosed by fencing, walls or other accessible and convenient. structures have the following internal dimensions (separate from

Page 22 of 36 Printed on 22/11/2021

any waste storage area): (a) single width car parking spaces: a minimum length of 5.4m per space (ii) a minimum width of 3.0m (iii) a minimum garage door width of 2.4m (b) double width car parking spaces (side by side): a minimum length of 5.4m (ii) a minimum width of 5.4m (iii) minimum garage door width of 2.4m per space. PO 23.2 DTS/DPF 23.2 Uncovered car parking space are of dimensions to be functional, Uncovered car parking spaces have: accessible and convenient. a minimum length of 5.4m (b) a minimum width of 2.4m (c) a minimum width between the centre line of the space and any fence, wall or other obstruction of 1.5m. PO 23.3 **DTS/DPF 23.3** Driveways and access points are located and designed to facilitate Driveways and access points satisfy (a) or (b): safe access and egress while maximising land available for street sites with a frontage to a public road of 10m or less, have tree planting, domestic waste collection, landscaped street a width between 3.0 and 3.2 metres measured at the frontages and on-street parking. property boundary and are the only access point provided on the site (b) sites with a frontage to a public road greater than 10m: have a maximum width of 5m measured at the property boundary and are the only access point provided on the site; (ii) have a width between 3.0 metres and 3.2 metres measured at the property boundary and no more than two access points are provided on site, separated by no less than 1m. DTS/DPF 23.4 PO 23.4 Vehicle access is safe, convenient, minimises interruption to the Vehicle access to designated car parking spaces satisfy (a) or (b): operation of public roads and does not interfere with street (a) is provided via a lawfully existing or authorised access infrastructure or street trees. point or an access point for which consent has been granted as part of an application for the division of land (b) where newly proposed, is set back: 0.5m or more from any street furniture, street pole, infrastructure services pit, or other stormwater or utility infrastructure unless consent is provided from the asset owner (ii) 2m or more from the base of the trunk of a street tree unless consent is provided from the tree owner for a lesser distance 6m or more from the tangent point of an intersection of 2 or more roads outside of the marked lines or infrastructure dedicating a pedestrian crossing.

Page 23 of 36 Printed on 22/11/2021

PO 31.3

PO 23.5	DTS/DPF 23.5
Driveways are designed to enable safe and convenient vehicle movements from the public road to on-site parking spaces.	Driveways are designed and sited so that:
inevenients from the public road to on-site parking spaces.	 (a) the gradient from the place of access on the boundary of the allotment to the finished floor level at the front of the garage or carport is not steeper than 1-in-4 on average (b) they are aligned relative to the street so that there is no more than a 20 degree deviation from 90 degrees between the centreline of any dedicated car parking space to which it provides access (measured from the front of that space) and the road boundary. (c) if located so as to provide access from an alley, lane or right of way - the alley, lane or right or way is at least 6.2m wide along the boundary of the allotment / site
PO 23.6	DTS/DPF 23.6
Driveways and access points are designed and distributed to optimise the provision of on-street visitor parking.	Where on-street parking is available abutting the site's street frontage, on-street parking is retained in accordance with the following requirements:
	(a) minimum 0.33 on-street spaces per dwelling on the site (rounded up to the nearest whole number)
	(b) minimum car park length of 5.4m where a vehicle can enter or exit a space directly
	(c) minimum carpark length of 6m for an intermediate space located between two other parking spaces or to an end obstruction where the parking is indented.
Waste	storage
PO 24.1	DTS/DPF 24.1
Provision is made for the convenient storage of waste bins in a	Where dwellings abut both side boundaries a waste bin storage
location screened from public view.	area is provided behind the building line of each dwelling that:
location screened from public view.	(a) has a minimum area of 2m ² with a minimum dimension of
location screened from public view.	(a) has a minimum area of 2m ² with a minimum dimension of 900mm (separate from any designated car parking spaces
	 (a) has a minimum area of 2m² with a minimum dimension of 900mm (separate from any designated car parking spaces or private open space); and (b) has a continuous unobstructed path of travel (excluding moveable objects like gates, vehicles and roller doors) with a minimum width of 800mm between the waste bin storage
	 (a) has a minimum area of 2m² with a minimum dimension of 900mm (separate from any designated car parking spaces or private open space); and (b) has a continuous unobstructed path of travel (excluding moveable objects like gates, vehicles and roller doors) with a minimum width of 800mm between the waste bin storage area and the street.
Design of Trans PO 25.1 The sub-floor space beneath transportable buildings is enclosed to	(a) has a minimum area of 2m² with a minimum dimension of 900mm (separate from any designated car parking spaces or private open space); and (b) has a continuous unobstructed path of travel (excluding moveable objects like gates, vehicles and roller doors) with a minimum width of 800mm between the waste bin storage area and the street.
Design of Trans	(a) has a minimum area of 2m² with a minimum dimension of 900mm (separate from any designated car parking spaces or private open space); and (b) has a continuous unobstructed path of travel (excluding moveable objects like gates, vehicles and roller doors) with a minimum width of 800mm between the waste bin storage area and the street. DTS/DPF 25.1
Design of Trans PO 25.1 The sub-floor space beneath transportable buildings is enclosed to give the appearance of a permanent structure.	(a) has a minimum area of 2m² with a minimum dimension of 900mm (separate from any designated car parking spaces or private open space); and (b) has a continuous unobstructed path of travel (excluding moveable objects like gates, vehicles and roller doors) with a minimum width of 800mm between the waste bin storage area and the street. portable Buildings DTS/DPF 25.1 Buildings satisfy (a) or (b): (a) are not transportable (b) the sub-floor space between the building and ground level
Design of Trans PO 25.1 The sub-floor space beneath transportable buildings is enclosed to give the appearance of a permanent structure. Group Dwellings, Residential Flat B	(a) has a minimum area of 2m² with a minimum dimension of 900mm (separate from any designated car parking spaces or private open space); and (b) has a continuous unobstructed path of travel (excluding moveable objects like gates, vehicles and roller doors) with a minimum width of 800mm between the waste bin storage area and the street. portable Buildings DTS/DPF 25.1 Buildings satisfy (a) or (b): (a) are not transportable (b) the sub-floor space between the building and ground level is clad in a material and finish consistent with the building.
Design of Trans PO 25.1 The sub-floor space beneath transportable buildings is enclosed to give the appearance of a permanent structure. Group Dwellings, Residential Flat B	(a) has a minimum area of 2m² with a minimum dimension of 900mm (separate from any designated car parking spaces or private open space); and (b) has a continuous unobstructed path of travel (excluding moveable objects like gates, vehicles and roller doors) with a minimum width of 800mm between the waste bin storage area and the street. portable Buildings DTS/DPF 25.1 Buildings satisfy (a) or (b): (a) are not transportable (b) the sub-floor space between the building and ground level is clad in a material and finish consistent with the building.
Design of Trans PO 25.1 The sub-floor space beneath transportable buildings is enclosed to give the appearance of a permanent structure. Group Dwellings, Residential Flat E	(a) has a minimum area of 2m² with a minimum dimension of 900mm (separate from any designated car parking spaces or private open space); and (b) has a continuous unobstructed path of travel (excluding moveable objects like gates, vehicles and roller doors) with a minimum width of 800mm between the waste bin storage area and the street. portable Buildings DTS/DPF 25.1 Buildings satisfy (a) or (b): (a) are not transportable (b) the sub-floor space between the building and ground level is clad in a material and finish consistent with the building. Buildings and Battle axe Development

Page 24 of 36 Printed on 22/11/2021

DTS/DPF 31.3

Folicy24 - Eliquily	
Development maximises the number of dwellings that face public open space and public streets and limits dwellings oriented towards adjoining properties.	None are applicable.
PO 31.4	DTS/DPF 31.4
Battle-axe development is appropriately sited and designed to	Dwelling sites/allotments are not in the form of a battle-axe
respond to the existing neighbourhood context.	arrangement.
Car parking, access	s and manoeuvrability
PO 33.1	DTS/DPF 33.1
Driveways and access points are designed and distributed to optimise the provision of on-street visitor parking.	Where on-street parking is available directly adjacent the site, on- street parking is retained adjacent the subject site in accordance with the following requirements:
	(a) minimum 0.33 on-street car parks per proposed dwelling (rounded up to the nearest whole number)
	(b) minimum car park length of 5.4m where a vehicle can enter or exit a space directly
	(c) minimum carpark length of 6m for an intermediate space located between two other parking spaces or to an end obstruction where the parking is indented.
PO 33.4	DTS/DPF 33.4
Residential driveways that service more than one dwelling or a dwelling on a battle-axe site are designed to allow passenger vehicles to enter and exit and manoeuvre within the site in a safe and convenient manner.	Driveways providing access to more than one dwelling, or a dwelling on a battle-axe site, allow a B85 passenger vehicle to enter and exit the garages or parking spaces in no more than a three-point turn manoeuvre.
PO 33.5	DTS/DPF 33.5
Dwellings are adequately separated from common driveways and manoeuvring areas.	Dwelling walls with entry doors or ground level habitable room windows are set back at least 1.5m from any driveway or area designated for the movement and manoeuvring of vehicles.
Soft lan	dscaping
PO 34.2	DTS/DPF 34.2
Battle-axe or common driveways incorporate landscaping and	Battle-axe or common driveways satisfy (a) and (b):
permeability to improve appearance and assist in stormwater management.	(a) are constructed of a minimum of 50% permeable or
	porous material (b) where the driveway is located directly adjacent the side or rear boundary of the site, soft landscaping with a minimum dimension of 1m is provided between the driveway and site boundary (excluding along the perimeter of a passing point).
Laneway D	Development Development
Infrastructur	e and Access
PO 44.1	DTS/DPF 44.1
Development with a primary street comprising a laneway, alley, lane, right of way or similar minor thoroughfare only occurs where:	Development with a primary street frontage that is not an alley, lane right of way or similar public thoroughfare.
(a) existing utility infrastructure and services are capable of accommodating the development	
(b) the mineral street consumer to a construction of the construct	

Page 25 of 36 Printed on 22/11/2021

the primary street can support access by emergency and

regular service vehicles (such as waste collection)

(b)

- it does not require the provision or upgrading of infrastructure on public land (such as footpaths and stormwater management systems)
 safety of pedestrians or vehicle movement is maintained
- (e) any necessary grade transition is accommodated within the site of the development to support an appropriate development intensity and orderly development of land fronting minor thoroughfares.

Table 1 - Private Open Space

Dwelling Type	Dwelling / Site	Minimum Rate
	Configuration	
Dwelling (at ground level, other than a residential flat building that includes above ground dwellings)		Total private open space area: (a) Site area <301m2: 24m2 located behind the building line. (b) Site area ≥ 301m2: 60m2 located behind the building line. Minimum directly accessible from a living room: 16m2 / with a minimum dimension 3m.
Cabin or caravan (permanently fixed to the ground) in a residential park or caravan and tourist park		Total area: 16m ² , which may be uses as second car parking space, provided on each site intended for residential occupation.
Dwelling in a residential flat building or mixed use building which incorporate	Dwellings at ground level:	15m ² / minimum dimension 3m
above ground level dwellings	Dwellings above ground level:	
	Studio (no separate bedroom)	4m ² / minimum dimension 1.8m
	One bedroom dwelling	8m ² / minimum dimension 2.1m
	Two bedroom dwelling	11m ² / minimum dimension 2.4m
	Three + bedroom dwelling	15 m ² / minimum dimension 2.6m

Infrastructure and Renewable Energy Facilities

Assessment Provisions (AP)

	Desired Outcome	
DO 1	Efficient provision of infrastructure networks and services, renewable energy facilities and ancillary development in a manner that minimises hazard, is environmentally and culturally sensitive and manages adverse visual impacts on natural and rural landscapes and residential amenity.	

Performance Outcomes (PO) and Deemed-to-Satisfy (DTS) Criteria / Designated Performance Feature (DPF)

Page 26 of 36 Printed on 22/11/2021

Performance Outcome

Deemed-to-Satisfy Criteria / Designated Performance Feature

Water Supply

PO 11.2

Dwellings are connected to a reticulated water scheme or mains water supply with the capacity to meet the requirements of the intended use. Where this is not available an appropriate rainwater tank or storage system for domestic use is provided.

DTS/DPF 11.2

A dwelling is connected, or will be connected, to a reticulated water scheme or mains water supply with the capacity to meet the requirements of the development. Where this is not available it is serviced by a rainwater tank or tanks capable of holding at least 50.000 litres of water which is:

- (a) exclusively for domestic use
- (b) connected to the roof drainage system of the dwelling.

Wastewater Services

PO 12.1

Development is connected to an approved common wastewater disposal service with the capacity to meet the requirements of the intended use. Where this is not available an appropriate on-site service is provided to meet the ongoing requirements of the intended use in accordance with the following:

- it is wholly located and contained within the allotment of the development it will service
- (b) in areas where there is a high risk of contamination of surface, ground, or marine water resources from on-site disposal of liquid wastes, disposal systems are included to minimise the risk of pollution to those water resources
- (c) septic tank effluent drainage fields and other wastewater disposal areas are located away from watercourses and flood prone, sloping, saline or poorly drained land to minimise environmental harm.

DTS/DPF 12.1

Development is connected, or will be connected, to an approved common wastewater disposal service with the capacity to meet the requirements of the development. Where this is not available it is instead capable of being serviced by an on-site waste water treatment system in accordance with the following:

- (a) the system is wholly located and contained within the allotment of development it will service; and
- (b) the system will comply with the requirements of the South Australian Public Health Act 2011.

PO 12.2

Effluent drainage fields and other wastewater disposal areas are maintained to ensure the effective operation of waste systems and minimise risks to human health and the environment.

DTS/DPF 12.2

Development is not built on, or encroaches within, an area that is, or will be, required for a sewerage system or waste control system.

Interface between Land Uses

Assessment Provisions (AP)

Desired Outcome Development is located and designed to mitigate adverse effects on or from neighbouring and proximate land uses.

Performance Outcomes (PO) and Deemed-to-Satisfy (DTS) Criteria / Designated Performance Feature (DPF)

Performance Outcome Deemed-to-Satisfy Criteria /
Designated Performance

Page 27 of 36 Printed on 22/11/2021

	Feature
Oversha	adowing
PO 3.1 Overshadowing of habitable room windows of adjacent residential land uses in:	DTS/DPF 3.1 North-facing windows of habitable rooms of adjacent residential land uses in a neighbourhood-type zone receive at least 3 hours of direct sunlight between 9.00am and 3.00pm on 21 June.
 a. a neighbourhood-type zone is minimised to maintain access to direct winter sunlight b. other zones is managed to enable access to direct winter sunlight. 	direct suring it between 3.00am and 3.00pm on 21 durie.
PO 3.2	DTS/DPF 3.2
Overshadowing of the primary area of private open space or communal open space of adjacent residential land uses in: a. a neighbourhood type zone is minimised to maintain access to direct winter sunlight b. other zones is managed to enable access to direct winter sunlight.	Development maintains 2 hours of direct sunlight between 9.00 am and 3.00 pm on 21 June to adjacent residential land uses in a neighbourhood-type zone in accordance with the following: a. for ground level private open space, the smaller of the following: i. half the existing ground level open space or ii. 35m2 of the existing ground level open space (with at least one of the area's dimensions measuring 2.5m) b. for ground level communal open space, at least half of the existing ground level open space.
PO 3.3 Development does not unduly reduce the generating capacity of adjacent rooftop solar energy facilities taking into account:	DTS/DPF 3.3 None are applicable.
(a) the form of development contemplated in the zone (b) the orientation of the solar energy facilities (c) the extent to which the solar energy facilities are already overshadowed.	

Site Contamination

DO 1

Assessment Provisions (AP)

Desired Outcome Ensure land is suitable for the proposed use in circumstances where it is, or may have been, subject to site contamination.

Performance Outcome	Deemed-to-Satisfy Criteria / Designated Performance Feature
PO 1.1	DTS/DPF 1.1
Ensure land is suitable for use when land use changes to a more sensitive use.	Development satisfies (a), (b), (c) or (d): (a) does not involve a change in the use of land (b) involves a change in the use of land that does not

Page 28 of 36 Printed on 22/11/2021

constitute a change to a more sensitive use (c) involves a change in the use of land to a more sensitive

use on land at which site contamination is unlikely to exist (as demonstrated in a site contamination declaration form)

involves a change in the use of land to a more sensitive use on land at which site contamination exists, or may exist (as demonstrated in a site contamination declaration form), and satisfies both of the following:

> a site contamination audit report has been prepared under Part 10A of the Environment Protection Act 1993 in relation to the land within the previous 5 years which states that-

> > site contamination does not exist (or no longer exists) at the land

B. the land is suitable for the proposed use or range of uses (without the need for any further remediation)

where remediation is, or remains, necessary for the proposed use (or range of uses), remediation work has been carried out or will be carried out (and the applicant has provided a written undertaking that the remediation works will be implemented in association with the development)

and

no other class 1 activity or class 2 activity has taken place at the land since the preparation of the site contamination audit report (as demonstrated in a site contamination declaration form).

Transport, Access and Parking

Assessment Provisions (AP)

	Desired Outcome
DO 1	A comprehensive, integrated and connected transport system that is safe, sustainable, efficient, convenient and accessible to all users.

Performance Outcomes (PO) and Deemed-to-Satisfy (DTS) Criteria / Designated Performance Feature (DPF)

Deemed-to-Satisfy Criteria / **Performance Outcome Designated Performance Feature** Vehicle Parking Rates PO 5.1 DTS/DPF 5.1 Sufficient on-site vehicle parking and specifically marked Development provides a number of car parking spaces on-site at a accessible car parking places are provided to meet the needs of the rate no less than the amount calculated using one of the following, development or land use having regard to factors that may support whichever is relevant: a reduced on-site rate such as:

Printed on 22/11/2021 Page 29 of 36

(a) Transport, Access and Parking Table 1 - General Off-Street Car Parking Requirements (a) availability of on-street car parking (b) Transport, Access and Parking Table 2 - Off-Street Vehicle (b) shared use of other parking areas Parking Requirements in Designated Areas (c) in relation to a mixed-use development, where the hours of (c) if located in an area where a lawfully established operation of commercial activities complement the carparking fund operates, the number of spaces residential use of the site, the provision of vehicle parking calculated under (a) or (b) less the number of spaces may be shared offset by contribution to the fund. (d) the adaptive reuse of a State or Local Heritage Place. Corner Cut-Offs PO 10.1 DTS/DPF 10.1 Development is located and designed to ensure drivers can safely Development does not involve building work, or building work is turn into and out of public road junctions. located wholly outside the land shown as Corner Cut-Off Area in the following diagram: Allotment Boundary Corner Cut-Off Area

Table 1 - General Off-Street Car Parking Requirements

The following parking rates apply and if located in an area where a lawfully established carparking fund operates, the number of spaces is reduced by an amount equal to the number of spaces offset by contribution to the fund.

Class of Development	Car Parking Rate (unless varied by Table 2 onwards)
	Where a development comprises more than one development type, then the overall car parking rate will be taken to be the sum of the car parking rates for each development type.
Residential Development	
Detached Dwelling	Dwelling with 1 bedroom (including rooms capable of being used as a bedroom) - 1 space per dwelling.
	Dwelling with 2 or more bedrooms (including rooms capable of being used as a bedroom) - 2 spaces per dwelling, 1 of which is to be covered.
Group Dwelling	Dwelling with 1 or 2 bedrooms (including rooms capable of being used as a bedroom) - 1 space per dwelling.
	Dwelling with 3 or more bedrooms (including rooms capable of being used as a bedroom) - 2 spaces per dwelling, 1 of which is to be covered.
	0.33 spaces per dwelling for visitor parking where development involves 3 or more dwellings.
Residential Flat Building	Dwelling with 1 or 2 bedrooms (including rooms capable of being used as a bedroom) - 1 space per dwelling.
	Dwelling with 3 or more bedrooms (including rooms capable of being used as a bedroom) - 2 spaces per dwelling, 1 of which is to be covered.

Page 30 of 36 Printed on 22/11/2021

	0.33 spaces per dwelling for visitor parking where development involves 3 or more dwellings.
Row Dwelling where vehicle access is from the primary street	Dwelling with 1 bedroom (including rooms capable of being used as a bedroom) - 1 space per dwelling.
primary street	Dwelling with 2 or more bedrooms (including rooms capable of being used as a bedroom) - 2 spaces per dwelling, 1 of which is to be covered.
Row Dwelling where vehicle access is not from the primary street (i.e. rear-loaded)	Dwelling with 1 or 2 bedrooms (including rooms capable of being used as a bedroom) - 1 space per dwelling.
	Dwelling with 3 or more bedrooms (including rooms capable of being used as a bedroom) - 2 spaces per dwelling, 1 of which is to be covered.
Semi-Detached Dwelling	Dwelling with 1 bedroom (including rooms capable of being used as a bedroom) - 1 space per dwelling.
	Dwelling with 2 or more bedrooms (including rooms capable of being used as a bedroom) - 2 spaces per dwelling, 1 of which is to be covered.
Aged / Supported Accommodation	
Retirement village	Dwelling with 1 or 2 bedrooms (including rooms capable of being used as a bedroom) - 1 space per dwelling.
	Dwelling with 3 or more bedrooms (including rooms capable of being used as a bedroom) - 2 spaces per dwelling.
	0.2 spaces per dwelling for visitor parking.
Supported accommodation	0.3 spaces per bed.
Residential Development (Other)	
Ancillary accommodation	No additional requirements beyond those associated with the main dwelling.
Residential park	Dwelling with 1 or 2 bedrooms (including rooms capable of being used as a bedroom) - 1 space per dwelling.
	Dwelling with 3 or more bedrooms (including rooms capable of being used as a bedroom) - 2 spaces per dwelling.
	0.2 spaces per dwelling for visitor parking.
Student accommodation	0.3 spaces per bed.
Workers' accommodation	0.5 spaces per bed plus 0.2 spaces per bed for visitor parking.
Tourist	
Caravan park / tourist park	Parks with 100 sites or less - a minimum of 1 space per 10 sites to be used for accommodation.
	Parks with more than 100 sites - a minimum of 1 space per 15 sites used for accommodation.
	A minimum of 1 space for every caravan (permanently fixed to the ground) or cabin.

Page 31 of 36 Printed on 22/11/2021

	· · · ·	
Commercial Uses		
Auction room/ depot	1 space per 100m ² of building floor area plus an additional 2 spaces.	
Automotive collision repair	3 spaces per service bay.	
Call centre	8 spaces per 100m ² of gross leasable floor area.	
Motor repair station	3 spaces per service bay.	
Office	4 spaces per 100m ² of gross leasable floor area.	
Retail fuel outlet	3 spaces per 100m ² gross leasable floor area.	
Service trade premises	2.5 spaces per 100m ² of gross leasable floor area	
	1 space per 100m ² of outdoor area used for display purposes.	
Shop (no commercial kitchen)	5.5 spaces per 100m ² of gross leasable floor area where not located in an integrated complex containing two or more tenancies (and which may comprise more than one building) where facilities for off-street vehicle parking, vehicle loading and unloading, and the storage and collection of refuse are shared.	
	5 spaces per 100m ² of gross leasable floor area where located in an integrated complex containing two or more tenancies (and which may comprise more than one building) where facilities for off-street vehicle parking, vehicle loading and unloading, and the storage and collection of refuse are shared.	
Shop (in the form of a bulky goods outlet)	2.5 spaces per 100m ² of gross leasable floor area.	
Shop (in the form of a restaurant or involving a commercial kitchen)	Premises with a dine-in service only (which may include a take-away component with no drive-through) - 0.4 spaces per seat.	
	Premises with take-away service but with no seats - 12 spaces per 100m ² of total floor area plus a drive-through queue capacity of ten vehicles measured from the pick-up point.	
	Premises with a dine-in and drive-through take-away service - 0.3 spaces per seat plus a drive through queue capacity of 10 vehicles measured from the pick-up point.	
Community and Civic Uses		
Childcare centre	0.25 spaces per child	
Library	4 spaces per 100m ² of total floor area.	
Community facility	10 spaces per 100m ² of total floor area.	

Page 32 of 36 Printed on 22/11/2021

Policy24 - Eriquiry	
Hall / meeting hall	0.2 spaces per seat.
Place of worship	1 space for every 3 visitor seats.
Pre-school	1 per employee plus 0.25 per child (drop off/pick up bays)
Educational establishment	For a primary school - 1.1 space per full time equivalent employee plus 0.25 spaces per student for a pickup/set down area either on-site or on the public realm within 300m of the site.
	For a secondary school - 1.1 per full time equivalent employee plus 0.1 spaces per student for a pickup/set down area either on-site or on the public realm within 300m of the site.
	For a tertiary institution - 0.4 per student based on the maximum number of students on the site at any time.
Health Related Uses	
Hospital	4.5 spaces per bed for a public hospital.
	1.5 spaces per bed for a private hospital.
Consulting room	4 spaces per consulting room excluding ancillary facilities.
Recreational and Entertainment Uses	
Cinema complex	0.2 spaces per seat.
Concert hall / theatre	0.2 spaces per seat.
Hotel	1 space for every 2m ² of total floor area in a public bar plus 1 space for every 6m ² of total floor area available to the public in a lounge, beer garden plus 1 space per 2 gaming machines, plus 1 space per 3 seats in a restaurant.
Indoor recreation facility	6.5 spaces per 100m ² of total floor area for a Fitness Centre
	4.5 spaces per 100m ² of total floor area for all other Indoor recreation facilities.
Industry/Employment Uses	
Fuel depot	1.5 spaces per 100m ² total floor area
	1 spaces per 100m ² of outdoor area used for fuel depot activity purposes.
Industry	1.5 spaces per 100m ² of total floor area.
Store	0.5 spaces per 100m ² of total floor area.

Page 33 of 36 Printed on 22/11/2021

Timber yard	1.5 spaces per 100m ² of total floor area	
	1 space per 100m ² of outdoor area used for display purposes.	
Warehouse	0.5 spaces per 100m ² total floor area.	
Other Uses		
Funeral Parlour	1 space per 5 seats in the chapel plus 1 space for each vehicle operated by the parlour.	
Radio or Television Station	5 spaces per 100m ² of total building floor area.	

Table 2 - Off-Street Car Parking Requirements in Designated Areas

The following parking rates apply in any zone, subzone or other area described in the 'Designated Areas' column subject to the following:

- (a) the location of the development is unable to satisfy the requirements of Table 2 Criteria (other than where a location is exempted from the application of those criteria) or
- (b) the development satisfies Table 2 Criteria (or is exempt from those criteria) and is located in an area where a lawfully established carparking fund operates, in which case the number of spaces are reduced by an amount equal to the number of spaces offset by contribution to the fund.

Class of Development	Car Parking Rate Where a development comprises more than one development type, then the overall car parking rate will be taken to be the sum of the car parking rates for each development type.		Designated Areas
	Minimum number of spaces	Maximum number of spaces	
Development generally			
All classes of development	No minimum.	No maximum except in the Primary Pedestrian Area identified in the Primary Pedestrian Area Concept Plan, where the maximum is: 1 space for each dwelling with a total floor area less than 75 square metres 2 spaces for each dwelling with a total floor area between 75 square metres and 150 square metres 3 spaces for each dwelling with a total floor area greater than 150 square metres. Residential flat building or	Capital City Zone City Main Street Zone City Riverbank Zone Adelaide Park Lands Zone Business Neighbourhood Zone (within the City of Adelaide) The St Andrews Hospital Precinct Subzone and Women's and Children's Hospital Precinct Subzone of the Community Facilities Zone

Page 34 of 36 Printed on 22/11/2021

		Residential component of a multi-storey building: 1 visitor space for each 6 dwellings.	
Non-residential developr	ment		
Non-residential development excluding tourist accommodation	3 spaces per 100m ² of gross leasable floor area.	5 spaces per 100m ² of gross leasable floor area.	City Living Zone Urban Corridor (Boulevard) Zone Urban Corridor (Business) Zone Urban Corridor (Living) Zone Urban Corridor (Main Street) Zone Urban Neighbourhood Zone
Non-residential development excluding tourist accommodation	3 spaces per 100m ² of gross leasable floor area.	6 spaces per 100m ² of gross leasable floor area.	Strategic Innovation Zone Suburban Activity Centre Zone Suburban Business Zone Business Neighbourhood Zone Suburban Main Street Zone Urban Activity Centre Zone
Tourist accommodation	1 space for every 4 bedrooms up to 100 bedrooms plus 1 space for every 5 bedrooms over 100 bedrooms	1 space per 2 bedrooms up to 100 bedrooms and 1 space per 4 bedrooms over 100 bedrooms	City Living Zone Urban Activity Centre Zone Urban Corridor (Boulevard) Zone Urban Corridor (Business) Zone Urban Corridor (Living) Zone Urban Corridor (Main Street) Zone Urban Neighbourhood Zone
Residential development			
Residential component of a multi-storey building	Dwelling with no separate bedroom -0.25 spaces per dwelling 1 bedroom dwelling - 0.75 spaces per dwelling 2 bedroom dwelling - 1 space per dwelling 3 or more bedroom dwelling - 1.25 spaces per dwelling 0.25 spaces per dwelling for visitor parking.	None specified.	City Living Zone Strategic Innovation Zone Urban Activity Centre Zone Urban Corridor (Boulevard) Zone Urban Corridor (Business) Zone Urban Corridor (Living) Zone Urban Corridor (Main Street) Zone Urban Neighbourhood Zone

Page 35 of 36 Printed on 22/11/2021

Residential flat building	Dwelling with no separate bedroom -0.25 spaces per dwelling	None specified.	City Living Zone Urban Activity Centre Zone
	1 bedroom dwelling - 0.75 spaces per dwelling 2 bedroom dwelling - 1 space per dwelling 3 or more bedroom dwelling - 1.25 spaces per dwelling 0.25 spaces per dwelling for visitor parking.		Urban Corridor (Boulevard) Zone Urban Corridor (Business) Zone Urban Corridor (Living) Zone Urban Corridor (Main Street) Zone Urban Neighbourhood Zone

Table 2 - Criteria:

The following criteria are used in conjunction with Table 2. The 'Exception' column identifies locations where the criteria do not apply and the car parking rates in Table 2 are applicable.

	Criteria		Exceptions
Metro	esignated area is wholly located within politan Adelaide and any part of the opment site satisfies one or more of the ing:	(a) (b)	All zones in the City of Adelaide Strategic Innovation Zone in the following locations: (i) City of Burnside (ii) City of Marion (iii) City of Mitcham
(a)	is within 200 metres of any section of road reserve along which a bus service operates as a high frequency public transit service ⁽²⁾	(c) (d) (e)	Urban Corridor (Boulevard) Zone Urban Corridor (Business) Zone Urban Corridor (Living) Zone
(b)	is within 400 metres of a bus interchange ⁽¹⁾	(f) (g)	Urban Corridor (Main Street) Zone Urban Neighbourhood Zone
(c)	is within 400 metres of an O-Bahn interchange ⁽¹⁾	,	
(d)	is within 400 metres of a passenger rail station ⁽¹⁾		
(e)	is within 400 metres of a passenger tram station ⁽¹⁾		
(f)	is within 400 metres of the Adelaide Parklands.		

[NOTE(S): (1)Measured from an area that contains any platform(s), shelter(s) or stop(s) where people congregate for the purpose waiting to board a bus, tram or train, but does not include areas used for the parking of vehicles. (2) A high frequency public transit service is a route serviced every 15 minutes between 7.30am and 6.30pm Monday to Friday and every 30 minutes at night, Saturday, Sunday and public holidays until 10pm.]

Page 36 of 36 Printed on 22/11/2021