# **61 TRISTANIA TCE DERNANCOURT SA 5075**

# Address:

Click to view a detailed interactive SAILIS in SAILIS

To view a detailed interactive property map in SAPPA click on the map below



# **Property Zoning Details**

# Overlay

Airport Building Heights (Regulated) (All structures over 45 metres)

Affordable Housing

Hazards (Flooding - Evidence Required)

Prescribed Wells Area

Regulated and Significant Tree

Stormwater Management

**Urban Tree Canopy** 

# Zone

General Neighbourhood

# **Development Pathways**

# General Neighbourhood

# 1. Accepted Development

Means that the development type does not require planning consent (planning approval). Please ensure compliance with relevant land use and development controls in the Code.

- · Air handling unit, air conditioning system or exhaust fan
- Brush fence
- · Building work on railway land
- Carport
- Internal building work
- Outbuilding
- · Partial demolition of a building or structure
- Private bushfire shelter
- · Shade sail
- Solar photovoltaic panels (roof mounted)
- · Swimming pool or spa pool
- Verandah
- Water tank (above ground)
- · Water tank (underground)

Page 1 of 126 Printed on 5/07/2022

2. Code Assessed - Deemed to Satisfy

Means that the development type requires consent (planning approval). Please ensure compliance with relevant land use and development controls in the Code.

- · Ancillary accommodation
- Carport
- · Detached dwelling
- · Dwelling addition
- · Dwelling or residential flat building undertaken by:
  - (a) the South Australian Housing Trust either individually or jointly with other persons or bodies or
  - (b) a provider registered under the Community Housing National Law participating in a program relating to the renewal of housing endorsed by the South Australian Housing Trust.
- · Land division
- Outbuilding
- Replacement building
- Row dwelling
- Semi-detached dwelling
- · Temporary accommodation in an area affected by bushfire
- Verandah

## 3. Code Assessed - Performance Assessed

Performance Assessed development types listed below are those for which the Code identifies relevant policies. Additional development types that are not listed as Accepted, Deemed to Satisfy or Restricted default to a Performance assessed Pathway. Please contact your local council for more information.

- · Ancillary accommodation
- Carport
- Demolition
- Detached dwelling
- · Dwelling addition
- Dwelling or residential flat building undertaken by:
  - (a) the South Australian Housing Trust either individually or jointly with other persons or bodies or
  - (b) a provider registered under the Community Housing National Law participating in a program relating to the renewal of housing endorsed by the South Australian Housing Trust.
- Fence
- · Group dwelling
- · Land division
- Outbuilding
- · Residential flat building
- · Retaining wall
- Row dwelling
- Semi-detached dwelling
- · Tree-damaging activity
- Verandah

# 4. Impact Assessed - Restricted

Means that the development type requires approval. Classes of development that are classified as Restricted are listed in Table 4 of the relevant Zones.

**Property Policy Information for above selection** 

# Part 2 - Zones and Sub Zones

# **General Neighbourhood Zone**

# **Assessment Provisions (AP)**

Page 2 of 126 Printed on 5/07/2022

# **Desired Outcome**

DO 1

Low-rise, low and medium-density housing that supports a range of needs and lifestyles located within easy reach of services and facilities. Employment and community service uses contribute to making the neighbourhood a convenient place to live without compromising residential amenity.

Performance Outcomes (PO) and Deemed to Satisfy (DTS) / Designated Performance Feature (DPF) Criteria

| Performance Outcome   | Deemed-to-Satisfy Criteria / Designated Performance Feature   |
|---|---|
| Land Use  | and Intensity   |
| PO 1.1  | DTS/DPF 1.1   |
| Predominantly residential development with complementary non- residential uses that support an active, convenient, and walkable neighbourhood.  | (a) Ancillary accommodation (b) Community facility (c) Consulting room (d) Dwelling (e) Educational establishment (f) Office (g) Place of Worship (h) Pre-school (i) Recreation area (j) Residential flat building (k) Retirement facility (l) Shop (m) Student accommodation (n) Supported accommodation |
| PO 1.2  | DTS/DPF 1.2   |
| Non-residential development located and designed to improve community accessibility to services, primarily in the form of:  (a) small scale commercial uses such as offices, shops and consulting rooms  (b) community services such as educational establishments, community centres, places of worship, pre-schools, and other health and welfare services  (c) services and facilities ancillary to the function or operation of supported accommodation or retirement facilities  (d) open space and recreation facilities. | None are applicable.  |
| PO 1.3  | DTS/DPF 1.3   |
| Non-residential development sited and designed to complement the residential character and amenity of the neighbourhood.  | None are applicable.  |
| PO 1.4  | DTS/DPF 1.4   |
| Commercial activities improve community access to services are of a scale and type to maintain residential amenity.   | A shop, consulting room or office (or any combination thereof) satisfies any one of the following:  |

Page 3 of 126 Printed on 5/07/2022

- (a) it is located on the same allotment and in conjunction with a dwelling where all the following are satisfied:
  - (i) does not exceed 50m<sup>2</sup> gross leasable floor area
  - (ii) does not involve the display of goods in a window or about the dwelling or its curtilage
- (b) it reinstates a former shop, consulting room or office in an existing building (or portion of a building) and satisfies one of the following:
  - (i) the building is a State or Local Heritage Place
  - (ii) is in conjunction with a dwelling and there is no increase in the gross leasable floor area previously used for non-residential purposes
- (c) is located more than 500m from an Activity Centre and satisfies one of the following:
  - (i) does not exceed 100m<sup>2</sup> gross leasable floor area (individually or combined, in a single building) where the site does not have a frontage to a State Maintained Road
  - (ii) does not exceed 200m<sup>2</sup> gross leasable floor area (individually or combined, in a single building) where the site has a frontage to a State Maintained Road
- (d) the development site abuts an Activity Centre and all the following are satisfied:
  - it does not exceed 200m<sup>2</sup> gross leasable floor area (individually or combined, in a single building)
  - (ii) the proposed development will not result in a combined gross leasable floor area (existing and proposed) of all shops, consulting rooms and offices that abut the Activity Centre in this zone exceeding the lesser of the following:
    - A. 50% of the existing gross leasable floor area within the Activity Centre
    - B. 1000m<sup>2</sup>

# PO 1.5

Expansion of existing community services such as educational establishments, community facilities and pre-schools in a manner which complements the scale of development envisaged by the desired outcome for the neighbourhood.

# DTS/DPF 1.5

Alteration of or addition to existing educational establishments, community facilities or pre-schools where all the following are satisfied:

- (a) set back at least 3m from any boundary shared with a residential land use
- (b) building height not exceeding 1 building level
- (c) the total floor area of the building not exceeding 150% of the total floor area prior to the addition/alteration
- (d) off-street vehicular parking exists or will be provided in accordance with the rate(s) specified in Transport, Access and Parking Table 1 - General Off-Street Car Parking Requirements or Table 2 - Off-Street Car Parking Requirements in Designated Areas to the nearest whole number.

Site Dimensions and Land Division

Page 4 of 126 Printed on 5/07/2022

### PO 2.1

Allotments/sites created for residential purposes are of suitable size and dimension to accommodate the anticipated dwelling form and remain compatible with the pattern of development in a low-rise and predominantly low-density neighbourhood, with higher densities closer to public open space, public transport stations and activity centres.

### DTS/DPF 2.1

Development will not result in more than 1 dwelling on an existing allotment

or

Allotments/sites for residential purposes accord with the following:

| Dwelling Type  | Minimum<br>site/allotment area<br>per dwelling               | Minimum<br>site/allotment<br>frontage   |
|--|--|---|
| Detached dwelling (not in a terrace arrangement)             | 300m² (exclusive of<br>any battle-axe<br>allotment 'handle') | 9m where not<br>on a battle-<br>axe site<br>5m where on<br>a battle-axe<br>site |
| Semi-detached dwelling                                       | 300m <sup>2</sup>  | 9m  |
| Row dwelling (or detached dwelling in a terrace arrangement) | 250m <sup>2</sup>  | 7m<br>(averaged)  |
| Group dwelling   | 300m² (average,<br>including common<br>areas)                | 15m (total)   |
| Dwelling within a residential flat building                  | 300m² (average, including common areas)                      | 15m (total)   |

### PO 2.2

Development creating new allotments/sites in conjunction with retention of an existing dwelling ensures the site of the existing dwelling remains fit for purpose.

### DTS/DPF 2.2

Where the site of a dwelling does not comprise an entire allotment:

- the balance of the allotment accords with site area and frontage requirements specified in General Neighbourhood Zone DTS/DPF 2.1
- (b) if there is an existing dwelling on the allotment that will remain on the allotment after completion of the development, it will not contravene:
  - Private open space requirements specified in Design in Urban Areas Table 1 - Private Open Space
  - (ii) off-street vehicular parking exists in accordance with the rate(s) specified in Transport, Access and Parking Table 1 - General Off-Street Car Parking Requirements or Table 2 - Off-Street Car Parking Requirements in Designated Areas to the nearest whole number.

# PO 2.3

Land division results in sites that are accessible and suitable for their intended purpose.

# DTS/DPF 2.3

Division of land satisfies (a), (b) or (c):

- (a) reflects the site boundaries illustrated and approved in an existing development authorisation under the Development Act 1993 or Planning, Development and Infrastructure Act 2016 where the allotments are used or are proposed to be used solely for residential purposes
- is proposed as part of a combined land division application with deemed-to-satisfy dwellings on the proposed allotments
- (c) satisfies all of the following:
  - (i) No more than 5 additional allotments are created
  - (ii) Each proposed allotment has a minimum site area

Page 5 of 126 Printed on 5/07/2022

of 300m<sup>2</sup> and frontage of 9m

- (iii) Each proposed allotment has a slope less than 12.5% (1-in-8)
- (iv) There are no regulated trees on or within 20m of the subject land, with the distance measured from the base of the trunk of the tree (or the nearest trunk of the tree) to the subject land
- (v) The division does not involve creation of a public road
- (vi) Vehicle access from a public road can be provided to all proposed allotments which satisfies Design in Urban Areas DTS/DPF 23.3, 23.4 and 23.6, and would be located wholly on one side of the allotment, or located no more than 1m from the side boundary alignment
- (vii) No allotments are in a battle-axe configuration and
- (viii) Each proposed allotment is of a size and dimension capable of containing a rectangle 9m in width and 15m in depth.

## Site Coverage

### PO 3.1

Building footprints allow sufficient space around buildings to limit visual impact, provide an attractive outlook and access to light and ventilation.

### DTS/DPF 3.1

The development does not result in site coverage exceeding 60%.

## **Building Height**

# PO 4.1

# DTS/DPF 4.1

Buildings contribute to a low-rise suburban character.

Building height (excluding garages, carports and outbuildings) no greater than:

- (a) 2 building levels and 9m
- (b) wall height that is no greater than 7m except in the case of a gable end.

# Primary Street Setback

# PO 5.1

Buildings are setback from primary street boundaries to contribute to the existing/emerging pattern of street setbacks in the streetscape.

# DTS/DPF 5.1

The building line of a building set back from the primary street boundary:

- (a) no more than 1m in front of the average setback to the building line of existing buildings on adjoining sites which face the same primary street (including those buildings that would adjoin the site if not separated by a public road or a vacant allotment)
- (b) where there is only one existing building on adjoining sites which face the same primary street (including those that would adjoin if not separated by a public road or a vacant allotment), no more than 1m in front of the setback to the building line of that building

or

(c) not less than 5m where no building exists on an adjoining site with the same primary street frontage.

Secondary Street Setback

Page 6 of 126 Printed on 5/07/2022

# PO 6.1

Buildings are set back from secondary street boundaries to achieve separation between building walls and public streets and contribute to a suburban streetscape character.

### DTS/DPF 6.1

Building walls are set back from the boundary of the allotment with a secondary street frontage:

- (a) at least 900mm
- (b) if a dwelling on any adjoining allotment is closer to the secondary street than 900mm, at least the distance of that dwelling from the boundary with the secondary street.

# **Boundary Walls**

### PO 7.1

Dwelling boundary walls are limited in height and length to manage visual and overshadowing impacts on adjoining properties.

### DTS/DPF 7.1

Except where the dwelling is located on a central site within a row dwelling or terrace arrangement, side boundary walls occur only on one side boundary and satisfy (a) or (b) below:

- (a) side boundary walls adjoin or abut a boundary wall of a building on adjoining land for the same or lesser length and height
- (b) side boundary walls do not:
  - (i) exceed 3m in height from the top of footings
  - (ii) exceed 11.5m in length
  - (iii) when combined with other walls on the boundary of the subject development site, exceed a maximum 45% of the length of the boundary
  - (iv) encroach within 3m of any other existing or proposed boundary walls on the subject land.

### PO 7.2

Dwellings in a semi-detached, row or terrace arrangement maintain space between buildings consistent with a suburban streetscape character.

# DTS/DPF 7.2

Dwelling walls in a semi-detached, row or terrace arrangement are setback at least 900mm from side boundaries shared with allotments outside the development site.

# Side boundary setback

# PO 8.1

Building walls are set back from side boundaries to provide:

(a) separation between dwellings in a way that contributes to a suburban character

and

(b) access to natural light and ventilation for neighbours.

# DTS/DPF 8.1

Other than walls located on a side boundary, building walls are set back from side boundaries:

- (a) at least 900mm where the wall height is up to 3m
- (b) other than for a wall facing a southern side boundary, at least 900mm plus 1/3 of the wall height above 3m

and

(c) at least 1900mm plus 1/3 of the wall height above 3m for walls facing a southern side boundary.

# Rear boundary setback

# PO 9.1

Dwelling walls are set back from rear boundaries to provide:

- (a) separation between dwellings in a way that contributes to a suburban character
- (b) access to natural light and ventilation for neighbours

# DTS/DPF 9.1

Dwelling walls are set back from the rear boundary at least:

- (a) if the size of the site is less than 301m<sup>2</sup>—
  - (i) 3m in relation to the ground floor of the dwelling
  - (ii) 5m in relation to any other building level of the dwelling

Page 7 of 126 Printed on 5/07/2022

- (c) private open space
- (d) space for landscaping and vegetation.

- (b) if the size of the site is 301m<sup>2</sup> or more—
  - (i) 4m in relation to the ground floor of the dwelling
  - (ii) 6m in relation to any other building level of the dwelling.

# Concept Plans

### PO 10.1

Development is compatible with the outcomes sought by any relevant Concept Plan contained within Part 12 - Concept Plans of the Planning and Design Code to support the orderly development of land through staging of development and provision of infrastructure.

### **DTS/DPF 10.1**

The site of the development is wholly located outside any relevant Concept Plan boundary. The following Concept Plans are relevant:

In relation to DTS/DPF 10.1, in instances where:

- (a) one or more Concept Plan is returned, refer to Part 12 -Concept Plans in the Planning and Design Code to determine if a Concept Plan is relevant to the site of the proposed development. Note: multiple concept plans may be relevant.
- (b) in instances where 'no value' is returned, there is no relevant concept plan and DTS/DPF 10.1 is met.

# Ancillary Buildings and Structures

### PO 11 1

Residential ancillary buildings are sited and designed to not detract from the streetscape or appearance of primary residential buildings on the site or neighbouring properties.

### DTS/DPF 11.1

# Ancillary buildings:

- (a) are ancillary to a dwelling erected on the same site
- (b) have a floor area not exceeding 60m2
- (c) are not constructed, added to or altered so that any part is situated:
  - in front of any part of the building line of the dwelling to which it is ancillary or
  - (ii) within 900mm of a boundary of the allotment with a secondary street (if the land has boundaries on two or more roads)
- (d) in the case of a garage or carport, the garage or carport:
  - is set back at least 5.5m from the boundary of the primary street
  - (ii) have a door / opening not exceeding:
    - A. for dwellings of single building level 7m in width or 50% of the site frontage, whichever is the lesser
    - B. for dwellings comprising two or more building levels at the building line fronting the same public street 7m in width
- (e) if situated on a boundary (not being a boundary with a primary street or secondary street), do not exceed a length of 11.5m unless:
  - a longer wall or structure exists on the adjacent site and is situated on the same allotment boundary and
  - (ii) the proposed wall or structure will be built along

Page 8 of 126 Printed on 5/07/2022

the same length of boundary as the existing adjacent wall or structure to the same or lesser if situated on a boundary of the allotment (not being a boundary with a primary street or secondary street), all walls or structures on the boundary will not exceed 45% of the length of that boundary will not be located within 3m of any other wall along the same boundary unless on an adjacent site on that boundary there is an existing wall of a building that would be adjacent to or about the proposed wall or structure have a wall height or post height not exceeding 3m (and not including a gable end) have a roof height where no part of the roof is more than 5m above the natural ground level if clad in sheet metal, is pre-colour treated or painted in a non-reflective colour retains a total area of soft landscaping in accordance with (i) or (ii), whichever is less: a total area as determined by the following table: Dwelling site area (or in the case **Minimum** of residential flat building or group percentage of dwelling(s), average site area) (m<sup>2</sup>)<150 10% 150-200 15% 201-450 20% >450 25%

the amount of existing soft landscaping prior to the development occurring.

# PO 11.2

Ancillary buildings and structures do not impede on-site functional requirements such as private open space provision, car parking requirements or result in over-development of the site.

# DTS/DPF 11.2

(g)

(h)

(i)

(k)

(i)

Ancillary buildings and structures do not result in:

- less private open space than specified in Design in Urban (a) Areas Table 1 - Private Open Space
- (b) less on-site car parking than specified in Transport, Access and Parking Table 1 - General Off-Street Car Parking Requirements or Table 2 - Off-Street Car Parking Requirements in Designated Areas.

# Advertisements

Advertisements identify the associated business activity, and do not detract from the residential character of the locality.

# DTS/DPF 12.1

Advertisements relating to a lawful business activity associated with a residential use do not exceed 0.3m2 and mounted flush with a wall or fence.

# Table 5 - Procedural Matters (PM) - Notification

The following table identifies, pursuant to section 107(6) of the Planning, Development and Infrastructure Act 2016, classes of

Printed on 5/07/2022 Page 9 of 126

performance assessed development that are excluded from notification. The table also identifies any exemptions to the placement of notices when notification is required.

# Interpretation

Notification tables exclude the classes of development listed in Column A from notification provided that they do not fall within a corresponding exclusion prescribed in Column B.

Where a development or an element of a development falls within more than one class of development listed in Column A, it will be excluded from notification if it is excluded (in its entirety) under any of those classes of development. It need not be excluded under all applicable classes of development.

Where a development involves multiple performance assessed elements, all performance assessed elements will require notification (regardless of whether one or more elements are excluded in the applicable notification table) unless every performance assessed element of the application is excluded in the applicable notification table, in which case the application will not require notification.

| Class of Development   | Exceptions  |
|--|---|
| (Column A)   | (Column B)  |
| <ol> <li>Development which, in the opinion of the relevant<br/>authority, is of a minor nature only and will not<br/>unreasonably impact on the owners or occupiers of land<br/>in the locality of the site of the development.</li> </ol>   | None specified.   |
| All development undertaken by:         (a) the South Australian Housing Trust either individually or jointly with other persons or bodies or         (b) a provider registered under the Community Housing National Law participating in a program relating to the renewal of housing endorsed by the South Australian Housing Trust.  | <ol> <li>residential flat building(s) of 3 or more building levels</li> <li>the demolition of a State or Local Heritage Place</li> <li>the demolition of a building (except an ancillary building) in a Historic Area Overlay.</li> </ol>   |
| 3. Any development involving any of the following (or of any combination of any of the following):  (a) air handling unit, air conditioning system or exhaust fan  (b) ancillary accommodation  (c) building work on railway land  (d) carport  (e) deck  (f) dwelling  (g) dwelling addition  (h) fence  (i) outbuilding  (j) pergola  (k) private bushfire shelter  (l) residential flat building  (m) retaining wall  (n) retirement facility  (o) shade sail  (p) solar photovoltaic panels (roof mounted)  (q) student accommodation  (r) supported accommodation | <ol> <li>does not satisfy General Neighbourhood Zone DTS/DPF 4.1 or</li> <li>involves a building wall (or structure) that is proposed to be situated on (or abut) an allotment boundary (not being a boundary with a primary street or secondary street or an excluded boundary) and:         <ul> <li>(a) the length of the proposed wall (or structure) exceeds 11.5m (other than where the proposed wall abuts an existing wall or structure of greater length on the adjoining allotment) or</li> <li>(b) the height of the proposed wall (or post height) exceeds 3m measured from the top of footings (other than where the proposed wall (or post) abuts an existing wall or structure of greater height on the adjoining allotment).</li> </ul> </li> </ol> |

Page 10 of 126 Printed on 5/07/2022

None specified.

| (s) swimming pool or spa pool  |  |
|--|--|
| (t) verandah   |  |
| (u) water tank.  |  |
|  |  |
| Any development involving any of the following (or of any  | Except development that:   |
| combination of any of the following):  | Except development that.   |
| (a) consulting room  | 1. does not satisfy any of the following:  |
| (b) office   | (a) General Neighbourhood Zone DTS/DPF 1.4   |
| (c) shop.  | (b) General Neighbourhood Zone DTS/DPF 4.1   |
|  | (1)  |
|  | or   |
|  | <ol><li>involves a building wall (or structure) that is proposed to be<br/>situated on (or abut) an allotment boundary (not being a<br/>boundary with a primary street or secondary street or an<br/>excluded boundary) and:</li></ol>         |
|  | <ul> <li>(a) the length of the proposed wall (or structure)         exceeds 11.5m (other than where the proposed         wall abuts an existing wall or structure of greater         length on the adjoining allotment)         or</li> </ul>  |
|  | (b) the height of the proposed wall (or post height)<br>exceeds 3m measured from the top of<br>footings (other than where the proposed wall (or<br>post) abuts an existing wall or structure of greater<br>height on the adjoining allotment). |
| 5. Any development involving any of the following (or of any combination of any of the following):   | None specified.  |
| (a) internal building works  |  |
| (b) land division  |  |
| (c) recreation area  |  |
| (d) replacement building   |  |
| (e) temporary accommodation in an area affected by bushfire  |  |
| (f) tree damaging activity.  |  |
|  |  |
| <ul> <li>6. Alteration of or addition to any development involving the following (or of any combination of any of the following):</li> <li>(a) community facility</li> <li>(b) educational establishment</li> <li>(c) pre-school.</li> </ul> | Except development that does not satisfy General Neighbourhood Zone DTS/DPF 1.5.   |
| 7. Demolition.   | Except any of the following:   |
|  | <ol> <li>the demolition of a State or Local Heritage Place</li> <li>the demolition of a building (except an ancillary building) in<br/>a Historic Area Overlay.</li> </ol>   |
| Placement of Notices - Exemptions for Performance Assessed   | Development  |

Page 11 of 126 Printed on 5/07/2022

# Placement of Notices - Exemptions for Restricted Development

None specified.

# Part 3 - Overlays

# **Affordable Housing Overlay**

# **Assessment Provisions (AP)**

|      | Desired Outcome  |  |  |
|------|--|--|--|
| DO 1 | Affordable housing is integrated with residential and mixed use development. |  |  |
| DO 2 | Affordable housing caters for a variety of household structures.             |  |  |

Performance Outcomes (PO) and Deemed-to-Satisfy (DTS) Criteria / Designated Performance Feature (DPF)

| Performance Outcome  | Deemed-to-Satisfy Criteria / Designated Performance Feature   |
|--|---|
| Land   | Division  |
| PO 1.1   | DTS/DPF 1.1   |
| Development comprising 20 or more dwellings / allotments incorporates affordable housing.  | Development results in 0-19 additional allotments / dwellings.  |
| PO 1.2   | DTS/DPF 1.2   |
| Development comprising 20 or more dwellings or residential allotments provides housing suited to a range of incomes including households with low to moderate incomes. | Development comprising 20 or more dwellings / or residential allotments includes a minimum of 15% affordable housing except where:  (a) it can be demonstrated that any shortfall in affordable housing has been provided in a previous stage of development or  (b) it can be demonstrated that any shortfall in affordable housing will be accommodated in a subsequent stage or stages of development. |
| PO 1.3   | DTS/DPF 1.3   |
| Affordable housing is distributed throughout the development to avoid an overconcentration.  | None are applicable.  |
| Built Form a   | and Character   |
| PO 2.1   | DTS/DPF 2.1   |

Page 12 of 126 Printed on 5/07/2022

Affordable housing is designed to complement the design and character of residential development within the locality.

None are applicable.

## Affordable Housing Incentives

# PO 3.1

To support the provision of affordable housing, minimum allotment sizes may be reduced below the minimum allotment size specified in a zone while providing allotments of a suitable size and dimension to accommodate dwellings with a high standard of occupant amenity.

## DTS/DPF 3.1

The minimum site area specified for a dwelling can be reduced by up to 20%, or the maximum density per hectare increased by up to 20%, where it is to be used to accommodate affordable housing except where the development is located within the Character Area Overlay or Historic Area Overlay.

### PO 3.2

To support the provision of affordable housing, building heights may be increased above the maximum specified in a zone.

### DTS/DPF 3.2

Where a building incorporates dwellings above ground level and includes at least 15% affordable housing, the maximum building height specified in any relevant zone policy can be increased by 1 building level in the:

- (a) Business Neighbourhood Zone
- (b) City Living Zone
- (c) Established Neighbourhood Zone
- (d) General Neighbourhood Zone
- (e) Hills Neighbourhood Zone
- (f) Housing Diversity Neighbourhood Zone
- (g) Neighbourhood Zone
- (h) Master Planned Neighbourhood Zone
- (i) Master Planned Renewal Zone
- (j) Master Planned Township Zone
- (k) Rural Neighbourhood Zone
- (I) Suburban Business Zone
- (m) Suburban Neighbourhood Zone
- (n) Township Neighbourhood Zone
- (o) Township Zone
- (p) Urban Renewal Neighbourhood Zone
- (q) Waterfront Neighbourhood Zone

and up to 30% in any other zone, except where:

- (a) the development is located within the Character Area Overlay or Historic Area Overlay or
- (b) other height incentives already apply to the development.

# Movement and Car Parking

# PO 4.1

Sufficient car parking is provided to meet the needs of occupants of affordable housing.

# DTS/DPF 4.1

Dwellings constituting affordable housing are provided with car parking in accordance with the following:

- (a) 0.3 carparks per dwelling within a building which incorporates dwellings located above ground level within either:
  - 200 metres of any section of road reserve along which a bus service operates as a high frequency public transit service<sup>(2)</sup>
  - (ii) is within 400 metres of a bus interchange<sup>(1)</sup>
  - (iii) is within 400 metres of an O-Bahn interchange<sup>(1)</sup>

Page 13 of 126 Printed on 5/07/2022

| 1 Olloy24 - Eliquii y |  |  |
|-----------------------|--|--|
|                       | (iv) is within 400 metres of a passenger rail station <sup>(1)</sup>   |  |
|                       | (v) is within 400 metres of a passenger tram station <sup>(1)</sup>  |  |
|                       | (vi) is within 400 metres of the Adelaide Parklands.   |  |
|                       | or   |  |
|                       | (b) 1 carpark per dwelling for any other dwelling.   |  |
|                       |  |  |
|                       | [NOTE(S): (1) Measured from an area that contains any platform(s), shelter(s) or stop(s) where people congregate for the |  |
|                       | purpose waiting to board a bus, tram or train, but does not include  |  |
|                       | areas used for the parking of vehicles. (2) A high frequency public  |  |
|                       | transit service is a route serviced every 15 minutes between 7.30am and 6.30pm Monday to Friday and every 30 minutes at  |  |
|                       | night, Saturday, Sunday and public holidays until 10pm.]   |  |
|                       | g, catalaay, canaay and rondays until roping   |  |
|                       |  |  |

# Procedural Matters (PM) - Referrals

The following table identifies classes of development / activities that require referral in this Overlay and the applicable referral body. It sets out the purpose of the referral as well as the relevant statutory reference from Schedule 9 of the Planning, Development and Infrastructure (General) Regulations 2017.

| Class of Development / Activity   |   | Purpose of<br>Referral   | Statutory<br>Reference  |
|---|---|--|---|
| Development for the purposes of the provision of affordable housing (applying the criteria determined under regulation 4 of the South Australian Housing Trust Regulations 2010). | Minister responsible for administering the South Australian Housing Trust Act 1995. | To provide direction on the conditions required to secure the provision of dwellings or allotments for affordable housing. | Development of a class to which Schedule 9 clause 3 item 20 of the Planning, Development and Infrastructure (General) Regulations 2017 applies. |

# Airport Building Heights (Regulated) Overlay

# **Assessment Provisions (AP)**

|      | Desired Outcome   |
|------|---|
| DO 1 | Management of potential impacts of buildings and generated emissions to maintain operational and safety requirements of registered and certified commercial and military airfields, airports, airstrips and helicopter landing sites. |

Performance Outcomes (PO) and Deemed-to-Satisfy (DTS) Criteria / Designated Performance Feature (DPF)

Page 14 of 126 Printed on 5/07/2022

| Performance Outcome  | Deemed-to-Satisfy Criteria / Designated Performance Feature   |
|--|---|
| Built  | Form  |
| PO 1.1  Building height does not pose a hazard to the operation of a certified or registered aerodrome.  | DTS/DPF 1.1  Buildings are located outside the area identified as 'All structures' (no height limit is prescribed) and do not exceed the height specified in the Airport Building Heights (Regulated) Overlay which applies to the subject site as shown on the SA Property and Planning Atlas.  In instances where more than one value applies to the site, the lowest value relevant to the site of the proposed development is applicable. |
| PO 1.2  Exhaust stacks are designed and sited to minimise plume impacts on aircraft movements associated with a certified or registered aerodrome. | DTS/DPF 1.2  Development does not include exhaust stacks.   |

# Procedural Matters (PM) - Referrals

The following table identifies classes of development / activities that require referral in this Overlay and the applicable referral body. It sets out the purpose of the referral as well as the relevant statutory reference from Schedule 9 of the Planning, Development and Infrastructure (General) Regulations 2017.

| Class of Development / Activity  | Referral Body   | Purpose of Referral   | Statutory Reference   |
|--|---|---|---|
| <ul> <li>Any of the following classes of development:</li> <li>(a) building located in an area identified as 'All structures' (no height limit is prescribed) or will exceed the height specified in the Airport Building Heights (Regulated) Overlay</li> <li>(b) building comprising exhaust stacks that generates plumes, or may cause plumes to be generated, above a height specified in the Airport Building Heights (Regulated) Overlay.</li> </ul> | The airport-operator company for the relevant airport within the meaning of the <i>Airports Act 1996</i> of the Commonwealth or, if there is no airport-operator company, the Secretary of the Minister responsible for the administration of the <i>Airports Act 1996</i> of the Commonwealth. | To provide expert assessment and direction to the relevant authority on potential impacts on the safety and operation of aviation activities. | Development of a class to<br>which Schedule 9 clause 3<br>item 1 of the Planning,<br>Development and<br>Infrastructure (General)<br>Regulations 2017 applies. |

# Hazards (Flooding - Evidence Required) Overlay

# **Assessment Provisions (AP)**

| Desired Outcome |   |  |
|-----------------|---|--|
| DO 1            | Development adopts a precautionary approach to mitigate potential impacts on people, property, infrastructure and the environment from potential flood risk through the appropriate siting and design of development. |  |

Performance Outcomes (PO) and Deemed-to-Satisfy (DTS) Criteria / Designated Performance Feature (DPF)

| i diffiliation datability britaria | Performance Outcome | Deemed-to-Satisfy Criteria / |
|------------------------------------|---------------------|------------------------------|
|------------------------------------|---------------------|------------------------------|

Page 15 of 126 Printed on 5/07/2022

|   | Designated Performance<br>Feature   |
|---|---|
|   | realuie   |
| Flood R   | esilience   |
| PO 1.1  | DTS/DPF 1.1   |
| Development is sited, designed and constructed to minimise the risk of entry of potential floodwaters where the entry of flood waters is likely to result in undue damage to or compromise ongoing activities within buildings. | Habitable buildings, commercial and industrial buildings, and buildings used for animal keeping incorporate a finished floor level at least 300mm above:  (a) the highest point of top of kerb of the primary street or (b) the highest point of natural ground level at the primary street boundary where there is no kerb |
| Environmen  | tal Protection  |
| PO 2.1  | DTS/DPF 2.1   |
| Buildings and structures used either partly or wholly to contain or store hazardous materials are designed to prevent spills or leaks leaving the confines of the building.   | Development does not involve the storage of hazardous materials.  |

# Procedural Matters (PM) - Referrals

The following table identifies classes of development / activities that require referral in this Overlay and the applicable referral body. It sets out the purpose of the referral as well as the relevant statutory reference from Schedule 9 of the Planning, Development and Infrastructure (General) Regulations 2017.

| Class of Development / Activity | Referral Body | Purpose of Referral | Statutory<br>Reference |
|---------------------------------|---------------|---------------------|------------------------|
| None                            | None          | None                | None                   |

# **Prescribed Wells Area Overlay**

# **Assessment Provisions (AP)**

| Desired Outcome |  |  |
|-----------------|--|--|
| DO 1            | Sustainable water use in prescribed wells areas. |  |

| Performance Outcome  | Deemed-to-Satisfy Criteria / Designated Performance Feature  |
|--|--|
| PO 1.1   | DTS/DPF 1.1  |
| All development, but in particular involving any of the following: | Development satisfies either of the following:   |
| (a) horticulture (b) activities requiring irrigation               | (a) the applicant has a current water licence in which sufficient spare capacity exists to accommodate the water |

Page 16 of 126 Printed on 5/07/2022

- (c) aquaculture
- (d) industry
- (e) intensive animal husbandry
- (f) commercial forestry

has a lawful, sustainable and reliable water supply that does not place undue strain on water resources in prescribed wells areas.

needs of the proposed use

(b) the proposal does not involve the taking of water for which a licence would be required under the *Landscape South Australia Act 2019*.

# **Procedural Matters (PM) - Referrals**

The following table identifies classes of development / activities that require referral in this Overlay and the applicable referral body. It sets out the purpose of the referral as well as the relevant statutory reference from Schedule 9 of the Planning, Development and Infrastructure (General) Regulations 2017.

| Class of Development / Activity   | Referral Body   | Purpose of Referral  | Statutory<br>Reference  |
|---|---|--|---|
| Any of the following classes of development that require or may require water to be taken in addition to any allocation that has already been granted under the Landscape South Australia Act 2019:  (a) horticulture (b) activities requiring irrigation (c) aquaculture (d) industry (e) intensive animal husbandry (f) commercial forestry.  Commercial forestry that requires a forest water licence under Part 8 Division 6 of the Landscape South Australia Act 2019. | The Chief Executive of the Department of the Minister responsible for the administration of the Landscape South Australia Act 2019. | To provide expert technical assessment and direction to the relevant authority on the taking of water to ensure development is undertaken sustainably. | Development of a class to which Schedule 9 clause 3 item 13 of the Planning, Development and Infrastructure (General) Regulations 2017 applies. |

# **Regulated and Significant Tree Overlay**

**Assessment Provisions (AP)** 

|      | Desired Outcome   |
|------|---|
| DO 1 | Conservation of regulated and significant trees to provide aesthetic and environmental benefits and mitigate tree loss. |

Performance Outcomes (PO) and Deemed to Satisfy (DTS) / Designated Performance Feature (DPF) Criteria

| Perform | ance Outcome | Deemed-to-Satisfy Criteria / Designated Performance Feature |
|---------|--------------|---|
|         | Tree Retenti | on and Health   |
| PO 1.1  |              | DTS/DPF 1.1   |

Page 17 of 126 Printed on 5/07/2022

Regulated trees are retained where they: None are applicable. (a) make an important visual contribution to local character and amenity (b) are indigenous to the local area and listed under the National Parks and Wildlife Act 1972 as a rare or endangered native species and / or (c) provide an important habitat for native fauna. PO 1.2 DTS/DPF 1.2 Significant trees are retained where they: None are applicable. (a) make an important contribution to the character or amenity of the local area (b) are indigenous to the local area and are listed under the National Parks and Wildlife Act 1972 as a rare or endangered native species (c) represent an important habitat for native fauna (d) are part of a wildlife corridor of a remnant area of native vegetation (e) are important to the maintenance of biodiversity in the local environment and / or (f) form a notable visual element to the landscape of the local PO 1.3 DTS/DPF 1.3 A tree damaging activity not in connection with other development None are applicable. satisfies (a) and (b): (a) tree damaging activity is only undertaken to: remove a diseased tree where its life expectancy (i) mitigate an unacceptable risk to public or private (ii) safety due to limb drop or the like rectify or prevent extensive damage to a building of value as comprising any of the following: A. a Local Heritage Place В. a State Heritage Place a substantial building of value and there is no reasonable alternative to rectify or prevent such damage other than to undertake a tree damaging activity reduce an unacceptable hazard associated with a tree within 20m of an existing residential, tourist accommodation or other habitable building from bushfire treat disease or otherwise in the general interests of the health of the tree and / or (vi) maintain the aesthetic appearance and structural integrity of the tree (b) in relation to a significant tree, tree-damaging activity is avoided unless all reasonable remedial treatments and measures have been determined to be ineffective.

Page 18 of 126 Printed on 5/07/2022

Policy24 - Enquiry

Policy24 - Enquiry

A tree-damaging activity in connection with other development satisfies all the following:

(a) it accommodates the reasonable development of land in accordance with the relevant zone or subzone where such development might not otherwise be possible

(b) in the case of a significant tree, all reasonable development options and design solutions have been considered to prevent substantial tree-damaging activity occurring.

Ground work

Policy24 - Enquiry

A tree-damaging activity in connection with other development of land in accordance with the relevant zone or subzone where such development might not otherwise be possible

(b) in the case of a significant tree, all reasonable development options and design solutions have been considered to prevent substantial tree-damaging activity occurring.

DTS/DPF 1.4

None are applicable.

Ground work affecting trees

Regulated and significant trees, including their root systems, are not unduly compromised by excavation and / or filling of land, or the sealing of surfaces within the vicinity of the tree to support their retention and health.

DTS/DPF 2.1

None are applicable.

Land Division

PO 3.1

Land division results in an allotment configuration that enables its subsequent development and the retention of regulated and significant trees as far as is reasonably practicable.

DTS/DPF 3.1

Land division where:

- (a) there are no regulated or significant trees located within or adjacent to the plan of division
- (b) the application demonstrates that an area exists to accommodate subsequent development of proposed allotments after an allowance has been made for a tree protection zone around any regulated tree within and adjacent to the plan of division.

# Procedural Matters (PM) - Referrals

The following table identifies classes of development / activities that require referral in this Overlay and the applicable referral body. It sets out the purpose of the referral as well as the relevant statutory reference from Schedule 9 of the Planning, Development and Infrastructure (General) Regulations 2017.

| Class of Development / Activity | Referral Body | Purpose of Referral | Statutory<br>Reference |
|---------------------------------|---------------|---------------------|------------------------|
| None                            | None          | None                | None                   |

# **Stormwater Management Overlay**

**Assessment Provisions (AP)** 

|      | Desired Outcome  |
|------|--|
| DO 1 | Development incorporates water sensitive urban design techniques to capture and re-use stormwater. |

**Performance Outcome** 

Deemed-to-Satisfy Criteria / Designated Performance

Page 19 of 126 Printed on 5/07/2022

# Policy24 - Enquiry **Feature** PO 1.1 DTS/DPF 1.1 Residential development is designed to capture and re-use Residential development comprising detached, semi-detached or stormwater to: row dwellings, or less than 5 group dwellings or dwellings within a residential flat building: (a) maximise conservation of water resources (a) includes rainwater tank storage: (b) manage peak stormwater runoff flows and volume to ensure the carrying capacities of downstream systems are (i) connected to at least: not overloaded in relation to a detached dwelling (not in (c) manage stormwater runoff quality. a battle-axe arrangement), semidetached dwelling or row dwelling, 60% of the roof area В. in all other cases, 80% of the roof area (ii) connected to either a toilet, laundry cold water outlets or hot water service for sites less than 200m<sup>2</sup> (iii) connected to one toilet and either the laundry cold water outlets or hot water service for sites of 200m<sup>2</sup> or greater (iv) with a minimum total capacity in accordance with Table 1 (v) where detention is required, includes a 20-25 mm diameter slow release orifice at the bottom of the detention component of the tank (b) incorporates dwelling roof area comprising at least 80% of the site's impervious area Table 1: Rainwater Tank Site size Minimum detention Minimum volume (Litres) (m<sup>2</sup>)retention volume (Litres) <200 1000 1000 200-400 2000 Site perviousness <30%: 1000

# Procedural Matters (PM) - Referrals

The following table identifies classes of development / activities that require referral in this Overlay and the applicable referral body. It sets out the purpose of the referral as well as the relevant statutory reference from Schedule 9 of the Planning, Development and Infrastructure (General) Regulations 2017.

>401

4000

Site perviousness ≥30%: N/A

Site perviousness <35%: 1000

Site perviousness ≥35%: N/A

Page 20 of 126 Printed on 5/07/2022

| Class of Development / Activity | Referral Body |      | Statutory<br>Reference |
|---------------------------------|---------------|------|------------------------|
| None                            | None          | None | None                   |

# **Urban Tree Canopy Overlay**

# Assessment Provisions (AP)

|      | Desired Outcome   |
|------|---|
| DO 1 | Residential development preserves and enhances urban tree canopy through the planting of new trees and retention of |
|      | existing mature trees where practicable.  |

| Performance Outcome  |              | signat                        |                               | y Criteria /<br>formance                                      |
|--|--------------|-------------------------------|-------------------------------|---|
| PO 1.1   | DTS/DPF 1.1  |                               |                               |   |
| Trees are planted or retained to contribute to an urban tree canopy. |              | ith the following:            |                               |   |
|  | Site size p  | er dwelling                   | Tree size* a dwelling         | nd number required per  |
|  | <450         |                               | 1 small tree                  |   |
|  | 450-800      |                               | 1 medium tro                  | ee or 2 small trees   |
|  | >800         |                               | 1 large tree<br>small trees   | or 2 medium trees or 4  |
|  | *refer Table | 1 Tree Size                   |                               |   |
|  | Table 1 Tre  | ee Size                       |                               |   |
|  | Tree size    | Mature<br>height<br>(minimum) | Mature<br>spread<br>(minimum) | Soil area around tree<br>within development<br>site (minimum) |
|  | Small        | 4 m                           | 2m                            | 10m <sup>2</sup> and min.<br>dimension of 1.5m                |
|  | Medium       | 6 m                           | 4 m                           | 30m <sup>2</sup> and min.<br>dimension of 2m                  |
|  | Large        | 12 m                          | 8m                            | 60m <sup>2</sup> and min.<br>dimension of 4m                  |

Page 21 of 126 Printed on 5/07/2022

The discount in Column D of Table 2 discounts the number of trees required to be planted in DTS/DPF 1.1 where existing tree(s) are retained on the subject land that meet the criteria in Columns A, B and C of Table 2, and are not a species identified in Regulation 3F(4)(b) of the Planning Development and Infrastructure (General) Regulations 2017.

| Table 2 Tree Discounts                   |                                       |  |   |
|--|---------------------------------------|--|---|
| Retained<br>tree height<br>(Column<br>A) | Retained tree<br>spread<br>(Column B) | Retained soil<br>area around<br>tree within<br>development<br>site<br>(Column C) | Discount applied (Column D)                               |
| 4-6m                                     | 2-4m                                  | 10m <sup>2</sup> and min.<br>dimension of<br>1.5m                                | 2 small trees (or<br>1 medium tree)                       |
| 6-12m                                    | 4-8m                                  | 30m <sup>2</sup> and min.<br>dimension of<br>3m                                  | 2 medium trees<br>(or 4 small trees)                      |
| >12m                                     | >8m                                   | 60m <sup>2</sup> and min.<br>dimension of<br>6m                                  | 2 large trees (or<br>4 medium trees,<br>or 8 small trees) |

Note: In order to satisfy DTS/DPF 1.1, payment may be made in accordance with a relevant off-set scheme established by the Minister under section 197 of the Planning, Development and Infrastructure Act 2016, provided the provisions and requirements of that scheme are satisfied. For the purposes of section 102(4) of the Planning, Development and Infrastructure Act 2016, an applicant may elect for any of the matters in DTS/DPF 1.1 to be reserved.

# Procedural Matters (PM) - Referrals

The following table identifies classes of development / activities that require referral in this Overlay and the applicable referral body. It sets out the purpose of the referral as well as the relevant statutory reference from Schedule 9 of the Planning, Development and Infrastructure (General) Regulations 2017.

| Class of Development / Activity | Referral Body |      | Statutory<br>Reference |
|---------------------------------|---------------|------|------------------------|
| None                            | None          | None | None                   |

# Part 4 - General Development Policies

Page 22 of 126 Printed on 5/07/2022

# **Advertisements**

# **Assessment Provisions (AP)**

| Desired Outcome |  |  |  |
|-----------------|--|--|--|
| DO 1            | Advertisements and advertising hoardings are appropriate to context, efficient and effective in communicating with the public, limited in number to avoid clutter, and do not create hazard. |  |  |

Performance Outcomes (PO) and Deemed-to-Satisfy (DTS) Criteria / Designated Performance Feature (DPF)

# **Performance Outcome** Deemed-to-Satisfy Criteria / **Designated Performance Feature** Appearance PO 1.1 DTS/DPF 1.1 Advertisements are compatible and integrated with the design of the Advertisements attached to a building satisfy all of the following: building and/or land they are located on. (a) are not located in a Neighbourhood-type zone (b) where they are flush with a wall: if located at canopy level, are in the form of a fascia sign if located above canopy level: do not have any part rising above parapet height are not attached to the roof of the building (c) where they are not flush with a wall: if attached to a verandah, no part of the advertisement protrudes beyond the outer limits of the verandah structure if attached to a two-storey building: has no part located above the finished

(d) if located below canopy level, are flush with a wall

(e) if located at canopy level, are in the form of a fascia sign

1m2 per side.

floor level of the second storey of the

of any verandah structure below

does not protrude beyond the outer limits

does not have a sign face that exceeds

(f) if located above a canopy:

B.

C.

(i) are flush with a wall

Page 23 of 126 Printed on 5/07/2022

| • • •  |  |
|--|--|
|  | do not have any part rising above parapet height     iii) are not attached to the roof of the building.  |
|  | (g) if attached to a verandah, no part of the advertisement  |
|  | protrudes beyond the outer limits of the verandah structure  (h) if attached to a two-storey building, have no part located above the finished floor level of the second storey of the |
|  | building  (i) where they are flush with a wall, do not, in combination with any other existing sign, cover more than 15% of the building facade to which they are attached.            |
| PO 1.2   | DTS/DPF 1.2  |
| Advertising hoardings do not disfigure the appearance of the land upon which they are situated or the character of the locality. | Where development comprises an advertising hoarding, the supporting structure is:  |
|  | (a) concealed by the associated advertisement and decorative detailing or     (b) not visible from an adjacent public street or thoroughfare,  |
|  | other than a support structure in the form of a single or dual post design.  |
| PO 1.3   | DTS/DPF 1.3  |
| Advertising does not encroach on public land or the land of an adjacent allotment.   | Advertisements and/or advertising hoardings are contained within the boundaries of the site.   |
| PO 1.4   | DTS/DPF 1.4  |
| Where possible, advertisements on public land are integrated with existing structures and infrastructure.                        | Advertisements on public land that meet at least one of the following:   |
|  | (a) achieves Advertisements DTS/DPF 1.1     (b) are integrated with a bus shelter.   |
| PO 1.5   | DTS/DPF 1.5  |
| Advertisements and/or advertising hoardings are of a scale and size appropriate to the character of the locality.                | None are applicable.   |
| Proliferation of   | Advertisements   |
| PO 2.1   | DTS/DPF 2.1  |
| Proliferation of advertisements is minimised to avoid visual clutter and untidiness.   | No more than one freestanding advertisement is displayed per occupancy.  |
| PO 2.2   | DTS/DPF 2.2  |
| Multiple business or activity advertisements are co-located and coordinated to avoid visual clutter and untidiness.              | Advertising of a multiple business or activity complex is located on a single advertisement fixture or structure.  |
| PO 2.3   | DTS/DPF 2.3  |
| Proliferation of advertisements attached to buildings is minimised to avoid visual clutter and untidiness.                       | Advertisements satisfy all of the following:   |
|  | (a) are attached to a building   |
|  | (b) other than in a Neighbourhood-type zone, where they are flush with a wall, cover no more than 15% of the building facade to which they are attached                                |
|  | (c) do not result in more than one sign per occupancy that is  |

Page 24 of 126 Printed on 5/07/2022

|  | not flush with a wall.  |
|--|---|
| Advertis   | ing Content   |
| PO 3.1   | DTS/DPF 3.1   |
| Advertisements are limited to information relating to the lawful use of land they are located on to assist in the ready identification of the activity or activities on the land and avoid unrelated content that contributes to visual clutter and untidiness.  | Advertisements contain information limited to a lawful existing or proposed activity or activities on the same site as the advertisement.   |
| Amen   | ty Impacts  |
| PO 4.1   | DTS/DPF 4.1   |
| Light spill from advertisement illumination does not unreasonably compromise the amenity of sensitive receivers.   | Advertisements do not incorporate any illumination.   |
| 5  | afety   |
| PO 5.1   | DTS/DPF 5.1   |
| Advertisements and/or advertising hoardings erected on a veranda or projecting from a building wall are designed and located to allow for safe and convenient pedestrian access.   | Advertisements have a minimum clearance of 2.5m between the top of the footpath and base of the underside of the sign.  |
| PO 5.2   | DTS/DPF 5.2   |
| Advertisements and/or advertising hoardings do not distract or create a hazard to drivers through excessive illumination.  | No advertisement illumination is proposed.  |
| PO 5.3   | DTS/DPF 5.3   |
| Advertisements and/or advertising hoardings do not create a hazar to drivers by:  (a) being liable to interpretation by drivers as an official traffic sign or signal  (b) obscuring or impairing drivers' view of official traffic signs or signals  (c) obscuring or impairing drivers' view of features of a road that are potentially hazardous (such as junctions, bends, changes in width and traffic control devices) or other road or rail vehicles at/or approaching level crossings. | (a) are not located in a public road or rail reserve  (b) are located wholly outside the land shown as 'Corner Cut- Off Area' in the following diagram  Corner Cut- Off Area  Allotment Boundary  |
| PO 5.4   | DTS/DPF 5.4   |
| Advertisements and/or advertising hoardings do not create a hazar by distracting drivers from the primary driving task at a location where the demands on driver concentration are high.   | Advertisements and/or advertising hoardings are not located along or adjacent to a road having a speed limit of 80km/h or more.   |
| PO 5.5   | DTS/DPF 5.5   |
| Advertisements and/or advertising hoardings provide sufficient clearance from the road carriageway to allow for safe and convenient movement by all road users.  | (a) on a kerbed road with a speed zone of 60km/h or less, the advertisement or advertising hoarding is located at least 0.6m from the roadside edge of the kerb  (b) on an unkerbed road with a speed zone of 60km/h or less, the advertisement or advertising hoarding is located at least 5.5m from the edge of the seal  (c) on any other kerbed or unkerbed road, the advertisement or advertising hoarding is located a minimum of the |

Page 25 of 126 Printed on 5/07/2022

|   | following distance from the roadside edge of the kerb or the seal:   |  |
|---|--|--|
|   | <ul> <li>(a) 110 km/h road - 14m</li> <li>(b) 100 km/h road - 13m</li> <li>(c) 90 km/h road - 10m</li> <li>(d) 70 or 80 km/h road - 8.5m.</li> </ul>               |  |
| PO 5.6 Advertising near signalised intersections does not cause unreasonable distraction to road users through illumination, flashing lights, or moving or changing displays or messages. | DTS/DPF 5.6  Advertising:  (a) is not illuminated  (b) does not incorporate a moving or changing display or message  (c) does not incorporate a flashing light(s). |  |

# **Animal Keeping and Horse Keeping**

# **Assessment Provisions (AP)**

| Desired Outcome |  |  |
|-----------------|--|--|
| DO 1            | Animals are kept at a density that is not beyond the carrying capacity of the land and in a manner that minimises their adverse effects on the environment, local amenity and surrounding development. |  |

Performance Outcomes (PO) and Deemed-to-Satisfy (DTS) Criteria / Designated Performance Feature (DPF)

| Performance Outcome   | Deemed-to-Satisfy Criteria / Designated Performance Feature |  |
|---|---|--|
| Siting ar   | nd Design   |  |
| PO 1.1  | DTS/DPF 1.1   |  |
| Animal keeping, horse keeping and associated activities do not create adverse impacts on the environment or the amenity of the locality.              | None are applicable.  |  |
| PO 1.2  | DTS/DPF 1.2   |  |
| Animal keeping and horse keeping is located and managed to minimise the potential transmission of disease to other operations where animals are kept. | None are applicable.  |  |
| Horse Keeping   |   |  |
| PO 2.1  | DTS/DPF 2.1   |  |
| Water from stable wash-down areas is directed to appropriate absorption areas and/or drainage pits to minimise pollution of land and water.           | None are applicable.  |  |

Page 26 of 126 Printed on 5/07/2022

|   | ,   |
|---|---|
| PO 2.2  | DTS/DPF 2.2   |
| Stables, horse shelters or associated yards are sited appropriate distances away from sensitive receivers and/or allotments in other ownership to avoid adverse impacts from dust, erosion and odour.                     | Stables, horse shelters and associated yards are sited in accordance with all of the following:  (a) 30m or more from any sensitive receivers (existing or approved) on land in other ownership  (b) where an adjacent allotment is vacant and in other ownership, 30m or more from the boundary of that allotment. |
| PO 2.3  | DTS/DPF 2.3   |
| All areas accessible to horses are separated from septic tank effluent disposal areas to protect the integrity of that system. Stable flooring is constructed with an impervious material to facilitate regular cleaning. | Septic tank effluent disposal areas are enclosed with a horse-proof barrier such as a fence to exclude horses from this area.   |
| PO 2.4  | DTS/DPF 2.4   |
| To minimise environmental harm and adverse impacts on water resources, stables, horse shelters and associated yards are appropriately set back from a watercourse.  | Stables, horse shelters and associated yards are set back 50m or more from a watercourse.   |
| PO 2.5  | DTS/DPF 2.5   |
| Stables, horse shelters and associated yards are located on slopes that are stable to minimise the risk of soil erosion and water runoff.   | Stables, horse shelters and associated yards are not located on land with a slope greater than 10% (1-in-10).   |
| Ker   | nnels   |
| PO 3.1  | DTS/DPF 3.1   |
| Kennel flooring is constructed with an impervious material to facilitate regular cleaning.  | The floors of kennels satisfy all of the following:  (a) are constructed of impervious concrete  (b) are designed to be self-draining when washed down.   |
| PO 3.2  | DTS/DPF 3.2   |
| Kennels and exercise yards are designed and sited to minimise noise nuisance to neighbours through measures such as:  | Kennels are sited 500m or more from the nearest sensitive receiver on land in other ownership.  |
| <ul><li>(a) adopting appropriate separation distances</li><li>(b) orientating openings away from sensitive receivers.</li></ul>   |   |
| PO 3.3  | DTS/DPF 3.3   |
| Dogs are regularly observed and managed to minimise nuisance impact on adjoining sensitive receivers from animal behaviour.   | Kennels are sited in association with a permanent dwelling on the land.   |
| Wa  | stes  |
| PO 4.1  | DTS/DPF 4.1   |
| Storage of manure, used litter and other wastes (other than wastewater lagoons) is designed, constructed and managed to minimise attracting and harbouring vermin.  | None are applicable.  |
| PO 4.2  | DTS/DPF 4.2   |
| Facilities for the storage of manure, used litter and other wastes (other than wastewater lagoons) are located to minimise the potential for polluting water resources.   | Waste storage facilities (other than wastewater lagoons) are located outside the 1% AEP flood event areas.  |

Page 27 of 126 Printed on 5/07/2022

# **Aquaculture**

# **Assessment Provisions (AP)**

|      | Desired Outcome   |  |  |  |
|------|---|--|--|--|
| DO 1 | Aquaculture facilities are developed in an ecologically, economically and socially sustainable manner to support an equitable sharing of marine, coastal and inland resources and mitigate conflict with other water-based and land-based uses. |  |  |  |

Performance Outcomes (PO) and Deemed-to-Satisfy (DTS) Criteria / Designated Performance Feature (DPF)

| Performance Outcome  | Deemed-to-Satisfy Criteria / Designated Performance Feature   |
|--|---|
| Land-based   | Aquaculture   |
| PO 1.1   | DTS/DPF 1.1   |
| Land-based aquaculture and associated components are sited and designed to mitigate adverse impacts on nearby sensitive receivers.   | Land-based aquaculture and associated components are located to satisfy all of the following:  (a) 200m or more from a sensitive receiver in other ownership  (b) 500m or more from the boundary of a zone primarily intended to accommodate sensitive receivers. |
| PO 1.2   | DTS/DPF 1.2   |
| Land-based aquaculture and associated components are sited and designed to prevent surface flows from entering ponds in a 1% AEP sea flood level event.  | None are applicable.  |
| PO 1.3   | DTS/DPF 1.3   |
| Land-based aquaculture and associated components are sited and designed to prevent pond leakage that would pollute groundwater.  | None are applicable.  |
| PO 1.4   | DTS/DPF 1.4   |
| Land-based aquaculture and associated components are sited and designed to prevent farmed species escaping and entering into any waters.   | None are applicable.  |
| PO 1.5   | DTS/DPF 1.5   |
| Land-based aquaculture and associated components, including intake and discharge pipes, are designed to minimise the need to traverse sensitive areas to minimise impact on the natural environment. | None are applicable.  |
| PO 1.6   | DTS/DPF 1.6   |

Page 28 of 126 Printed on 5/07/2022

| Policy24 - Eriquity   |  |
|---|--|
| Pipe inlets and outlets associated with land-based aquaculture are sited and designed to minimise the risk of disease transmission.   | None are applicable.   |
| PO 1.7  | DTS/DPF 1.7  |
| Storage areas associated with aquaculture activity are integrated with the use of the land and sited and designed to minimise their visual impact on the surrounding environment.   | None are applicable.   |
| Marine Based  | d Aquaculture  |
| PO 2.1  | DTS/DPF 2.1  |
| Marine aquaculture is sited and designed to minimise its adverse impacts on sensitive ecological areas including:   | None are applicable.   |
| <ul> <li>(a) creeks and estuaries</li> <li>(b) wetlands</li> <li>(c) significant seagrass and mangrove communities</li> <li>(d) marine habitats and ecosystems.</li> </ul>  |  |
| PO 2.2  | DTS/DPF 2.2  |
| Marine aquaculture is sited in areas with adequate water current to disperse sediments and dissolve particulate wastes to prevent the build-up of waste that may cause environmental harm.  | None are applicable.   |
| PO 2.3  | DTS/DPF 2.3  |
| Marine aquaculture is designed to not involve discharge of human waste on the site, on any adjacent land or into nearby waters.   | None are applicable.   |
| PO 2.4  | DTS/DPF 2.4  |
| Marine aquaculture (other than inter-tidal aquaculture) is located an appropriate distance seaward of the high water mark.  | Marine aquaculture development is located 100m or more seaward of the high water mark. |
| PO 2.5  | DTS/DPF 2.5  |
| Marine aquaculture is sited and designed to not obstruct or interfere with:   | None are applicable.   |
| <ul> <li>(a) areas of high public use</li> <li>(b) areas, including beaches, used for recreational activities such as swimming, fishing, skiing, sailing and other water sports</li> <li>(c) areas of outstanding visual or environmental value</li> <li>(d) areas of high tourism value</li> <li>(e) areas of important regional or state economic activity, including commercial ports, wharfs and jetties</li> <li>(f) the operation of infrastructure facilities including inlet and outlet pipes associated with the desalination of sea water.</li> </ul> |  |
| PO 2.6  | DTS/DPF 2.6  |
| Marine aquaculture is sited and designed to minimise interference and obstruction to the natural processes of the coastal and marine environment.   | None are applicable.   |
| PO 2.7  | DTS/DPF 2.7  |
| Marine aquaculture is designed to be as unobtrusive as practicable  | None are applicable.   |

Page 29 of 126 Printed on 5/07/2022

|          | - Linquity  |   |
|----------|---|---|
| by inco  | rporating measures such as:   |   |
| (a)      | using feed hoppers painted in subdued colours and suspending them as close as possible to the surface of the water  |   |
| (b)      | positioning structures to protrude the minimum distance practicable above the surface of the water  |   |
| (c)      | avoiding the use of shelters and structures above cages and platforms unless necessary to exclude predators and protected species from interacting with the farming structures and/or stock inside the cages, or for safety reasons |   |
| (d)      | positioning racks, floats and other farm structures in unobtrusive locations landward from the shoreline.   |   |
| PO 2.8   |   | DTS/DPF 2.8   |
| establis | , launching and maintenance facilities utilise existing shed roads, tracks, ramps and paths to or from the sea possible to minimise environmental and amenity impacts.  | None are applicable.  |
| PO 2.9   |   | DTS/DPF 2.9   |
| commo    | , launching and maintenance facilities are developed as in user facilities and are co-located where practicable to eadverse impacts on coastal areas.   | None are applicable.  |
| PO 2.10  |   | DTS/DPF 2.10  |
| protect  | aquaculture is sited to minimise potential impacts on, and to the integrity of, reserves under the <i>National Parks and Act 1972</i> .   | Marine aquaculture is located 1000m or more seaward of the boundary of any reserve under the <i>National Parks and Wildlife Act</i> 1972. |
| PO 2.11  |   | DTS/DPF 2.11  |
|          | re storage, cooling and processing facilities do not impair the and its visual amenity by:  | None are applicable.  |
| (a)      | being sited, designed, landscaped and of a scale to reduce the overall bulk and appearance of buildings and complement the coastal landscape  |   |
| (b)      | making provision for appropriately sited and designed vehicular access arrangements, including using existing vehicular access arrangements as far as practicable   |   |
| (c)      | incorporating appropriate waste treatment and disposal.   |   |
|          | Navigation  | and Safety  |
| PO 3.1   |   | DTS/DPF 3.1   |
|          | aquaculture sites are suitably marked to maintain ional safety.   | None are applicable.  |
| PO 3.2   |   | DTS/DPF 3.2   |
|          | aquaculture is sited to provide adequate separation between or safe navigation.   | None are applicable.  |
|          | Environmenta  | Il Management   |
| PO 4.1   |   | DTS/DPF 4.1   |
|          | aquaculture is maintained to prevent hazards to people and including breeding grounds and habitats of native marine   | None are applicable.  |
|          |   |   |

Page 30 of 126 Printed on 5/07/2022

| mammals and terrestrial fauna, especially migratory species.   |                      |
|--|----------------------|
| PO 4.2   | DTS/DPF 4.2          |
| Marine aquaculture is designed to facilitate the relocation or removal of structures in the case of emergency such as oil spills, algal blooms and altered water flows.  | None are applicable. |
| PO 4.3   | DTS/DPF 4.3          |
| Marine aquaculture provides for progressive or future reclamation of disturbed areas ahead of, or upon, decommissioning.   | None are applicable. |
| PO 4.4   | DTS/DPF 4.4          |
| Aquaculture operations incorporate measures for the removal and disposal of litter, disused material, shells, debris, detritus, dead animals and animal waste to prevent pollution of waters, wetlands, or the nearby coastline. | None are applicable. |

# **Beverage Production in Rural Areas**

# **Assessment Provisions (AP)**

|      | Desired Outcome  |
|------|--|
| DO 1 | Mitigation of potential amenity and environmental impacts of value-adding beverage production facilities such as wineries, distilleries, cideries and breweries. |

Performance Outcomes (PO) and Deemed-to-Satisfy (DTS) Criteria / Designated Performance Feature (DPF)

| Performance Outcome  | Deemed-to-Satisfy Criteria / Designated Performance Feature |
|--|---|
| Odour a  | nd Noise  |
| PO 1.1   | DTS/DPF 1.1   |
| Beverage production activities are designed and sited to minimise odour impacts on rural amenity.  | None are applicable.  |
| PO 1.2   | DTS/DPF 1.2   |
| Beverage production activities are designed and sited to minimise noise impacts on sensitive receivers.  | None are applicable.  |
| PO 1.3   | DTS/DPF 1.3   |
| Fermentation, distillation, manufacturing, storage, packaging and bottling activities occur within enclosed buildings to improve the visual appearance within a locality and manage noise associated | None are applicable.  |

Page 31 of 126 Printed on 5/07/2022

| Policy24 - Eriquity  |  |
|--|--|
| with these activities.   |  |
| PO 1.4   | DTS/DPF 1.4  |
| Breweries are designed to minimise odours emitted during boiling and fermentation stages of production.  | Brew kettles are fitted with a vapour condenser.   |
| PO 1.5   | DTS/DPF 1.5  |
| Beverage production solid wastes are stored in a manner that minimises odour impacts on sensitive receivers in other ownership.  | Solid waste from beverage production is collected and stored in sealed containers and removed from the site within 48 hours. |
| Water  | Quality  |
| PO 2.1   | DTS/DPF 2.1  |
| Beverage production wastewater management systems (including wastewater irrigation) are set back from watercourses to minimise adverse impacts on water resources.   | Wastewater management systems are set back 50m or more from the banks of watercourses and bores.                             |
| PO 2.2   | DTS/DPF 2.2  |
| The storage or disposal of chemicals or hazardous substances is undertaken in a manner to prevent pollution of water resources.  | None are applicable.   |
| PO 2.3   | DTS/DPF 2.3  |
| Stormwater runoff from areas that may cause contamination due to beverage production activities (including vehicle movements and machinery operations) is drained to an onsite stormwater treatment system to manage potential environmental impacts.    | None are applicable.   |
| PO 2.4   | DTS/DPF 2.4  |
| Stormwater runoff from areas unlikely to cause contamination by beverage production and associated activities (such as roof catchments and clean hard-paved surfaces) is diverted away from beverage production areas and wastewater management systems. | None are applicable.   |
| Wastewat   | er Irrigation  |
| PO 3.1   | DTS/DPF 3.1  |
| Beverage production wastewater irrigation systems are designed and located to not contaminate soil and surface and ground water resources or damage crops.   | None are applicable.   |
| PO 3.2   | DTS/DPF 3.2  |
| Beverage production wastewater irrigation systems are designed and located to minimise impact on amenity and avoid spray drift onto adjoining land.  | Beverage production wastewater is not irrigated within 50m of any dwelling in other ownership.                               |
| PO 3.3   | DTS/DPF 3.3  |
| Beverage production wastewater is not irrigated onto areas that pose an undue risk to the environment or amenity such as:  | None are applicable.   |
| /-\  |  |
| <ul> <li>(a) waterlogged areas</li> <li>(b) land within 50m of a creek, swamp or domestic or stock water bore</li> <li>(c) land subject to flooding</li> </ul>   |  |

Page 32 of 126 Printed on 5/07/2022

(e) rocky or highly permeable soil overlaying an unconfined aquifer.

# **Bulk Handling and Storage Facilities**

# **Assessment Provisions (AP)**

|      | Desired Outcome   |
|------|---|
| DO 1 | Facilities for the bulk handling and storage of agricultural, mineral, petroleum, rock, ore or other similar commodities are designed to minimise adverse impacts on transport networks, the landscape and surrounding land uses. |

Performance Outcomes (PO) and Deemed-to-Satisfy (DTS) Criteria / Designated Performance Feature (DPF)

# **Performance Outcome Deemed-to-Satisfy Criteria** / **Designated Performance Feature** Siting and Design DTS/DPF 1.1 PO 1.1 Bulk handling and storage facilities are sited and designed to Facilities for the handling, storage and dispatch of commodities in minimise risks of adverse air quality and noise impacts on sensitive bulk (excluding processing) meet the following minimum separation receivers. distances from sensitive receivers: bulk handling of agricultural crop products, rock, ores, minerals, petroleum products or chemicals at a wharf or wharf side facility (including sea-port grain terminals), where the handling of these materials into or from vessels does not exceed 100 tonnes per day: 300m or more from residential premises not associated with the facility bulk handling of agricultural crop products, rock, ores, minerals, petroleum products or chemicals to or from any commercial storage facility: 300m or more from residential premises not associated with the facility (c) bulk petroleum storage involving individual containers with a capacity up to 200 litres and a total on-site storage capacity not exceeding 1,000 cubic metres: 500m or more coal handling with: a. capacity up to 1 tonne per day or a storage capacity up to 50 tonnes: 500m or more b. capacity exceeding 1 tonne per day but not exceeding 100 tonnes per day or a storage capacity exceeding 50 tonnes but not exceeding 5000 tonnes: 1000m or more. Buffers and Landscaping PO 2.1 DTS/DPF 2.1 Bulk handling and storage facilities incorporate a buffer area for the None are applicable.

Page 33 of 126 Printed on 5/07/2022

establishment of dense landscaping adjacent road frontages to enhance the appearance of land and buildings from public

| . Glioyz i Zinqany   |  |
|--|--|
| thoroughfares.   |  |
| PO 2.2   | DTS/DPF 2.2  |
| Bulk handling and storage facilities incorporate landscaping to assist with screening and dust filtration.   | None are applicable.   |
| Access a   | nd Parking   |
| PO 3.1   | DTS/DPF 3.1  |
| Roadways and vehicle parking areas associated with bulk handling and storage facilities are designed and surfaced to control dust emissions and prevent drag out of material from the site.                | Roadways and vehicle parking areas are sealed with an all-weather surface. |
| Slipways, Whan   | ves and Pontoons   |
| PO 4.1   | DTS/DPF 4.1  |
| Slipways, wharves and pontoons used for the handling of bulk materials (such as fuel, oil, catch, bait and the like) incorporate catchment devices to avoid the release of materials into adjacent waters. | None are applicable.   |

# **Clearance from Overhead Powerlines**

# **Assessment Provisions (AP)**

|      | Desired Outcome   |
|------|---|
| DO 1 | Protection of human health and safety when undertaking development in the vicinity of overhead transmission powerlines. |

| Performance Outcome   | Deemed-to-Satisfy Criteria /<br>Designated Performance<br>Feature   |
|---|---|
| PO 1.1  Buildings are adequately separated from aboveground powerlines to minimise potential hazard to people and property. | One of the following is satisfied:  (a) a declaration is provided by or on behalf of the applicant to the effect that the proposal would not be contrary to the regulations prescribed for the purposes of section 86 of the <i>Electricity Act 1996</i> (b) there are no aboveground powerlines adjoining the site that are the subject of the proposed development. |

# Design

# **Assessment Provisions (AP)**

Page 34 of 126 Printed on 5/07/2022

# Development is: (a) contextual - by considering, recognising and carefully responding to its natural surroundings or built environment and positively contributes to the character of the immediate area (b) durable - fit for purpose, adaptable and long lasting (c) inclusive - by integrating landscape design to optimise pedestrian and cyclist usability, privacy and equitable access, and promoting the provision of quality spaces integrated with the public realm that can be used for access and recreation and help optimise security and safety both internally and within the public realm, for occupants and visitors

# (d) sustainable - by integrating sustainable techniques into the design and siting of development and landscaping to improve community health, urban heat, water management, environmental performance, biodiversity and local amenity and to minimise energy consumption.

# **Performance Outcome**

# Deemed-to-Satisfy Criteria / Designated Performance Feature

|   | reature  |
|---|--|
| All de  | velopment  |
| External  | Appearance   |
| PO 1.1  | DTS/DPF 1.1  |
| Buildings reinforce corners through changes in setback, articulation, materials, colour and massing (including height, width, bulk, roof form and slope).   | None are applicable.   |
| PO 1.2  | DTS/DPF 1.2  |
| Where zero or minor setbacks are desirable, development provides shelter over footpaths (in the form of verandahs, awnings, canopies and the like, with adequate lighting) to positively contribute to the walkability, comfort and safety of the public realm. | •  |
| PO 1.3  | DTS/DPF 1.3  |
| Building elevations facing the primary street (other than ancillary buildings) are designed and detailed to convey purpose, identify main access points and complement the streetscape.   | None are applicable.   |
| PO 1.4  | DTS/DPF 1.4  |
| Plant, exhaust and intake vents and other technical equipment is integrated into the building design to minimise visibility from the public realm and negative impacts on residential amenity by:   | Development does not incorporate any structures that protrude beyond the roofline. |
| <ul> <li>(a) positioning plant and equipment in unobtrusive locations<br/>viewed from public roads and spaces</li> </ul>  |  |
| (b) screening rooftop plant and equipment from view   |  |
| (c) when located on the roof of non-residential development,<br>locating the plant and equipment as far as practicable fron<br>adjacent sensitive land uses.  |  |
| PO 1.5  | DTS/DPF 1.5  |
| The negative visual impact of outdoor storage, waste management,  | None are applicable.   |

Page 35 of 126 Printed on 5/07/2022

| loading and service areas is minimised by integrating them into the building design and screening them from public view (such as fencing, landscaping and built form) taking into account the form of development contemplated in the relevant zone.   |  |
|--|--|
| Sa   | řety   |
| PO 2.1   | DTS/DPF 2.1  |
| Development maximises opportunities for passive surveillance of the public realm by providing clear lines of sight, appropriate lighting and the use of visually permeable screening wherever practicable.   | None are applicable.   |
| PO 2.2   | DTS/DPF 2.2  |
| Development is designed to differentiate public, communal and private areas.   | None are applicable.   |
| PO 2.3   | DTS/DPF 2.3  |
| Buildings are designed with safe, perceptible and direct access from public street frontages and vehicle parking areas.  | None are applicable.   |
| PO 2.4   | DTS/DPF 2.4  |
| Development at street level is designed to maximise opportunities for passive surveillance of the adjacent public realm.   | None are applicable.   |
| PO 2.5   | DTS/DPF 2.5  |
| Common areas and entry points of buildings (such as the foyer areas of residential buildings), and non-residential land uses at  | None are applicable.   |
| street level, maximise passive surveillance from the public realm to the inside of the building at night.  |  |
| the inside of the building at night.   | caping   |
| the inside of the building at night.   | caping DTS/DPF 3.1   |
| the inside of the building at night.  Lands  |  |
| the inside of the building at night.  Lands PO 3.1   | DTS/DPF 3.1  |
| the inside of the building at night.  Lands  PO 3.1  Soft landscaping and tree planting is incorporated to:  (a) minimise heat absorption and reflection (b) maximise shade and shelter (c) maximise stormwater infiltration (d) enhance the appearance of land and streetscapes   | DTS/DPF 3.1  |
| the inside of the building at night.  Lands  PO 3.1  Soft landscaping and tree planting is incorporated to:  (a) minimise heat absorption and reflection (b) maximise shade and shelter (c) maximise stormwater infiltration (d) enhance the appearance of land and streetscapes (e) contribute to biodiversity.   | DTS/DPF 3.1  None are applicable.                                    |
| Lands PO 3.1  Soft landscaping and tree planting is incorporated to:  (a) minimise heat absorption and reflection (b) maximise shade and shelter (c) maximise stormwater infiltration (d) enhance the appearance of land and streetscapes (e) contribute to biodiversity.  PO 3.2  Soft landscaping and tree planting maximises the use of locally indigenous plant species, incorporates plant species best suited to current and future climate conditions and avoids pest plant and weed species.               | DTS/DPF 3.1  None are applicable.  DTS/DPF 3.2                       |
| Lands PO 3.1  Soft landscaping and tree planting is incorporated to:  (a) minimise heat absorption and reflection (b) maximise shade and shelter (c) maximise stormwater infiltration (d) enhance the appearance of land and streetscapes (e) contribute to biodiversity.  PO 3.2  Soft landscaping and tree planting maximises the use of locally indigenous plant species, incorporates plant species best suited to current and future climate conditions and avoids pest plant and weed species.               | DTS/DPF 3.1  None are applicable.  DTS/DPF 3.2  None are applicable. |
| Lands PO 3.1  Soft landscaping and tree planting is incorporated to:  (a) minimise heat absorption and reflection (b) maximise shade and shelter (c) maximise stormwater infiltration (d) enhance the appearance of land and streetscapes (e) contribute to biodiversity.  PO 3.2  Soft landscaping and tree planting maximises the use of locally indigenous plant species, incorporates plant species best suited to current and future climate conditions and avoids pest plant and weed species.  Environments | DTS/DPF 3.1  None are applicable.  DTS/DPF 3.2  None are applicable. |

Page 36 of 126 Printed on 5/07/2022

Buildings are sited and designed to maximise passive environmental None are applicable. performance and minimise energy consumption and reliance on mechanical systems, such as heating and cooling. PO 4.3 DTS/DPF 4.3 Buildings incorporate climate-responsive techniques and features None are applicable. such as building and window orientation, use of eaves, verandahs and shading structures, water harvesting, at ground landscaping, green walls, green roofs and photovoltaic cells. Water Sensitive Design PO 5.1 DTS/DPF 5.1 Development is sited and designed to maintain natural hydrological None are applicable. systems without negatively impacting: the quantity and quality of surface water and groundwater (b) the depth and directional flow of surface water and groundwater (c) the quality and function of natural springs. On-site Waste Treatment Systems PO 6.1 DTS/DPF 6.1 Dedicated on-site effluent disposal areas do not include any areas Effluent disposal drainage areas do not: to be used for, or could be reasonably foreseen to be used for, encroach within an area used as private open space or private open space, driveways or car parking. result in less private open space than that specified in Design Table 1 - Private Open Space (b) use an area also used as a driveway (c) encroach within an area used for on-site car parking or result in less on-site car parking than that specified in Transport, Access and Parking Table 1 - General Off-Street Car Parking Requirements or Table 2 - Off-Street Car Parking Requirements in Designated Areas. Carparking Appearance DTS/DPF 7.1 Development facing the street is designed to minimise the negative None are applicable. impacts of any semi-basement and undercroft car parking on the streetscapes through techniques such as: (a) limiting protrusion above finished ground level (b) screening through appropriate planting, fencing and mounding (c) limiting the width of openings and integrating them into the building structure. PO 7.2 DTS/DPF 7.2 Vehicle parking areas are appropriately located, designed and None are applicable. constructed to minimise impacts on adjacent sensitive receivers through measures such as ensuring they are attractively developed and landscaped, screen fenced and the like. PO 7.3 DTS/DPF 7.3 Safe, legible, direct and accessible pedestrian connections are None are applicable. provided between parking areas and the development.

Page 37 of 126 Printed on 5/07/2022

|  | <u> </u>   |  |
|--|--|--|
|  |  |  |
| PO 7.4   | DTS/DPF 7.4  |  |
| Street level vehicle parking areas incorporate tree planting to provide shade and reduce solar heat absorption and reflection.   | None are applicable.   |  |
| PO 7.5   | DTS/DPF 7.5  |  |
| Street level parking areas incorporate soft landscaping to improve visual appearance when viewed from within the site and from public places.  | None are applicable.   |  |
| PO 7.6   | DTS/DPF 7.6  |  |
| Vehicle parking areas and associated driveways are landscaped to provide shade and positively contribute to amenity.   | None are applicable.   |  |
| PO 7.7   | DTS/DPF 7.7  |  |
| Vehicle parking areas and access ways incorporate integrated stormwater management techniques such as permeable or porous surfaces, infiltration systems, drainage swales or rain gardens that integrate with soft landscaping.  | None are applicable.   |  |
| Earthworks ai  | nd sloping land  |  |
| PO 8.1   | DTS/DPF 8.1  |  |
| Development, including any associated driveways and access tracks, minimises the need for earthworks to limit disturbance to natural topography.   | Development does not involve any of the following:  (a) excavation exceeding a vertical height of 1m  (b) filling exceeding a vertical height of 1m  (c) a total combined excavation and filling vertical height of 2m or more.                      |  |
| PO 8.2   | DTS/DPF 8.2  |  |
| Driveways and access tracks are designed and constructed to allow safe and convenient access on sloping land (with a gradient exceeding 1 in 8).   | Driveways and access tracks on sloping land (with a gradient exceeding 1 in 8) satisfy (a) and (b):  (a) do not have a gradient exceeding 25% (1-in-4) at any point along the driveway  (b) are constructed with an all-weather trafficable surface. |  |
| PO 8.3   | DTS/DPF 8.3  |  |
| Driveways and access tracks on sloping land (with a gradient exceeding 1 in 8):  | None are applicable.   |  |
| <ul> <li>(a) do not contribute to the instability of embankments and cuttings</li> <li>(b) provide level transition areas for the safe movement of people and goods to and from the development</li> <li>(c) are designed to integrate with the natural topography of the land.</li> </ul> |  |  |
| PO 8.4   | DTS/DPF 8.4  |  |
| Development on sloping land (with a gradient exceeding 1 in 8) avoids the alteration of natural drainage lines and includes on-site drainage systems to minimise erosion.  | None are applicable.   |  |

Page 38 of 126 Printed on 5/07/2022

| 7005   | DTO/DDF 0.5  |
|--|--|
| PO 8.5   | DTS/DPF 8.5  |
| Development does not occur on land at risk of landslip nor increases the potential for landslip or land surface instability.   | None are applicable.   |
|  | and Walls  |
| PO 9.1   | DTS/DPF 9.1  |
| Fences, walls and retaining walls are of sufficient height to maintain privacy and security without unreasonably impacting the visual amenity and adjoining land's access to sunlight or the amenity of public places. | None are applicable.   |
| PO 9.2   | DTS/DPF 9.2  |
| Landscaping incorporated on the low side of retaining walls is visible from public roads and public open space to minimise visual impacts.   | A vegetated landscaped strip 1m wide or more is provided against the low side of a retaining wall.   |
| Overlooking / Visual Privacy   | (in building 3 storeys or less)  |
| PO 10.1  | DTS/DPF 10.1   |
| Development mitigates direct overlooking from upper level windows to habitable rooms and private open spaces of adjoining residential uses.  | Upper level windows facing side or rear boundaries shared with a residential allotment/site satisfy one of the following:  (a) are permanently obscured to a height of 1.5m above finished floor level and are fixed or not capable of being opened more than 200mm  (b) have sill heights greater than or equal to 1.5m above finished floor level  (c) incorporate screening with a maximum of 25% openings, permanently fixed no more than 500mm from the window surface and sited adjacent to any part of the window less than 1.5 m above the finished floor level.   |
| PO 10.2  Development mitigates direct overlooking from balconies, terraces and decks to habitable rooms and private open space of adjoining residential uses.  | One of the following is satisfied:  (a) the longest side of the balcony or terrace will face a public road, public road reserve or public reserve that is at least 15m wide in all places faced by the balcony or terrace or  (b) all sides of balconies or terraces on upper building levels are permanently obscured by screening with a maximum 25% transparency/openings fixed to a minimum height of:  (i) 1.5m above finished floor level where the balcony is located at least 15 metres from the nearest habitable window of a dwelling on adjacent land or  (ii) 1.7m above finished floor level in all other cases |
| All Residentia   | al development   |
| Front elevations and   | l passive surveillance   |
| PO 11.1  | DTS/DPF 11.1   |

Page 39 of 126 Printed on 5/07/2022

Each dwelling with a frontage to a public street:

Dwellings incorporate windows along primary street frontages to

encourage passive surveillance and make a positive contribution to

(a) includes at least one window facing the primary street from the streetscape. a habitable room that has a minimum internal room dimension of 2.4m (b) has an aggregate window area of at least 2m<sup>2</sup> facing the primary street. PO 11.2 DTS/DPF 11.2 Dwellings incorporate entry doors within street frontages to address Dwellings with a frontage to a public street have an entry door the street and provide a legible entry point for visitors. visible from the primary street boundary. Outlook and amenity PO 12.1 **DTS/DPF 12.1** A living room of a dwelling incorporates a window with an outlook Living rooms have an external outlook to provide a high standard of amenity for occupants. towards the street frontage or private open space, public open space, or waterfront areas. PO 12.2 DTS/DPF 12.2 Bedrooms are separated or shielded from active communal None are applicable. recreation areas, common access areas and vehicle parking areas and access ways to mitigate noise and artificial light intrusion. **Ancillary Development** PO 13.1 **DTS/DPF 13.1** Ancillary buildings: Residential ancillary buildings and structures are sited and (a) are ancillary to a dwelling erected on the same site designed to not detract from the streetscape or appearance of (b) have a floor area not exceeding 60m2 buildings on the site or neighbouring properties. (c) are not constructed, added to or altered so that any part is situated: (i) in front of any part of the building line of the dwelling to which it is ancillary (ii) within 900mm of a boundary of the allotment with a secondary street (if the land has boundaries on two or more roads) in the case of a garage or carport, the garage or carport: (d) is set back at least 5.5m from the boundary of the primary street (ii) when facing a primary street or secondary street, has a total door / opening not exceeding: for dwellings of single building level - 7m in width or 50% of the site frontage, whichever is the lesser В. for dwellings comprising two or more building levels at the building line fronting the same public street - 7m in width (e) if situated on a boundary (not being a boundary with a primary street or secondary street), do not exceed a length of 11.5m unless: (i) a longer wall or structure exists on the adjacent site and is situated on the same allotment boundary and

Page 40 of 126 Printed on 5/07/2022

(ii)

the proposed wall or structure will be built along

the same length of boundary as the existing adjacent wall or structure to the same or lesser extent

- (f) if situated on a boundary of the allotment (not being a boundary with a primary street or secondary street), all walls or structures on the boundary will not exceed 45% of the length of that boundary
- (g) will not be located within 3m of any other wall along the same boundary unless on an adjacent site on that boundary there is an existing wall of a building that would be adjacent to or about the proposed wall or structure
- (h) have a wall height or post height not exceeding 3m above natural ground level (and not including a gable end)
- (i) have a roof height where no part of the roof is more than 5m above the natural ground level
- if clad in sheet metal, is pre-colour treated or painted in a non-reflective colour
- (k) retains a total area of soft landscaping in accordance with (i) or (ii), whichever is less:
  - (i) a total area as determined by the following table:

| Dwelling site area (or in the case of residential flat building or group dwelling(s), average site area) (m <sup>2</sup> ) | Minimum<br>percentage of<br>site |
|--|----------------------------------|
| <150   | 10%                              |
| 150-200  | 15%                              |
| 201-450  | 20%                              |
| >450   | 25%                              |

(ii) the amount of existing soft landscaping prior to the development occurring.

### PO 13.2

Ancillary buildings and structures do not impede on-site functional requirements such as private open space provision or car parking requirements and do not result in over-development of the site.

### DTS/DPF 13.2

Ancillary buildings and structures do not result in:

- (a) less private open space than specified in Design in Urban Areas Table 1 - Private Open Space
- (b) less on-site car parking than specified in Transport, Access and Parking Table 1 - General Off-Street Car Parking Requirements or Table 2 - Off-Street Car Parking Requirements in Designated Areas.

#### PO 13.3

Fixed plant and equipment in the form of pumps and/or filtration systems for a swimming pool or spa is positioned and/or housed to not cause unreasonable noise nuisance to adjacent sensitive receivers.

#### **DTS/DPF 13.3**

The pump and/or filtration system is ancillary to a dwelling erected on the same site and is:

- (a) enclosed in a solid acoustic structure that is located at least 5m from the nearest habitable room located on an adjoining allotment
- (b) located at least 12m from the nearest habitable room

Page 41 of 126 Printed on 5/07/2022

located on an adjoining allotment. Garage appearance **DTS/DPF 14.1** PO 14.1 Garaging is designed to not detract from the streetscape or Garages and carports facing a street: appearance of a dwelling. are situated so that no part of the garage or carport is in front of any part of the building line of the dwelling (b) are set back at least 5.5m from the boundary of the primary street (c) have a garage door / opening not exceeding 7m in width (d) have a garage door /opening width not exceeding 50% of the site frontage unless the dwelling has two or more building levels at the building line fronting the same public street. Massing PO 15.1 **DTS/DPF 15.1** The visual mass of larger buildings is reduced when viewed from None are applicable adjoining allotments or public streets. **Dwelling additions** PO 16.1 DTS / DPF 16.1 Dwelling additions are sited and designed to not detract from the Dwelling additions: streetscape or amenity of adjoining properties and do not impede are not constructed, added to or altered so that any part is on-site functional requirements. situated closer to a public street (b) do not result in: (i) excavation exceeding a vertical height of 1m (ii) filling exceeding a vertical height of 1m a total combined excavation and filling vertical height of 2m or more (iv) less Private Open Space than specified in Design Table 1 - Private Open Space (v) less on-site parking than specified in Transport Access and Parking Table 1 - General Off-Street Car Parking Requirements or Table 2 - Off-Street Car Parking Requirements in Designated Areas (vi) upper level windows facing side or rear boundaries unless: A. they are permanently obscured to a height of 1.5m above finished floor level that is fixed or not capable of being opened more than 200mm В. have sill heights greater than or equal to 1.5m above finished floor level C. incorporate screening to a height of 1.5m above finished floor level all sides of balconies or terraces on upper building levels are permanently obscured by screening with a maximum 25% transparency/openings fixed to a minimum height A. 1.5m above finished floor level where the

Page 42 of 126 Printed on 5/07/2022

balcony is located at least 15 metres from the nearest habitable window of a dwelling on adjacent land

B. 1.7m above finished floor level in all other cases.

### Private Open Space

#### PO 17.1

Dwellings are provided with suitable sized areas of usable private open space to meet the needs of occupants.

#### **DTS/DPF 17.1**

Private open space is provided in accordance with Design Table 1 - Private Open Space.

### Water Sensitive Design

#### PO 18.1

Residential development creating a common driveway / access includes stormwater management systems that minimise the discharge of sediment, suspended solids, organic matter, nutrients, bacteria, litter and other contaminants to the stormwater system, watercourses or other water bodies.

#### **DTS/DPF 18.1**

Residential development creating a common driveway / access that services 5 or more dwellings achieves the following stormwater runoff outcomes:

- (a) 80 per cent reduction in average annual total suspended solids
- (b) 60 per cent reduction in average annual total phosphorus
- (c) 45 per cent reduction in average annual total nitrogen.

#### PO 18.2

Residential development creating a common driveway / access includes a stormwater management system designed to mitigate peak flows and manage the rate and duration of stormwater discharges from the site to ensure that the development does not increase the peak flows in downstream systems.

#### **DTS/DPF 18.2**

Development creating a common driveway / access that services 5 or more dwellings:

(a) maintains the pre-development peak flow rate from the site based upon a 0.35 runoff coefficient for the 18.1% AEP 30-minute storm and the stormwater runoff time to peak is not increased

or

captures and retains the difference in pre-development runoff volume (based upon a 0.35 runoff coefficient) vs post development runoff volume from the site for an 18.1% AEP 30-minute storm; and

(b) manages site generated stormwater runoff up to and including the 1% AEP flood event to avoid flooding of buildings.

### Car parking, access and manoeuvrability

#### PO 19.1

Enclosed parking spaces are of a size and dimensions to be functional, accessible and convenient.

#### **DTS/DPF 19.1**

Residential car parking spaces enclosed by fencing, walls or other structures have the following internal dimensions (separate from any waste storage area):

- (a) single width car parking spaces:
  - (i) a minimum length of 5.4m per space
  - (ii) a minimum width of 3.0m
  - (iii) a minimum garage door width of 2.4m
- (b) double width car parking spaces (side by side):
  - (i) a minimum length of 5.4m
  - (ii) a minimum width of 5.4m
  - (iii) minimum garage door width of 2.4m per space.

Page 43 of 126 Printed on 5/07/2022

| PO 19.2  | DTS/DPF 19.2   |  |
|--|--|--|
| Uncovered parking spaces are of a size and dimensions to be functional, accessible and convenient.   | Uncovered car parking spaces have:  (a) a minimum length of 5.4m  (b) a minimum width of 2.4m  (c) a minimum width between the centre line of the space and any fence, wall or other obstruction of 1.5m   |  |
| PO 19.3  | DTS/DPF 19.3   |  |
| Driveways are located and designed to facilitate safe access and egress while maximising land available for street tree planting, landscaped street frontages, domestic waste collection and onstreet parking. | Driveways and access points on sites with a frontage to a public road of 10m or less have a width between 3.0 and 3.2 metres measured at the property boundary and are the only access point provided on the site.   |  |
| PO 19.4  | DTS/DPF 19.4   |  |
| Vehicle access is safe, convenient, minimises interruption to the operation of public roads and does not interfere with street infrastructure or street trees.   | Vehicle access to designated car parking spaces satisfy (a) or (b):      (a) is provided via a lawfully existing or authorised access point or an access point for which consent has been granted as part of an application for the division of land                                       |  |
|  | (b) where newly proposed:  (i) is set back 6m or more from the tangent point of an intersection of 2 or more roads  (ii) is set back outside of the marked lines or  |  |
|  | infrastructure dedicating a pedestrian crossing  (iii) does not involve the removal, relocation or damage to of mature street trees, street furniture or utility infrastructure services.  |  |
| PO 19.5  | DTS/DPF 19.5   |  |
| Driveways are designed to enable safe and convenient vehicle movements from the public road to on-site parking spaces.   | Driveways are designed and sited so that:  |  |
|  | (a) the gradient from the place of access on the boundary of the allotment to the finished floor level at the front of the garage or carport is not steeper than 1:4 on average  |  |
|  | (b) they are aligned relative to the street boundary so that<br>there is no more than a 20 degree deviation from 90<br>degrees between the centreline of any dedicated car<br>parking space to which it provides access (measured fron<br>the front of that space) and the street boundary |  |
|  | (c) if located to provide access from an alley, lane or right of way - the alley, land or right or way is at least 6.2m wide along the boundary of the allotment / site  |  |
| PO 19.6  | DTS/DPF 19.6   |  |
| Driveways and access points are designed and distributed to optimise the provision of on-street visitor parking.   | Where on-street parking is available abutting the site's street frontage, on-street parking is retained in accordance with the following requirements:   |  |
|  | (a) minimum 0.33 on-street spaces per dwelling on the site (rounded up to the nearest whole number)  |  |
|  | <ul> <li>(b) minimum car park length of 5.4m where a vehicle can enter or exit a space directly</li> <li>(c) minimum carpark length of 6m for an intermediate space</li> </ul>   |  |

Page 44 of 126 Printed on 5/07/2022

Policy24 - Enquiry located between two other parking spaces or to an end obstruction where the parking is indented. Waste storage PO 20.1 DTS/DPF 20.1 Provision is made for the adequate and convenient storage of waste | None are applicable. bins in a location screened from public view. Design of Transportable Dwellings PO 21.1 DTS/DPF 21.1 The sub-floor space beneath transportable buildings is enclosed to Buildings satisfy (a) or (b): give the appearance of a permanent structure. (a) are not transportable (b) the sub-floor space between the building and ground level is clad in a material and finish consistent with the building. Group dwelling, residential flat buildings and battle-axe development Amenity PO 22.1 DTS/DPF 22.1 Dwellings are of a suitable size to accommodate a layout that is well Dwellings have a minimum internal floor area in accordance with organised and provides a high standard of amenity for occupants. the following table: Number of bedrooms Minimum internal floor area Studio 35m<sup>2</sup> 1 bedroom 50m<sup>2</sup> 2 bedroom 65m<sup>2</sup> 3+ bedrooms 80m<sup>2</sup> and any dwelling over 3 bedrooms provides an additional 15m<sup>2</sup> for every additional bedroom PO 22.2 DTS/DPF 22.2 The orientation and siting of buildings minimises impacts on the None are applicable. amenity, outlook and privacy of occupants and neighbours. PO 22.3 DTS/DPF 22.3 Development maximises the number of dwellings that face public None are applicable. open space and public streets and limits dwellings oriented towards adjoining properties. PO 22.4 DTS/DPF 22.4 Dwelling sites/allotments are not in the form of a battle-axe Battle-axe development is appropriately sited and designed to respond to the existing neighbourhood context. arrangement.

Communal Open Space

Page 45 of 126 Printed on 5/07/2022

| PO 23.1   | DTS/DPF 23.1  |
|---|---|
| Private open space provision may be substituted for communal open space which is designed and sited to meet the recreation and amenity needs of residents.              | None are applicable.  |
| PO 23.2   | DTS/DPF 23.2  |
| Communal open space is of sufficient size and dimensions to cater for group recreation.   | Communal open space incorporates a minimum dimension of 5 metres.   |
| PO 23.3   | DTS/DPF 23.3  |
| Communal open space is designed and sited to:   | None are applicable.  |
| (a) be conveniently accessed by the dwellings which it services   |   |
| (b) have regard to acoustic, safety, security and wind effects.   |   |
| PO 23.4   | DTS/DPF 23.4  |
| Communal open space contains landscaping and facilities that are functional, attractive and encourage recreational use.   | None are applicable.  |
| PO 23.5   | DTS/DPF 23.5  |
| Communal open space is designed and sited to:   | None are applicable.  |
| (a) in relation to rooftop or elevated gardens, minimise overlooking into habitable room windows or onto the useable private open space of other dwellings              |   |
| (b) in relation to ground floor communal space, be overlooked by habitable rooms to facilitate passive surveillance.  |   |
| Carparking, access  | and manoeuvrability   |
| PO 24.1   | DTS/DPF 24.1  |
| Driveways and access points are designed and distributed to optimise the provision of on-street visitor parking.  | Where on-street parking is available directly adjacent the site, on-<br>street parking is retained adjacent the subject site in accordance<br>with the following requirements:              |
|   | <ul> <li>(a) minimum 0.33 on-street car parks per proposed dwellings (rounded up to the nearest whole number)</li> <li>(b) minimum car park length of 5.4m where a vehicle can</li> </ul>   |
|   | enter or exit a space directly  (c) minimum carpark length of 6m for an intermediate space located between two other parking spaces or to an end obstruction where the parking is indented. |
| PO 24.2   | DTS/DPF 24.2  |
| The number of vehicular access points onto public roads is minimised to reduce interruption of the footpath and positively contribute to public safety and walkability. | Access to group dwellings or dwellings within a residential flat building is provided via a single common driveway.   |
| PO 24.3   | DTS/DPF 24.3  |
| Residential driveways that service more than one dwelling are designed to allow safe and convenient movement.   | Driveways that service more than 1 dwelling or a dwelling on a battle-axe site:   |
|   | (a) have a minimum width of 3m (b) for driveways servicing more than 3 dwellings:   |

Page 46 of 126 Printed on 5/07/2022

| PO 24.4  Residential driveways in a battle-axe configuration are designed to allow safe and convenient movement.  PO 24.5  Residential driveways that service more than one dwelling are designed to allow passenger vehicles to enter and exit the site and manoeuvre within the site in a safe and convenient manner. | (i) have a width of 5.5m or more and a length of 6m or more at the kerb of the primary street  (ii) where the driveway length exceeds 30m, incorporate a passing point at least every 30 metres with a minimum width of 5.5m and a minimum length of 6m.  DTS/DPF 24.4  Where in a battle-axe configuration, a driveway servicing one dwelling has a minimum width of 3m.  DTS/DPF 24.5  Driveways providing access to more than one dwelling, or a dwelling on a battle-axe site, allow a B85 passenger vehicle to enter and exit the garages or parking spaces in no more than a three-point turn managenery. |  |
|---|---|--|
| PO 24.6   | point turn manoeuvre.  DTS/DPF 24.6   |  |
| Dwellings are adequately separated from common driveways and manoeuvring areas.   | Dwelling walls with entry doors or ground level habitable room windows are set back at least 1.5m from any driveway or area designated for the movement and manoeuvring of vehicles.  |  |
| Soft Lan  | dscaping  |  |
| PO 25.1  Soft landscaping is provided between dwellings and common driveways to improve the outlook for occupants and appearance of common areas.   | Other than where located directly in front of a garage or a building entry, soft landscaping with a minimum dimension of 1m is provided between a dwelling and common driveway.   |  |
| PO 25.2  Soft landscaping is provided that improves the appearance of common driveways.   | DTS/DPF 25.2  Where a common driveway is located directly adjacent the side or rear boundary of the site, soft landscaping with a minimum dimension of 1m is provided between the driveway and site boundary (excluding along the perimeter of a passing point).  |  |
| Site Facilities /   | Waste Storage   |  |
| PO 26.1  Provision is made for suitable mailbox facilities close to the major pedestrian entry to the site or conveniently located considering the nature of accommodation and mobility of occupants.   | DTS/DPF 26.1  None are applicable.  |  |
| PO 26.2   | DTS/DPF 26.2  |  |
| Provision is made for suitable external clothes drying facilities.  | None are applicable.  |  |
| PO 26.3  Provision is made for suitable household waste and recyclable material storage facilities which are:  (a) located away, or screened, from public view, and (b) conveniently located in proximity to dwellings and the waste collection point.  | DTS/DPF 26.3  None are applicable.  |  |
| PO 26.4  Waste and recyclable material storage areas are located away from  | DTS/DPF 26.4  Dedicated waste and recyclable material storage areas are located   |  |

Page 47 of 126 Printed on 5/07/2022

| Policy24 - Enquiry  |   |
|---|---|
| dwellings.  | at least 3m from any habitable room window.                       |
| PO 26.5   | DTS/DPF 26.5  |
| Where waste bins cannot be conveniently collected from the street, provision is made for on-site waste collection, designed to accommodate the safe and convenient access, egress and movement of waste collection vehicles.  | None are applicable.  |
| PO 26.6   | DTS/DPF 26.6  |
| Services including gas and water meters are conveniently located and screened from public view.   | None are applicable.  |
| Supported accommodation   | on and retirement facilities                                      |
| Siting and C  | Configuration   |
| PO 27.1   | DTS/DPF 27.1  |
| Supported accommodation and housing for aged persons and people with disabilities is located where on-site movement of residents is not unduly restricted by the slope of the land.   | None are applicable.  |
| Movement  | and Access  |
| PO 28.1   | DTS/DPF 28.1  |
| Development is designed to support safe and convenient access and movement for residents by providing:  | None are applicable.  |
| <ul> <li>(a) ground-level access or lifted access to all units</li> <li>(b) level entry porches, ramps, paths, driveways, passenger loading areas and areas adjacent to footpaths that allow for the passing of wheelchairs and resting places</li> <li>(c) car parks with gradients no steeper than 1-in-40 and of sufficient area to provide for wheelchair manoeuvrability</li> <li>(d) kerb ramps at pedestrian crossing points.</li> </ul> |   |
| Communal  | Open Space  |
| PO 29.1   | DTS/DPF 29.1  |
| Development is designed to provide attractive, convenient and comfortable indoor and outdoor communal areas to be used by residents and visitors.   | None are applicable.  |
| PO 29.2   | DTS/DPF 29.2  |
| Private open space provision may be substituted for communal open space which is designed and sited to meet the recreation and amenity needs of residents.  | None are applicable.  |
| PO 29.3   | DTS/DPF 29.3  |
| Communal open space is of sufficient size and dimensions to cater for group recreation.   | Communal open space incorporates a minimum dimension of 5 metres. |
| PO 29.4   | DTS/DPF 29.4  |
| Communal open space is designed and sited to:   | None are applicable.  |
| (a) be conveniently accessed by the dwellings which it services   |   |
| (b) have regard to acoustic, safety, security and wind effects.   |   |

Page 48 of 126 Printed on 5/07/2022

| Policy24 - Eliquii y   |   |  |
|--|---|--|
|  |   |  |
| PO 29.5  | DTS/DPF 29.5  |  |
| Communal open space contains landscaping and facilities that are functional, attractive and encourage recreational use.  | None are applicable.  |  |
| PO 29.6  | DTS/DPF 29.6  |  |
| Communal open space is designed and sited to:  | None are applicable.  |  |
| <ul> <li>in relation to rooftop or elevated gardens, minimise overlooking into habitable room windows or onto the useable private open space of other dwellings</li> <li>in relation to ground floor communal space, be overlooked by habitable rooms to facilitate passive surveillance.</li> </ul> |   |  |
| Site Facilities /  | Waste Storage   |  |
| PO 30.1  | DTS/DPF 30.1  |  |
| Development is designed to provide storage areas for personal items and specialised equipment such as small electric powered vehicles, including facilities for the recharging of small electric powered vehicles.   | None are applicable.  |  |
| PO 30.2  | DTS/DPF 30.2  |  |
| Provision is made for suitable mailbox facilities close to the major pedestrian entry to the site or conveniently located considering the nature of accommodation and mobility of occupants.   | None are applicable.  |  |
| PO 30.3  | DTS/DPF 28.3  |  |
| Provision is made for suitable external clothes drying facilities.   | None are applicable.  |  |
| PO 30.4  | DTS/DPF 30.4  |  |
| Provision is made for suitable household waste and recyclable material storage facilities conveniently located and screened from public view.  | None are applicable.  |  |
| PO 30.5  | DTS/DPF 30.5  |  |
| Waste and recyclable material storage areas are located away from dwellings.   | Dedicated waste and recyclable material storage areas are located at least 3m from any habitable room window. |  |
| PO 30.6  | DTS/DPF 30.6  |  |
| Provision is made for on-site waste collection where 10 or more bins are to be collected at any one time.  | None are applicable.  |  |
| PO 30.7  | DTS/DPF 30.7  |  |
| Services including gas and water meters are conveniently located and screened from public view.  | None are applicable.  |  |
| All non-residential development  |   |  |
| Water Sensitive Design   |   |  |
| PO 31.1  | DTS/DPF 31.1  |  |
| Development likely to result in significant risk of export of litter, oil or grease includes stormwater management systems designed to   | None are applicable.  |  |

Page 49 of 126 Printed on 5/07/2022

minimise pollutants entering stormwater.

| Policy24  | - Enquiry |   |                       |
|---|-----------|---|-----------------------|
| PO 31.2   |           |   | DTS/DPF 31.2          |
| Water discharged from a development site is of a physical, chemical and biological condition equivalent to or better than its pre-developed state.              |           | ological condition equivalent to or better than its   | None are applicable.  |
|   |           | Wash-down and Waste   | Loading and Unloading |
| PO 32.1   |           |   | DTS/DPF 32.1          |
| waste r<br>wash-d   | efuse bin | es including loading and unloading, storage of<br>is in commercial and industrial development or<br>is used for the cleaning of vehicles, vessels, plant or             | None are applicable.  |
| (a) designed to contain all wastewater likely to pollute stormwater within a bunded and roofed area to exclude the entry of external surface stormwater run-off |           | ater within a bunded and roofed area to exclude the   |                       |
| (b) paved with an impervious material to facilitate wastewater collection   |           | •   |                       |
| (c) of sufficient size to prevent 'splash-out' or 'over-spray' of wastewater from the wash-down area  |           |   |                       |
| (d)   | •         | ed to drain wastewater to either:   |                       |
|   | (i)       | a treatment device such as a sediment trap and coalescing plate oil separator with subsequent disposal to a sewer, private or Community Wastewater Management Scheme or |                       |
|   | (ii)      | a holding tank and its subsequent removal off-site on a regular basis.  |                       |

# **Table 1 - Private Open Space**

| Dwelling Type  | Minimum Rate  |
|--|---|
| Dwelling (at ground level)   | <ul> <li>Total private open space area:</li> <li>(a) Site area &lt;301m2: 24m2 located behind the building line.</li> <li>(b) Site area ≥ 301m2: 60m2 located behind the building line.</li> <li>Minimum directly accessible from a living room: 16m2 / with a minimum dimension 3m.</li> </ul> |
| Dwelling (above ground level)  | Studio (no separate bedroom): 4m <sup>2</sup> with a minimum dimension 1.8m  One bedroom: 8m <sup>2</sup> with a minimum dimension 2.1m  Two bedroom dwelling: 11m <sup>2</sup> with a minimum dimension 2.4m  Three + bedroom dwelling: 15m <sup>2</sup> with a minimum dimension 2.6m         |
| Cabin or caravan (permanently fixed to the ground) in a residential park or a caravan and tourist park | Total area: 16m <sup>2</sup> , which may be used as second car parking space, provided on each site intended for residential occupation.  |

Page 50 of 126 Printed on 5/07/2022

# **Design in Urban Areas**

## **Assessment Provisions (AP)**

| Desired Outcome |                 |  |  |
|-----------------|-----------------|--|--|
| DO 1            | Development is: |  |  |
|                 | (a)             | contextual - by considering, recognising and carefully responding to its natural surroundings or built environment and positively contributing to the character of the locality  |  |
|                 | (b)             | durable - fit for purpose, adaptable and long lasting  |  |
|                 | (c)             | inclusive - by integrating landscape design to optimise pedestrian and cyclist usability, privacy and equitable access and promoting the provision of quality spaces integrated with the public realm that can be used for access and recreation and help optimise security and safety both internally and within the public realm, for occupants and visitors |  |
|                 | (d)             | sustainable - by integrating sustainable techniques into the design and siting of development and landscaping to improve community health, urban heat, water management, environmental performance, biodiversity and local amenity and to minimise energy consumption.   |  |

# **Performance Outcome** Deemed-to-Satisfy Criteria / **Designated Performance Feature** All Development External Appearance PO 1.1 DTS/DPF 1.1 Buildings reinforce corners through changes in setback, None are applicable. articulation, materials, colour and massing (including height, width, bulk, roof form and slope). PO 1.2 DTS/DPF 1.2 Where zero or minor setbacks are desirable, development provides None are applicable. shelter over footpaths (in the form of verandahs, awnings, canopies and the like, with adequate lighting) to positively contribute to the walkability, comfort and safety of the public realm. PO 1.3 DTS/DPF 1.3 Building elevations facing the primary street (other than ancillary None are applicable. buildings) are designed and detailed to convey purpose, identify main access points and complement the streetscape. PO 1.4 DTS/DPF 1.4 Plant, exhaust and intake vents and other technical equipment are Development does not incorporate any structures that protrude integrated into the building design to minimise visibility from the beyond the roofline. public realm and negative impacts on residential amenity by: (a) positioning plant and equipment discretely, in unobtrusive locations as viewed from public roads and spaces (b) screening rooftop plant and equipment from view

Page 51 of 126 Printed on 5/07/2022

| Policy24 - Enquiry   |                      |
|--|----------------------|
| (c) when located on the roof of non-residential development, locating the plant and equipment as far as practicable from adjacent sensitive land uses.   |                      |
| PO 1.5   | DTS/DPF 1.5          |
| The negative visual impact of outdoor storage, waste management, loading and service areas is minimised by integrating them into the building design and screening them from public view (such as fencing, landscaping and built form), taking into account the form of development contemplated in the relevant zone. | None are applicable. |
| Sat  | fety                 |
| PO 2.1   | DTS/DPF 2.1          |
| Development maximises opportunities for passive surveillance of the public realm by providing clear lines of sight, appropriate lighting and the use of visually permeable screening wherever practicable.   | None are applicable. |
| PO 2.2   | DTS/DPF 2.2          |
| Development is designed to differentiate public, communal and private areas.   | None are applicable. |
| PO 2.3   | DTS/DPF 2.3          |
| Buildings are designed with safe, perceptible and direct access from public street frontages and vehicle parking areas.  | None are applicable. |
| PO 2.4   | DTS/DPF 2.4          |
| Development at street level is designed to maximise opportunities for passive surveillance of the adjacent public realm.   | None are applicable. |
| PO 2.5   | DTS/DPF 2.5          |
| Common areas and entry points of buildings (such as the foyer areas of residential buildings) and non-residential land uses at street level, maximise passive surveillance from the public realm to the inside of the building at night.   | None are applicable. |
| Lands  | caping               |
| PO 3.1   | DTS/DPF 3.1          |
| Soft landscaping and tree planting are incorporated to:  | None are applicable. |
| <ul> <li>(a) minimise heat absorption and reflection</li> <li>(b) maximise shade and shelter</li> <li>(c) maximise stormwater infiltration</li> <li>(d) enhance the appearance of land and streetscapes.</li> </ul>  |                      |
| Environmenta   | l Performance        |
| PO 4.1   | DTS/DPF 4.1          |
| Buildings are sited, oriented and designed to maximise natural sunlight access and ventilation to main activity areas, habitable rooms, common areas and open spaces.  | None are applicable. |
| PO 4.2   | DTS/DPF 4.2          |
| Buildings are sited and designed to maximise passive environmental   | None are applicable. |

Page 52 of 126 Printed on 5/07/2022

| Policy24 - Eriquity   |   |  |
|---|---|--|
| performance and minimise energy consumption and reliance on mechanical systems, such as heating and cooling.  |   |  |
| PO 4.3  | DTS/DPF 4.3   |  |
| Buildings incorporate climate responsive techniques and features such as building and window orientation, use of eaves, verandahs and shading structures, water harvesting, at ground landscaping, green walls, green roofs and photovoltaic cells.   | None are applicable.  |  |
| Water Sens  | sitive Design   |  |
| PO 5.1  | DTS/DPF 5.1   |  |
| Development is sited and designed to maintain natural hydrological systems without negatively impacting:  | None are applicable.  |  |
| (a) the quantity and quality of surface water and groundwater     (b) the depth and directional flow of surface water and groundwater   |   |  |
| (c) the quality and function of natural springs.  |   |  |
| On-site Waste Tr  | eatment Systems   |  |
| PO 6.1  | DTS/DPF 6.1   |  |
| Dedicated on-site effluent disposal areas do not include any areas to be used for, or could be reasonably foreseen to be used for, private open space, driveways or car parking.  | (a) encroach within an area used as private open space or result in less private open space than that specified in Design in Urban Areas Table 1 - Private Open Space (b) use an area also used as a driveway (c) encroach within an area used for on-site car parking or result in less on-site car parking than that specified in Transport, Access and Parking Table 1 - General Off-Street Car Parking Requirements or Table 2 - Off-Street Car Parking Requirements in Designated Areas. |  |
| Car parking   | appearance  |  |
| PO 7.1  | DTS/DPF 7.1   |  |
| Development facing the street is designed to minimise the negative impacts of any semi-basement and undercroft car parking on streetscapes through techniques such as:  (a) limiting protrusion above finished ground level  (b) screening through appropriate planting, fencing and mounding  (c) limiting the width of openings and integrating them into the building structure. | None are applicable.  |  |
| PO 7.2  | DTS/DPF 7.2   |  |
| Vehicle parking areas appropriately located, designed and constructed to minimise impacts on adjacent sensitive receivers through measures such as ensuring they are attractively developed and landscaped, screen fenced and the like.   | None are applicable.  |  |
| PO 7.3  | DTS/DPF 7.3   |  |
| Safe, legible, direct and accessible pedestrian connections are provided between parking areas and the development.   | None are applicable.  |  |
| PO 7.4  | DTS/DPF 7.4   |  |
|   | l   |  |

Page 53 of 126 Printed on 5/07/2022

| Street-level vehicle parking areas incorporate tree planting to provide shade, reduce solar heat absorption and reflection.   | Vehicle parking areas that are open to the sky and comprise 10 or more car parking spaces include a shade tree with a mature canopy of 4m diameter spaced for each 10 car parking spaces provided and a landscaped strip on any road frontage of a minimum dimension of 1m. |
|---|---|
| PO 7.5  | DTS/DPF 7.5   |
| Street level parking areas incorporate soft landscaping to improve visual appearance when viewed from within the site and from public places.   | Vehicle parking areas comprising 10 or more car parking spaces include soft landscaping with a minimum dimension of:  (a) 1m along all public road frontages and allotment boundaries  (b) 1m between double rows of car parking spaces.                                    |
| PO 7.6  | DTS/DPF 7.6   |
| Vehicle parking areas and associated driveways are landscaped to provide shade and positively contribute to amenity.  | None are applicable.  |
| PO 7.7  | DTS/DPF 7.7   |
| Vehicle parking areas and access ways incorporate integrated stormwater management techniques such as permeable or porous surfaces, infiltration systems, drainage swales or rain gardens that integrate with soft landscaping. | None are applicable.  |
| Earthworks a  | nd sloping land   |
| PO 8.1  | DTS/DPF 8.1   |
| Development, including any associated driveways and access tracks, minimises the need for earthworks to limit disturbance to natural topography.  | Development does not involve any of the following:  (a) excavation exceeding a vertical height of 1m  (b) filling exceeding a vertical height of 1m  (c) a total combined excavation and filling vertical height of 2m or more.   |
| PO 8.2  | DTS/DPF 8.2   |
| Driveways and access tracks designed and constructed to allow safe and convenient access on sloping land.   | Driveways and access tracks on sloping land (with a gradient exceeding 1 in 8) satisfy (a) and (b):  (a) do not have a gradient exceeding 25% (1-in-4) at any point along the driveway  (b) are constructed with an all-weather trafficable surface.                        |
| PO 8.3  | DTS/DPF 8.3   |
| Driveways and access tracks on sloping land (with a gradient exceeding 1 in 8):   | None are applicable.  |
| do not contribute to the instability of embankments and cuttings     provide level transition areas for the safe movement of people and goods to and from the development   |   |
| (c) are designed to integrate with the natural topography of the land.  |   |
| PO 8.4  | DTS/DPF 8.4   |
| Development on sloping land (with a gradient exceeding 1 in 8)  | None are applicable.  |

Page 54 of 126 Printed on 5/07/2022

| Policy24 - Enquiry  |  |  |
|---|--|--|
| avoids the alteration of natural drainage lines and includes on site drainage systems to minimise erosion.  |  |  |
| PO 8.5  | DTS/DPF 8.5  |  |
| Development does not occur on land at risk of landslip or increase the potential for landslip or land surface instability.  | None are applicable.   |  |
| Fences  | and walls  |  |
| PO 9.1  | DTS/DPF 9.1  |  |
| Fences, walls and retaining walls of sufficient height maintain privacy and security without unreasonably impacting visual amenity and adjoining land's access to sunlight or the amenity of public places. | None are applicable.   |  |
| PO 9.2  | DTS/DPF 9.2  |  |
| Landscaping is incorporated on the low side of retaining walls that are visible from public roads and public open space to minimise visual impacts.   | A vegetated landscaped strip 1m wide or more is provided against the low side of a retaining wall.   |  |
| Overlooking / Visual Pr   | ivacy (low rise buildings)   |  |
| PO 10.1   | DTS/DPF 10.1   |  |
| Development mitigates direct overlooking from upper level windows to habitable rooms and private open spaces of adjoining residential uses in neighbourhood-type zones.                                     | Upper level windows facing side or rear boundaries shared with a residential use in a neighbourhood-type zone:  (a) are permanently obscured to a height of 1.5m above finished floor level and are fixed or not capable of being opened more than 125mm  (b) have sill heights greater than or equal to 1.5m above finished floor level  (c) incorporate screening with a maximum of 25% openings, permanently fixed no more than 500mm from the window surface and sited adjacent to any part of the window less than 1.5 m above the finished floor level.  |  |
| PO 10.2   | DTS/DPF 10.2   |  |
| Development mitigates direct overlooking from balconies to habitable rooms and private open space of adjoining residential  | One of the following is satisfied:   |  |
| uses in neighbourhood type zones.   | <ul> <li>(a) the longest side of the balcony or terrace will face a public road, public road reserve or public reserve that is at least 15m wide in all places faced by the balcony or terrace or</li> <li>(b) all sides of balconies or terraces on upper building levels are permanently obscured by screening with a maximum 25% transparency/openings fixed to a minimum height of: <ul> <li>(i) 1.5m above finished floor level where the balcony is located at least 15 metres from the nearest habitable window of a dwelling on adjacent land or</li> <li>(ii) 1.7m above finished floor level in all other cases</li> </ul> </li> </ul> |  |
| Site Facilities / Waste Storage (exclu  | iding low rise residential development)  |  |
| PO 11.1   | DTS/DPF 11.1   |  |
| Development provides a dedicated area for on-site collection and sorting of recyclable materials and refuse, green organic waste and wash bay facilities for the ongoing maintenance of bins that is        | None are applicable.   |  |

Page 55 of 126 Printed on 5/07/2022

wash bay facilities for the ongoing maintenance of bins that is adequate in size considering the number and nature of the activities

| they will serve and the frequency of collection.   |                      |
|--|----------------------|
| PO 11.2  | DTS/DPF 11.2         |
| Communal waste storage and collection areas are located, enclosed and designed to be screened from view from the public domain, open space and dwellings.  | None are applicable. |
| PO 11.3  | DTS/DPF 11.3         |
| Communal waste storage and collection areas are designed to be well ventilated and located away from habitable rooms.  | None are applicable. |
| PO 11.4  | DTS/DPF 11.4         |
| Communal waste storage and collection areas are designed to allow waste and recycling collection vehicles to enter and leave the site without reversing.   | None are applicable. |
| PO 11.5  | DTS/DPF 11.5         |
| For mixed use developments, non-residential waste and recycling storage areas and access provide opportunities for on-site management of food waste through composting or other waste recovery as appropriate. | None are applicable. |
| All Development - Medium and High Rise   |                      |

| recovery as appropriate.  |   |  |  |
|---|---|--|--|
| All Development - N   | ledium and High Rise  |  |  |
| External A  | Appearance  |  |  |
| PO 12.1   | DTS/DPF 12.1  |  |  |
| Buildings positively contribute to the character of the local area by responding to local context.  | None are applicable.  |  |  |
| PO 12.2   | DTS/DPF 12.2  |  |  |
| Architectural detail at street level and a mixture of materials at lower building levels near the public interface are provided to reinforce a human scale. | None are applicable.  |  |  |
| PO 12.3   | DTS/DPF 12.3  |  |  |
| Buildings are designed to reduce visual mass by breaking up building elevations into distinct elements.   | None are applicable.  |  |  |
| PO 12.4   | DTS/DPF 12.4  |  |  |
| Boundary walls visible from public land include visually interesting treatments to break up large blank elevations.   | None are applicable.  |  |  |
| PO 12.5   | DTS/DPF 12.5  |  |  |
| External materials and finishes are durable and age well to minimise ongoing maintenance requirements.  | Buildings utilise a combination of the following external materials and finishes:   |  |  |
|   | <ul> <li>(a) masonry</li> <li>(b) natural stone</li> <li>(c) pre-finished materials that minimise staining, discolouring or deterioration.</li> </ul>   |  |  |
| PO 12.6   | DTS/DPF 12.6  |  |  |
| Street-facing building elevations are designed to provide attractive, high quality and pedestrian-friendly street frontages.                                | Building street frontages incorporate:  (a) active uses such as shops or offices (b) prominent entry areas for multi-storey buildings (where it is a common entry) (c) habitable rooms of dwellings |  |  |
|   | <ul> <li>(d) areas of communal public realm with public art or the like,<br/>where consistent with the zone and/or subzone provisions.</li> </ul>   |  |  |

Page 56 of 126 Printed on 5/07/2022

### Policy24 - Enquiry PO 12.7 **DTS/DPF 12.7** Entrances to multi-storey buildings are safe, attractive, welcoming, Entrances to multi-storey buildings are: functional and contribute to streetscape character. (a) oriented towards the street (b) clearly visible and easily identifiable from the street and vehicle parking areas (c) designed to be prominent, accentuated and a welcoming feature if there are no active or occupied ground floor (d) designed to provide shelter, a sense of personal address and transitional space around the entry (e) located as close as practicable to the lift and / or lobby access to minimise the need for long access corridors designed to avoid the creation of potential areas of entrapment. PO 12.8 **DTS/DPF 12.8** Building services, plant and mechanical equipment are screened None are applicable. from the public realm. Landscaping PO 13.1 DTS/DPF 13.1 Development facing a street provides a well landscaped area that Buildings provide a 4m by 4m deep soil space in front of the contains a deep soil space to accommodate a tree of a species and building that accommodates a medium to large tree, except where size adequate to provide shade, contribute to tree canopy targets no building setback from front property boundaries is desired.

and soften the appearance of buildings.

# PO 13.2

Deep soil zones are provided to retain existing vegetation or provide areas that can accommodate new deep root vegetation, including tall trees with large canopies to provide shade and soften the appearance of multi-storey buildings.

# **DTS/DPF 13.2**

Multi-storey development provides deep soil zones and incorporates trees at not less than the following rates, except in a location or zone where full site coverage is desired.

| Site area                           | Minimum deep soil area                     | Minimum<br>dimension | Tree / deep<br>soil zones                        |
|-------------------------------------|--|----------------------|--|
| <300 m <sup>2</sup>                 | 10 m <sup>2</sup>                          | 1.5m                 | 1 small tree /<br>10 m <sup>2</sup>              |
| 300-1500 m <sup>2</sup>             | 7% site area                               | 3m                   | 1 medium tree<br>/ 30 m <sup>2</sup>             |
| >1500 m <sup>2</sup>                | 7% site area                               | 6m                   | 1 large or<br>medium tree /<br>60 m <sup>2</sup> |
| Tree size and site area definitions |  |                      |  |
| Small tree                          | 4-6m mature height and 2-4m canopy spread  |                      |  |
| Medium tree                         | 6-12m mature height and 4-8m canopy spread |                      |  |
|                                     |  |                      |  |

Printed on 5/07/2022 Page 57 of 126

| Folicy24 - Eliquily   |                      |   |
|---|----------------------|---|
|   | Large tree           | 12m mature height and >8m canopy spread   |
|   | Site area            | The total area for development site, not average area per dwelling  |
| PO 13.3   | DTS/DPF 13.3         |   |
| Deep soil zones with access to natural light are provided to assist in maintaining vegetation health.   | None are applicable. |   |
| PO 13.4   | DTS/DPF 13.4         |   |
| Unless separated by a public road or reserve, development sites adjacent to any zone that has a primary purpose of accommodating low-rise residential development incorporate a deep soil zone along the common boundary to enable medium to large trees to be retained or established to assist in screening new buildings of 3 or more building levels in height. | •                    |   |
| Enviro  | nmental              |   |
| PO 14.1   | DTS/DPF 14.1         |   |
| Development minimises detrimental micro-climatic impacts on adjacent land and buildings.  | None are applicable. |   |
| PO 14.2   | DTS/DPF 14.2         |   |
| Development incorporates sustainable design techniques and features such as window orientation, eaves and shading structures, water harvesting and use, green walls and roof designs that enable the provision of rain water tanks (where they are not provided elsewhere on site), green roofs and photovoltaic cells.   | None are app         | olicable.   |
| PO 14.3   | DTS/DPF 14.3         |   |
| Development of 5 or more building levels, or 21m or more in height (as measured from natural ground level and excluding roof-mounted mechanical plant and equipment) is designed to minimise the impacts of wind through measures such as:  | None are app         | olicable.   |
| (a) a podium at the base of a tall tower and aligned with the street to deflect wind away from the street   |                      |   |
| (b) substantial verandahs around a building to deflect downward travelling wind flows over pedestrian areas   |                      |   |
| (c) the placement of buildings and use of setbacks to deflect the wind at ground level  |                      |   |
| (d) avoiding tall shear elevations that create windy conditions at street level.  |                      |   |
| Car P   | Parking              |   |
| PO 15.1   | DTS/DPF 15.1         |   |
| Multi-level vehicle parking structures are designed to contribute to active street frontages and complement neighbouring buildings.   | (a) prov             | chicle parking structures within buildings:  ride land uses such as commercial, retail or other not parking uses along ground floor street frontages    |
|   | alon                 | rporate facade treatments in building elevations facing major street frontages that are sufficiently enclose detailed to complement adjacent buildings. |

Page 58 of 126 Printed on 5/07/2022

PO 15.2

DTS/DPF 15.2

Multi-level vehicle parking structures within buildings complement the surrounding built form in terms of height, massing and scale. None are applicable.

### Overlooking/Visual Privacy

PO 16.1

Development mitigates direct overlooking of habitable rooms and private open spaces of adjacent residential uses in neighbourhoodtype zones through measures such as:

- (a) appropriate site layout and building orientation
- (b) off-setting the location of balconies and windows of habitable rooms or areas with those of other buildings so that views are oblique rather than direct to avoid direct line of sight
- (c) building setbacks from boundaries (including building boundary to boundary where appropriate) that interrupt views or that provide a spatial separation between balconies or windows of habitable rooms
- (d) screening devices that are integrated into the building design and have minimal negative effect on residents' or neighbours' amenity.

**DTS/DPF 16.1** 

None are applicable.

All residential development

### Front elevations and passive surveillance

PO 17.1

Dwellings incorporate windows facing primary street frontages to encourage passive surveillance and make a positive contribution to the streetscape. **DTS/DPF 17.1** 

Each dwelling with a frontage to a public street:

- (a) includes at least one window facing the primary street from a habitable room that has a minimum internal room dimension of 2.4m
- (b) has an aggregate window area of at least 2m<sup>2</sup> facing the primary street.

PO 17.2

DTS/DPF 17.2

Dwellings incorporate entry doors within street frontages to address the street and provide a legible entry point for visitors.

Dwellings with a frontage to a public street have an entry door visible from the primary street boundary.

# Outlook and Amenity

PO 18.1

**DTS/DPF 18.1** 

Living rooms have an external outlook to provide a high standard of amenity for occupants.

A living room of a dwelling incorporates a window with an external outlook of the street frontage, private open space, public open space, or waterfront areas.

PO 18.2

DTS/DPF 18.2

Bedrooms are separated or shielded from active communal recreation areas, common access areas and vehicle parking areas and access ways to mitigate noise and artificial light intrusion.

None are applicable.

#### **Ancillary Development**

PO 19.1

DTS/DPF 19.1

Residential ancillary buildings are sited and designed to not detract from the streetscape or appearance of primary residential buildings Ancillary buildings:

(a) are ancillary to a dwelling erected on the same site

Page 59 of 126 Printed on 5/07/2022

on the site or neighbouring properties.

- (b) have a floor area not exceeding 60m2
- (c) are not constructed, added to or altered so that any part is situated:
  - in front of any part of the building line of the dwelling to which it is ancillary
  - (ii) within 900mm of a boundary of the allotment with a secondary street (if the land has boundaries on two or more roads)
- (d) in the case of a garage or carport, the garage or carport:
  - (i) is set back at least 5.5m from the boundary of the primary street
  - (ii) when facing a primary street or secondary street, has a total door / opening not exceeding:
    - A. for dwellings of single building level 7m in width or 50% of the site frontage, whichever is the lesser
    - B. for dwellings comprising two or more building levels at the building line fronting the same public street 7m in width
- (e) if situated on a boundary (not being a boundary with a primary street or secondary street), do not exceed a length of 11.5m unless:
  - a longer wall or structure exists on the adjacent site and is situated on the same allotment boundary
     and
  - (ii) the proposed wall or structure will be built along the same length of boundary as the existing adjacent wall or structure to the same or lesser extent
- (f) if situated on a boundary of the allotment (not being a boundary with a primary street or secondary street), all walls or structures on the boundary will not exceed 45% of the length of that boundary
- (g) will not be located within 3m of any other wall along the same boundary unless on an adjacent site on that boundary there is an existing wall of a building that would be adjacent to or about the proposed wall or structure
- (h) have a wall height or post height not exceeding 3m above natural ground level (and not including a gable end)
- (i) have a roof height where no part of the roof is more than 5m above the natural ground level
- if clad in sheet metal, is pre-colour treated or painted in a non-reflective colour
- (k) retains a total area of soft landscaping in accordance with (i) or (ii), whichever is less:
  - (i) a total area as determined by the following table:

| Dwelling site area (or in the case of residential flat building or group dwelling(s), average site area) (m <sup>2</sup> ) | Minimum<br>percentage of<br>site |
|--|----------------------------------|
| <150   | 10%                              |
|  |                                  |

Page 60 of 126 Printed on 5/07/2022

of common driveway areas.

| Policy24 - Enquiry   |                                  |   |   |
|--|----------------------------------|---|---|
|  |                                  | 150-200   | 15%   |
|  |                                  | 201-450   | 20%   |
|  |                                  | >450  | 25%   |
|  | (ii)                             | the amount of existing the development occur                                  | soft landscaping prior to rring.  |
| PO 19.2  | DTS/DPF 19.2                     |   |   |
| Ancillary buildings and structures do not impede on-site functional requirements such as private open space provision, car parking requirements or result in over-development of the site.             | (a) less pri                     | gs and structures do no<br>vate open space than s<br>Table 1 - Private Open S | pecified in Design in Urba  |
|  | (b) less on<br>Access<br>Parking | -site car parking than sp<br>and Parking Table 1 - 0                          | pecified in Transport,<br>General Off-Street Car<br>e 2 - Off-Street Car Parkin |
| PO 19.3  | DTS/DPF 19.3                     |   |   |
| Fixed plant and equipment in the form of pumps and/or filtration systems for a swimming pool or spa positioned and/or housed to not cause unreasonable noise nuisance to adjacent sensitive receivers. | The pump and/o                   |   | illary to a dwelling erected  |
|  | least 5r                         |   | ucture that is located at able room located on an                               |
|  |                                  | at least 12m from the noon an adjoining allotme                               |   |
| Residential Deve   | lopment - Low Rise               |   |   |
| External   | appearance                       |   |   |
| PO 20.1  | DTS/DPF 20.1                     |   |   |
| Garaging is designed to not detract from the streetscape or appearance of a dwelling.  | Garages and ca                   | rports facing a street:   |   |
|  |                                  | ated so that no part of the of any part of the building.                      | he garage or carport will b<br>ng line of the dwelling                          |
|  | (b) are set primary              | back at least 5.5m from   | the boundary of the   |
|  |                                  | garage door / opening v   | vidth not exceeding 7m  |
|  | the site                         | frontage unless the dwe   | vidth not exceeding 50%<br>elling has two or more<br>ne fronting the same publi |
| PO 20.2  | DTS/DPF 20.2                     |   |   |
| Dwelling elevations facing public streets and common driveways make a positive contribution to the streetscape and the appearance of common driveways group.   | within the building              | ng elevation facing a prir  | following design features mary street, and at least 2                           |

Page 61 of 126 Printed on 5/07/2022

driveway:

(a)

of the following design features within the building elevation facing any other public road (other than a laneway) or a common

a minimum of 30% of the building wall is set back an

additional 300mm from the building line

Policy24 - Enquiry (b) a porch or portico projects at least 1m from the building (c) a balcony projects from the building wall (d) a verandah projects at least 1m from the building wall (e) eaves of a minimum 400mm width extend along the width of the front elevation (f) a minimum 30% of the width of the upper level projects forward from the lower level primary building line by at least 300mm a minimum of two different materials or finishes are (g) incorporated on the walls of the front building elevation, with a maximum of 80% of the building elevation in a single material or finish. PO 20.3 DTS/DPF 20.3 The visual mass of larger buildings is reduced when viewed from None are applicable adjoining allotments or public streets. Private Open Space PO 21.1 DTS/DPF 21.1 Dwellings are provided with suitable sized areas of usable private Private open space is provided in accordance with Design in Urban open space to meet the needs of occupants. Areas Table 1 - Private Open Space. PO 21.2 **DTS/DPF 21.2** Private open space is positioned to provide convenient access from Private open space is directly accessible from a habitable room. internal living areas. Landscaping DTS/DPF 22.1 PO 22.1 Soft landscaping is incorporated into development to: Residential development incorporates soft landscaping with a minimum dimension of 700mm provided in accordance with (a) and (a) minimise heat absorption and reflection (b): (b) contribute shade and shelter (c) (a) a total area as determined by the following table: provide for stormwater infiltration and biodiversity (d) enhance the appearance of land and streetscapes.

| Dwelling site area (or in the case of residential flat building or group dwelling(s), average site area) (m <sup>2</sup> ) | Minimum<br>percentage of<br>site |  |
|--|----------------------------------|--|
| <150   | 10%                              |  |
| 150-200  | 15%                              |  |
| >200-450   | 20%                              |  |
| >450   | 25%                              |  |
| at least 30% of any land between the primary street  |                                  |  |

Page 62 of 126 Printed on 5/07/2022

(b)

| Folicy24 - Eliquily   |   |
|---|---|
|   | boundary and the primary building line.   |
| Car parking, access   | s and manoeuvrability   |
| PO 23.1   | DTS/DPF 23.1  |
| Enclosed car parking spaces are of dimensions to be functional, accessible and convenient.  | Residential car parking spaces enclosed by fencing, walls or other structures have the following internal dimensions (separate from any waste storage area):  |
|   | <ul> <li>(a) single width car parking spaces: <ul> <li>(i) a minimum length of 5.4m per space</li> <li>(ii) a minimum width of 3.0m</li> <li>(iii) a minimum garage door width of 2.4m</li> </ul> </li> <li>(b) double width car parking spaces (side by side): <ul> <li>(i) a minimum length of 5.4m</li> <li>(ii) a minimum width of 5.4m</li> <li>(iii) minimum garage door width of 2.4m per space.</li> </ul> </li> </ul>  |
| PO 23.2   | DTS/DPF 23.2  |
| Uncovered car parking space are of dimensions to be functional, accessible and convenient.  | Uncovered car parking spaces have:  (a) a minimum length of 5.4m (b) a minimum width of 2.4m (c) a minimum width between the centre line of the space and any fence, wall or other obstruction of 1.5m.   |
| PO 23.3   | DTS/DPF 23.3  |
| Driveways and access points are located and designed to facilitate safe access and egress while maximising land available for street tree planting, domestic waste collection, landscaped street frontages and on-street parking. | Driveways and access points satisfy (a) or (b):  (a) sites with a frontage to a public road of 10m or less, have a width between 3.0 and 3.2 metres measured at the property boundary and are the only access point provided  |
|   | on the site  (b) sites with a frontage to a public road greater than 10m:  (i) have a maximum width of 5m measured at the property boundary and are the only access point provided on the site;  (ii) have a width between 3.0 metres and 3.2 metres measured at the property boundary and no more than two access points are provided on site, separated by no less than 1m.   |
| PO 23.4   | DTS/DPF 23.4  |
| Vehicle access is safe, convenient, minimises interruption to the operation of public roads and does not interfere with street infrastructure or street trees.  | Vehicle access to designated car parking spaces satisfy (a) or (b):  (a) is provided via a lawfully existing or authorised access point or an access point for which consent has been granted as part of an application for the division of land  (b) where newly proposed, is set back:  (i) 0.5m or more from any street furniture, street pole, infrastructure services pit, or other stormwater or utility infrastructure unless consent is provided from the asset owner  (ii) 2m or more from the base of the trunk of a street |
|   | tree unless consent is provided from the tree   |

Page 63 of 126 Printed on 5/07/2022

tree unless consent is provided from the tree

# owner for a lesser distance (iii) 6m or more from the tangent point of an intersection of 2 or more roads outside of the marked lines or infrastructure dedicating a pedestrian crossing. PO 23.5 DTS/DPF 23.5 Driveways are designed to enable safe and convenient vehicle Driveways are designed and sited so that: movements from the public road to on-site parking spaces. the gradient from the place of access on the boundary of the allotment to the finished floor level at the front of the garage or carport is not steeper than 1-in-4 on average (b) they are aligned relative to the street so that there is no more than a 20 degree deviation from 90 degrees between the centreline of any dedicated car parking space to which it provides access (measured from the front of that space) and the road boundary. if located so as to provide access from an alley, lane or (c) right of way - the alley, lane or right or way is at least 6.2m wide along the boundary of the allotment / site PO 23.6 **DTS/DPF 23.6** Driveways and access points are designed and distributed to Where on-street parking is available abutting the site's street optimise the provision of on-street visitor parking. frontage, on-street parking is retained in accordance with the following requirements: minimum 0.33 on-street spaces per dwelling on the site (rounded up to the nearest whole number) minimum car park length of 5.4m where a vehicle can enter or exit a space directly (c) minimum carpark length of 6m for an intermediate space located between two other parking spaces or to an end obstruction where the parking is indented. Waste storage PO 24.1 DTS/DPF 24.1 Provision is made for the convenient storage of waste bins in a Where dwellings abut both side boundaries a waste bin storage location screened from public view. area is provided behind the building line of each dwelling that: has a minimum area of 2m<sup>2</sup> with a minimum dimension of 900mm (separate from any designated car parking spaces or private open space); and has a continuous unobstructed path of travel (excluding moveable objects like gates, vehicles and roller doors) with a minimum width of 800mm between the waste bin storage area and the street. Design of Transportable Buildings **DTS/DPF 25.1** PO 25 1 The sub-floor space beneath transportable buildings is enclosed to Buildings satisfy (a) or (b): give the appearance of a permanent structure. (a) are not transportable (b) the sub-floor space between the building and ground level is clad in a material and finish consistent with the building.

Page 64 of 126 Printed on 5/07/2022

Residential Development - Medium and High Rise (including serviced apartments)

| Outlook and <sup>1</sup>   | Visual Privacy  |
|--|---|
| PO 26.1  | DTS/DPF 26.1  |
| Ground level dwellings have a satisfactory short range visual outlook to public, communal or private open space.   | Buildings:  (a) provide a habitable room at ground or first level with a window facing toward the street  (b) limit the height / extent of solid walls or fences facing the street to 1.2m high above the footpath level or, where higher, to 50% of the site frontage. |
| PO 26.2  | DTS/DPF 26.2  |
| The visual privacy of ground level dwellings within multi-level buildings is protected.  | The finished floor level of ground level dwellings in multi-storey developments is raised by up to 1.2m.  |
| Private O <sub>l</sub>   | pen Space   |
| PO 27.1  | DTS/DPF 27.1  |
| Dwellings are provided with suitable sized areas of usable private open space to meet the needs of occupants.  | Private open space provided in accordance with Design in Urban Areas Table 1 - Private Open Space.  |
| Residential amenity i  | n multi-level buildings   |
| PO 28.1  | DTS/DPF 28.1  |
| Residential accommodation within multi-level buildings have habitable rooms, windows and balconies designed and positioned to be separated from those of other dwellings and accommodation to provide visual and acoustic privacy and allow for natural ventilation and the infiltration of daylight into interior and outdoor spaces. | Habitable rooms and balconies of independent dwellings and accommodation are separated by at least 6m from one another where there is a direct line of sight between them and 3m or more from a side or rear property boundary.   |
| PO 28.2  | DTS/DPF 28.2  |
| Balconies are designed, positioned and integrated into the overall architectural form and detail of the development to:  | Balconies utilise one or a combination of the following design elements:  |
| (a) respond to daylight, wind, and acoustic conditions to maximise comfort and provide visual privacy     (b) allow views and casual surveillance of the street while providing for safety and visual privacy of nearby living spaces and private outdoor areas.   | (a) sun screens (b) pergolas (c) louvres (d) green facades (e) openable walls.  |
| PO 28.3  | DTS/DPF 28.3  |
| Balconies are of sufficient size and depth to accommodate outdoor seating and promote indoor / outdoor living.   | Balconies open directly from a habitable room and incorporate a minimum dimension of 2m.  |
| PO 28.4  | DTS/DPF 28.4  |
| Dwellings are provided with sufficient space for storage to meet likely occupant needs.  | Dwellings (not including student accommodation or serviced apartments) are provided with storage at the following rates with at least 50% or more of the storage volume to be provided within the dwelling:   |
|  | (a) studio: not less than 6m <sup>3</sup> (b) 1 bedroom dwelling / apartment: not less than 8m <sup>3</sup> (c) 2 bedroom dwelling / apartment: not less than 10m <sup>3</sup> (d) 3+ bedroom dwelling / apartment: not less than 12m <sup>3</sup> .                    |

Page 65 of 126 Printed on 5/07/2022

| PO 28.5  Dwellings that use light wells for access to daylight, outlook and ventilation for habitable rooms, are designed to ensure a reasonable living amenity is provided.  PO 28.6  Attached or abutting dwellings are designed to minimise the transmission of sound between dwellings and, in particular, to protect bedrooms from possible noise intrusions.  PO 28.7  Dwellings are designed so that internal structural columns | Light wells:  (a) are not used as the primary source of outlook for living rooms  (b) up to 18m in height have a minimum horizontal dimension of 3m, or 6m if overlooked by bedrooms  (c) above 18m in height have a minimum horizontal dimension of 6m, or 9m if overlooked by bedrooms.  DTS/DPF 28.6  None are applicable.  DTS/DPF 28.7  None are applicable.   |  |  |
|---|---|--|--|
| correspond with the position of internal walls to ensure that the space within the dwelling/apartment is useable.   |   |  |  |
| Dwelling C  | onfiguration  |  |  |
| PO 29.1   | DTS/DPF 29.1  |  |  |
| Buildings containing in excess of 10 dwellings provide a variety of dwelling sizes and a range in the number of bedrooms per dwelling to contribute to housing diversity.   | Buildings containing in excess of 10 dwellings provide at least one of each of the following:  (a) studio (where there is no separate bedroom)  (b) 1 bedroom dwelling / apartment with a floor area of at leas 50m <sup>2</sup> (c) 2 bedroom dwelling / apartment with a floor area of at leas 65m <sup>2</sup> (d) 3+ bedroom dwelling / apartment with a floor area of at least 80m <sup>2</sup> , and any dwelling over 3 bedrooms provides ar additional 15m <sup>2</sup> for every additional bedroom. |  |  |
| PO 29.2   | DTS/DPF 29.2  |  |  |
| Dwellings located on the ground floor of multi-level buildings with 3 or more bedrooms have the windows of their habitable rooms overlooking internal courtyard space or other public space, where possible.  | None are applicable.  |  |  |
| Commo   | on Areas  |  |  |
| PO 30.1   | DTS/DPF 30.1  |  |  |
| The size of lifts, lobbies and corridors is sufficient to accommodate movement of bicycles, strollers, mobility aids and visitor waiting areas.   | Common corridor or circulation areas:  (a) have a minimum ceiling height of 2.7m  (b) provide access to no more than 8 dwellings  (c) incorporate a wider section at apartment entries where the corridors exceed 12m in length from a core.  |  |  |
| Group Dwellings, Residential Flat B   | uildings and Battle axe Development   |  |  |
|   | enity   |  |  |
| PO 31.1   | DTS/DPF 31.1  |  |  |
| Durallings are of a suitable size to provide a high standard of   | Dwallings have a minimum internal floor area in accordance with   |  |  |

Page 66 of 126 Printed on 5/07/2022

the following table:

Dwellings have a minimum internal floor area in accordance with

Dwellings are of a suitable size to provide a high standard of

amenity for occupants.

|   | Number of bedrooms   | Minimum internal floor area   |  |
|---|--|---|--|
|   | Studio   | 35m <sup>2</sup>  |  |
|   | 1 bedroom  | 50m <sup>2</sup>  |  |
|   | 2 bedroom  | 65m <sup>2</sup>  |  |
|   | 3+ bedrooms  | 80m <sup>2</sup> and any dwelling over 3<br>bedrooms provides an additional<br>15m <sup>2</sup> for every additional<br>bedroom |  |
| PO 31.2   | DTS/DPF 31.2   |   |  |
| The orientation and siting of buildings minimises impacts on the amenity, outlook and privacy of occupants and neighbours.  | None are applicable.   |   |  |
| PO 31.3   | DTS/DPF 31.3   |   |  |
| Development maximises the number of dwellings that face public open space and public streets and limits dwellings oriented towards adjoining properties.  | None are applicable.   |   |  |
| PO 31.4   | DTS/DPF 31.4   |   |  |
| Battle-axe development is appropriately sited and designed to respond to the existing neighbourhood context.  | Dwelling sites/allotments are not in the form of a battle-axe arrangement.   |   |  |
| Communal  | Open Space   |   |  |
| PO 32.1   | DTS/DPF 32.1   |   |  |
| Private open space provision may be substituted for communal open space which is designed and sited to meet the recreation and  | None are applicable.   |   |  |
| amenity needs of residents.   |  |   |  |
| amenity needs of residents. PO 32.2   | DTS/DPF 32.2   |   |  |
| ,   | DTS/DPF 32.2  Communal open space incorporal metres.   | tes a minimum dimension of 5  |  |
| PO 32.2 Communal open space is of sufficient size and dimensions to cater   | Communal open space incorporal metres.  DTS/DPF 32.3   | tes a minimum dimension of 5  |  |
| PO 32.2  Communal open space is of sufficient size and dimensions to cater for group recreation.  | Communal open space incorporate metres.  | tes a minimum dimension of 5  |  |
| PO 32.2  Communal open space is of sufficient size and dimensions to cater for group recreation.  PO 32.3   | Communal open space incorporal metres.  DTS/DPF 32.3   | tes a minimum dimension of 5  |  |
| PO 32.2  Communal open space is of sufficient size and dimensions to cater for group recreation.  PO 32.3  Communal open space is designed and sited to:  (a) be conveniently accessed by the dwellings which it  | Communal open space incorporal metres.  DTS/DPF 32.3   | tes a minimum dimension of 5  |  |
| PO 32.2  Communal open space is of sufficient size and dimensions to cater for group recreation.  PO 32.3  Communal open space is designed and sited to:  (a) be conveniently accessed by the dwellings which it services   | Communal open space incorporal metres.  DTS/DPF 32.3   | tes a minimum dimension of 5  |  |
| PO 32.2  Communal open space is of sufficient size and dimensions to cater for group recreation.  PO 32.3  Communal open space is designed and sited to:  (a) be conveniently accessed by the dwellings which it services  (b) have regard to acoustic, safety, security and wind effects.  | Communal open space incorporal metres.  DTS/DPF 32.3  None are applicable.   | tes a minimum dimension of 5  |  |
| PO 32.2  Communal open space is of sufficient size and dimensions to cater for group recreation.  PO 32.3  Communal open space is designed and sited to:  (a) be conveniently accessed by the dwellings which it services  (b) have regard to acoustic, safety, security and wind effects.  PO 32.4  Communal open space contains landscaping and facilities that are   | Communal open space incorporal metres.  DTS/DPF 32.3  None are applicable.  DTS/DPF 32.4                                     | tes a minimum dimension of 5  |  |
| PO 32.2  Communal open space is of sufficient size and dimensions to cater for group recreation.  PO 32.3  Communal open space is designed and sited to:  (a) be conveniently accessed by the dwellings which it services (b) have regard to acoustic, safety, security and wind effects.  PO 32.4  Communal open space contains landscaping and facilities that are functional, attractive and encourage recreational use.           | Communal open space incorporal metres.  DTS/DPF 32.3  None are applicable.  DTS/DPF 32.4  None are applicable.               | tes a minimum dimension of 5  |  |
| PO 32.2  Communal open space is of sufficient size and dimensions to cater for group recreation.  PO 32.3  Communal open space is designed and sited to:  (a) be conveniently accessed by the dwellings which it services  (b) have regard to acoustic, safety, security and wind effects.  PO 32.4  Communal open space contains landscaping and facilities that are functional, attractive and encourage recreational use.  PO 32.5 | Communal open space incorporal metres.  DTS/DPF 32.3  None are applicable.  DTS/DPF 32.4  None are applicable.  DTS/DPF 32.5 | tes a minimum dimension of 5  |  |

Page 67 of 126 Printed on 5/07/2022

| by habitable rooms to facilitate passive surveillance.   |  |  |  |
|--|--|--|--|
| Car parking, access  | and manoeuvrability  |  |  |
| PO 33.1  | DTS/DPF 33.1   |  |  |
| Driveways and access points are designed and distributed to optimise the provision of on-street visitor parking.   | Where on-street parking is available directly adjacent the site, on-<br>street parking is retained adjacent the subject site in accordance<br>with the following requirements:   |  |  |
|  | <ul> <li>(a) minimum 0.33 on-street car parks per proposed dwelling (rounded up to the nearest whole number)</li> <li>(b) minimum car park length of 5.4m where a vehicle can enter or exit a space directly</li> <li>(c) minimum carpark length of 6m for an intermediate space located between two other parking spaces or to an end obstruction where the parking is indented.</li> </ul> |  |  |
| PO 33.2  | DTS/DPF 33.2   |  |  |
| The number of vehicular access points onto public roads is minimised to reduce interruption of the footpath and positively contribute to public safety and walkability.  | Access to group dwellings or dwellings within a residential flat building is provided via a single common driveway.  |  |  |
| PO 33.3  | DTS/DPF 33.3   |  |  |
| Residential driveways that service more than one dwelling are designed to allow safe and convenient movement.  | Driveways that service more than 1 dwelling or a dwelling on a battle-axe site:  |  |  |
|  | (a) have a minimum width of 3m (b) for driveways servicing more than 3 dwellings:  (i) have a width of 5.5m or more and a length of 6m or more at the kerb of the primary street  (ii) where the driveway length exceeds 30m, incorporate a passing point at least every 30 metres with a minimum width of 5.5m and a minimum length of 6m.  |  |  |
| PO 33.4  | DTS/DPF 33.4   |  |  |
| Residential driveways that service more than one dwelling or a dwelling on a battle-axe site are designed to allow passenger vehicles to enter and exit and manoeuvre within the site in a safe and convenient manner. | Driveways providing access to more than one dwelling, or a dwelling on a battle-axe site, allow a B85 passenger vehicle to enter and exit the garages or parking spaces in no more than a three-point turn manoeuvre.  |  |  |
| PO 33.5  | DTS/DPF 33.5   |  |  |
| Dwellings are adequately separated from common driveways and manoeuvring areas.  | Dwelling walls with entry doors or ground level habitable room windows are set back at least 1.5m from any driveway or area designated for the movement and manoeuvring of vehicles.   |  |  |
| Soft lan   | dscaping   |  |  |
| PO 34.1  | DTS/DPF 34.1   |  |  |
| Soft landscaping is provided between dwellings and common driveways to improve the outlook for occupants and appearance of common areas.   | Other than where located directly in front of a garage or building entry, soft landscaping with a minimum dimension of 1m is provided between a dwelling and common driveway.  |  |  |
| PO 34.2  | DTS/DPF 34.2   |  |  |
| Battle-axe or common driveways incorporate landscaping and   | Battle-axe or common driveways satisfy (a) and (b):  |  |  |

Page 68 of 126 Printed on 5/07/2022

| permeability to improve appearance and assist in stormwater management.  | (a) are constructed of a minimum of 50% permeable or   |  |  |
|--|--|--|--|
|  | porous material  (b) where the driveway is located directly adjacent the side or rear boundary of the site, soft landscaping with a minimum dimension of 1m is provided between the driveway and site boundary (excluding along the perimeter of a passing point). |  |  |
| Site Facilities /  | Waste Storage  |  |  |
| PO 35.1  | DTS/DPF 35.1   |  |  |
| Provision is made for suitable mailbox facilities close to the major pedestrian entry to the site or conveniently located considering the nature of accommodation and mobility of occupants.   | None are applicable.   |  |  |
| PO 35.2  | DTS/DPF 35.2   |  |  |
| Provision is made for suitable external clothes drying facilities.   | None are applicable.   |  |  |
| PO 35.3  | DTS/DPF 35.3   |  |  |
| Provision is made for suitable household waste and recyclable material storage facilities which are:   | None are applicable.   |  |  |
| <ul> <li>(a) located away, or screened, from public view, and</li> <li>(b) conveniently located in proximity to dwellings and the waste collection point.</li> </ul>   |  |  |  |
| PO 35.4  | DTS/DPF 35.4   |  |  |
| Waste and recyclable material storage areas are located away from dwellings.   | Dedicated waste and recyclable material storage areas are located at least 3m from any habitable room window.  |  |  |
| PO 35.5  | DTS/DPF 35.5   |  |  |
| Where waste bins cannot be conveniently collected from the street, provision is made for on-site waste collection, designed to accommodate the safe and convenient access, egress and movement of waste collection vehicles.   | None are applicable.   |  |  |
| PO 35.6  | DTS/DPF 35.6   |  |  |
| Services including gas and water meters are conveniently located and screened from public view.  | None are applicable.   |  |  |
| Water sensitiv   | e urban design   |  |  |
| PO 36.1  | DTS/DPF 36.1   |  |  |
| Residential development creating a common driveway / access includes stormwater management systems that minimise the discharge of sediment, suspended solids, organic matter, nutrients, bacteria, litter and other contaminants to the stormwater system, watercourses or other water bodies.     | None are applicable.   |  |  |
| PO 36.2  | DTS/DPF 36.2   |  |  |
| Residential development creating a common driveway / access includes a stormwater management system designed to mitigate peak flows and manage the rate and duration of stormwater discharges from the site to ensure that the development does not increase the peak flows in downstream systems. | None are applicable.   |  |  |

Page 69 of 126 Printed on 5/07/2022

| Supported Accommodation and retirement facilities  |   |  |  |
|--|---|--|--|
|  | ation and Design  |  |  |
| PO 37.1  | DTS/DPF 37.1  |  |  |
| Supported accommodation and housing for aged persons and people with disabilities is located where on-site movement of   | None are applicable.  |  |  |
| residents is not unduly restricted by the slope of the land.   |   |  |  |
| PO 37.2  | DTS/DPF 37.2  |  |  |
| Universal design features are incorporated to provide options for  | None are applicable.  |  |  |
| people living with disabilities or limited mobility and / or to facilitate   | ''  |  |  |
| ageing in place.  Movement   | and Access  |  |  |
| PO 38.1  | DTS/DPF 38.1  |  |  |
| Development is designed to support safe and convenient access  | None are applicable.  |  |  |
| and movement for residents by providing:   |   |  |  |
| (a) ground-level access or lifted access to all units  |   |  |  |
| (b) level entry porches, ramps, paths, driveways, passenger loading areas and areas adjacent to footpaths that allow for the passing of wheelchairs and resting places |   |  |  |
| (c) car parks with gradients no steeper than 1-in-40, and of   |   |  |  |
| sufficient area to provide for wheelchair manoeuvrability (d) kerb ramps at pedestrian crossing points.  |   |  |  |
| 7 7 7 7 31   |   |  |  |
|  | Open Space  |  |  |
| PO 39.1  | DTS/DPF 39.1  |  |  |
| Development is designed to provide attractive, convenient and comfortable indoor and outdoor communal areas to be used by  | None are applicable.  |  |  |
| residents and visitors.  |   |  |  |
| PO 39.2  | DTS/DPF 39.2  |  |  |
| Private open space provision may be substituted for communal   | None are applicable.  |  |  |
| open space which is designed and sited to meet the recreation and amenity needs of residents.  |   |  |  |
| amenity needs of residents.  |   |  |  |
| PO 39.3  | DTS/DPF 39.3  |  |  |
| Communal open space is of sufficient size and dimensions to cater for group recreation.  | Communal open space incorporates a minimum dimension of 5 metres. |  |  |
| PO 39.4  | DTS/DPF 39.4  |  |  |
| Communal open space is designed and sited to:  | None are applicable.  |  |  |
| (a) be conveniently accessed by the dwellings which it services  |   |  |  |
| (b) have regard to acoustic, safety, security and wind effects.  |   |  |  |
| PO 39.5  | DTS/DPF 39.5  |  |  |
| Communal open space contains landscaping and facilities that are functional, attractive and encourage recreational use.  | None are applicable.  |  |  |
| PO 39.6  | DTS/DPF 39.6  |  |  |

Page 70 of 126 Printed on 5/07/2022

Communal open space is designed and sited to: None are applicable. (a) in relation to rooftop or elevated gardens, minimise overlooking into habitable room windows or onto the useable private open space of other dwellings (b) in relation to ground floor communal space, be overlooked by habitable rooms to facilitate passive surveillance. Site Facilities / Waste Storage DTS/DPF 40.1 PO 40.1 Development is designed to provide storage areas for personal None are applicable. items and specialised equipment such as small electric powered vehicles, including facilities for the recharging of small electricpowered vehicles. PO 40.2 DTS/DPF 40.2 Provision is made for suitable mailbox facilities close to the major None are applicable. pedestrian entry to the site or conveniently located considering the nature of accommodation and mobility of occupants. PO 40.3 DTS/DPF 40.3 Provision is made for suitable external clothes drying facilities. None are applicable. PO 40.4 DTS/DPF 40.4 Provision is made for suitable household waste and recyclable None are applicable. material storage facilities conveniently located away, or screened, from view. PO 40.5 DTS/DPF 40.5 Waste and recyclable material storage areas are located away from Dedicated waste and recyclable material storage areas are located dwellings. at least 3m from any habitable room window. PO 40.6 DTS/DPF 40.6 Provision is made for on-site waste collection where 10 or more None are applicable. bins are to be collected at any one time. PO 40.7 DTS/DPF 40.7 Services, including gas and water meters, are conveniently located None are applicable. and screened from public view. Student Accommodation PO 41.1 **DTS/DPF 41.1** Student accommodation is designed to provide safe, secure, Student accommodation provides: attractive, convenient and comfortable living conditions for a range of living options to meet a variety of residents, including an internal layout and facilities that are accommodation needs, such as one-bedroom, twodesigned to provide sufficient space and amenity for the bedroom and disability access units requirements of student life and promote social interaction. common or shared facilities to enable a more efficient use of space, including: (i) shared cooking, laundry and external drying internal and external communal and private open space provided in accordance with Design in Urban Areas Table 1 - Private Open Space

Page 71 of 126 Printed on 5/07/2022

|                   |  | (ii                  | ii)   | common storage facilities at the rate of 8m <sup>3</sup> for every 2 dwellings or students   |
|-------------------|--|----------------------|-------|--|
|                   |  | (iv                  | v)    | common on-site parking in accordance with<br>Transport, Access and Parking Table 1 - General<br>Off-Street Car Parking Requirements or Table 2 -<br>Off-Street Car Parking Requirements in<br>Designated Areas |
|                   |  | (v                   | /)    | bicycle parking at the rate of one space for every 2 students.   |
| PO 41.2           |  | DTS/DPF 41.2         |       |  |
| the build         | accommodation is designed to provide easy adaptation of ling to accommodate an alternative use of the building in the is no longer required for student housing.   | None are applicable. |       |  |
|                   | All non-resident   | ial development      | t     |  |
|                   | Water Sens   | itive Design         |       |  |
| PO 42.1           |  | DTS/DPF 42.1         |       |  |
| solids, o         | ment likely to result in risk of export of sediment, suspended organic matter, nutrients, oil and grease include stormwater ment systems designed to minimise pollutants entering tter.                                  | None are applicable. |       |  |
| PO 42.2           |  | DTS/DPF 42.2         |       |  |
| chemica           | ischarged from a development site is of a physical, al and biological condition equivalent to or better than its eloped state.   | None are applicable. |       |  |
| PO 42.3           |  | DTS/DPF 42.3         |       |  |
| peak floodischarg | ment includes stormwater management systems to mitigate ws and manage the rate and duration of stormwater ges from the site to ensure that development does not a peak flows in downstream systems.                      | None are ap          | plica | able.  |
|                   | Wash-down and Waste  | Loading and Ur       | nload | ding   |
| PO 43.1           |  | DTS/DPF 43.1         |       |  |
| waste re          | or activities including loading and unloading, storage of<br>efuse bins in commercial and industrial development or<br>own areas used for the cleaning of vehicles, plant or<br>ent are:                                 | None are ap          | plica | able.  |
| (a)               | designed to contain all wastewater likely to pollute<br>stormwater within a bunded and roofed area to exclude the<br>entry of external surface stormwater run-off  |                      |       |  |
| (b)               | paved with an impervious material to facilitate wastewater collection  |                      |       |  |
| (c)               | of sufficient size to prevent 'splash-out' or 'over-spray' of wastewater from the wash-down area   |                      |       |  |
| (d)               | are designed to drain wastewater to either:  (i) a treatment device such as a sediment trap and coalescing plate oil separator with subsequent disposal to a sewer, private or Community Wastewater Management Scheme or |                      |       |  |

Page 72 of 126 Printed on 5/07/2022

Policy24 - Enquiry (ii) a holding tank and its subsequent removal off-site on a regular basis. Laneway Development Infrastructure and Access DTS/DPF 44.1 PO 44.1 Development with a primary street frontage that is not an alley, lane, Development with a primary street comprising a laneway, alley, right of way or similar public thoroughfare. lane, right of way or similar minor thoroughfare only occurs where: (a) existing utility infrastructure and services are capable of accommodating the development (b) the primary street can support access by emergency and regular service vehicles (such as waste collection)

(c) it does not require the provision or upgrading of

infrastructure on public land (such as footpaths and stormwater management systems)

- (d) safety of pedestrians or vehicle movement is maintained
- (e) any necessary grade transition is accommodated within the site of the development to support an appropriate development intensity and orderly development of land fronting minor thoroughfares.

**Table 1 - Private Open Space** 

| Dwelling Type   | Dwelling / Site               | Minimum Rate  |  |
|---|-------------------------------|---|--|
|   | Configuration                 |   |  |
| Dwelling (at ground level, other than a residential flat building that includes above ground dwellings) |                               | <ul> <li>Total private open space area: <ul> <li>(a) Site area &lt;301m2: 24m2 located behind the building line.</li> <li>(b) Site area ≥ 301m2: 60m2 located behind the building line.</li> </ul> </li> <li>Minimum directly accessible from a living room: 16m2 / with a minimum dimension 3m.</li> </ul> |  |
| Cabin or caravan (permanently fixed to the ground) in a residential park or caravan and tourist park    |                               | Total area: 16m <sup>2</sup> , which may be uses as second car parking space, provided on each site intended for residential occupation.  |  |
| Dwelling in a residential flat building or mixed use building which incorporate                         | Dwellings at ground level:    | 15m <sup>2</sup> / minimum dimension 3m   |  |
| above ground level dwellings  | Dwellings above ground level: |   |  |
|   | Studio (no separate bedroom)  | 4m <sup>2</sup> / minimum dimension 1.8m  |  |
|   | One bedroom dwelling          | 8m <sup>2</sup> / minimum dimension 2.1m  |  |
|   | Two bedroom dwelling          | 11m <sup>2</sup> / minimum dimension 2.4m   |  |
|   |                               |   |  |

Page 73 of 126 Printed on 5/07/2022

| Three + bedroom dwelling | 15 m <sup>2</sup> / minimum dimension 2.6m |
|--------------------------|--|
|                          |  |

## **Forestry**

## **Assessment Provisions (AP)**

|      | Desired Outcome  |
|------|--|
| DO 1 | Commercial forestry is designed and sited to maximise economic benefits whilst managing potential negative impacts on the environment, transport networks, surrounding land uses and landscapes. |

Performance Outcomes (PO) and Deemed-to-Satisfy (DTS) Criteria / Designated Performance Feature (DPF)

| Performance Outcome   | Deemed-to-Satisfy Criteria / Designated Performance Feature   |
|---|---|
| Si  | ting  |
| PO 1.1  | DTS/DPF 1.1   |
| Commercial forestry plantations are established where there is no detrimental effect on the physical environment or scenic quality of the rural landscape.  | None are applicable.  |
| PO 1.2  | DTS/DPF 1.2   |
| Commercial forestry plantations are established on slopes that are stable to minimise the risk of soil erosion.   | Commercial forestry plantations are not located on land with a slope exceeding 20% (1-in-5).  |
| PO 1.3  | DTS/DPF 1.3   |
| Commercial forestry plantations and operations associated with their establishment, management and harvesting are appropriately set back from any sensitive receiver to minimise fire risk and noise disturbance.                 | Commercial forestry plantations and operations associated with their establishment, management and harvesting are set back 50m or more from any sensitive receiver.   |
| PO 1.4  | DTS/DPF 1.4   |
| Commercial forestry plantations are separated from reserves gazetted under the <i>National Parks and Wildlife Act 1972</i> and/or <i>Wilderness Protection Act 1992</i> to minimise fire risk and potential for weed infestation. | Commercial forestry plantations and operations associated with their establishment, management and harvesting are set back 50m or more from a reserve gazetted under the <i>National Parks and Wildlife Act 1972</i> and/or <i>Wilderness Protection Act 1992</i> . |
| Water F   | Protection  |
| PO 2.1  | DTS/DPF 2.1   |
| Commercial forestry plantations incorporate artificial drainage lines (i.e. culverts, runoffs and constructed drains) integrated with natural drainage lines to minimise concentrated water flows onto or from plantation areas.  | None are applicable.  |

Page 74 of 126 Printed on 5/07/2022

# Policy24 - Enquiry PO 2 2 Appropriate siting, layout and design measures are adopted to minimise the impact of commercial forestry plantations on surface water resources. PO 3.1 Commercial forestry plantations incorporate appropriate firebreaks and fire management design elements.

#### DTS/DPF 2.2

Commercial forestry plantations:

- (a) do not involve cultivation (excluding spot cultivation) in drainage lines
- (b) are set back 20m or more from the banks of any major watercourse (a third order or higher watercourse), lake, reservoir, wetland or sinkhole (with direct connection to an aquifer)
- (c) are set back 10m or more from the banks of any first or second order watercourse or sinkhole ( with no direct connection to an aquifer).

#### Fire Management

#### DTS/DPF 3.1

Commercial forestry plantations provide:

- (a) 7m or more wide external boundary firebreaks for plantations of 40ha or less
- (b) 10m or more wide external boundary firebreaks for plantations of between 40ha and 100ha
- 20m or more wide external boundary firebreaks, or 10m with an additional 10m or more of fuel-reduced plantation, for plantations of 100ha or greater.

#### PO 3.2

Commercial forestry plantations incorporate appropriate fire management access tracks.

#### DTS/DPF 3.2

Commercial forestry plantation fire management access tracks:

- (a) are incorporated within all firebreaks
- (b) are 7m or more wide with a vertical clearance of 4m or
- (c) are aligned to provide straight through access at junctions, or if they are a no through access track are appropriately signposted and provide suitable turnaround areas for firefighting vehicles
- (d) partition the plantation into units of 40ha or less in area.

#### Power-line Clearances

#### PO 4.1

Commercial forestry plantations achieve and maintain appropriate clearances from aboveground powerlines.

#### DTS/DPF 4.1

Commercial forestry plantations incorporating trees with an expected mature height of greater than 6m meet the clearance requirements listed in the following table:

| Voltage of transmission line | Tower or<br>Pole | Minimum horizontal clearance distance between plantings and transmission lines |
|------------------------------|------------------|--|
| 500 kV                       | Tower            | 38m  |
| 275 kV                       | Tower            | 25m  |
| 132 kV                       | Tower            | 30m  |

Page 75 of 126 Printed on 5/07/2022

| 132 kV          | Pole | 20m |
|-----------------|------|-----|
| 66 kV           | Pole | 20m |
| Less than 66 kV | Pole | 20m |

## **Housing Renewal**

## **Assessment Provisions (AP)**

|      | Desired Outcome   |
|------|---|
| DO 1 | Renewed residential environments replace older social housing and provide new social housing infrastructure and other housing options and tenures to enhance the residential amenity of the local area. |

Performance Outcomes (PO) and Deemed-to-Satisfy (DTS) Criteria / Designated Performance Feature (DPF)

| Performance Outcome   | Deemed-to-Satisfy Criteria /<br>Designated Performance<br>Feature  |  |
|---|--|--|
| Land Use a  | and Intensity  |  |
| PO 1.1  | DTS/DPF 1.1  |  |
| Residential development provides a range of housing choices.  | Development comprises one or more of the following:  (a) detached dwellings (b) semi-detached dwellings (c) row dwellings (d) group dwellings (e) residential flat buildings.        |  |
| PO 1.2  | DTS/DPF 1.2  |  |
| Medium-density housing options or higher are located in close proximity to public transit, open space and/or activity centres.                | None are applicable.   |  |
| Building Height   |  |  |
| PO 2.1  Buildings generally do not exceed 3 building levels unless in locations close to public transport, centres and/or open space.         | DTS/DPF 2.1  Building height (excluding garages, carports and outbuildings) doe not exceed 3 building levels and 12m and wall height does not exceed 9m (not including a gable end). |  |
| PO 2.2  Medium or high rise residential flat buildings located within or at the interface with zones which restrict heights to a maximum of 2 | DTS/DPF 2.2  None are applicable.  |  |

Page 76 of 126 Printed on 5/07/2022

| Buildings are set back from the primary street boundary to contribute to an attractive streetscape character.  Secondary Street Sett  PO 4.1  Buildings are set back from secondary street boundaries to maintain separation between building walls and public streets and contribute to a suburban streetscape character.  Boundary Walls  PO 5.1  Boundary walls are limited in height and length to manage visual impacts and access to natural light and ventilation.  DTS/DP  Dwellings in a semi-detached, row or terrace arrangement maintain space between buildings consistent with a suburban streetscape character.  DTS/DP  Dwellings in a semi-detached, row or terrace arrangement maintain space between buildings consistent with a suburban streetscape character.  Side Boundary Setter  PO 6.1  Buildings are set back from side boundaries to provide:  Other to |  |  |  |  |
|--|--|--|--|--|
| Buildings are set back from the primary street boundary to contribute to an attractive streetscape character.    Secondary Street Sett   |  |  |  |  |
| Buildings are set back from the primary street boundary to contribute to an attractive streetscape character.    Secondary Street Sett   | Primary Street Setback   |  |  |  |
| PO 4.1  Buildings are set back from secondary street boundaries to maintain separation between building walls and public streets and contribute to a suburban streetscape character.  Boundary Walls  PO 5.1  Boundary walls are limited in height and length to manage visual impacts and access to natural light and ventilation.  Except dwellin are site (a)  (b)  PO 5.2  Dwellings in a semi-detached, row or terrace arrangement maintain space between buildings consistent with a suburban streetscape character.  Side Boundary Setber PO 6.1  Buildings are set back from side boundaries to provide:  (a) separation between dwellings in a way that contributes to a suburban character  (a) separation between dwellings in a way that contributes to a suburban character   | DTS/DPF 3.1  Buildings are no closer to the primary street (excluding any balcony, verandah, porch, awning or similar structure) than 3m.  |  |  |  |
| Buildings are set back from secondary street boundaries to maintain separation between building walls and public streets and contribute to a suburban streetscape character.  Boundary Walls  PO 5.1  Boundary walls are limited in height and length to manage visual impacts and access to natural light and ventilation.  Except dwellin are site (a)  (b)  PO 5.2  Dwellings in a semi-detached, row or terrace arrangement maintain space between buildings consistent with a suburban streetscape character.  Side Boundary Setbar PO 6.1  Buildings are set back from side boundaries to provide:  (a) separation between dwellings in a way that contributes to a suburban character  (a) separation between dwellings in a way that contributes to a suburban character   | ack  |  |  |  |
| PO 5.1  Boundary walls are limited in height and length to manage visual impacts and access to natural light and ventilation.  Except dwellin are site (a)  (b)  PO 5.2  Dwellings in a semi-detached, row or terrace arrangement maintain space between buildings consistent with a suburban streetscape character.  DTS/DP  Dwellings are set back from side boundaries to provide:  (a) separation between dwellings in a way that contributes to a suburban character  (a) separation between dwellings in a way that contributes to a suburban character  (a) separation between dwellings in a way that contributes to a suburban character  (b)  DTS/DP  Other to from side suburban character  (a) separation between dwellings in a way that contributes to a suburban character  | DTS/DPF 4.1  Buildings are set back at least 900mm from the boundary of the allotment with a secondary street frontage.  |  |  |  |
| Boundary walls are limited in height and length to manage visual impacts and access to natural light and ventilation.  PO 5.2  Dwellings in a semi-detached, row or terrace arrangement maintain space between buildings consistent with a suburban streetscape character.  Discolor buildings are set back from side boundaries to provide:  (a) separation between dwellings in a way that contributes to a suburban character  (a) separation between dwellings in a way that contributes to a suburban character  (b) DTS/DP  Other to from side suburban character  (a) separation between dwellings in a way that contributes to a suburban character  |  |  |  |  |
| Dwellings in a semi-detached, row or terrace arrangement maintain space between buildings consistent with a suburban streetscape character.  Side Boundary Setbate  PO 6.1  Buildings are set back from side boundaries to provide:  (a) separation between dwellings in a way that contributes to a suburban character  (a) (a)   | where the dwelling is located on a central site within a row g or terrace arrangement, dwellings with side boundary walls ad on only one side boundary and satisfy (a) or (b):  adjoin or abut a boundary wall of a building on adjoining land for the same length and height do not:  (i) exceed 3.2m in height from the lower of the natural or finished ground level  (ii) exceed 11.5m in length  (iii) when combined with other walls on the boundary of the subject development site, a maximum 45% of the length of the boundary  (iv) encroach within 3 metres of any other existing or proposed boundary walls on the subject land. |  |  |  |
| space between buildings consistent with a suburban streetscape outside  Side Boundary Setbar  PO 6.1  Buildings are set back from side boundaries to provide:  (a) separation between dwellings in a way that contributes to a suburban character  (a) (a)   | = 5.2  |  |  |  |
| PO 6.1  Buildings are set back from side boundaries to provide:  (a) separation between dwellings in a way that contributes to a suburban character  (a) (a)   | Dwellings in a semi-detached or row arrangement are set back 900mm or more from side boundaries shared with allotments outside the development site, except for a carport or garage.   |  |  |  |
| Buildings are set back from side boundaries to provide:  (a) separation between dwellings in a way that contributes to a suburban character  (a) (a)   | ck   |  |  |  |
| (c)  | <ul> <li>(a) at least 900mm where the wall height is up to 3m</li> <li>(b) other than for a wall facing a southern side boundary, at least 900mm plus 1/3 of the wall height above 3m</li> </ul>   |  |  |  |
| Rear Boundary Setba  | ack  |  |  |  |
| PO 7.1 DTS/DP Buildings are set back from rear boundaries to provide: Dwellin  | gs are set back from the rear boundary:  |  |  |  |

Page 77 of 126 Printed on 5/07/2022

separation between dwellings in a way that contributes to a (a) 3m or more for the first building level (a) suburban character (b) 5m or more for any subsequent building level. (b) access to natural light and ventilation for neighbours (c) private open space (d) space for landscaping and vegetation. Buildings elevation design PO 8.1 DTS/DPF 8.1 Dwelling elevations facing public streets and common driveways Each dwelling includes at least 3 of the following design features make a positive contribution to the streetscape and common within the building elevation facing a primary street, and at least 2 driveway areas. of the following design features within the building elevation facing any other public road (other than a laneway) or a common driveway: a minimum of 30% of the building elevation is set back an additional 300mm from the building line (b) a porch or portico projects at least 1m from the building elevation (c) a balcony projects from the building elevation (d) a verandah projects at least 1m from the building elevation (e) eaves of a minimum 400mm width extend along the width of the front elevation (f) a minimum 30% of the width of the upper level projects forward from the lower level primary building line by at least 300mm. a minimum of two different materials or finishes are (g) incorporated on the walls of the building elevation, with a maximum of 80% of the building elevation in a single material or finish. DTS/DPF 8.2 PO 8.2 Dwellings incorporate windows along primary street frontages to Each dwelling with a frontage to a public street: encourage passive surveillance and make a positive contribution to includes at least one window facing the primary street from the streetscape. a habitable room that has a minimum internal room dimension of 2.4m (b) has an aggregate window area of at least 2m<sup>2</sup> facing the primary street PO 8.3 DTS/DPF 8.3 The visual mass of larger buildings is reduced when viewed from None are applicable. adjoining allotments or public streets. PO 8.4 DTS/DPF 8.4 Built form considers local context and provides a quality design None are applicable. response through scale, massing, materials, colours and architectural expression. PO 8.5 DTS/DPF 8.5 Entrances to multi-storey buildings are: None are applicable. (a) oriented towards the street (b) visible and easily identifiable from the street (c) designed to include a common mail box structure.

Outlook and amenity

Page 78 of 126 Printed on 5/07/2022

| olicy24 - Eriquii y   | 1   |   |   |  |
|---|---|---|---|--|
| PO 9.1  | DTS/DPF 9.1   |   |   |  |
| Living rooms have an external outlook to provide a high standard of amenity for occupants.  | A living room of a dwelling incorporates a window with an external outlook towards the street frontage or private open space. |   |   |  |
| PO 9.2  | DTS/DPF 9.2   |   |   |  |
| Bedrooms are separated or shielded from active communal recreation areas, common access areas and vehicle parking areas and access ways to mitigate noise and artificial light intrusion. | None are applicable.  |   |   |  |
| Private C   | Dpen Space  |   |   |  |
| PO 10.1   | DTS/DPF 10.1  |   |   |  |
| Dwellings are provided with suitable sized areas of usable private open space to meet the needs of occupants.  Private open stable:   |   | open space is provided in accordance with the following |   |  |
|   | Dwelling Type   | Dwelling / Site   | Minimum Rate  |  |
|   |   | Configuration   |   |  |
|   | Dwelling (at ground level)  |   | Total area: 24m <sup>2</sup> located behind the building line                   |  |
|   |   |   | Minimum adjacent to a living room: 16m <sup>2</sup> with a minimum dimension 3m |  |
|   | Dwelling (above ground level)   | Studio  | 4m <sup>2</sup> / minimum<br>dimension 1.8m                                     |  |
|   |   | One bedroom dwelling                                    | 8m <sup>2</sup> / minimum<br>dimension 2.1m                                     |  |
|   |   | Two bedroom<br>dwelling                                 | 11m <sup>2</sup> / minimum<br>dimension 2.4m                                    |  |
|   |   | Three + bedroom dwelling                                | 15 m <sup>2</sup> / minimum<br>dimension 2.6m                                   |  |
| PO 10.2   | DTS/DPF 10.2  | 1   | ı   |  |
| Private open space positioned to provide convenient access from internal living areas.  | At least 50% of the accessible from a   | e required area of priva<br>habitable room.             | ate open space is   |  |
| PO 10.3   | DTS/DPF 10.3  |   |   |  |
| Private open space is positioned and designed to:   | None are applicab   | le.   |   |  |
| (a) provide useable outdoor space that suits the needs of occupants;  |   |   |   |  |
| (b) take advantage of desirable orientation and vistas; and   |   |   |   |  |

Page 79 of 126 Printed on 5/07/2022

#### PO 11.1

Development mitigates direct overlooking from upper level windows to habitable rooms and private open spaces of adjoining residential uses.

#### DTS/DPF 11.1

Upper level windows facing side or rear boundaries shared with another residential allotment/site satisfy one of the following:

- (a) are permanently obscured to a height of 1.5m above finished floor level and are fixed or not capable of being opened more than 200mm
- (b) have sill heights greater than or equal to 1.5m above finished floor level
- (c) incorporate screening with a maximum of 25% openings, permanently fixed no more than 500mm from the window surface and sited adjacent to any part of the window less than 1.5m above the finished floor.

#### PO 11.2

Development mitigates direct overlooking from upper level balconies and terraces to habitable rooms and private open space of adjoining residential uses.

#### **DTS/DPF 11.2**

One of the following is satisfied:

- (a) the longest side of the balcony or terrace will face a public road, public road reserve or public reserve that is at least 15m wide in all places faced by the balcony or terrace or
- (b) all sides of balconies or terraces on upper building levels are permanently obscured by screening with a maximum 25% transparency/openings fixed to a minimum height of:
  - 1.5m above finished floor level where the balcony is located at least 15 metres from the nearest habitable window of a dwelling on adjacent land or
  - (ii) 1.7m above finished floor level in all other cases

#### Landscaping

#### PO 12.1

Soft landscaping is incorporated into development to:

- (a) minimise heat absorption and reflection
- (b) maximise shade and shelter
- (c) maximise stormwater infiltration and biodiversity
- (d) enhance the appearance of land and streetscapes.

#### **DTS/DPF 12.1**

Residential development incorporates pervious areas for soft landscaping with a minimum dimension of 700mm provided in accordance with (a) and (b):

(a) a total area as determined by the following table:

| Dwelling site area (or in the case of residential flat | Minimum    |
|--|------------|
| building or group dwelling(s), average site area)      | percentage |
| (m <sup>2</sup> )                                      | of site    |
|  |            |
| <150   | 10%        |
| <200   | 15%        |
| 200-450  | 20%        |
| >450   | 25%        |

(b) at least 30% of land between the road boundary and the building line.

#### Water Sensitive Design

#### PO 13.1

Residential development is designed to capture and use stormwater to:

(a) maximise efficient use of water resources

DTS/DPF 13.1

None are applicable.

Page 80 of 126 Printed on 5/07/2022

| - Charles - Char |  |  |  |  |
|--|--|--|--|--|
| (b) manage peak stormwater runoff flows and volume to ensure the carrying capacities of downstream systems are not overloaded  |  |  |  |  |
| (c) manage runoff quality to maintain, as close as practical, pre-development conditions.  |  |  |  |  |
| L Car Parking  |  |  |  |  |
| PO 14.1  | DTS/DPF 14.1   |  |  |  |
| On-site car parking is provided to meet the anticipated demand of residents, with less on-site parking in areas in close proximity to public transport.  | On-site car parking is provided at the following rates per dwelling:  (a) 2 or fewer bedrooms - 1 car parking space  (b) 3 or more bedrooms - 2 car parking spaces.  |  |  |  |
| PO 14.2  | DTS/DPF 14.2   |  |  |  |
| Enclosed car parking spaces are of dimensions to be functional, accessible and convenient.   | Residential parking spaces enclosed by fencing, walls or other obstructions with the following internal dimensions (separate from any waste storage area):   |  |  |  |
|  | (a) single parking spaces:  (i) a minimum length of 5.4m  (ii) a minimum width of 3.0m  (iii) a minimum garage door width of 2.4m  (b) double parking spaces (side by side):  (i) a minimum length of 5.4m  (ii) a minimum width of 5.5m  (iii) minimum garage door width of 2.4m per space. |  |  |  |
| PO 14.3  Uncovered car parking spaces are of dimensions to be functional,  | DTS/DPF 14.3 Uncovered car parking spaces have:  |  |  |  |
| accessible and convenient.   | <ul> <li>(a) a minimum length of 5.4m</li> <li>(b) a minimum width of 2.4m</li> <li>(c) a minimum width between the centre line of the space and any fence, wall or other obstruction of 1.5m.</li> </ul>  |  |  |  |
| PO 14.4  | DTS/DPF 14.4   |  |  |  |
| Residential flat buildings and group dwelling developments provide sufficient on-site visitor car parking to cater for anticipated demand.   | Visitor car parking for group and residential flat buildings incorporating 4 or more dwellings is provided on-site at a minimum ratio of 0.25 car parking spaces per dwelling.   |  |  |  |
| PO 14.5  | DTS/DPF 14.5   |  |  |  |
| Residential flat buildings provide dedicated areas for bicycle parking.  | Residential flat buildings provide one bicycle parking space per dwelling.   |  |  |  |
| Oversh   | adowing  |  |  |  |
| PO 15.1  | DTS/DPF 15.1   |  |  |  |
| Development minimises overshadowing of the private open spaces of adjoining land by ensuring that ground level open space associated with residential buildings receive direct sunlight for a minimum of 2 hours between 9am and 3pm on 21 June.   | None are applicable.   |  |  |  |
| Wa   | aste   |  |  |  |
| '  |  |  |  |  |

Page 81 of 126 Printed on 5/07/2022

#### **DTS/DPF 16.1** PO 16.1 Provision is made for the convenient storage of waste bins in a A waste bin storage area is provided behind the primary building location screened from public view. line that: has a minimum area of 2m<sup>2</sup> with a minimum dimension of 900mm (separate from any designated car parking spaces or private open space).; and (b) has a continuous unobstructed path of travel (excluding moveable objects like gates, vehicles and roller doors) with a minimum width of 800mm between the waste bin storage area and the street. PO 16.2 **DTS/DPF 16.2** Residential flat buildings provide a dedicated area for the on-site None are applicable. storage of waste which is: (a) easily and safely accessible for residents and for collection vehicles (b) screened from adjoining land and public roads (c) of sufficient dimensions to be able to accommodate the waste storage needs of the development considering the intensity and nature of the development and the frequency of collection. Vehicle Access PO 17.1 DTS/DPF 17.1 Driveways are located and designed to facilitate safe access and None are applicable. egress while maximising land available for street tree planting, landscaped street frontages and on-street parking. PO 17.2 DTS/DPF 17.2 Vehicle access is safe, convenient, minimises interruption to the Vehicle access to designated car parking spaces satisfy (a) or (b): operation of public roads and does not interfere with street (a) is provided via a lawfully existing or authorised access infrastructure or street trees. point or an access point for which consent has been granted as part of an application for the division of land where newly proposed, is set back: (b) 0.5m or more from any street furniture, street pole, infrastructure services pit, or other stormwater or utility infrastructure unless consent is provided from the asset owner (ii) 2m or more from the base of the trunk of a street tree unless consent is provided from the tree owner for a lesser distance 6m or more from the tangent point of an intersection of 2 or more roads outside of the marked lines or infrastructure dedicating a pedestrian crossing. PO 17.3 **DTS/DPF 17.3** Driveways are designed to enable safe and convenient vehicle Driveways are designed and sited so that: movements from the public road to on-site parking spaces. (a) the gradient from the place of access on the boundary of the allotment to the finished floor level at the front of the garage or carport is not more than 1-in-4 on average (b) they are aligned relative to the street so that there is no

Page 82 of 126 Printed on 5/07/2022

| PO 17.4  Driveways and access points are designed and distributed to optimise the provision of on-street parking.   | more than a 20 degree deviation from 90 degrees between the centreline of any dedicated car parking space to which it provides access (measured from the front of that space) and the road boundary.  (c) if located so as to provide access from an alley, lane or right of way - the alley, lane or right or way is at least 6.2m wide along the boundary of the allotment / site.  DTS/DPF 17.4  Where on-street parking is available abutting the site's street frontage, on-street parking is retained in accordance with the following requirements:  1. minimum 0.33 on-street spaces per dwelling on the site (rounded up to the nearest whole number)  2. Minimum car park length of 5.4m where a vehicle can enter or exit a space directly  3. minimum car park length of 6m for an intermediate space located between two other parking spaces |
|---|--|
|   | located between two other parking spaces.  |
| PO 17.5  Residential driveways that service more than one dwelling of a dimension to allow safe and convenient movement.  | DTS/DPF 17.5  Where on-street parking is available abutting the site's street frontage, on-street parking is retained in accordance with the following requirements:   |
|   | <ul> <li>(a) minimum 0.33 on-street spaces per dwelling on the site (rounded up to the nearest whole number)</li> <li>(b) minimum car park length of 5.4m where a vehicle can enter or exit a space directly</li> <li>(c) minimum carpark length of 6m for an intermediate space located between two other parking spaces or to an end obstruction where the parking is indented.</li> </ul>   |
| PO 17.6  Residential driveways that service more than one dwelling are designed to allow passenger vehicles to enter and exit the site and manoeuvre within the site in a safe and convenient manner. | DTS/DPF 17.6  Driveways providing access to more than one dwelling, or a dwelling on a battle-axe site, allow a B85 passenger vehicle to enter and exit the garages or parking spaces in no more than a three-point turn manoeuvre   |
| PO 17.7  Dwellings are adequately separated from common driveways and manoeuvring areas.  | DTS/DPF 17.7  Dwelling walls with entry doors or ground level habitable room windows are set back at least 1.5m from any driveway or area designated for the movement and manoeuvring of vehicles.   |
| Q+o   | rage   |
| PO 18.1   | DTS/DPF 18.1   |
| Dwellings are provided with sufficient and accessible space for storage to meet likely occupant needs.  | Dwellings are provided with storage at the following rates and 50% or more of the storage volume is provided within the dwelling:  |
|   | <ul> <li>(a) studio: not less than 6m<sup>3</sup></li> <li>(b) 1 bedroom dwelling / apartment: not less than 8m<sup>3</sup></li> <li>(c) 2 bedroom dwelling / apartment: not less than 10m<sup>3</sup></li> <li>(d) 3+ bedroom dwelling / apartment: not less than 12m<sup>3</sup>.</li> </ul>   |
| Earth   | works  |
| PO 19.1   | DTS/DPF 19.1   |

Page 83 of 126 Printed on 5/07/2022

Development, including any associated driveways and access tracks, minimises the need for earthworks to limit disturbance to natural topography. The development does not involve:

- (a) excavation exceeding a vertical height of 1m or
- (b) filling exceeding a vertical height of 1m or
- (c) a total combined excavation and filling vertical height exceeding 2m.

Service connections and infrastructure

#### PO 20.1

Dwellings are provided with appropriate service connections and infrastructure.

#### DTS/DPF 20.1

The site and building:

- (a) have the ability to be connected to a permanent potable water supply
- (b) have the ability to be connected to a sewerage system, or a wastewater system approved under the *South Australian* Public Health Act 2011
- (c) have the ability to be connected to electricity supply
- (d) have the ability to be connected to an adequate water supply (and pressure) for fire-fighting purposes
- (e) would not be contrary to the Regulations prescribed for the purposes of Section 86 of the *Electricity Act 1996*.

Site contamination

#### PO 21.1

Land that is suitable for sensitive land uses to provide a safe environment.

#### DTS/DPF 21.1

Development satisfies (a), (b), (c) or (d):

- (a) does not involve a change in the use of land
- (b) involves a change in the use of land that does not constitute a change to a <u>more sensitive use</u>
- (c) involves a change in the use of land to a <u>more sensitive</u>
  <u>use</u> on land at which <u>site contamination</u> does not exist (as demonstrated in a <u>site contamination declaration form</u>)
- (d) involves a change in the use of land to a <u>more sensitive</u> <u>use</u> on land at which <u>site contamination</u> exists, or may exist (as demonstrated in a site contamination declaration form), and satisfies both of the following:
  - (i) <u>a site contamination audit report</u> has been prepared under Part 10A of the *Environment Protection Act 1993* in relation to the land within the previous 5 years which states that
    - <u>site contamination</u> does not exist (or no longer exists) at the land or
    - B. the land is suitable for the proposed use or range of uses (without the need for any further <u>remediation</u>) or
    - C. where <u>remediation</u> is, or remains, necessary for the proposed use (or range of uses), <u>remediation work</u> has been carried out or will be carried out (and the applicant has provided a written undertaking that the remediation works will be implemented in association with the development)

and

Page 84 of 126 Printed on 5/07/2022

| Policy24 - Enquiry |      |  |
|--------------------|------|--|
|                    | (ii) | no other <u>class 1 activity</u> or <u>class 2 activity</u> has taken place at the land since the preparation of the site contamination audit report (as demonstrated in a <u>site contamination declaration form</u> ). |

## Infrastructure and Renewable Energy Facilities

## **Assessment Provisions (AP)**

|      | Desired Outcome   |  |  |
|------|---|--|--|
| DO 1 | Efficient provision of infrastructure networks and services, renewable energy facilities and ancillary development in a manner that minimises hazard, is environmentally and culturally sensitive and manages adverse visual impacts on natural and rural landscapes and residential amenity. |  |  |

Performance Outcomes (PO) and Deemed-to-Satisfy (DTS) Criteria / Designated Performance Feature (DPF)

| Р   | erformance Outcome  | Deemed-to-Satisfy Criteria /          |
|---|---|---------------------------------------|
|   |   | <b>Designated Performance Feature</b> |
|   |   | General                               |
| PO 1.1  |   | DTS/DPF 1.1                           |
| Development is located and designed to minimise hazard or nuisance to adjacent development and land uses. |   | None are applicable.                  |
|   |   | Visual Amenity                        |
| PO 2.1  |   | DTS/DPF 2.1                           |
| and se<br>renewa  | sual impact of above-ground infrastructure networks ervices (excluding high voltage transmission lines), able energy facilities (excluding wind farms), energy e facilities and ancillary development is minimised ownships, scenic routes and public roads by:  utilising features of the natural landscape to obscure views where practicable siting development below ridgelines where | None are applicable.                  |
| (c)   | practicable avoiding visually sensitive and significant landscapes  |                                       |
| (d)   | using materials and finishes with low-reflectivity and colours that complement the surroundings   |                                       |
| (e)<br>(f)  | using existing vegetation to screen buildings incorporating landscaping or landscaped mounding around the perimeter of a site and between adjacent allotments accommodating or zoned to primarily accommodate sensitive receivers.  |                                       |

Page 85 of 126 Printed on 5/07/2022

| DTS/DPF 2.2  None are applicable.  DTS/DPF 2.3  None are applicable.  Rehabilitation  DTS/DPF 3.1 |
|---|
| DTS/DPF 2.3  None are applicable.  Rehabilitation   |
| None are applicable.  Rehabilitation  |
| Rehabilitation  |
|   |
| DTS/DPF 3.1   |
|   |
| None are applicable.  |
| Hazard Management   |
| DTS/DPF 4.1   |
| None are applicable.  |
| DTS/DPF 4.2   |
| None are applicable.  |
| DTS/DPF 4.3   |
| None are applicable.  |
| astructure and Battery Storage Facilities   |
| DTS/DPF 5.1   |
| None are applicable.  |
|   |
|   |

Page 86 of 126 Printed on 5/07/2022

| i Olicy24                   | F - Enquiry   |                                   |
|-----------------------------|---|-----------------------------------|
| (b)                         | grouping utility buildings and structures with non-<br>residential development, where practicable.  |                                   |
| PO 5.2                      |   | DTS/DPF 5.2                       |
| new de<br>underg            | city supply (excluding transmission lines) serving evelopment in urban areas and townships installed tround, excluding lines having a capacity exceeding al to 33kV.  | None are applicable.              |
| PO 5.3                      |   | DTS/DPF 5.3                       |
| infrastr                    | storage facilities are co-located with substation ucture where practicable to minimise the pment footprint and reduce environmental impacts.  | None are applicable.              |
|                             | Tel   | ecommunication Facilities         |
| PO 6.1                      |   | DTS/DPF 6.1                       |
| form of<br>where<br>other c | oliferation of telecommunications facilities in the fowers/monopoles in any one locality is managed, technically feasible, by co-locating a facility with ommunications facilities to mitigate impacts from on visual amenity.  | None are applicable.              |
| practica                    | mmunications antennae are located as close as able to support structures to manage overall bulk tigate impacts on visual amenity.   | DTS/DPF 6.2  None are applicable. |
| PO 6.3                      |   | DTS/DPF 6.3                       |
| towers/                     | mmunications facilities, particularly<br>/monopoles, are located and sized to mitigate visual<br>s by the following methods:  | None are applicable.              |
| (a)                         | where technically feasible, incorporating the facility within an existing structure that may serve another purpose  |                                   |
|                             | or all of the following:  |                                   |
| (b)                         | using existing buildings and landscape features to obscure or interrupt views of a facility from nearby public roads, residential areas and places of high public amenity to the extent practical without unduly hindering the effective provision of telecommunications services |                                   |
| (c)                         | using materials and finishes that complement the environment  |                                   |
| (d)                         | screening using landscaping and vegetation, particularly for equipment shelters and huts.   |                                   |
|                             | Rei   | newable Energy Facilities         |
| PO 7.1                      |   | DTS/DPF 7.1                       |
| practica                    | rable energy facilities are located as close as able to existing transmission infrastructure to be connections and minimise environmental impacts   | None are applicable.              |

Page 87 of 126 Printed on 5/07/2022

| as a result of extending transmission infrastructure.   |   |
|---|---|
| Renewab   | le Energy Facilities (Wind Farm)  |
| PO 8.1  | DTS/DPF 8.1   |
| Visual impact of wind turbine generators on the amenity of residential and tourist development is reduced through appropriate separation.   | (a) set back at least 2000m from the base of a turbine to any of the following zones:  (i) Rural Settlement Zone  (ii) Township Zone  (iii) Rural Living Zone  (iv) Rural Neighbourhood Zone  with an additional 10m setback per additional metre over 150m overall turbine height (measured from the base of the turbine).  (b) set back at least 1500m from the base of the turbine to non-associated (non-stakeholder) dwellings and tourist accommodation |
| PO 8.2  | DTS/DPF 8.2   |
| The visual impact of wind turbine generators on natural landscapes is managed by:  (a) designing wind turbine generators to be uniform in colour, size and shape (b) coordinating blade rotation and direction (c) mounting wind turbine generators on tubular towers as opposed to lattice towers. | None are applicable.  |
| PO 8.3  | DTS/DPF 8.3   |
| Wind turbine generators and ancillary development minimise potential for bird and bat strike.   | None are applicable.  |
| PO 8.4  | DTS/DPF 8.4   |
| Wind turbine generators incorporate recognition systems or physical markers to minimise the risk to aircraft operations.  | No Commonwealth air safety (CASA / ASA) or Defence requirement is applicable.   |
| PO 8.5  | DTS/DPF 8.5   |
| Meteorological masts and guidewires are identifiable to aircraft through the use of colour bands, marker balls, high visibility sleeves or flashing strobes.  | None are applicable.  |
| Renewable Energy Facilities (Solar Power)   |   |
| PO 9.1 DTS/DPF 9.1  |   |
| Ground mounted solar power facilities generating 5MW or more are not located on land requiring the clearance of areas of intact native vegetation or on land of high environmental, scenic or cultural value.   | None are applicable.  |
| PO 9.2  | DTS/DPF 9.2   |
| Ground mounted solar power facilities allow for movement of wildlife by:  | None are applicable.  |
| (a) incorporating wildlife corridors and habitat  |   |

Page 88 of 126 Printed on 5/07/2022

refuges

(b) avoiding the use of extensive security or perimeter fencing or incorporating fencing that enables the passage of small animals without unreasonably compromising the security of the facility.

#### PO 9.3

Amenity impacts of solar power facilities are minimised through separation from conservation areas and sensitive receivers in other ownership.

#### DTS/DPF 9.3

Ground mounted solar power facilities are set back from land boundaries, conservation areas and relevant zones in accordance with the following criteria:

| Generation<br>Capacity | Approximate size of array | Setback<br>from<br>adjoining<br>land<br>boundary | Setback<br>from<br>conservation<br>areas | Setback from Township, Rural Settlement, Rural Neighbourhood and Rural Living Zones <sup>1</sup> |
|------------------------|---------------------------|--|--|--|
| 50MW>                  | 80ha+                     | 30m  | 500m                                     | 2km  |
| 10MW<50MW              | 16ha-<80ha                | 25m  | 500m                                     | 1.5km  |
| 5MW<10MW               | 8ha to <16ha              | 20m  | 500m                                     | 1km  |
| 1MW<5MW                | 1.6ha to<br><8ha          | 15m  | 500m                                     | 500m   |
| 100kW<1MW              | 0.5ha<1.6ha               | 10m  | 500m                                     | 100m   |
| <100kW                 | <0.5ha                    | 5m   | 500m                                     | 25m  |

#### Notes:

1. Does not apply when the site of the proposed ground mounted solar power facility is located within one of these zones.

#### PO 9.4

Ground mounted solar power facilities incorporate landscaping within setbacks from adjacent road frontages and boundaries of adjacent allotments accommodating non-host dwellings, where balanced with infrastructure access and bushfire safety considerations.

#### DTS/DPF 9.4

None are applicable.

Hydropower / Pumped Hydropower Facilities

PO 10.1

**DTS/DPF 10.1** 

Hydropower / pumped hydropower facility storage is designed and operated to minimise the risk of storage dam failure.

None are applicable.

Page 89 of 126 Printed on 5/07/2022

#### PO 10.2 **DTS/DPF 10.2** Hydropower / pumped hydropower facility storage is None are applicable. designed and operated to minimise water loss through increased evaporation or system leakage, with the incorporation of appropriate liners, dam covers, operational measures or detection systems. PO 10.3 **DTS/DPF 10.3** Hydropower / pumped hydropower facilities on existing or None are applicable. former mine sites minimise environmental impacts from site contamination, including from mine operations or water sources subject to such processes, now or in the future. Water Supply PO 11.1 DTS/DPF 11.1 Development is connected to an appropriate water supply Development is connected, or will be connected, to a reticulated water to meet the ongoing requirements of the intended use. scheme or mains water supply with the capacity to meet the on-going requirements of the development. PO 11.2 **DTS/DPF 11.2** Dwellings are connected to a reticulated water scheme or A dwelling is connected, or will be connected, to a reticulated water scheme mains water supply with the capacity to meet the or mains water supply with the capacity to meet the requirements of the requirements of the intended use. Where this is not development. Where this is not available it is serviced by a rainwater tank or available an appropriate rainwater tank or storage system tanks capable of holding at least 50,000 litres of water which is: for domestic use is provided. (a) exclusively for domestic use (b) connected to the roof drainage system of the dwelling. Wastewater Services PO 12.1 DTS/DPF 12.1 Development is connected to an approved common Development is connected, or will be connected, to an approved common wastewater disposal service with the capacity to meet the wastewater disposal service with the capacity to meet the requirements of the requirements of the intended use. Where this is not development. Where this is not available it is instead capable of being available an appropriate on-site service is provided to serviced by an on-site waste water treatment system in accordance with the following: meet the ongoing requirements of the intended use in accordance with the following: the system is wholly located and contained within the allotment of (a) development it will service; and (a) it is wholly located and contained within the allotment of the development it will service (b) the system will comply with the requirements of the South Australian Public Health Act 2011. (b) in areas where there is a high risk of contamination of surface, ground, or marine water resources from on-site disposal of liquid wastes, disposal systems are included to minimise the risk of pollution to those water resources (c) septic tank effluent drainage fields and other wastewater disposal areas are located away from watercourses and flood prone, sloping, saline or poorly drained land to minimise environmental harm. DTS/DPF 12.2 PO 12.2 Effluent drainage fields and other wastewater disposal Development is not built on, or encroaches within, an area that is, or will be, areas are maintained to ensure the effective operation of required for a sewerage system or waste control system.

Page 90 of 126 Printed on 5/07/2022

| waste systems and minimise risks to human health and the environment.   |  |
|---|--|
|   | Temporary Facilities   |
| PO 13.1  In rural and remote locations, development that is likely to generate significant waste material during construction, including packaging waste, makes provision for a temporary on-site waste storage enclosure to minimise the incidence of wind-blown litter. | DTS/DPF 13.1  A waste collection and disposal service is used to dispose of the volume of waste at the rate it is generated. |
| PO 13.2  Temporary facilities to support the establishment of renewable energy facilities (including borrow pits, concrete batching plants, laydown, storage, access roads and worker amenity areas) are sited and operated to minimise environmental impact.             | DTS/DPF 13.2  None are applicable.   |

## **Intensive Animal Husbandry and Dairies**

## **Assessment Provisions (AP)**

|      | Desired Outcome   |  |  |
|------|---|--|--|
| DO 1 | Development of intensive animal husbandry and dairies in locations that are protected from encroachment by sensitive receivers and in a manner that minimises their adverse effects on amenity and the environment. |  |  |

Performance Outcomes (PO) and Deemed-to-Satisfy (DTS) Criteria / Designated Performance Feature (DPF)

| Performance Outcome   | Deemed-to-Satisfy Criteria / Designated Performance Feature |
|---|---|
| Siting ar   | nd Design   |
| PO 1.1  | DTS/DPF 1.1   |
| Intensive animal husbandry, dairies and associated activities are sited, designed, constructed and managed to not unreasonably impact on the environment or amenity of the locality.                    | None are applicable.  |
| PO 1.2  | DTS/DPF 1.2   |
| Intensive animal husbandry, dairies and associated activities are sited, designed, constructed and managed to prevent the potential transmission of disease to other operations where animals are kept. | None are applicable.  |
| PO 1.3  | DTS/DPF 1.3   |
| Intensive animal husbandry and associated activities such as  | None are applicable.  |

Page 91 of 126 Printed on 5/07/2022

| Policy24  | Enquiry  |  |  |
|---|--|--|--|
| designe   | vater lagoons and liquid/solid waste disposal areas are sited, ed, constructed and managed to not unreasonably impact on ve receivers in other ownership in terms of noise and air ons.  |  |  |
| PO 1.4  |  | DTS/DPF 1.4  |  |
| Dairies and associated activities such as wastewater lagoons and liquid/solid waste disposal areas are sited, designed, constructed and managed to not unreasonably impact on sensitive receivers in other ownership in terms of noise and air emissions. |  | Dairies, associated wastewater lagoon(s) and liquid/solid waste storage and disposal facilities are located 500m or more from the nearest sensitive receiver in other ownership.                           |  |
| PO 1.5  |  | DTS/DPF 1.5  |  |
| adequa  | ns for the storage or treatment of milking shed effluent is ately separated from roads to minimise impacts from odour general public.  | Lagoons for the storage or treatment of milking shed effluent are set back 20m or more from public roads.  |  |
|   | Wa   | ste  |  |
| PO 2.1  |  | DTS/DPF 2.1  |  |
| _   | e of manure, used litter and other wastes (other than waste agoons) is sited, designed, constructed and managed to:  avoid attracting and harbouring vermin avoid polluting water resources be located outside 1% AEP flood event areas. | None are applicable.   |  |
|   | Soil and Wat   | er Protection  |  |
| PO 3.1  |  | DTS/DPF 3.1  |  |
|   | d environmental harm and adverse effects on water<br>ces, intensive animal husbandry operations are appropriately  | Intensive animal husbandry operations are set back:  (a) 800m or more from a public water supply reservoir   |  |
| (a)<br>(b)<br>(c)   | public water supply reservoirs major watercourses (third order or higher stream) any other watercourse, bore or well used for domestic or stock water supplies.  | <ul> <li>(b) 200m or more from a major watercourse (third order or higher stream)</li> <li>(c) 100m or more from any other watercourse, bore or well used for domestic or stock water supplies.</li> </ul> |  |
| PO 3.2  |  | DTS/DPF 3.2  |  |
|   | ve animal husbandry operations and dairies incorporate riately designed effluent and run-off facilities that:  | None are applicable.   |  |
| (a)   | have sufficient capacity to hold effluent and runoff from the operations on site   |  |  |
| (b)   | ensure effluent does not infiltrate and pollute groundwater, soil or other water resources.  |  |  |

## **Interface between Land Uses**

## **Assessment Provisions (AP)**

Page 92 of 126 Printed on 5/07/2022

DO 1

# Desired Outcome Development is located and designed to mitigate adverse effects on or from neighbouring and proximate land uses.

Performance Outcomes (PO) and Deemed-to-Satisfy (DTS) Criteria / Designated Performance Feature (DPF)

| Performance Outcome   | Deemed-to-Satisfy Criteria /<br>Designated Performance<br>Feature   |
|---|---|
| General Land U  | lse Compatibility   |
| PO 1.1  | DTS/DPF 1.1   |
| Sensitive receivers are designed and sited to protect residents and occupants from adverse impacts generated by lawfully existing land uses (or lawfully approved land uses) and land uses desired in the zone. | None are applicable.  |
| PO 1.2  | DTS/DPF 1.2   |
| Development adjacent to a site containing a sensitive receiver (or lawfully approved sensitive receiver) or zone primarily intended to accommodate sensitive receivers is designed to minimise adverse impacts. | None are applicable.  |
| Hours of  | Operation   |
| PO 2.1  | DTS/DPF 2.1   |
| Non-residential development does not unreasonably impact the amenity of sensitive receivers (or lawfully approved sensitive   | Development operating within the following hours:   |
| receivers) or an adjacent zone primarily for sensitive receivers through its hours of operation having regard to:   | Class of Development Hours of operation   |
| <ul> <li>(a) the nature of the development</li> <li>(b) measures to mitigate off-site impacts</li> <li>(c) the extent to which the development is desired in the zone</li> </ul>                                | Consulting room 7am to 9pm, Monday to Friday 8am to 5pm, Saturday   |
| (d) measures that might be taken in an adjacent zone primarily<br>for sensitive receivers that mitigate adverse impacts<br>without unreasonably compromising the intended use of<br>that land.                  | Office 7am to 9pm, Monday to Friday 8am to 5pm, Saturday  |
|   | Shop, other than any one or combination of the following:  (a) restaurant (b) cellar door in the Productive Rural Landscape Zone, Rural Zone or Rural Horticulture Zone |

Page 93 of 126 Printed on 5/07/2022

#### Overshadowing DTS/DPF 3.1 PO 3 1 Overshadowing of habitable room windows of adjacent residential North-facing windows of habitable rooms of adjacent residential land uses in: land uses in a neighbourhood-type zone receive at least 3 hours of direct sunlight between 9.00am and 3.00pm on 21 June. a. a neighbourhood-type zone is minimised to maintain access to direct winter sunlight other zones is managed to enable access to direct winter sunlight. PO 3.2 DTS/DPF 3.2 Overshadowing of the primary area of private open space or Development maintains 2 hours of direct sunlight between 9.00 am communal open space of adjacent residential land uses in: and 3.00 pm on 21 June to adjacent residential land uses in a neighbourhood-type zone in accordance with the following: a. a neighbourhood type zone is minimised to maintain access to direct winter sunlight for ground level private open space, the smaller of the b. other zones is managed to enable access to direct winter following: sunlight. i. half the existing ground level open space or 35m2 of the existing ground level open space (with at least one of the area's dimensions measuring 2.5m) for ground level communal open space, at least half of the existing ground level open space. PO 3.3 DTS/DPF 3.3 Development does not unduly reduce the generating capacity of None are applicable. adjacent rooftop solar energy facilities taking into account: (a) the form of development contemplated in the zone (b) the orientation of the solar energy facilities (c) the extent to which the solar energy facilities are already overshadowed. PO 3.4 DTS/DPF 3.4 Development that incorporates moving parts, including windmills and None are applicable. wind farms, are located and operated to not cause unreasonable nuisance to nearby dwellings and tourist accommodation caused by shadow flicker. Activities Generating Noise or Vibration PO 4.1 DTS/DPF 4.1 Development that emits noise (other than music) does not Noise that affects sensitive receivers achieves the relevant unreasonably impact the amenity of sensitive receivers (or lawfully Environment Protection (Noise) Policy criteria. approved sensitive receivers). PO 4.2 DTS/DPF 4.2 Areas for the on-site manoeuvring of service and delivery vehicles, None are applicable. plant and equipment, outdoor work spaces (and the like) are designed and sited to not unreasonably impact the amenity of adjacent sensitive receivers (or lawfully approved sensitive receivers) and zones primarily intended to accommodate sensitive receivers due to noise and vibration by adopting techniques

Page 94 of 126 Printed on 5/07/2022

#### including: (a) locating openings of buildings and associated services away from the interface with the adjacent sensitive receivers and zones primarily intended to accommodate sensitive receivers (b) when sited outdoors, locating such areas as far as practicable from adjacent sensitive receivers and zones primarily intended to accommodate sensitive receivers (c) housing plant and equipment within an enclosed structure or acoustic enclosure (d) providing a suitable acoustic barrier between the plant and / or equipment and the adjacent sensitive receiver boundary or zone. PO 4.3 DTS/DPF 4.3 Fixed plant and equipment in the form of pumps and/or filtration The pump and/or filtration system ancillary to a dwelling erected on systems for a swimming pool or spa are positioned and/or housed the same site is: to not cause unreasonable noise nuisance to adjacent sensitive receivers (or lawfully approved sensitive receivers). enclosed in a solid acoustic structure located at least 5m from the nearest habitable room located on an adjoining allotment or (b) located at least 12m from the nearest habitable room located on an adjoining allotment. PO 4.4 DTS/DPF 4.4 External noise into bedrooms is minimised by separating or Adjacent land is used for residential purposes. shielding these rooms from service equipment areas and fixed noise sources located on the same or an adjoining allotment. PO 4.5 DTS/DPF 4.5 None are applicable. Outdoor areas associated with licensed premises (such as beer gardens or dining areas) are designed and/or sited to not cause unreasonable noise impact on existing adjacent sensitive receivers (or lawfully approved sensitive receivers). PO 4.6 DTS/DPF 4.6 Development incorporating music achieves suitable acoustic Development incorporating music includes noise attenuation amenity when measured at the boundary of an adjacent sensitive measures that will achieve the following noise levels: receiver (or lawfully approved sensitive receiver) or zone primarily intended to accommodate sensitive receivers. **Assessment location** Music noise level Less than 8dB above the level of Externally at the nearest background noise (L<sub>90,15min</sub>) in any existing or envisaged noise sensitive location octave band of the sound spectrum (LOCT10,15 < LOCT90,15 + 8dB) Air Quality PO 5.1 DTS/DPF 5.1 Development with the potential to emit harmful or nuisance-None are applicable. generating air pollution incorporates air pollution control measures to prevent harm to human health or unreasonably impact the amenity of sensitive receivers (or lawfully approved sensitive

Page 95 of 126 Printed on 5/07/2022

receivers) within the locality and zones primarily intended to

| Policy24 - Enquiry  |   |
|---|---|
| accommodate sensitive receivers.  |   |
| PO 5.2  | DTS/DPF 5.2   |
| Development that includes chimneys or exhaust flues (including cafes, restaurants and fast food outlets) is designed to minimise nuisance or adverse health impacts to sensitive receivers (or lawfully approved sensitive receivers) by:   | None are applicable.  |
| <ul> <li>(a) incorporating appropriate treatment technology before exhaust emissions are released</li> <li>(b) locating and designing chimneys or exhaust flues to maximise the dispersion of exhaust emissions, taking into account the location of sensitive receivers.</li> </ul>                |   |
| Ligh  | t Spill   |
| PO 6.1  | DTS/DPF 6.1   |
| External lighting is positioned and designed to not cause unreasonable light spill impact on adjacent sensitive receivers (or lawfully approved sensitive receivers).   | None are applicable.  |
| PO 6.2  | DTS/DPF 6.2   |
| External lighting is not hazardous to motorists and cyclists.   | None are applicable.  |
| Solar Refle   | ctivity / Glare   |
| PO 7.1  | DTS/DPF 7.1   |
| Development is designed and comprised of materials and finishes that do not unreasonably cause a distraction to adjacent road users and pedestrian areas or unreasonably cause heat loading and micro-climatic impacts on adjacent buildings and land uses as a result of reflective solar glare.   | None are applicable.  |
| Electrical  | interference  |
| PO 8.1  | DTS/DPF 8.1   |
| Development in rural and remote areas does not unreasonably diminish or result in the loss of existing communication services due to electrical interference.   | The building or structure:  (a) is no greater than 10m in height, measured from existing ground level or  (b) is not within a line of sight between a fixed transmitter and fixed receiver (antenna) other than where an alternative service is available via a different fixed transmitter or cable. |
| Interface with Rural Activities   |   |
| PO 9.1  Sensitive receivers are located and designed to mitigate impacts from lawfully existing horticultural and farming activities (or lawfully approved horticultural and farming activities), including spray drift and noise and do not prejudice the continued operation of these activities. | DTS/DPF 9.1  None are applicable.   |
| PO 9.2  | DTS/DPF 9.2   |
| Sensitive receivers are located and designed to mitigate potential impacts from lawfully existing intensive animal husbandry activities   | None are applicable.  |

Page 96 of 126 Printed on 5/07/2022

| and do not prejudice the continued operation of these activities.  |  |
|--|--|
| PO 9.3  Sensitive receivers are located and designed to mitigate potential impacts from lawfully existing land-based aquaculture activities and do not prejudice the continued operation of these activities.  | DTS/DPF 9.3  Sensitive receivers are located at least 200m from the boundary of a site used for land-based aquaculture and associated components in other ownership.   |
| PO 9.4   | DTS/DPF 9.4  |
| Sensitive receivers are located and designed to mitigate potential impacts from lawfully existing dairies including associated wastewater lagoons and liquid/solid waste storage and disposal facilities and do not prejudice the continued operation of these activities.   | Sensitive receivers are sited at least 500m from the boundary of a site used for a dairy and associated wastewater lagoon(s) and liquid/solid waste storage and disposal facilities in other ownership.  |
| PO 9.5   | DTS/DPF 9.5  |
| Sensitive receivers are located and designed to mitigate the potential impacts from lawfully existing facilities used for the handling, transportation and storage of bulk commodities (recognising the potential for extended hours of operation) and do not prejudice the continued operation of these activities. | Sensitive receivers are located away from the boundary of a site used for the handling, transportation and/or storage of bulk commodities in other ownership in accordance with the following:  (a) 300m or more, where it involves the handling of agricultural crop products, rock, ores, minerals, petroleum products or chemicals to or from any commercial storage facility  (b) 300m or more, where it involves the handling of agricultural crop products, rock, ores, minerals, petroleum products or chemicals at a wharf or wharf side facility (including seaport grain terminals) where the handling of these materials into or from vessels does not exceed 100 tonnes per day  (c) 500m or more, where it involves the storage of bulk petroleum in individual containers with a capacity up to 200 litres and a total on-site storage capacity not exceeding 1000 cubic metres  (d) 500m or more, where it involves the handling of coal with a capacity up to 1 tonne per day or a storage capacity up to 50 tonnes  (e) 1000m or more, where it involves the handling of coal with a capacity exceeding 1 tonne per day but not exceeding 100 tonnes per day or a storage capacity exceeding 50 tonnes but not exceeding 5000 tonnes. |
| PO 9.6   | DTS/DPF 9.6  |
| Setbacks and vegetation plantings along allotment boundaries should be incorporated to mitigate the potential impacts of spray drift and other impacts associated with agricultural and horticultural activities.  | None are applicable.   |
| PO 9.7   | DTS/DPF 9.7  |
| Urban development does not prejudice existing agricultural and horticultural activities through appropriate separation and design techniques.  | None are applicable.   |
| Interface with Mines and Qua   | arries (Rural and Remote Areas)  |
| PO 10.1  Sensitive receivers are separated from existing mines to minimise the adverse impacts from noise, dust and vibration.   | DTS/DPF 10.1  Sensitive receivers are located no closer than 500m from the boundary of a Mining Production Tenement under the <i>Mining Act</i> 1971.  |

Page 97 of 126 Printed on 5/07/2022

#### **Land Division**

#### **Assessment Provisions (AP)**

| Desired Outcome |  |  |
|-----------------|--|--|
| DO 1            | Land division:   |  |
|                 | <ul> <li>(a) creates allotments with the appropriate dimensions and shape for their intended use</li> <li>(b) allows efficient provision of new infrastructure and the optimum use of underutilised infrastructure</li> <li>(c) integrates and allocates adequate and suitable land for the preservation of site features of value, including significant vegetation, watercourses, water bodies and other environmental features</li> <li>(d) facilitates solar access through allotment orientation</li> <li>(e) creates a compact urban form that supports active travel, walkability and the use of public transport</li> <li>(f) avoids areas of high natural hazard risk.</li> </ul> |  |

## Deemed-to-Satisfy Criteria / **Performance Outcome Designated Performance Feature** All land division Allotment configuration PO 1.1 DTS/DPF 1.1 Land division creates allotments suitable for their intended use. Division of land satisfies (a) or (b): reflects the site boundaries illustrated and approved in an operative or existing development authorisation for residential development under the Development Act 1993 or Planning, Development and Infrastructure Act 2016 where the allotments are used or are proposed to be used solely for residential purposes (b) is proposed as part of a combined land division application with deemed-to-satisfy dwellings on the proposed allotments. PO 1.2 DTS/DPF 1.2 Land division considers the physical characteristics of the land, None are applicable. preservation of environmental and cultural features of value and the prevailing context of the locality. Design and Layout DTS/DPF 2.1 PO 2.1 Land division results in a pattern of development that minimises the None are applicable. likelihood of future earthworks and retaining walls. PO 2.2 DTS/DPF 2.2 Land division enables the appropriate management of interface None are applicable. impacts between potentially conflicting land uses and/or zones.

Page 98 of 126 Printed on 5/07/2022

|   | <u> </u>  |
|---|---|
| PO 2.3  | DTS/DPF 2.3   |
| Land division maximises the number of allotments that face public open space and public streets.  | None are applicable.  |
| PO 2.4  | DTS/DPF 2.4   |
| Land division is integrated with site features, adjacent land uses, the existing transport network and available infrastructure.  | None are applicable.  |
| PO 2.5  | DTS/DPF 2.5   |
| Development and infrastructure is provided and staged in a manner that supports an orderly and economic provision of land, infrastructure and services.   | None are applicable.  |
| PO 2.6  | DTS/DPF 2.6   |
| Land division results in watercourses being retained within open space and development taking place on land not subject to flooding.  | None are applicable.  |
| PO 2.7  | DTS/DPF 2.7   |
| Land division results in legible street patterns connected to the surrounding street network.   | None are applicable.  |
| PO 2.8  | DTS/DPF 2.8   |
| Land division is designed to preserve existing vegetation of value including native vegetation and regulated and significant trees.   | None are applicable.  |
|   |   |
| Roads at  | nd Access   |
| Roads at PO 3.1   | DTS/DPF 3.1   |
|   |   |
| PO 3.1  Land division provides allotments with access to an all-weather   | DTS/DPF 3.1   |
| PO 3.1  Land division provides allotments with access to an all-weather public road.  | DTS/DPF 3.1  None are applicable.   |
| PO 3.1  Land division provides allotments with access to an all-weather public road.  PO 3.2  Street patterns and intersections are designed to enable the safe   | DTS/DPF 3.1  None are applicable.  DTS/DPF 3.2  |
| PO 3.1  Land division provides allotments with access to an all-weather public road.  PO 3.2  Street patterns and intersections are designed to enable the safe and efficient movement of pedestrian, cycle and vehicular traffic.  | DTS/DPF 3.1  None are applicable.  DTS/DPF 3.2  None are applicable.  |
| PO 3.1  Land division provides allotments with access to an all-weather public road.  PO 3.2  Street patterns and intersections are designed to enable the safe and efficient movement of pedestrian, cycle and vehicular traffic.  PO 3.3  Land division does not impede access to publicly owned open   | DTS/DPF 3.1  None are applicable.  DTS/DPF 3.2  None are applicable.  DTS/DPF 3.3   |
| PO 3.1  Land division provides allotments with access to an all-weather public road.  PO 3.2  Street patterns and intersections are designed to enable the safe and efficient movement of pedestrian, cycle and vehicular traffic.  PO 3.3  Land division does not impede access to publicly owned open space and/or recreation facilities.   | DTS/DPF 3.1  None are applicable.  DTS/DPF 3.2  None are applicable.  DTS/DPF 3.3  None are applicable.   |
| PO 3.1  Land division provides allotments with access to an all-weather public road.  PO 3.2  Street patterns and intersections are designed to enable the safe and efficient movement of pedestrian, cycle and vehicular traffic.  PO 3.3  Land division does not impede access to publicly owned open space and/or recreation facilities.  PO 3.4  Road reserves provide for safe and convenient movement and parking of projected volumes of vehicles and allow for the efficient  | DTS/DPF 3.1  None are applicable.  DTS/DPF 3.2  None are applicable.  DTS/DPF 3.3  None are applicable.  DTS/DPF 3.4                                    |
| PO 3.1  Land division provides allotments with access to an all-weather public road.  PO 3.2  Street patterns and intersections are designed to enable the safe and efficient movement of pedestrian, cycle and vehicular traffic.  PO 3.3  Land division does not impede access to publicly owned open space and/or recreation facilities.  PO 3.4  Road reserves provide for safe and convenient movement and parking of projected volumes of vehicles and allow for the efficient movement of service and emergency vehicles.  | DTS/DPF 3.1  None are applicable.  DTS/DPF 3.2  None are applicable.  DTS/DPF 3.3  None are applicable.  DTS/DPF 3.4  None are applicable.              |
| PO 3.1  Land division provides allotments with access to an all-weather public road.  PO 3.2  Street patterns and intersections are designed to enable the safe and efficient movement of pedestrian, cycle and vehicular traffic.  PO 3.3  Land division does not impede access to publicly owned open space and/or recreation facilities.  PO 3.4  Road reserves provide for safe and convenient movement and parking of projected volumes of vehicles and allow for the efficient movement of service and emergency vehicles.  PO 3.5  Road reserves are designed to accommodate pedestrian and cycling infrastructure, street tree planting, landscaping and street | DTS/DPF 3.1  None are applicable.  DTS/DPF 3.2  None are applicable.  DTS/DPF 3.3  None are applicable.  DTS/DPF 3.4  None are applicable.  DTS/DPF 3.5 |

Page 99 of 126 Printed on 5/07/2022

| utilities.   |  |
|--|--|
| PO 3.7   | DTS/DPF 3.7  |
| Road reserves provide unobstructed vehicular access and egress to and from individual allotments and sites.  |  |
| PO 3.8   | DTS/DPF 3.8  |
| Street patterns and intersections are designed to enable the safe and efficient movement of pedestrian, cycle and vehicular traffic.   | None are applicable.   |
| PO 3.9   | DTS/DPF 3.9  |
| Roads, open space and thoroughfares provide safe and convenient linkages to the surrounding open space and transport network.  | None are applicable.   |
| PO 3.10  | DTS/DPF 3.10   |
| Public streets are designed to enable tree planting to provide shade and enhance the amenity of streetscapes.  | None are applicable.   |
| PO 3.11  | DTS/DPF 3.11   |
| Local streets are designed to create low-speed environments that are safe for cyclists and pedestrians.  | None are applicable.   |
| Infrasi  | ructure  |
| PO 4.1   | DTS/DPF 4.1  |
| Land division incorporates public utility services within road reserves or dedicated easements.  | None are applicable.   |
| PO 4.2   | DTS/DPF 4.2  |
| Waste water, sewage and other effluent is capable of being disposed of from each allotment without risk to public health or the environment.   | (a) a waste water treatment plant that has the hydraulic volume and pollutant load treatment and disposal capacity for the maximum predicted wastewater volume generated by subsequent development of the proposed allotment or  (b) a form of on-site waste water treatment and disposal that meets relevant public health and environmental standards. |
| PO 4.3   | DTS/DPF 4.3  |
| Septic tank effluent drainage fields and other waste water disposal areas are maintained to ensure the effective operation of waste systems and minimise risks to human health and the environment.  | Development is not built on, or encroaches within, an area that is or will be, required for a sewerage system or waste control system.   |
| PO 4.4   | DTS/DPF 4.4  |
| Constructed wetland systems, including associated detention and retention basins, are sited and designed to ensure public health and safety is protected, including by minimising potential public health risks arising from the breeding of mosquitoes. | None are applicable.   |
| PO 4.5   | DTS/DPF 4.5  |
| Constructed wetland systems, including associated detention and retention basins, are sited and designed to allow sediments to settle prior to discharge into watercourses or the marine environment.  | None are applicable.   |

Page 100 of 126 Printed on 5/07/2022

| Policy24 - Enquiry  |  |
|---|--|
| PO 4.6  | DTS/DPF 4.6  |
| Constructed wetland systems, including associated detention and retention basins, are sited and designed to function as a landscape feature.  | None are applicable.   |
| Minor Land Division   | (Under 20 Allotments)  |
| Open  | Space  |
| PO 5.1  | DTS/DPF 5.1  |
| Land division proposing an additional allotment under 1 hectare provides or supports the provision of open space.   | None are applicable.   |
| Solar O   | rientation   |
| PO 6.1  | DTS/DPF 6.1  |
| Land division for residential purposes facilitates solar access through allotment orientation.  | None are applicable.   |
| Water Sens  | sitive Design  |
| PO 7.1  | DTS/DPF 7.1  |
| Land division creating a new road or common driveway includes stormwater management systems that minimise the discharge of sediment, suspended solids, organic matter, nutrients, bacteria, litter and other contaminants to the stormwater system, watercourses or other water bodies. | None are applicable.   |
| PO 7.2  | DTS/DPF 7.2  |
| Land division designed to mitigate peak flows and manage the rate and duration of stormwater discharges from the site to ensure that the development does not increase the peak flows in downstream systems.  | None are applicable.   |
| Battle-Axe I  | Development Development  |
| PO 8.1  | DTS/DPF 8.1  |
| Battle-axe development appropriately responds to the existing neighbourhood context.  | Allotments are not in the form of a battle-axe arrangement.  |
| PO 8.2  | DTS/DPF 8.2  |
| Battle-axe development designed to allow safe and convenient movement.  | The handle of a battle-axe development:  |
|   | (a) has a minimum width of 4m     or     (b) where more than 3 allotments are proposed, a minimum width of 5.5m.                     |
| PO 8.3  | DTS/DPF 8.3  |
| Battle-axe allotments and/or common land are of a suitable size and dimension to allow passenger vehicles to enter and exit and manoeuvre within the site in a safe and convenient manner.  | Battle-axe development allows a B85 passenger vehicle to enter and exit parking spaces in no more than a three-point turn manoeuvre. |
| PO 8.4  | DTS/DPF 8.4  |
| Battle-axe or common driveways incorporate landscaping and permeability to improve appearance and assist in stormwater  | Battle-axe or common driveways satisfy (a) and (b):  |
| management.   | (a) are constructed of a minimum of 50% permeable or porous material   |
|   | (b) where the driveway is located directly adjacent the side or  |

Page 101 of 126 Printed on 5/07/2022

|   | rear boundary of the site, soft landscaping with a minimum dimension of 1m is provided between the driveway and site boundary (excluding along the perimeter of a passing point). |
|---|---|
| Major Land Divisio  | on (20+ Allotments)   |
| Open  | Space   |
| PO 9.1  | DTS/DPF 9.1   |
| Land division allocates or retains evenly distributed, high quality areas of open space to improve residential amenity and provide urban heat amelioration.   | None are applicable.  |
| PO 9.2  | DTS/DPF 9.2   |
| Land allocated for open space is suitable for its intended active and passive recreational use considering gradient and potential for inundation.   | None are applicable.  |
| PO 9.3  | DTS/DPF 9.3   |
| Land allocated for active recreation has dimensions capable of accommodating a range of active recreational activities.   | None are applicable.  |
| Water Sens  | sitive Design   |
| PO 10.1   | DTS/DPF 10.1  |
| Land division creating 20 or more residential allotments includes a stormwater management system designed to mitigate peak flows and manage the rate and duration of stormwater discharges from the site to ensure that the development does not increase the peak flows in downstream systems.     | None are applicable.  |
| PO 10.2   | DTS/DPF 10.2  |
| Land division creating 20 or more non-residential allotments includes a stormwater management system designed to mitigate peak flows and manage the rate and duration of stormwater discharges from the site to ensure that the development does not increase the peak flows in downstream systems. | None are applicable.  |
| PO 10.3   | DTS/DPF 10.3  |
| Land division creating 20 or more allotments includes stormwater management systems that minimise the discharge of sediment, suspended solids, organic matter, nutrients, bacteria, litter and other contaminants to the stormwater system, watercourses or other water bodies.                     | None are applicable.  |
| Solar Or  | rientation  |
| PO 11.1   | DTS/DPF 11.1  |
| Land division creating 20 or more allotments for residential purposes facilitates solar access through allotment orientation and allotment dimensions.  | None are applicable.  |

## **Marinas and On-Water Structures**

Page 102 of 126 Printed on 5/07/2022

## **Assessment Provisions (AP)**

| Desired Outcome |   |
|-----------------|---|
| DO 1            | Marinas and on-water structures are located and designed to minimise the impairment of commercial, recreational and navigational activities and adverse impacts on the environment. |

Performance Outcomes (PO) and Deemed-to-Satisfy (DTS) Criteria / Designated Performance Feature (DPF)

| Performance Outcome  | Deemed-to-Satisfy Criteria /<br>Designated Performance<br>Feature   |
|--|---|
| Navigation   | and Safety  |
| PO 1.1   | DTS/DPF 1.1   |
| Safe public access is provided or maintained to the waterfront, public infrastructure and recreation areas.                                | None are applicable.  |
| PO 1.2   | DTS/DPF 1.2   |
| The operation of wharves is not impaired by marinas and on-water structures.   | None are applicable.  |
| PO 1.3   | DTS/DPF 1.3   |
| Navigation and access channels are not impaired by marinas and on-water structures.  | None are applicable.  |
| PO 1.4   | DTS/DPF 1.4   |
| Commercial shipping lanes are not impaired by marinas and onwater structures.  | Marinas and on-water structures are set back 250m or more from commercial shipping lanes.   |
| PO 1.5  Marinas and on-water structures are located to avoid interfering with the operation or function of a water supply pumping station. | On-water structures are set back:  (a) 3km or more from upstream water supply pumping station take-off points  (b) 500m or more from downstream water supply pumping station take-off points. |
| PO 1.6   | DTS/DPF 1.6   |
| Maintenance of on-water infrastructure, including revetment walls, is not impaired by marinas and on-water structures.                     | None are applicable.  |
| Environmen   | tal Protection  |
| PO 2.1   | DTS/DPF 2.1   |
| Development is sited and designed to facilitate water circulation and exchange.  | None are applicable.  |

Page 103 of 126 Printed on 5/07/2022

## **Open Space and Recreation**

## **Assessment Provisions (AP)**

| Desired Outcome  |  |  |
|--|--|--|
| Pleasant, functional and accessible open space and recreation facilities are provided at State, regional, district, neighbourhood and local levels for active and passive recreation, biodiversity, community health, urban cooling, tree canopy cover, visual amenity, gathering spaces, wildlife and waterway corridors, and a range of other functions and at a range of sizes that reflect the purpose of that open space. |  |  |

Performance Outcomes (PO) and Deemed-to-Satisfy (DTS) Criteria / Designated Performance Feature (DPF)

| Performance Outcome  | Deemed-to-Satisfy Criteria /<br>Designated Performance<br>Feature |
|--|---|
| Land Use a   | and Intensity   |
| PO 1.1   | DTS/DPF 1.1   |
| Recreation facilities are compatible with surrounding land uses and activities.  | None are applicable.  |
| PO 1.2   | DTS/DPF 1.2   |
| Open space areas include natural or landscaped areas using locally indigenous plant species and large trees.               | None are applicable.  |
| Design and Siting  |   |
| PO 2.1   | DTS/DPF 2.1   |
| Open space and recreation facilities address adjacent public roads to optimise pedestrian access and visibility.           | None are applicable.  |
| PO 2.2   | DTS/DPF 2.2   |
| Open space and recreation facilities incorporate park furniture, shaded areas and resting places.                          | None are applicable.  |
| PO 2.3   | DTS/DPF 2.3   |
| Open space and recreation facilities link habitats, wildlife corridors and existing open spaces and recreation facilities. | None are applicable.  |
| Pedestrians and Cyclists   |   |
| PO 3.1   | DTS/DPF 3.1   |
| Open space incorporates:   | None are applicable.  |
| (a) pedestrian and cycle linkages to other open spaces, centres, schools and public transport nodes;                       |   |

Page 104 of 126 Printed on 5/07/2022

| Policy24 - Enquiry  |                      |
|---|----------------------|
| <ul><li>(b) safe crossing points where pedestrian routes intersect the<br/>road network;</li></ul>  |                      |
| (c) easily identified access points.  |                      |
| Usa   | bility               |
| PO 4.1  | DTS/DPF 4.1          |
| Land allocated for open space is suitable for its intended active and passive recreational use taking into consideration its gradient and potential for inundation.   | None are applicable. |
| Safety ar   | d Security           |
| PO 5.1  | DTS/DPF 5.1          |
| Open space is overlooked by housing, commercial or other development to provide casual surveillance where possible.   | None are applicable. |
| PO 5.2  | DTS/DPF 5.2          |
| Play equipment is located to maximise opportunities for passive surveillance.   | None are applicable. |
| PO 5.3  | DTS/DPF 5.3          |
| Landscaping provided in open space and recreation facilities  | None are applicable. |
| maximises opportunities for casual surveillance throughout the park.  |                      |
| PO 5.4  | DTS/DPF 5.4          |
| Fenced parks and playgrounds have more than one entrance or exit to minimise potential entrapment.  | None are applicable. |
| PO 5.5  | DTS/DPF 5.5          |
| Adequate lighting is provided around toilets, telephones, seating, litter bins, bicycle storage, car parks and other such facilities.   | None are applicable. |
| PO 5.6  | DTS/DPF 5.6          |
| Pedestrian and bicycle movement after dark is focused along clearly defined, adequately lit routes with observable entries and exits.   | None are applicable. |
| Sign  | nage                 |
| PO 6.1  | DTS/DPF 6.1          |
| Signage is provided at entrances to and within the open space and recreation facilities to provide clear orientation to major points of interest such as the location of public toilets, telephones, safe routes, park activities and the like. | None are applicable. |
| Buildings and Structures  |                      |
| PO 7.1  | DTS/DPF 7.1          |
| Buildings and car parking areas in open space areas are designed, located and of a scale to be unobtrusive.   | None are applicable. |
| PO 7.2  | DTS/DPF 7.2          |
| Buildings and structures in open space areas are clustered where practical to ensure that the majority of the site remains open.  | None are applicable. |
| PO 7.3  | DTS/DPF 7.3          |
|   |                      |

Page 105 of 126 Printed on 5/07/2022

| None are applicable. |  |
|----------------------|--|
|                      |  |
| DTS/DPF 7.4          |  |
| None are applicable. |  |
| Landscaping          |  |
| DTS/DPF 8.1          |  |
| None are applicable. |  |
| DTS/DPF 8.2          |  |
| None are applicable. |  |
|                      |  |
|                      |  |
|                      |  |
| DTS/DPF 8.3          |  |
| None are applicable. |  |
| DTS/DPF 8.4          |  |
| None are applicable. |  |
|                      |  |

## **Out of Activity Centre Development**

## **Assessment Provisions (AP)**

|     | Desired Outcome  |  |
|-----|--|--|
| DO1 | The role of Activity Centres in contributing to the form and pattern of development and enabling equitable and convenient      |  |
|     | access to a range of shopping, administrative, cultural, entertainment and other facilities in a single trip is maintained and |  |
|     | reinforced.  |  |

|        | Performance Outcome  | Deemed-to-Satisfy Criteria /<br>Designated Performance<br>Feature |
|--------|--|---|
| PO 1.1 |  | DTS/DPF 1.1   |
|        | sidential development outside Activity Centres of a scale and at does not diminish the role of Activity Centres: | None are applicable.  |
| (a)    | as primary locations for shopping, administrative, cultural, entertainment and community services                |   |
| (b)    | as a focus for regular social and business gatherings  |   |
| (c)    | in contributing to or maintaining a pattern of development   |   |

Page 106 of 126 Printed on 5/07/2022

|        | that supports equitable community access to services and facilities.   |                      |
|--------|--|----------------------|
| PO 1.2 |  | DTS/DPF 1.2          |
|        | activity centre non-residential development complements Centres through the provision of services and facilities: that support the needs of local residents and workers, particularly in underserviced locations | None are applicable. |
| (b)    | at the edge of Activities Centres where they cannot readily<br>be accommodated within an existing Activity Centre to<br>expand the range of services on offer and support the role<br>of the Activity Centre.    |                      |

## **Resource Extraction**

## **Assessment Provisions (AP)**

|      | Desired Outcome  |
|------|--|
| DO 1 | Resource extraction activities are developed in a manner that minimises human and environmental impacts. |

Performance Outcomes (PO) and Deemed-to-Satisfy (DTS) Criteria / Designated Performance Feature (DPF)

| Performance Outcome   | Deemed-to-Satisfy Criteria / Designated Performance Feature |
|---|---|
| Land Use a  | and Intensity   |
| PO 1.1  | DTS/DPF 1.1   |
| Resource extraction activities minimise landscape damage outside of those areas unavoidably disturbed to access and exploit a resource and provide for the progressive reclamation and betterment of disturbed areas. | None are applicable.  |
| PO 1.2  | DTS/DPF 1.2   |
| Resource extraction activities avoid damage to cultural sites or artefacts.   | None are applicable.  |
| Water Quality   |   |
| PO 2.1  | DTS/DPF 2.1   |
| Stormwater and/or wastewater from resource extraction activities is diverted into appropriately sized treatment and retention systems to enable reuse on site.  | None are applicable.  |

Page 107 of 126 Printed on 5/07/2022

| Separation Treatments, Buffers and Landscaping   |                      |
|--|----------------------|
| PO 3.1   | DTS/DPF 3.1          |
| Resource extraction activities minimise adverse impacts upon sensitive receivers through incorporation of separation distances and/or mounding/vegetation. | None are applicable. |
| PO 3.2   | DTS/DPF 3.2          |
| Resource extraction activities are screened from view from adjacent land by perimeter landscaping and/or mounding.   | None are applicable. |

## **Site Contamination**

## **Assessment Provisions (AP)**

## Desired Outcome Do 1 Ensure land is suitable for the proposed use in circumstances where it is, or may have been, subject to site contamination.

| Ensure land is suitable for the proposed use in circun                         | nstances where it is, or may have been, subject to site contamination.   |
|--|--|
| Performance Outcome  | Deemed-to-Satisfy Criteria / Designated Performance  |
|  | Feature  |
| PO 1.1   | DTS/DPF 1.1  |
| Ensure land is suitable for use when land use changes to a more sensitive use. | Development satisfies (a), (b), (c) or (d):  |
|  | (a) does not involve a change in the use of land   |
|  | (b) involves a change in the use of land that does not constitute a change to a more sensitive use   |
|  | (c) involves a change in the use of land to a more sensitive use on land at which site contamination is unlikely to exist (as demonstrated in a site contamination declaration form)   |
|  | (d) involves a change in the use of land to a more sensitive<br>use on land at which site contamination exists, or may<br>exist (as demonstrated in a site contamination declaration<br>form), and satisfies both of the following:      |
|  | (i) a site contamination audit report has been prepared under Part 10A of the <i>Environment Protection Act 1993</i> in relation to the land within the previous 5 years which states that-  |
|  | A. site contamination does not exist (or no longer exists) at the land   |
|  | or  B. the land is suitable for the proposed use or range of uses (without the need for any further remediation)   |
|  | or C. where remediation is, or remains, necessary for the proposed use (or range of uses), remediation work has been carried out or will be carried out (and the applicant has provided a written undertaking that the remediation works |

Page 108 of 126 Printed on 5/07/2022

|      | will be implemented in association with the development)   |
|------|--|
| (ii) | and no other class 1 activity or class 2 activity has taken place at the land since the preparation of the site contamination audit report (as demonstrated in a site contamination declaration form). |

# **Tourism Development**

# **Assessment Provisions (AP)**

|      | Desired Outcome  |  |  |
|------|--|--|--|
| DO 1 | Tourism development is built in locations that cater to the needs of visitors and positively contributes to South Australia's visitor economy. |  |  |

Performance Outcomes (PO) and Deemed-to-Satisfy (DTS) Criteria / Designated Performance Feature (DPF)

| Performance Outcome  | Deemed-to-Satisfy Criteria / Designated Performance Feature |
|--|---|
| Gel  | neral   |
| PO 1.1   | DTS/DPF 1.1   |
| Tourism development complements and contributes to local, natural, cultural or historical context where:   | None are applicable.  |
| (a) it supports immersive natural experiences  |   |
| (b) it showcases South Australia's landscapes and produce  |   |
| (c) its events and functions are connected to local food, wine and nature.   |   |
| PO 1.2   | DTS/DPF 1.2   |
| Tourism development comprising multiple accommodation units (including any facilities and activities for use by guests and visitors) is clustered to minimise environmental and contextual impact. | None are applicable.  |
| Caravan and  | Tourist Parks   |
| PO 2.1   | DTS/DPF 2.1   |
| Potential conflicts between long-term residents and short-term tourists are minimised through suitable siting and design measures.   | None are applicable.  |
| PO 2.2   | DTS/DPF 2.2   |

Page 109 of 126 Printed on 5/07/2022

| Policy24 - Enquiry   |   |
|--|---|
| Occupants are provided privacy and amenity through landscaping and fencing.  | None are applicable.  |
| PO 2.3   | DTS/DPF 2.3   |
| Communal open space and centrally located recreation facilities are provided for guests and visitors.  | 12.5% or more of a caravan park comprises clearly defined communal open space, landscaped areas and areas for recreation. |
| PO 2.4   | DTS/DPF 2.4   |
| Perimeter landscaping is used to enhance the amenity of the locality.  | None are applicable.  |
| PO 2.5   | DTS/DPF 2.5   |
| Amenity blocks (showers, toilets, laundry and kitchen facilities) are sufficient to serve the full occupancy of the development.   | None are applicable.  |
| PO 2.6   | DTS/DPF 2.6   |
| Long-term occupation does not displace tourist accommodation, particularly in important tourist destinations such as coastal and riverine locations.   | None are applicable.  |
| Tourist accommodation in areas constituted u   | under the National Parks and Wildlife Act 1972  |
| PO 3.1   | DTS/DPF 3.1   |
| Tourist accommodation avoids delicate or environmentally sensitive areas such as sand dunes, cliff tops, estuaries, wetlands or substantially intact strata of native vegetation (including regenerated areas of native vegetation lost through bushfire).   | None are applicable.  |
| PO 3.2   | DTS/DPF 3.2   |
| Tourist accommodation is sited and designed in a manner that is subservient to the natural environment and where adverse impacts on natural features, landscapes, habitats and cultural assets are avoided.  | None are applicable.  |
| PO 3.3   | DTS/DPF 3.3   |
| Tourist accommodation and recreational facilities, including associated access ways and ancillary structures, are located on cleared (other than where cleared as a result of bushfire) or degraded areas or where environmental improvements can be achieved.   | None are applicable.  |
| PO 3.4   | DTS/DPF 3.4   |
| Tourist accommodation is designed to prevent conversion to private dwellings through:  | None are applicable.  |
| <ul> <li>(a) comprising a minimum of 10 accommodation units</li> <li>(b) clustering separated individual accommodation units</li> <li>(c) being of a size unsuitable for a private dwelling</li> <li>(d) ensuring functional areas that are generally associated with a private dwelling such as kitchens and laundries are excluded from, or physically separated from individual accommodation units, or are of a size unsuitable for a private dwelling.</li> </ul> |   |

Page 110 of 126 Printed on 5/07/2022

# **Transport, Access and Parking**

# **Assessment Provisions (AP)**

| Desired Outcome |  |
|-----------------|--|
| DO 1            | A comprehensive, integrated and connected transport system that is safe, sustainable, efficient, convenient and accessible to all users. |

Performance Outcomes (PO) and Deemed-to-Satisfy (DTS) Criteria / Designated Performance Feature (DPF)

| Performance Outcome   | Deemed-to-Satisfy Criteria / Designated Performance Feature |
|---|---|
| Movemen   | nt Systems  |
| PO 1.1  | DTS/DPF 1.1   |
| Development is integrated with the existing transport system and designed to minimise its potential impact on the functional performance of the transport system.   | None are applicable.  |
| PO 1.2  | DTS/DPF 1.2   |
| Development is designed to discourage commercial and industrial vehicle movements through residential streets and adjacent other sensitive receivers.   | None are applicable.  |
| PO 1.3  | DTS/DPF 1.3   |
| Industrial, commercial and service vehicle movements, loading areas and designated parking spaces are separated from passenger vehicle car parking areas to ensure efficient and safe movement and minimise potential conflict. | None are applicable.  |
| PO 1.4  | DTS/DPF 1.4   |
| Development is sited and designed so that loading, unloading and turning of all traffic avoids interrupting the operation of and queuing on public roads and pedestrian paths.  | All vehicle manoeuvring occurs onsite.                      |
| Sightlines  |   |
| PO 2.1  | DTS/DPF 2.1   |
| Sightlines at intersections, pedestrian and cycle crossings, and crossovers to allotments for motorists, cyclists and pedestrians are maintained or enhanced to ensure safety for all road users and pedestrians.               | None are applicable.  |
| PO 2.2  | DTS/DPF 2.2   |
| Walls, fencing and landscaping adjacent to driveways and corner   | None are applicable.  |

Page 111 of 126 Printed on 5/07/2022

| sites are designed to provide adequate sightlines between vehicles and pedestrians.  |  |
|--|--|
| Vehicle  | Access   |
| PO 3.1  Safe and convenient access minimises impact or interruption on the operation of public roads.  PO 3.2  Development incorporating vehicular access ramps ensures vehicles can enter and exit a site safely and without creating a   | DTS/DPF 3.1  |
| hazard to pedestrians and other vehicular traffic.  PO 3.3  Access points are sited and designed to accommodate the type and volume of traffic likely to be generated by the development or land use.  | DTS/DPF 3.3  None are applicable.  |
| PO 3.4  Access points are sited and designed to minimise any adverse impacts on neighbouring properties.   | DTS/DPF 3.4  None are applicable.  |
| Access points are located so as not to interfere with street trees, existing street furniture (including directional signs, lighting, seating and weather shelters) or infrastructure services to maintain the appearance of the streetscape, preserve local amenity and minimise disruption to utility infrastructure assets. | Vehicle access to designated car parking spaces satisfy (a) or (b):  (a) is provided via a lawfully existing or authorised access point or an access point for which consent has been granted as part of an application for the division of land  (b) where newly proposed, is set back:  (i) 0.5m or more from any street furniture, street pole, infrastructure services pit, or other stormwater or utility infrastructure unless consent is provided from the asset owner  (ii) 2m or more from the base of the trunk of a street tree unless consent is provided from the tree owner for a lesser distance  (iii) 6m or more from the tangent point of an intersection of 2 or more roads  (iv) outside of the marked lines or infrastructure dedicating a pedestrian crossing. |
| PO 3.6  Driveways and access points are separated and minimised in number to optimise the provision of on-street visitor parking (where on-street parking is appropriate).   | DTS/DPF 3.6  Driveways and access points:  (a) for sites with a frontage to a public road of 20m or less, one access point no greater than 3.5m in width is provided (b) for sites with a frontage to a public road greater than 20m:  (i) a single access point no greater than 6m in width is provided or  |

Page 112 of 126 Printed on 5/07/2022

| . 6.16,2  |   | (ii) not more than two access points with a width of 3.5m each are provided.   |
|---|---|--|
| PO 3.7  |   | DTS/DPF 3.7  |
|   | s points are appropriately separated from level crossings to interference and ensure their safe ongoing operation.  | Development does not involve a new or modified access or cause an increase in traffic through an existing access that is located within the following distance from a railway crossing:  (a) 80 km/h road - 110m (b) 70 km/h road - 90m (c) 60 km/h road - 70m (d) 50km/h or less road - 50m.  |
| PO 3.8  |   | DTS/DPF 3.8  |
| designe<br>manoe  | rays, access points, access tracks and parking areas are ed and constructed to allow adequate movement and uvrability having regard to the types of vehicles that are ably anticipated.   | None are applicable.   |
| PO 3.9  |   | DTS/DPF 3.9  |
| Development is designed to ensure vehicle circulation between activity areas occurs within the site without the need to use public roads. |   | None are applicable.   |
|   | Access for People   | e with Disabilities  |
| PO 4.1  |   | DTS/DPF 4.1  |
|   | pment is sited and designed to provide safe, dignified and nient access for people with a disability.   | None are applicable.   |
|   | Vehicle Pa  | I<br>rking Rates   |
| PO 5.1  |   | DTS/DPF 5.1  |
| access<br>develor   | ent on-site vehicle parking and specifically marked sible car parking places are provided to meet the needs of the pment or land use having regard to factors that may support ced on-site rate such as:  | Development provides a number of car parking spaces on-site at a rate no less than the amount calculated using one of the following, whichever is relevant:  |
| (a)   | availability of on-street car parking   | (a) Transport, Access and Parking Table 1 - General Off-<br>Street Car Parking Requirements  |
| (b)<br>(c)  | shared use of other parking areas in relation to a mixed-use development, where the hours of operation of commercial activities complement the residential use of the site, the provision of vehicle parking may be shared the adaptive reuse of a State or Local Heritage Place. | <ul> <li>(b) Transport, Access and Parking Table 2 - Off-Street Vehicle Parking Requirements in Designated Areas</li> <li>(c) if located in an area where a lawfully established carparking fund operates, the number of spaces calculated under (a) or (b) less the number of spaces offset by contribution to the fund.</li> </ul> |
|   | Vehicle Pa  | I<br>rking Areas   |
| PO 6.1  |   | DTS/DPF 6.1  |
| the ope   | e parking areas are sited and designed to minimise impact on eration of public roads by avoiding the use of public roads moving from one part of a parking area to another.   | Movement between vehicle parking areas within the site can occur without the need to use a public road.  |
| PO 6.2  |   | DTS/DPF 6.2  |
| Vehicle   | e parking areas are appropriately located, designed and   | None are applicable.   |

Page 113 of 126 Printed on 5/07/2022

| Policy24 - Enquiry  |   |
|---|---|
| constructed to minimise impacts on adjacent sensitive receivers through measures such as ensuring they are attractively developed and landscaped, screen fenced, and the like.                      |   |
| PO 6.3  | DTS/DPF 6.3   |
| Vehicle parking areas are designed to provide opportunity for integration and shared-use of adjacent car parking areas to reduce the total extent of vehicle parking areas and access points.       | None are applicable.  |
| PO 6.4  | DTS/DPF 6.4   |
| Pedestrian linkages between parking areas and the development are provided and are safe and convenient.   | None are applicable.  |
| PO 6.5  | DTS/DPF 6.5   |
| Vehicle parking areas that are likely to be used during non-daylight hours are provided with sufficient lighting to entry and exit points to ensure clear visibility to users.                      | None are applicable.  |
| PO 6.6  | DTS/DPF 6.6   |
| Loading areas and designated parking spaces for service vehicles are provided within the boundary of the site.  | Loading areas and designated parking spaces are wholly located within the site.   |
| PO 6.7  | DTS/DPF 6.7   |
| On-site visitor parking spaces are sited and designed to be accessible to all visitors at all times.  | None are applicable.  |
| Undercroft and Below Ground C   | Garaging and Parking of Vehicles  |
| PO 7.1  | DTS/DPF 7.1   |
| Undercroft and below ground garaging of vehicles is designed to enable safe entry and exit from the site without compromising pedestrian or cyclist safety or causing conflict with other vehicles. | None are applicable.  |
| Internal Roads and Parking Areas in Resid   | ential Parks and Caravan and Tourist Parks  |
| PO 8.1  | DTS/DPF 8.1   |
| Internal road and vehicle parking areas are surfaced to prevent dust becoming a nuisance to park residents and occupants.   | None are applicable.  |
| PO 8.2  | DTS/DPF 8.2   |
| Traffic circulation and movement within the park is pedestrian friendly and promotes low speed vehicle movement.  | None are applicable.  |
| Bicycle Parking in Designated Areas   |   |
| PO 9.1  | DTS/DPF 9.1   |
| The provision of adequately sized on-site bicycle parking facilities encourages cycling as an active transport mode.  | Areas and / or fixtures are provided for the parking and storage of bicycles at a rate not less than the amount calculated using Transport, Access and Parking Table 3 - Off Street Bicycle Parking Requirements. |
| PO 9.2  | DTS/DPF 9.2   |
| Bicycle parking facilities provide for the secure storage and tethering of bicycles in a place where casual surveillance is possible, is well lit and signed for the safety and convenience of      | None are applicable.  |

Page 114 of 126 Printed on 5/07/2022

| 1 Olloy24 - Eriquily   |   |
|--|---|
| cyclists and deters property theft.  |   |
| PO 9.3   | DTS/DPF 9.3   |
| Non-residential development incorporates end-of-journey facilities for employees such as showers, changing facilities and secure lockers, and signage indicating the location of the facilities to encourage cycling as a mode of journey-to-work transport. | None are applicable.  |
| Corner   | Cut-Offs  |
| PO 10.1  | DTS/DPF 10.1  |
| Development is located and designed to ensure drivers can safely turn into and out of public road junctions.   | Development does not involve building work, or building work is located wholly outside the land shown as Corner Cut-Off Area in the following diagram:  Corner Cut-Off Area  Allotment Boundary  Allotment Boundary  Road Reserve |

# **Table 1 - General Off-Street Car Parking Requirements**

The following parking rates apply and if located in an area where a lawfully established carparking fund operates, the number of spaces is reduced by an amount equal to the number of spaces offset by contribution to the fund.

| Class of Development      | Car Parking Rate (unless varied by Table 2 onwards)  Where a development comprises more than one development type, then the overall car parking rate will be taken to be the sum of the car parking rates for each development type. |
|---------------------------|--|
| Residential Development   |  |
| Detached Dwelling         | Dwelling with 1 bedroom (including rooms capable of being used as a bedroom) - 1 space per dwelling.   |
|                           | Dwelling with 2 or more bedrooms (including rooms capable of being used as a bedroom) - 2 spaces per dwelling, 1 of which is to be covered.  |
| Group Dwelling            | Dwelling with 1 or 2 bedrooms (including rooms capable of being used as a bedroom) - 1 space per dwelling.   |
|                           | Dwelling with 3 or more bedrooms (including rooms capable of being used as a bedroom) - 2 spaces per dwelling, 1 of which is to be covered.  |
|                           | 0.33 spaces per dwelling for visitor parking where development involves 3 or more dwellings.   |
| Residential Flat Building | Dwelling with 1 or 2 bedrooms (including rooms capable of being used as a bedroom) - 1 space per dwelling.   |
|                           | Dwelling with 3 or more bedrooms (including rooms capable of being used as a bedroom) - 2 spaces per dwelling, 1 of which is to be covered.  |

Page 115 of 126 Printed on 5/07/2022

| Folicy24 - Eriquity   |   |
|---|---|
|   | 0.33 spaces per dwelling for visitor parking where development involves 3 or more dwellings.  |
| Row Dwelling where vehicle access is from the primary street                        | Dwelling with 1 bedroom (including rooms capable of being used as a bedroom) - 1 space per dwelling.  |
| primary subst   | Dwelling with 2 or more bedrooms (including rooms capable of being used as a bedroom) - 2 spaces per dwelling, 1 of which is to be covered.   |
| Row Dwelling where vehicle access is not from the primary street (i.e. rear-loaded) | Dwelling with 1 or 2 bedrooms (including rooms capable of being used as a bedroom) - 1 space per dwelling.  Dwelling with 3 or more bedrooms (including rooms capable of being used as a bedroom) - 2 spaces per dwelling, 1 of which is to be covered. |
| Semi-Detached Dwelling  | Dwelling with 1 bedroom (including rooms capable of being used as a bedroom) - 1 space per dwelling.  |
|   | Dwelling with 2 or more bedrooms (including rooms capable of being used as a bedroom) - 2 spaces per dwelling, 1 of which is to be covered.   |
| Aged / Supported Accommodation  |   |
| Retirement village  | Dwelling with 1 or 2 bedrooms (including rooms capable of being used as a bedroom) - 1 space per dwelling.  |
|   | Dwelling with 3 or more bedrooms (including rooms capable of being used as a bedroom) - 2 spaces per dwelling.  |
|   | 0.2 spaces per dwelling for visitor parking.  |
| Supported accommodation   | 0.3 spaces per bed.   |
| Residential Development (Other)   |   |
| Ancillary accommodation   | No additional requirements beyond those associated with the main dwelling.  |
| Residential park  | Dwelling with 1 or 2 bedrooms (including rooms capable of being used as a bedroom) - 1 space per dwelling.  |
|   | Dwelling with 3 or more bedrooms (including rooms capable of being used as a bedroom) - 2 spaces per dwelling.  |
|   | 0.2 spaces per dwelling for visitor parking.  |
| Student accommodation   | 0.3 spaces per bed.   |
| Workers' accommodation  | 0.5 spaces per bed plus 0.2 spaces per bed for visitor parking.   |
| Tourist   |   |
| Caravan park / tourist park   | Parks with 100 sites or less - a minimum of 1 space per 10 sites to be used for accommodation.  |
|   | Parks with more than 100 sites - a minimum of 1 space per 15 sites used for accommodation.  |
|   | A minimum of 1 space for every caravan (permanently fixed to the ground) or cabin.  |
|   |   |

Page 116 of 126 Printed on 5/07/2022

| Commercial Uses  |  |
|--|--|
| Auction room/ depot  | 1 space per 100m <sup>2</sup> of building floor area plus an additional 2 spaces.  |
| Automotive collision repair  | 3 spaces per service bay.  |
| Call centre  | 8 spaces per 100m <sup>2</sup> of gross leasable floor area.   |
| Motor repair station   | 3 spaces per service bay.  |
| Office   | 4 spaces per 100m <sup>2</sup> of gross leasable floor area.   |
| Retail fuel outlet   | 3 spaces per 100m <sup>2</sup> gross leasable floor area.  |
| Service trade premises   | 2.5 spaces per 100m <sup>2</sup> of gross leasable floor area  |
|  | 1 space per 100m <sup>2</sup> of outdoor area used for display purposes.   |
| Shop (no commercial kitchen)   | 5.5 spaces per 100m <sup>2</sup> of gross leasable floor area where not located in an integrated complex containing two or more tenancies (and which may comprise more than one building) where facilities for off-street vehicle parking, vehicle loading and unloading, and the storage and collection of refuse are shared. |
|  | 5 spaces per 100m <sup>2</sup> of gross leasable floor area where located in an integrated complex containing two or more tenancies (and which may comprise more than one building) where facilities for off-street vehicle parking, vehicle loading and unloading, and the storage and collection of refuse are shared.       |
| Shop (in the form of a bulky goods outlet)                           | 2.5 spaces per 100m <sup>2</sup> of gross leasable floor area.   |
| Shop (in the form of a restaurant or involving a commercial kitchen) | Premises with a dine-in service only (which may include a take-away component with no drive-through) - 0.4 spaces per seat.  |
|  | Premises with take-away service but with no seats - 12 spaces per 100m <sup>2</sup> of total floor area plus a drive-through queue capacity of ten vehicles measured from the pick-up point.   |
|  | Premises with a dine-in and drive-through take-away service - 0.3 spaces per seat plus a drive through queue capacity of 10 vehicles measured from the pick-up point.  |
| Community and Civic Uses   |  |
| Childcare centre   | 0.25 spaces per child  |
| Library  | 4 spaces per 100m <sup>2</sup> of total floor area.  |
| Community facility   | 10 spaces per 100m <sup>2</sup> of total floor area.   |
|  |  |

Page 117 of 126 Printed on 5/07/2022

| Policy24 - Eriquiry                 |   |
|-------------------------------------|---|
| Hall / meeting hall                 | 0.2 spaces per seat.  |
| Place of worship                    | 1 space for every 3 visitor seats.  |
| Pre-school                          | 1 per employee plus 0.25 per child (drop off/pick up bays)  |
| Educational establishment           | For a primary school - 1.1 space per full time equivalent employee plus 0.25 spaces per student for a pickup/set down area either on-site or on the public realm within 300m of the site.   |
|                                     | For a secondary school - 1.1 per full time equivalent employee plus 0.1 spaces per student for a pickup/set down area either on-site or on the public realm within 300m of the site.  |
|                                     | For a tertiary institution - 0.4 per student based on the maximum number of students on the site at any time.   |
| Health Related Uses                 |   |
| Hospital                            | 4.5 spaces per bed for a public hospital.   |
|                                     | 1.5 spaces per bed for a private hospital.  |
| Consulting room                     | 4 spaces per consulting room excluding ancillary facilities.  |
| Recreational and Entertainment Uses |   |
| Cinema complex                      | 0.2 spaces per seat.  |
| Concert hall / theatre              | 0.2 spaces per seat.  |
| Hotel                               | 1 space for every 2m <sup>2</sup> of total floor area in a public bar plus 1 space for every 6m <sup>2</sup> of total floor area available to the public in a lounge, beer garden plus 1 space per 2 gaming machines, plus 1 space per 3 seats in a restaurant. |
| Indoor recreation facility          | 6.5 spaces per 100m <sup>2</sup> of total floor area for a Fitness Centre   |
|                                     | 4.5 spaces per 100m <sup>2</sup> of total floor area for all other Indoor recreation facilities.  |
| Industry/Employment Uses            |   |
| Fuel depot                          | 1.5 spaces per 100m <sup>2</sup> total floor area   |
|                                     | 1 spaces per 100m <sup>2</sup> of outdoor area used for fuel depot activity purposes.   |
| Industry                            | 1.5 spaces per 100m <sup>2</sup> of total floor area.   |
| Store                               | 0.5 spaces per 100m <sup>2</sup> of total floor area.   |
|                                     |   |

Page 118 of 126 Printed on 5/07/2022

| Timber yard                 | 1.5 spaces per 100m <sup>2</sup> of total floor area                                     |
|-----------------------------|--|
|                             | 1 space per 100m <sup>2</sup> of outdoor area used for display purposes.                 |
| Warehouse                   | 0.5 spaces per 100m <sup>2</sup> total floor area.                                       |
| Other Uses                  |  |
| Funeral Parlour             | 1 space per 5 seats in the chapel plus 1 space for each vehicle operated by the parlour. |
| Radio or Television Station | 5 spaces per 100m <sup>2</sup> of total building floor area.                             |

### Table 2 - Off-Street Car Parking Requirements in Designated Areas

The following parking rates apply in any zone, subzone or other area described in the 'Designated Areas' column subject to the following:

- (a) the location of the development is unable to satisfy the requirements of Table 2 Criteria (other than where a location is exempted from the application of those criteria) or
- (b) the development satisfies Table 2 Criteria (or is exempt from those criteria) and is located in an area where a lawfully established carparking fund operates, in which case the number of spaces are reduced by an amount equal to the number of spaces offset by contribution to the fund.

| Class of Development       | Car Parking Rate  Where a development comprises more than one development type, then the overall car parking rate will be taken to be the sum of the car parking rates for each development type. |   | Designated Areas  |
|----------------------------|---|---|---|
|                            | Minimum number of spaces  | Maximum number of spaces  |   |
| Development generally      |   |   |   |
| All classes of development | No minimum.   | No maximum except in the Primary Pedestrian Area identified in the Primary Pedestrian Area Concept Plan, where the maximum is:  1 space for each dwelling with a total floor area less than 75 square metres  2 spaces for each dwelling with a total floor area between 75 square metres and 150 square metres  3 spaces for each dwelling with a total floor area greater than 150 square metres.  Residential flat building or | Capital City Zone City Main Street Zone City Riverbank Zone Adelaide Park Lands Zone Business Neighbourhood Zone (within the City of Adelaide) The St Andrews Hospital Precinct Subzone and Women's and Children's Hospital Precinct Subzone of the Community Facilities Zone |

Page 119 of 126 Printed on 5/07/2022

|   |   | Residential component of a multi-storey building: 1 visitor space for each 6 dwellings.      |  |
|---|---|--|--|
| Non-residential develop                                     | ment  |  |  |
| Non-residential development excluding tourist accommodation | 3 spaces per 100m <sup>2</sup> of gross leasable floor area.  | 5 spaces per 100m <sup>2</sup> of gross leasable floor area.                                 | City Living Zone  Urban Corridor (Boulevard) Zone  Urban Corridor (Business) Zone  Urban Corridor (Living) Zone  Urban Corridor (Main Street ) Zone  Urban Neighbourhood Zone  |
| Non-residential development excluding tourist accommodation | 3 spaces per 100m <sup>2</sup> of gross leasable floor area.  | 6 spaces per 100m <sup>2</sup> of gross leasable floor area.                                 | Strategic Innovation Zone Suburban Activity Centre Zone Suburban Business Zone Business Neighbourhood Zone Suburban Main Street Zone Urban Activity Centre Zone  |
| Tourist accommodation                                       | 1 space for every 4 bedrooms<br>up to 100 bedrooms plus 1<br>space for every 5 bedrooms<br>over 100 bedrooms  | 1 space per 2 bedrooms up to<br>100 bedrooms and 1 space per<br>4 bedrooms over 100 bedrooms | City Living Zone  Urban Activity Centre Zone  Urban Corridor (Boulevard) Zone  Urban Corridor (Business) Zone  Urban Corridor (Living) Zone  Urban Corridor (Main Street ) Zone  Urban Neighbourhood Zone                            |
| Residential development                                     |   |  |  |
| Residential component of a multi-storey building            | Dwelling with no separate bedroom -0.25 spaces per dwelling  1 bedroom dwelling - 0.75 spaces per dwelling  2 bedroom dwelling - 1 space per dwelling  3 or more bedroom dwelling - 1.25 spaces per dwelling  0.25 spaces per dwelling for visitor parking. | None specified.  | City Living Zone  Strategic Innovation Zone  Urban Activity Centre Zone  Urban Corridor (Boulevard) Zone  Urban Corridor (Business) Zone  Urban Corridor (Living) Zone  Urban Corridor (Main Street ) Zone  Urban Neighbourhood Zone |

Page 120 of 126 Printed on 5/07/2022

| Residential flat building | Dwelling with no separate                 | None specified. | City Living Zone                   |
|---------------------------|---|-----------------|------------------------------------|
| Residential flat building | bedroom -0.25 spaces per                  | None specified. | City Living Zone                   |
|                           | dwelling                                  |                 | Urban Activity Centre Zone         |
|                           | 1 bedroom dwelling - 0.75                 |                 | Urban Corridor (Boulevard) Zone    |
|                           | spaces per dwelling                       |                 | Urban Corridor (Business) Zone     |
|                           | 2 bedroom dwelling - 1 space per dwelling |                 | Urban Corridor (Living) Zone       |
|                           | 3 or more bedroom dwelling -              |                 | Urban Corridor (Main Street ) Zone |
|                           | 1.25 spaces per dwelling                  |                 | Urban Neighbourhood Zone           |
|                           | 0.25 spaces per dwelling for              |                 |                                    |
|                           | visitor parking.                          |                 |                                    |

Table 2 - Criteria:

The following criteria are used in conjunction with Table 2. The 'Exception' column identifies locations where the criteria do not apply and the car parking rates in Table 2 are applicable.

|       | Criteria   |                   | Exceptions  |
|-------|--|-------------------|---|
| Metro | esignated area is wholly located within politan Adelaide and any part of the opment site satisfies one or more of the ing:                       | (a)<br>(b)        | All zones in the City of Adelaide Strategic Innovation Zone in the following locations:  (i) City of Burnside  (ii) City of Marion  (iii) City of Mitcham |
| (a)   | is within 200 metres of any section of road reserve along which a bus service operates as a high frequency public transit service <sup>(2)</sup> | (c)<br>(d)<br>(e) | Urban Corridor (Boulevard) Zone<br>Urban Corridor (Business) Zone<br>Urban Corridor (Living) Zone   |
| (b)   | is within 400 metres of a bus interchange <sup>(1)</sup>   | (f)<br>(g)        | Urban Corridor (Main Street ) Zone<br>Urban Neighbourhood Zone  |
| (c)   | is within 400 metres of an O-Bahn interchange <sup>(1)</sup>   | ,                 |   |
| (d)   | is within 400 metres of a passenger rail station <sup>(1)</sup>  |                   |   |
| (e)   | is within 400 metres of a passenger tram station <sup>(1)</sup>  |                   |   |
| (f)   | is within 400 metres of the Adelaide Parklands.  |                   |   |

[NOTE(S): (1)Measured from an area that contains any platform(s), shelter(s) or stop(s) where people congregate for the purpose waiting to board a bus, tram or train, but does not include areas used for the parking of vehicles. (2) A high frequency public transit service is a route serviced every 15 minutes between 7.30am and 6.30pm Monday to Friday and every 30 minutes at night, Saturday, Sunday and public holidays until 10pm.]

### **Table 3 - Off-Street Bicycle Parking Requirements**

The bicycle parking rates apply within designated areas located within parts of the State identified in the Schedule to Table 3.

| Class of Development | Bicycle Parking Rate  |
|----------------------|---|
|                      | Where a development comprises more than one development type, then the overall bicycle parking rate will be taken to be the sum of the bicycle parking rates for each development type. |

Page 121 of 126 Printed on 5/07/2022

| Consulting Room                                  | 1 space per 20 employees plus 1 space per 20 consulting rooms for customers.  |
|--|---|
| Educational establishment                        | For a secondary school - 1 space per 20 full-time time employees plus 10 percent of the total number of employee spaces for visitors.   |
|  | For tertiary education - 1 space per 20 employees plus 1 space per 10 full time students.   |
| Hospital   | 1 space per 15 beds plus 1 space per 30 beds for visitors.  |
| Indoor recreation facility                       | 1 space per 4 employees plus 1 space per 200m <sup>2</sup> of gross leasable floor area for visitors.   |
| Licensed Premises                                | 1 per 20 employees, plus 1 per 60 square metres total floor area, plus 1 per 40 square metres of bar floor area, plus 1 per 120 square metres lounge and beer garden floor area, plus 1 per 60 square metres dining floor area, plus 1 per 40 square metres gaming room floor area.   |
| Office   | 1 space for every 200m <sup>2</sup> of gross leasable floor area plus 2 spaces plus 1 space per 1000m <sup>2</sup> of gross leasable floor area for visitors.   |
| Pre-school                                       | 1 space per 20 full time employees plus 1 space per 40 full time children.  |
| Recreation area                                  | 1 per 1500 spectator seats for employees plus 1 per 250 visitor and customers.  |
| Residential flat building                        | Within the City of Adelaide 1 for every dwelling for residents with a total floor area less than 150 square metres, 2 for every dwelling for residents with a total floor area greater than 150 square metres, plus 1 for every 10 dwellings for visitors, and in all other cases 1 space for every 4 dwellings for residents plus 1 for every 10 dwellings for visitors.       |
| Residential component of a multi-storey building | Within the City of Adelaide 1 for every dwelling for residents with a total floor area less than 150 square metres, 2 for every dwelling for residents with a total floor area greater than 150 square metres, plus 1 for every 10 dwellings for visitors, and in all other cases 1 space for every 4 dwellings for residents plus 1 space for every 10 dwellings for visitors. |
| Shop   | 1 space for every 300m <sup>2</sup> of gross leasable floor area plus 1 space for every 600m <sup>2</sup> of gross leasable floor area for customers.   |
| Tourist accommodation                            | 1 space for every 20 employees plus 2 for the first 40 rooms and 1 for every additional 40 rooms for visitors.  |
| Schodulo to Table 2                              |   |

## Schedule to Table 3

| Designated Area             | Relevant part of the State  The bicycle parking rate applies to a designated area located in a relevant part of the State described below. |
|-----------------------------|--|
| All zones                   | City of Adelaide   |
| Business Neighbourhood Zone | Metropolitan Adelaide  |

Page 122 of 126 Printed on 5/07/2022

| Strategic Innovation Zone          |  |
|------------------------------------|--|
| Suburban Activity Centre Zone      |  |
| Suburban Business Zone             |  |
| Suburban Main Street Zone          |  |
| Urban Activity Centre Zone         |  |
| Urban Corridor (Boulevard) Zone    |  |
| Urban Corridor (Business) Zone     |  |
| Urban Corridor (Living) Zone       |  |
| Urban Corridor (Main Street ) Zone |  |
| Urban Neighbourhood Zone           |  |

# **Waste Treatment and Management Facilities**

# **Assessment Provisions (AP)**

|      | Desired Outcome   |
|------|---|
| DO 1 | Mitigation of the potential environmental and amenity impacts of waste treatment and management facilities. |

Performance Outcomes (PO) and Deemed-to-Satisfy (DTS) Criteria / Designated Performance Feature (DPF)

| Performance Outcome   | Deemed-to-Satisfy Criteria / Designated Performance Feature |
|---|---|
| Si  | ting  |
| PO 1.1  | DTS/DPF 1.1   |
| Waste treatment and management facilities incorporate separation distances and attenuation measures within the site between waste operations areas (including all closed, operating and future cells) and sensitive receivers and sensitive environmental features to mitigate off-site impacts from noise, air and dust emissions. | None are applicable.  |
| Soil and Water Protection   |   |
| PO 2.1  | DTS/DPF 2.1   |
| Soil, groundwater and surface water are protected from contamination from waste treatment and management facilities through measures such as:   | None are applicable.  |

Page 123 of 126 Printed on 5/07/2022

| i Olicy24 | - Enquiry   |  |
|-----------|---|--|
| (a)       | containing potential groundwater and surface water contaminants within waste operations areas                   |  |
| (b)       | diverting clean stormwater away from waste operations areas and potentially contaminated areas                  |  |
| (c)       | providing a leachate barrier between waste operations areas and underlying soil and groundwater.                |  |
| PO 2.2    |   | DTS/DPF 2.2  |
| Wastev    | vater lagoons are set back from watercourses to minimise  | Wastewater lagoons are set back 50m or more from watercourse |
|           | mental harm and adverse effects on water resources.   | banks.   |
| PO 2.3    |   | DTS/DPF 2.3  |
| Wastev    | vater lagoons are designed and sited to:  | None are applicable.   |
| (a)       | avoid intersecting underground waters;  |  |
| (b)       | avoid inundation by flood waters;   |  |
| (c)       | ensure lagoon contents do not overflow;   |  |
| (d)       | include a liner designed to prevent leakage.  |  |
| PO 2.4    |   | DTS/DPF 2.4  |
| Waste     | operations areas of landfills and organic waste processing  | Waste operations areas are set back 100m or more from        |
|           | s are set back from watercourses to minimise adverse  | watercourse banks.   |
| impacts   | s on water resources.   |  |
|           | Am  | lenity   |
| PO 3.1    |   | DTS/DPF 3.1  |
|           | treatment and management facilities are screened, located signed to minimise adverse visual impacts on amenity. | None are applicable.   |
| PO 3.2    |   | DTS/DPF 3.2  |
|           | routes to waste treatment and management facilities via tial streets is avoided.                                | None are applicable.   |
| PO 3.3    |   | DTS/DPF 3.3  |
| Litter co | ontrol measures minimise the incidence of windblown litter.   | None are applicable.   |
| PO 3.4    |   | DTS/DPF 3.4  |
| Waste t   | treatment and management facilities are designed to   | None are applicable.   |
| minimis   | se adverse impacts on both the site and surrounding areas eed and vermin infestation.                           |  |
|           | Access  |  |
| PO 4.1    |   | DTS/DPF 4.1  |
| Traffic   | circulation movements within any waste treatment or   | None are applicable.   |
| _         | ement site are designed to enable vehicles to enter and exit  |  |
| the site  | in a forward direction.   |  |
| PO 4.2    |   | DTS/DPF 4.2  |
|           | e access for emergency vehicles is provided to and within reatment or management sites.                         | None are applicable.   |
|           | Fencing a   | nd Security  |
| ı         |   | Т  |

Page 124 of 126 Printed on 5/07/2022

| ,  |   |
|--|---|
| PO 5.1   | DTS/DPF 5.1   |
| Security fencing provided around waste treatment and management facilities prevents unauthorised access to operations and potential hazard to the public.  | Chain wire mesh or pre-coated painted metal fencing 2m or more in height is erected along the perimeter of the waste treatment or waste management facility site. |
| Lar  | ndfill  |
| PO 6.1   | DTS/DPF 6.1   |
| Landfill gas emissions are managed in an environmentally acceptable manner.  | None are applicable.  |
| PO 6.2   | DTS/DPF 6.2   |
| Landfill facilities are separated from areas of environmental significance and land used for public recreation and enjoyment.  | Landfill facilities are set back 250m or more from a public open space reserve, forest reserve, national park or Conservation Zone.                               |
| PO 6.3   | DTS/DPF 6.3   |
| Landfill facilities are located on land that is not subject to land slip.  | None are applicable.  |
| PO 6.4   | DTS/DPF 6.4   |
| Landfill facilities are separated from areas subject to flooding.  | Landfill facilities are set back 500m or more from land inundated in a 1% AEP flood event.  |
| Organic Waste Pr   | ocessing Facilities   |
| PO 7.1   | DTS/DPF 7.1   |
| Organic waste processing facilities are separated from the coast to avoid potential environment harm.  | Organic waste processing facilities are set back 500m or more from the coastal high water mark.   |
| PO 7.2   | DTS/DPF 7.2   |
| Organic waste processing facilities are located on land where the engineered liner and underlying seasonal water table cannot intersect.   | None are applicable.  |
| PO 7.3   | DTS/DPF 7.3   |
| Organic waste processing facilities are sited away from areas of environmental significance and land used for public recreation and enjoyment.   | Organic waste processing facilities are set back 250m or more from a public open space reserve, forest reserve, national park or a Conservation Zone.             |
| PO 7.4   | DTS/DPF 7.4   |
| Organic waste processing facilities are located on land that is not subject to land slip.  | None are applicable.  |
| PO 7.5   | DTS/DPF 7.5   |
| Organic waste processing facilities separated from areas subject to flooding.  | Organic waste processing facilities are set back 500m or more from land inundated in a 1% AEP flood event.  |
| Major Wastewater   | Treatment Facilities  |
| PO 8.1   | DTS/DPF 8.1   |
| Major wastewater treatment and disposal systems, including lagoons, are designed to minimise potential adverse odour impacts on sensitive receivers, minimise public and environmental health risks and protect water quality. | None are applicable.  |
| PO 8.2   | DTS/DPF 8.2   |

Page 125 of 126 Printed on 5/07/2022

| Artificial wetland systems for the storage of treated wastewater are | None are applicable. |
|--|----------------------|
| designed and sited to minimise potential public health risks arising |                      |
| from the breeding of mosquitoes.                                     |                      |
|  |                      |

# **Workers' accommodation and Settlements**

# **Assessment Provisions (AP)**

|      | Desired Outcome  |
|------|--|
| DO 1 | Appropriately designed and located accommodation for seasonal and short-term workers in rural areas that minimises environmental and social impacts. |

| Performance Outcome  | Deemed-to-Satisfy Criteria /<br>Designated Performance<br>Feature |
|--|---|
| PO 1.1   | DTS/DPF 1.1   |
| Workers' accommodation and settlements are obscured from scenic routes, tourist destinations and areas of conservation significance or otherwise designed to complement the surrounding landscape. | None are applicable.  |
| PO 1.2   | DTS/DPF 1.2   |
| Workers' accommodation and settlements are sited and designed to minimise nuisance impacts on the amenity of adjacent users of land.   | None are applicable.  |
| PO 1.3   | DTS/DPF 1.3   |
| Workers' accommodation and settlements are built with materials and colours that blend with the landscape.   | None are applicable.  |
| PO 1.4   | DTS/DPF 1.4   |
| Workers' accommodation and settlements are supplied with service infrastructure such as power, water and effluent disposal sufficient to satisfy the living requirements of workers.               | None are applicable.  |

No criteria applies to this land use. Please check the definition of the land use for further detail.

Page 126 of 126 Printed on 5/07/2022

#### **59 TRISTANIA TCE DERNANCOURT SA 5075**

#### Address:

Click to view a detailed interactive SAILIS in SAILIS

To view a detailed interactive property map in SAPPA click on the map below



### **Property Zoning Details**

### Overlay

Airport Building Heights (Regulated) (All structures over 45 metres)

Affordable Housing

Hazards (Flooding - Evidence Required)

Prescribed Wells Area

Regulated and Significant Tree

Stormwater Management

**Urban Tree Canopy** 

#### Zone

General Neighbourhood

### **Development Pathways**

## General Neighbourhood

### 1. Accepted Development

Means that the development type does not require planning consent (planning approval). Please ensure compliance with relevant land use and development controls in the Code.

- · Air handling unit, air conditioning system or exhaust fan
- · Brush fence
- · Building work on railway land
- Carport
- · Internal building work
- Outbuilding
- · Partial demolition of a building or structure
- · Private bushfire shelter
- · Shade sail
- Solar photovoltaic panels (roof mounted)
- · Swimming pool or spa pool
- Verandah
- Water tank (above ground)
- · Water tank (underground)

Page 1 of 129 Printed on 5/07/2022

2. Code Assessed - Deemed to Satisfy

Means that the development type requires consent (planning approval). Please ensure compliance with relevant land use and development controls in the Code.

- · Ancillary accommodation
- Carport
- Detached dwelling
- · Dwelling addition
- Dwelling or residential flat building undertaken by:
  - (a) the South Australian Housing Trust either individually or jointly with other persons or bodies or
  - (b) a provider registered under the Community Housing National Law participating in a program relating to the renewal of housing endorsed by the South Australian Housing Trust.
- · Land division
- Outbuilding
- · Replacement building
- · Row dwelling
- · Semi-detached dwelling
- · Temporary accommodation in an area affected by bushfire
- Verandah

#### 3. Code Assessed - Performance Assessed

Performance Assessed development types listed below are those for which the Code identifies relevant policies. Additional development types that are not listed as Accepted, Deemed to Satisfy or Restricted default to a Performance assessed Pathway. Please contact your local council for more information.

- · Ancillary accommodation
- Carport
- Demolition
- · Detached dwelling
- Dwelling addition
- Dwelling or residential flat building undertaken by:
  - (a) the South Australian Housing Trust either individually or jointly with other persons or bodies or
  - (b) a provider registered under the Community Housing National Law participating in a program relating to the renewal of housing endorsed by the South Australian Housing Trust.
- Fence
- · Group dwelling
- · Land division
- Outbuilding
- · Residential flat building
- Retaining wall
- Row dwelling
- Semi-detached dwelling
- · Tree-damaging activity
- Verandah

#### 4. Impact Assessed - Restricted

Means that the development type requires approval. Classes of development that are classified as Restricted are listed in Table 4 of the relevant Zones.

**Property Policy Information for above selection** 

# Part 2 - Zones and Sub Zones

## **General Neighbourhood Zone**

#### **Assessment Provisions (AP)**

Page 2 of 129 Printed on 5/07/2022

# **Desired Outcome**

DO 1

Low-rise, low and medium-density housing that supports a range of needs and lifestyles located within easy reach of services and facilities. Employment and community service uses contribute to making the neighbourhood a convenient place to live without compromising residential amenity.

Performance Outcomes (PO) and Deemed to Satisfy (DTS) / Designated Performance Feature (DPF) Criteria

| Performance Outcome   | Deemed-to-Satisfy Criteria /<br>Designated Performance<br>Feature   |
|---|---|
| Land Use a  | nd Intensity  |
| PO 1.1  | DTS/DPF 1.1   |
| Predominantly residential development with complementary non-residential uses that support an active, convenient, and walkable neighbourhood.   | (a) Ancillary accommodation (b) Community facility (c) Consulting room (d) Dwelling (e) Educational establishment (f) Office (g) Place of Worship (h) Pre-school (i) Recreation area (j) Residential flat building (k) Retirement facility (l) Shop (m) Student accommodation (n) Supported accommodation |
| Non-residential development located and designed to improve community accessibility to services, primarily in the form of:  | DTS/DPF 1.2  None are applicable.   |
| <ul> <li>(a) small scale commercial uses such as offices, shops and consulting rooms</li> <li>(b) community services such as educational establishments, community centres, places of worship, pre-schools, and other health and welfare services</li> <li>(c) services and facilities ancillary to the function or operation of supported accommodation or retirement facilities</li> <li>(d) open space and recreation facilities.</li> </ul> |   |
| P01.3   | DTS/DPF 1.3   |
| Non-residential development sited and designed to complement the residential character and amenity of the neighbourhood.  | None are applicable.  |
| P0 1.4  | DTS/DPF 1.4   |
| Commercial activities improve community access to services are of a scale and type to maintain residential amenity.   | A shop, consulting room or office (or any combination thereof) satisfies any one of the following:  |

Page 3 of 129 Printed on 5/07/2022

- (a) it is located on the same allotment and in conjunction with a dwelling where all the following are satisfied:
  - (i) does not exceed 50m<sup>2</sup> gross leasable floor
  - (ii) does not involve the display of goods in a window or about the dwelling or its curtilage
- (b) it reinstates a former shop, consulting room or office in an existing building (or portion of a building) and satisfies one of the following:
  - (i) the building is a State or Local Heritage Place
  - is in conjunction with a dwelling and there is no increase in the gross leasable floor area previously used for non-residential purposes
- (c) is located more than 500m from an Activity Centre and satisfies one of the following:
  - does not exceed 100m<sup>2</sup> gross leasable floor area (individually or combined, in a single building) where the site does not have a frontage to a State Maintained Road
  - does not exceed 200m<sup>2</sup> gross leasable floor area (individually or combined, in a single building) where the site has a frontage to a State Maintained Road
- (d) the development site abuts an Activity Centre and all the following are satisfied:
  - it does not exceed 200m<sup>2</sup> gross leasable floor area (individually or combined, in a single building)
  - (ii) the proposed development will not result in a combined gross leasable floor area (existing and proposed) of all shops, consulting rooms and offices that abut the Activity Centre in this zone exceeding the lesser of the following:
    - A. 50% of the existing gross leasable floor area within the Activity Centre
    - B. 1000m<sup>2</sup>.

#### PO 1.5

Expansion of existing community services such as educational establishments, community facilities and pre-schools in a manner which complements the scale of development envisaged by the desired outcome for the neighbourhood.

#### DTS/DPF 1.5

Alteration of or addition to existing educational establishments, community facilities or pre-schools where all the following are satisfied:

- (a) set back at least 3m from any boundary shared with a residential land use
- (b) building height not exceeding 1 building level
- (c) the total floor area of the building not exceeding 150% of the total floor area prior to the addition/alteration
- (d) off-street vehicular parking exists or will be provided in accordance with the rate(s) specified in Transport, Access and Parking Table 1 - General Off-Street Car Parking Requirements or Table 2 - Off-Street Car Parking Requirements in Designated Areas to the nearest whole number.

Page 4 of 129 Printed on 5/07/2022

#### Site Dimensions and Land Division

#### PO 2.1

Allotments/sites created for residential purposes are of suitable size and dimension to accommodate the anticipated dwelling form and remain compatible with the pattern of development in a low-rise and predominantly low-density neighbourhood, with higher densities closer to public open space, public transport stations and activity centres.

#### DTS/DPF 2.1

Development will not result in more than 1 dwelling on an existing allotment

10

Allotments/sites for residential purposes accord with the following:

| Dwelling Type  | Minimum<br>site/allotment area<br>per dwelling                           | Minimum<br>site/allotment<br>frontage   |
|--|--|---|
| Detached dwelling (not in a terrace arrangement)             | 300m <sup>2</sup> (exclusive of<br>any battle-axe<br>allotment 'handle') | 9m where not<br>on a battle-<br>axe site<br>5m where on<br>a battle-axe<br>site |
| Semi-detached dwelling                                       | 300m <sup>2</sup>  | 9m  |
| Row dwelling (or detached dwelling in a terrace arrangement) | 250m <sup>2</sup>  | 7m<br>(averaged)  |
| Group dwelling   | 300m² (average, including common areas)                                  | 15m (total)   |
| Dwelling within a residential flat building                  | 300m <sup>2</sup> (average, including common areas)                      | 15m (total)   |

#### PO 2.2

Development creating new allotments/sites in conjunction with retention of an existing dwelling ensures the site of the existing dwelling remains fit for purpose.

### DTS/DPF 2.2

Where the site of a dwelling does not comprise an entire allotment:

- (a) the balance of the allotment accords with site area and frontage requirements specified in General Neighbourhood Zone DTS/DPF 2.1
- (b) if there is an existing dwelling on the allotment that will remain on the allotment after completion of the development, it will not contravene:
  - (i) Private open space requirements specified in Design in Urban Areas Table 1 Private Open Space
  - (ii) off-street vehicular parking exists in accordance with the rate(s) specified in Transport, Access and Parking Table 1 - General Off-Street Car Parking Requirements or Table 2 - Off-Street Car Parking Requirements in Designated Areas to the nearest whole number.

#### PO 2.3

Land division results in sites that are accessible and suitable for their intended purpose.

#### DTS/DPF 2.3

Division of land satisfies (a), (b) or (c):

- (a) reflects the site boundaries illustrated and approved in an existing development authorisation under the Development Act 1993 or Planning, Development and Infrastructure Act 2016 where the allotments are used or are proposed to be used solely for residential purposes
- (b) is proposed as part of a combined land division application with deemed-to-satisfy dwellings on the

Page 5 of 129 Printed on 5/07/2022

proposed allotments

- (c) satisfies all of the following:
  - (i) No more than 5 additional allotments are created
  - (ii) Each proposed allotment has a minimum site area of 300m<sup>2</sup> and frontage of 9m
  - (iii) Each proposed allotment has a slope less than 12.5% (1-in-8)
  - (iv) There are no regulated trees on or within 20m of the subject land, with the distance measured from the base of the trunk of the tree (or the nearest trunk of the tree) to the subject land
  - (v) The division does not involve creation of a public road
  - (vi) Vehicle access from a public road can be provided to all proposed allotments which satisfies Design in Urban Areas DTS/DPF 23.3, 23.4 and 23.6, and would be located wholly on one side of the allotment, or located no more than 1m from the side boundary alignment
  - (vii) No allotments are in a battle-axe configuration and
  - (viii) Each proposed allotment is of a size and dimension capable of containing a rectangle 9m in width and 15m in depth.

#### Site Coverage

PO 3.1

Building footprints allow sufficient space around buildings to limit visual impact, provide an attractive outlook and access to light and ventilation.

DTS/DPF 3.1

The development does not result in site coverage exceeding 60%.

#### **Building Height**

PO 4.1

Buildings contribute to a low-rise suburban character.

DTS/DPF 4.1

Building height (excluding garages, carports and outbuildings) no greater than:

- (a) 2 building levels and 9m and
- (b) wall height that is no greater than 7m except in the case of a gable end.

#### Primary Street Setback

PO 5.1

Buildings are setback from primary street boundaries to contribute to the existing/emerging pattern of street setbacks in the streetscape.

DTS/DPF 5.1

The building line of a building set back from the primary street boundary:

- (a) no more than 1m in front of the average setback to the building line of existing buildings on adjoining sites which face the same primary street (including those buildings that would adjoin the site if not separated by a public road or a vacant allotment)
- (b) where there is only one existing building on adjoining sites which face the same primary street (including those that would adjoin if not separated by a public road or a vacant allotment), no more than 1m in front of the setback to the building line of that building

Page 6 of 129 Printed on 5/07/2022

Policy24 - Enquiry (c) not less than 5m where no building exists on an adjoining site with the same primary street frontage. Secondary Street Setback PO 6.1 DTS/DPF 6.1 Buildings are set back from secondary street boundaries to Building walls are set back from the boundary of the allotment achieve separation between building walls and public streets and with a secondary street frontage: contribute to a suburban streetscape character. (a) at least 900mm ٥r (b) if a dwelling on any adjoining allotment is closer to the secondary street than 900mm, at least the distance of that dwelling from the boundary with the secondary street. **Boundary Walls** PO 7.1 DTS/DPF 7.1 Dwelling boundary walls are limited in height and length to Except where the dwelling is located on a central site within a manage visual and overshadowing impacts on adjoining row dwelling or terrace arrangement, side boundary walls occur properties. only on one side boundary and satisfy (a) or (b) below: side boundary walls adjoin or abut a boundary wall of a building on adjoining land for the same or lesser length and height (b) side boundary walls do not: (i) exceed 3m in height from the top of footings (ii) exceed 11.5m in length when combined with other walls on the boundary of the subject development site, exceed a maximum 45% of the length of the boundary (iv) encroach within 3m of any other existing or proposed boundary walls on the subject land. PO 7.2 DTS/DPF 7.2 Dwellings in a semi-detached, row or terrace arrangement Dwelling walls in a semi-detached, row or terrace arrangement are setback at least 900mm from side boundaries shared with maintain space between buildings consistent with a suburban streetscape character. allotments outside the development site. Side boundary setback PO 8.1 DTS/DPF 8.1 Building walls are set back from side boundaries to provide: Other than walls located on a side boundary, building walls are set back from side boundaries: (a) separation between dwellings in a way that contributes to a suburban character (a) at least 900mm where the wall height is up to 3m (b) other than for a wall facing a southern side boundary, at and least 900mm plus 1/3 of the wall height above 3m

Rear boundary setback

(c)

and

at least 1900mm plus 1/3 of the wall height above 3m

for walls facing a southern side boundary.

Page 7 of 129 Printed on 5/07/2022

(b)

access to natural light and ventilation for neighbours.

#### PO 9.1

Dwelling walls are set back from rear boundaries to provide:

- separation between dwellings in a way that contributes to a suburban character
- (b) access to natural light and ventilation for neighbours
- (c) private open space
- (d) space for landscaping and vegetation.

#### DTS/DPF 9.1

Dwelling walls are set back from the rear boundary at least:

- (a) if the size of the site is less than 301m<sup>2</sup>-
  - (i) 3m in relation to the ground floor of the dwelling
  - (ii) 5m in relation to any other building level of the dwelling
- (b) if the size of the site is 301m<sup>2</sup> or more—
  - (i) 4m in relation to the ground floor of the dwelling
  - (ii) 6m in relation to any other building level of the dwelling.

## Concept Plans

#### PO 10.1

Development is compatible with the outcomes sought by any relevant Concept Plan contained within Part 12 - Concept Plans of the Planning and Design Code to support the orderly development of land through staging of development and provision of infrastructure.

#### DTS/DPF 10.1

The site of the development is wholly located outside any relevant Concept Plan boundary. The following Concept Plans are relevant:

In relation to DTS/DPF 10.1, in instances where:

- (a) one or more Concept Plan is returned, refer to Part 12 -Concept Plans in the Planning and Design Code to determine if a Concept Plan is relevant to the site of the proposed development. Note: multiple concept plans may be relevant.
- (b) in instances where 'no value' is returned, there is no relevant concept plan and DTS/DPF 10.1 is met.

### **Ancillary Buildings and Structures**

#### PO 11.1

Residential ancillary buildings are sited and designed to not detract from the streetscape or appearance of primary residential buildings on the site or neighbouring properties.

#### DTS/DPF 11.1

#### Ancillary buildings:

- (a) are ancillary to a dwelling erected on the same site
- (b) have a floor area not exceeding 60m2
- (c) are not constructed, added to or altered so that any part is situated:
  - (i) in front of any part of the building line of the dwelling to which it is ancillary
  - (ii) within 900mm of a boundary of the allotment with a secondary street (if the land has boundaries on two or more roads)
- (d) in the case of a garage or carport, the garage or carport:
  - is set back at least 5.5m from the boundary of the primary street
  - (ii) have a door / opening not exceeding:
    - A. for dwellings of single building level 7m in width or 50% of the site frontage,
      whichever is the lesser
    - B. for dwellings comprising two or more building levels at the building line fronting the same public street 7m in

Page 8 of 129 Printed on 5/07/2022

width

- (e) if situated on a boundary (not being a boundary with a primary street or secondary street), do not exceed a length of 11.5m unless:
  - (i) a longer wall or structure exists on the adjacent site and is situated on the same allotment boundary and
  - (ii) the proposed wall or structure will be built along the same length of boundary as the existing adjacent wall or structure to the same or lesser extent
- (f) if situated on a boundary of the allotment (not being a boundary with a primary street or secondary street), all walls or structures on the boundary will not exceed 45% of the length of that boundary
- (g) will not be located within 3m of any other wall along the same boundary unless on an adjacent site on that boundary there is an existing wall of a building that would be adjacent to or about the proposed wall or structure
- (h) have a wall height or post height not exceeding 3m (and not including a gable end)
- (i) have a roof height where no part of the roof is more than 5m above the natural ground level
- (j) if clad in sheet metal, is pre-colour treated or painted in a non-reflective colour
- (k) retains a total area of soft landscaping in accordance with (i) or (ii), whichever is less:
- (i) a total area as determined by the following table:

| Dwelling site area (or in the case of residential flat building or group dwelling(s), average site area) (m <sup>2</sup> ) | Minimum<br>percentage of<br>site |
|--|----------------------------------|
| <150   | 10%                              |
| 150-200  | 15%                              |
| 201-450  | 20%                              |
| >450   | 25%                              |

(ii) the amount of existing soft landscaping prior to the development occurring.

#### PO 11.2

Ancillary buildings and structures do not impede on-site functional requirements such as private open space provision, car parking requirements or result in over-development of the site.

#### DTS/DPF 11.2

Ancillary buildings and structures do not result in:

- (a) less private open space than specified in Design in Urban Areas Table 1 Private Open Space
- (b) less on-site car parking than specified in Transport, Access and Parking Table 1 - General Off-Street Car Parking Requirements or Table 2 - Off-Street Car Parking Requirements in Designated Areas.

Page 9 of 129 Printed on 5/07/2022

| Advertisements   |   |
|--|---|
| PO 12.1  | DTS/DPF 12.1  |
| Advertisements identify the associated business activity, and do not detract from the residential character of the locality. | Advertisements relating to a lawful business activity associated with a residential use do not exceed 0.3m2 and mounted flush with a wall or fence. |

### Table 5 - Procedural Matters (PM) - Notification

The following table identifies, pursuant to section 107(6) of the *Planning, Development and Infrastructure Act 2016*, classes of performance assessed development that are excluded from notification. The table also identifies any exemptions to the placement of notices when notification is required.

#### Interpretation

Notification tables exclude the classes of development listed in Column A from notification provided that they do not fall within a corresponding exclusion prescribed in Column B.

Where a development or an element of a development falls within more than one class of development listed in Column A, it will be excluded from notification if it is excluded (in its entirety) under any of those classes of development. It need not be excluded under all applicable classes of development.

Where a development involves multiple performance assessed elements, all performance assessed elements will require notification (regardless of whether one or more elements are excluded in the applicable notification table) unless every performance assessed element of the application is excluded in the applicable notification table, in which case the application will not require notification.

| lass of Devel    | opment   | Exceptions   |
|------------------|--|--|
| Column A)        |  | (Column B)   |
| author<br>unreas | pment which, in the opinion of the relevant ity, is of a minor nature only and will not conably impact on the owners or occupiers of the locality of the site of the development.  | None specified.  |
| (a)              | the South Australian Housing Trust either individually or jointly with other persons or bodies or a provider registered under the Community Housing National Law participating in a program relating to the renewal of housing endorsed by the South Australian Housing Trust. | <ol> <li>residential flat building(s) of 3 or more building levels</li> <li>the demolition of a State or Local Heritage Place</li> <li>the demolition of a building (except an ancillary building) in a Historic Area Overlay.</li> </ol>  |
| any co<br>(a)    | carport<br>deck<br>dwelling<br>dwelling addition   | Except development that:  1. does not satisfy General Neighbourhood Zone DTS/DPF 4.1 or 2. involves a building wall (or structure) that is proposed to be situated on (or abut) an allotment boundary (not being a boundary with a primary street or secondary street or an excluded boundary) and:  (a) the length of the proposed wall (or structure) exceeds 11.5m (other than where the proposed wall abuts an existing wall or structure of greate length on the adjoining allotment) |

Page 10 of 129 Printed on 5/07/2022

(k) private bushfire shelter (b) the height of the proposed wall (or post height) exceeds 3m measured from the top of (I) residential flat building footings (other than where the proposed wall (or (m) retaining wall post) abuts an existing wall or structure of (n) retirement facility greater height on the adjoining allotment). (o) shade sail (p) solar photovoltaic panels (roof mounted) (g) student accommodation (r) supported accommodation (s) swimming pool or spa pool verandah (u) water tank. 4. Any development involving any of the following (or of Except development that: any combination of any of the following): (a) consulting room 1. does not satisfy any of the following: (b) office (a) General Neighbourhood Zone DTS/DPF 1.4 (c) shop. (b) General Neighbourhood Zone DTS/DPF 4.1 2. involves a building wall (or structure) that is proposed to be situated on (or abut) an allotment boundary (not being a boundary with a primary street or secondary street or an excluded boundary) and: (a) the length of the proposed wall (or structure) exceeds 11.5m (other than where the proposed wall abuts an existing wall or structure of greater length on the adjoining allotment) (b) the height of the proposed wall (or post height) exceeds 3m measured from the top of footings (other than where the proposed wall (or post) abuts an existing wall or structure of greater height on the adjoining allotment). 5. Any development involving any of the following (or of None specified. any combination of any of the following): (a) internal building works (b) land division (c) recreation area (d) replacement building (e) temporary accommodation in an area affected by bushfire (f) tree damaging activity. 6. Alteration of or addition to any development involving Except development that does not satisfy General Neighbourhood the following (or of any combination of any of the Zone DTS/DPF 1.5. following): (a) community facility (b) educational establishment (c) pre-school. 7. Demolition. Except any of the following: 1. the demolition of a State or Local Heritage Place

Page 11 of 129 Printed on 5/07/2022

2. the demolition of a building (except an ancillary building) in a Historic Area Overlay.

Placement of Notices - Exemptions for Performance Assessed Development

None specified.

**Placement of Notices - Exemptions for Restricted Development** 

None specified.

# Part 3 - Overlays

# **Affordable Housing Overlay**

## **Assessment Provisions (AP)**

|      | Desired Outcome  |
|------|--|
| DO 1 | Affordable housing is integrated with residential and mixed use development. |
| DO 2 | Affordable housing caters for a variety of household structures.             |

Performance Outcomes (PO) and Deemed-to-Satisfy (DTS) Criteria / Designated Performance Feature (DPF)

| Performance Outcome  | Deemed-to-Satisfy Criteria / Designated Performance Feature   |
|--|---|
| Lan  | d Division  |
| PO 1.1   | DTS/DPF 1.1   |
| Development comprising 20 or more dwellings / allotments incorporates affordable housing.  | Development results in 0-19 additional allotments / dwellings.  |
| PO 1.2   | DTS/DPF 1.2   |
| Development comprising 20 or more dwellings or residential allotments provides housing suited to a range of incomes including households with low to moderate incomes. | Development comprising 20 or more dwellings / or residential allotments includes a minimum of 15% affordable housing except where:        |
|  | (a) it can be demonstrated that any shortfall in affordable housing has been provided in a previous stage of development or               |
|  | <ul> <li>(b) it can be demonstrated that any shortfall in affordable<br/>housing will be accommodated in a subsequent stage or</li> </ul> |

Page 12 of 129 Printed on 5/07/2022

| Policy24 - Enquiry   |   |  |  |
|--|---|--|--|
|  | stages of development.  |  |  |
| P0 1.3   | DTS/DPF 1.3   |  |  |
| Affordable housing is distributed throughout the development to avoid an overconcentration.  | None are applicable.  |  |  |
| Built Form a   | and Character   |  |  |
| PO 2.1   | DTS/DPF 2.1   |  |  |
| Affordable housing is designed to complement the design and character of residential development within the locality.  | None are applicable.  |  |  |
| Affordable Hot   | using Incentives  |  |  |
| PO 3.1   | DTS/DPF 3.1   |  |  |
| To support the provision of affordable housing, minimum allotment sizes may be reduced below the minimum allotment size specified in a zone while providing allotments of a suitable size and dimension to accommodate dwellings with a high standard of occupant amenity. | The minimum site area specified for a dwelling can be reduced by up to 20%, or the maximum density per hectare increased by up to 20%, where it is to be used to accommodate affordable housing except where the development is located within the Character Area Overlay or Historic Area Overlay.   |  |  |
| PO 3.2   | DTS/DPF 3.2   |  |  |
| To support the provision of affordable housing, building heights may be increased above the maximum specified in a zone.   | Where a building incorporates dwellings above ground level and includes at least 15% affordable housing, the maximum building height specified in any relevant zone policy can be increased by 1 building level in the:  (a) Business Neighbourhood Zone (b) City Living Zone (c) Established Neighbourhood Zone (d) General Neighbourhood Zone (e) Hills Neighbourhood Zone (f) Housing Diversity Neighbourhood Zone (g) Neighbourhood Zone (h) Master Planned Neighbourhood Zone (i) Master Planned Renewal Zone (j) Master Planned Township Zone (k) Rural Neighbourhood Zone (l) Suburban Business Zone (m) Suburban Neighbourhood Zone (n) Township Neighbourhood Zone (o) Township Zone (p) Urban Renewal Neighbourhood Zone (q) Waterfront Neighbourhood Zone and up to 30% in any other zone, except where:  (a) the development is located within the Character Area Overlay or Historic Area Overlay or (b) other height incentives already apply to the development. |  |  |
|  |   |  |  |
|  | nd Car Parking<br>T   |  |  |
| PO 4.1   | DTS/DPF 4.1   |  |  |

Page 13 of 129 Printed on 5/07/2022

Dwellings constituting affordable housing are provided with car Sufficient car parking is provided to meet the needs of parking in accordance with the following: occupants of affordable housing. 0.3 carparks per dwelling within a building which incorporates dwellings located above ground level within either: 200 metres of any section of road reserve along which a bus service operates as a high frequency public transit service<sup>(2)</sup> is within 400 metres of a bus interchange<sup>(1)</sup> (iii) is within 400 metres of an O-Bahn interchange<sup>(1)</sup> is within 400 metres of a passenger rail station(1) (v) is within 400 metres of a passenger tram station<sup>(1)</sup> (vi) is within 400 metres of the Adelaide Parklands. (b) 1 carpark per dwelling for any other dwelling.

[NOTE(S): (1) Measured from an area that contains any platform(s), shelter(s) or stop(s) where people congregate for the purpose waiting to board a bus, tram or train, but does not include areas used for the parking of vehicles. (2) A high frequency public transit service is a route serviced every 15 minutes between 7.30am and 6.30pm Monday to Friday and every 30 minutes at night, Saturday, Sunday and public holidays until 10pm.]

### Procedural Matters (PM) - Referrals

The following table identifies classes of development / activities that require referral in this Overlay and the applicable referral body. It sets out the purpose of the referral as well as the relevant statutory reference from Schedule 9 of the Planning, Development and Infrastructure (General) Regulations 2017.

| Class of Development / Activity   | Referral Body   | Purpose of<br>Referral   | Statutory<br>Reference  |
|---|---|--|---|
| Development for the purposes of the provision of affordable housing (applying the criteria determined under regulation 4 of the South Australian Housing Trust Regulations 2010). | Minister responsible for administering the South Australian Housing Trust Act 1995. | To provide direction on the conditions required to secure the provision of dwellings or allotments for affordable housing. | Development of a class to which Schedule 9 clause 3 item 20 of the Planning, Development and Infrastructure (General) Regulations 2017 applies. |

# **Airport Building Heights (Regulated) Overlay**

Page 14 of 129 Printed on 5/07/2022

## **Assessment Provisions (AP)**

|      | Desired Outcome   |  |  |  |
|------|---|--|--|--|
| DO 1 | Management of potential impacts of buildings and generated emissions to maintain operational and safety requirements of registered and certified commercial and military airfields, airports, airstrips and helicopter landing sites. |  |  |  |

Performance Outcomes (PO) and Deemed-to-Satisfy (DTS) Criteria / Designated Performance Feature (DPF)

| Performance Outcome  | Deemed-to-Satisfy Criteria / Designated Performance Feature  |
|--|--|
| Buil   | t Form   |
| PO 1.1   | DTS/DPF 1.1  |
| Building height does not pose a hazard to the operation of a certified or registered aerodrome.  | Buildings are located outside the area identified as 'All structures' (no height limit is prescribed) and do not exceed the height specified in the Airport Building Heights (Regulated) Overlay which applies to the subject site as shown on the SA Property and Planning Atlas.  In instances where more than one value applies to the site, the lowest value relevant to the site of the proposed development is applicable. |
| PO 1.2   | DTS/DPF 1.2  |
| Exhaust stacks are designed and sited to minimise plume impacts on aircraft movements associated with a certified or registered aerodrome. | Development does not include exhaust stacks.   |

# Procedural Matters (PM) - Referrals

The following table identifies classes of development / activities that require referral in this Overlay and the applicable referral body. It sets out the purpose of the referral as well as the relevant statutory reference from Schedule 9 of the Planning, Development and Infrastructure (General) Regulations 2017.

| Class of Development / Activity  | Referral Body   | Purpose of Referral   | Statutory Reference  |
|--|---|---|--|
| Any of the following classes of development:  (a) building located in an area identified as 'All structures' (no height limit is prescribed) or will exceed the height specified in the Airport Building Heights (Regulated) Overlay  (b) building comprising exhaust stacks that generates plumes, or may cause plumes to be generated, above a height specified in the Airport Building Heights (Regulated) Overlay. | The airport-operator company for the relevant airport within the meaning of the <i>Airports Act 1996</i> of the Commonwealth or, if there is no airport-operator company, the Secretary of the Minister responsible for the administration of the <i>Airports Act 1996</i> of the Commonwealth. | To provide expert assessment and direction to the relevant authority on potential impacts on the safety and operation of aviation activities. | Development of a class<br>to which Schedule 9<br>clause 3 item 1 of the<br>Planning, Development<br>and Infrastructure<br>(General) Regulations<br>2017 applies. |

Page 15 of 129 Printed on 5/07/2022

# Hazards (Flooding - Evidence Required) Overlay

## **Assessment Provisions (AP)**

| Desired Outcome |   |  |
|-----------------|---|--|
|                 | Development adopts a precautionary approach to mitigate potential impacts on people, property, infrastructure and the environment from potential flood risk through the appropriate siting and design of development. |  |
|                 | the environment from potential flood risk through the appropriate sitting and design of development.  |  |

Performance Outcomes (PO) and Deemed-to-Satisfy (DTS) Criteria / Designated Performance Feature (DPF)

| Performance Outcome   | Deemed-to-Satisfy Criteria /<br>Designated Performance<br>Feature   |  |
|---|---|--|
| Flood R   | esilience   |  |
| P0 1.1  | DTS/DPF 1.1   |  |
| Development is sited, designed and constructed to minimise the risk of entry of potential floodwaters where the entry of flood waters is likely to result in undue damage to or compromise ongoing activities within buildings. | Habitable buildings, commercial and industrial buildings, and buildings used for animal keeping incorporate a finished floor level at least 300mm above:  (a) the highest point of top of kerb of the primary street or (b) the highest point of natural ground level at the primary street boundary where there is no kerb |  |
| Environment   | tal Protection  |  |
| PO 2.1  | DTS/DPF 2.1   |  |
| Buildings and structures used either partly or wholly to contain or<br>store hazardous materials are designed to prevent spills or leaks<br>leaving the confines of the building.   | _   · · · · · · · · · · · · · · · · · ·   |  |

### **Procedural Matters (PM) - Referrals**

The following table identifies classes of development / activities that require referral in this Overlay and the applicable referral body. It sets out the purpose of the referral as well as the relevant statutory reference from Schedule 9 of the Planning, Development and Infrastructure (General) Regulations 2017.

| Class of Development / Activity | Referral Body | Purpose of Referral | Statutory<br>Reference |
|---------------------------------|---------------|---------------------|------------------------|
| None                            | None          | None                | None                   |

# **Prescribed Wells Area Overlay**

**Assessment Provisions (AP)** 

# **Desired Outcome**

Page 16 of 129 Printed on 5/07/2022

DO 1

Sustainable water use in prescribed wells areas.

| Performance Outcome  | Deemed-to-Satisfy Criteria /<br>Designated Performance<br>Feature  |
|--|--|
| PO 1.1  All development, but in particular involving any of the following:   | DTS/DPF 1.1  Development satisfies either of the following:  |
| (a) horticulture (b) activities requiring irrigation (c) aquaculture (d) industry (e) intensive animal husbandry (f) commercial forestry  has a lawful, sustainable and reliable water supply that does not place undue strain on water resources in prescribed wells areas. | <ul> <li>(a) the applicant has a current water licence in which sufficient spare capacity exists to accommodate the water needs of the proposed use or</li> <li>(b) the proposal does not involve the taking of water for which a licence would be required under the Landscape South Australia Act 2019.</li> </ul> |

## Procedural Matters (PM) - Referrals

The following table identifies classes of development / activities that require referral in this Overlay and the applicable referral body. It sets out the purpose of the referral as well as the relevant statutory reference from Schedule 9 of the Planning, Development and Infrastructure (General) Regulations 2017.

| Class of Development / Activity   | Referral Body   | Purpose of Referral  | Statutory<br>Reference  |
|---|---|--|---|
| Any of the following classes of development that require or may require water to be taken in addition to any allocation that has already been granted under the Landscape South Australia Act 2019:  (a) horticulture (b) activities requiring irrigation (c) aquaculture (d) industry (e) intensive animal husbandry (f) commercial forestry.  Commercial forestry that requires a forest water licence under Part 8 Division 6 of the Landscape South Australia Act 2019. | The Chief Executive of the Department of the Minister responsible for the administration of the Landscape South Australia Act 2019. | To provide expert technical assessment and direction to the relevant authority on the taking of water to ensure development is undertaken sustainably. | Development<br>of a class to<br>which<br>Schedule 9<br>clause 3 item<br>13 of the<br>Planning,<br>Development<br>and<br>Infrastructure<br>(General)<br>Regulations<br>2017 applies. |

# **Regulated and Significant Tree Overlay**

**Assessment Provisions (AP)** 

# **Desired Outcome**

Page 17 of 129 Printed on 5/07/2022

DO 1

Conservation of regulated and significant trees to provide aesthetic and environmental benefits and mitigate tree loss.

Performance Outcomes (PO) and Deemed to Satisfy (DTS) / Designated Performance Feature (DPF) Criteria

# **Performance Outcome** Deemed-to-Satisfy Criteria / **Designated Performance Feature** Tree Retention and Health PO 1.1 DTS/DPF 1.1 Regulated trees are retained where they: None are applicable. (a) make an important visual contribution to local character and amenity (b) are indigenous to the local area and listed under the National Parks and Wildlife Act 1972 as a rare or endangered native species and / or (c) provide an important habitat for native fauna. PO 1.2 DTS/DPF 1.2 Significant trees are retained where they: None are applicable. (a) make an important contribution to the character or amenity of the local area (b) are indigenous to the local area and are listed under the National Parks and Wildlife Act 1972 as a rare or endangered native species (c) represent an important habitat for native fauna (d) are part of a wildlife corridor of a remnant area of native vegetation (e) are important to the maintenance of biodiversity in the local environment and / or (f) form a notable visual element to the landscape of the PO 1.3 DTS/DPF 1.3 A tree damaging activity not in connection with other None are applicable. development satisfies (a) and (b): (a) tree damaging activity is only undertaken to: remove a diseased tree where its life expectancy is short mitigate an unacceptable risk to public or private safety due to limb drop or the like rectify or prevent extensive damage to a building of value as comprising any of the followina: A. a Local Heritage Place B. a State Heritage Place C. a substantial building of value

Page 18 of 129 Printed on 5/07/2022

and there is no reasonable alternative to rectify or prevent such damage other than to undertake a tree damaging activity (iv) reduce an unacceptable hazard associated with a tree within 20m of an existing residential, tourist accommodation or other habitable building from bushfire treat disease or otherwise in the general interests of the health of the tree and / or (vi) maintain the aesthetic appearance and structural integrity of the tree (b) in relation to a significant tree, tree-damaging activity is avoided unless all reasonable remedial treatments and measures have been determined to be ineffective. PO 1.4 DTS/DPF 1.4 A tree-damaging activity in connection with other development None are applicable. satisfies all the following: (a) it accommodates the reasonable development of land in accordance with the relevant zone or subzone where such development might not otherwise be possible (b) in the case of a significant tree, all reasonable development options and design solutions have been considered to prevent substantial tree-damaging activity occurring. Ground work affecting trees PO 2.1 DTS/DPF 2.1 Regulated and significant trees, including their root systems, are None are applicable. not unduly compromised by excavation and / or filling of land, or the sealing of surfaces within the vicinity of the tree to support their retention and health. Land Division PO 3.1 DTS/DPF 3.1 Land division results in an allotment configuration that enables Land division where: its subsequent development and the retention of regulated and there are no regulated or significant trees located within significant trees as far as is reasonably practicable. or adjacent to the plan of division (b) the application demonstrates that an area exists to accommodate subsequent development of proposed allotments after an allowance has been made for a tree protection zone around any regulated tree within and adjacent to the plan of division.

### Procedural Matters (PM) - Referrals

The following table identifies classes of development / activities that require referral in this Overlay and the applicable referral body. It sets out the purpose of the referral as well as the relevant statutory reference from Schedule 9 of the Planning, Development and Infrastructure (General) Regulations 2017.

|   | Class of Development / Activity | Referral Body | Purpose of Referral | Statutory<br>Reference |
|---|---------------------------------|---------------|---------------------|------------------------|
| Ī |                                 |               |                     |                        |

Page 19 of 129 Printed on 5/07/2022

| None | None | None | None |
|------|------|------|------|
|      |      |      |      |

## **Stormwater Management Overlay**

## **Assessment Provisions (AP)**

# Development incorporates water sensitive urban design techniques to capture and re-use stormwater.

| Performance Outcome  | Deemed-to-Satisfy Criteria / Designated Performance  |
|--|--|
|  | Feature  |
| PO 1.1   | DTS/DPF 1.1  |
| Residential development is designed to capture and re-use stormwater to:  (a) maximise conservation of water resources (b) manage peak stormwater runoff flows and volume to ensure the carrying capacities of downstream systems are not overloaded (c) manage stormwater runoff quality. | Residential development comprising detached, semi-detached or row dwellings, or less than 5 group dwellings or dwellings within a residential flat building:  (a) includes rainwater tank storage:  (i) connected to at least:  A. in relation to a detached dwelling (not in a battle-axe arrangement), semi-detached dwelling or row dwelling, 60% of the roof area  B. in all other cases, 80% of the roof area  (ii) connected to either a toilet, laundry cold water outlets or hot water service for sites less than 200m²  (iii) connected to one toilet and either the laundry cold water outlets or hot water service for sites of 200m² or greater  (iv) with a minimum total capacity in accordance with Table 1  (v) where detention is required, includes a 20-25 mm diameter slow release orifice at the bottom of the detention component of the tank  (b) incorporates dwelling roof area comprising at least 80% of the site's impervious area  Table 1: Rainwater Tank  Site size Minimum Minimum (m²) retention detention volume (Litres)  (Litres) |
|  | 200-400 2000 Site perviousness <30%: 1000  |

Page 20 of 129 Printed on 5/07/2022

|  |      |      | Site perviousness<br>≥30%: N/A |
|--|------|------|--------------------------------|
|  | >401 | 4000 | Site perviousness              |
|  |      |      | Site perviousness<br>≥35%: N/A |
|  |      | ı    |                                |

### Procedural Matters (PM) - Referrals

The following table identifies classes of development / activities that require referral in this Overlay and the applicable referral body. It sets out the purpose of the referral as well as the relevant statutory reference from Schedule 9 of the Planning, Development and Infrastructure (General) Regulations 2017.

| Class of Development / Activity | Referral Body | Purpose of Referral | Statutory<br>Reference |
|---------------------------------|---------------|---------------------|------------------------|
| None                            | None          | None                | None                   |

## **Urban Tree Canopy Overlay**

**Assessment Provisions (AP)** 

|      | Desired Outcome   |  |  |
|------|---|--|--|
| DO 1 | Residential development preserves and enhances urban tree canopy through the planting of new trees and retention of |  |  |
|      | existing mature trees where practicable.  |  |  |

| Performance Outcome  | Designate                                | -Satisfy Criteria /<br>ed Performance<br>Feature |
|--|--|--|
| PO 1.1   | DTS/DPF 1.1                              |  |
| Trees are planted or retained to contribute to an urban tree canopy. | Tree planting is provided in             | accordance with the following:                   |
|  | Site size per dwelling (m <sup>2</sup> ) | Tree size* and number required per dwelling      |
|  | <450                                     | 1 small tree                                     |
|  | 450-800                                  | 1 medium tree or 2 small trees                   |
|  | >800                                     | 1 large tree or 2 medium trees or 4 small trees  |
|  | *refer Table 1 Tree Size                 |  |
|  | Table 1 Tree Size                        |  |

Page 21 of 129 Printed on 5/07/2022

| Tree size | Mature<br>height<br>(minimum) | Mature<br>spread<br>(minimum) | Soil area around tree<br>within development<br>site (minimum) |
|-----------|-------------------------------|-------------------------------|---|
| Small     | 4 m                           | 2m                            | 10m <sup>2</sup> and min.<br>dimension of 1.5m                |
| Medium    | 6 m                           | 4 m                           | 30m <sup>2</sup> and min.<br>dimension of 2m                  |
| Large     | 12 m                          | 8m                            | 60m <sup>2</sup> and min.<br>dimension of 4m                  |

The discount in Column D of Table 2 discounts the number of trees required to be planted in DTS/DPF 1.1 where existing tree(s) are retained on the subject land that meet the criteria in Columns A, B and C of Table 2, and are not a species identified in Regulation 3F(4)(b) of the Planning Development and Infrastructure (General) Regulations 2017.

| Table 2 Tree Discounts                   |                                       |  |   |
|--|---------------------------------------|--|---|
| Retained<br>tree height<br>(Column<br>A) | Retained tree<br>spread<br>(Column B) | Retained soil<br>area around<br>tree within<br>development<br>site<br>(Column C) | Discount<br>applied<br>(Column D)                         |
| 4-6m                                     | 2-4m                                  | 10m <sup>2</sup> and min.<br>dimension of<br>1.5m                                | 2 small trees (or<br>1 medium tree)                       |
| 6-12m                                    | 4-8m                                  | 30m <sup>2</sup> and min.<br>dimension of<br>3m                                  | 2 medium trees<br>(or 4 small<br>trees)                   |
| >12m                                     | >8m                                   | 60m <sup>2</sup> and min.<br>dimension of<br>6m                                  | 2 large trees (or<br>4 medium trees,<br>or 8 small trees) |

Note: In order to satisfy DTS/DPF 1.1, payment may be made in accordance with a relevant off-set scheme established by the Minister under section 197 of the Planning, Development and Infrastructure Act 2016, provided the provisions and requirements of that scheme are satisfied. For the purposes of section 102(4) of the Planning, Development and Infrastructure Act 2016, an applicant may elect for any of the matters in DTS/DPF 1.1 to be reserved.

Page 22 of 129 Printed on 5/07/2022

## **Procedural Matters (PM) - Referrals**

The following table identifies classes of development / activities that require referral in this Overlay and the applicable referral body. It sets out the purpose of the referral as well as the relevant statutory reference from Schedule 9 of the Planning, Development and Infrastructure (General) Regulations 2017.

| Class of Development / Activity | Referral Body | Purpose of Referral | Statutory<br>Reference |
|---------------------------------|---------------|---------------------|------------------------|
| None                            | None          | None                | None                   |

# Part 4 - General Development Policies

### **Advertisements**

### **Assessment Provisions (AP)**

|      | Desired Outcome  |  |
|------|--|--|
| DO 1 | Advertisements and advertising hoardings are appropriate to context, efficient and effective in communicating with the public, limited in number to avoid clutter, and do not create hazard. |  |

Performance Outcomes (PO) and Deemed-to-Satisfy (DTS) Criteria / Designated Performance Feature (DPF)

| Performance Outcome   | Deemed-to-Satisfy Criteria / Designated Performance Feature  |  |
|---|--|--|
| PO 1.1  | DTS/DPF 1.1  |  |
| Advertisements are compatible and integrated with the design of the building and/or land they are located on. | (a) are not located in a Neighbourhood-type zone (b) where they are flush with a wall:  (i) if located at canopy level, are in the form of a fascia sign  (ii) if located above canopy level:  A. do not have any part rising above parapet height  B. are not attached to the roof of the building  (c) where they are not flush with a wall: |  |

Page 23 of 129 Printed on 5/07/2022

|  | (i) if attached to a verandah, no part of the advertisement protrudes beyond the outer limits of the verandah structure (ii) if attached to a two-storey building:  A. has no part located above the finished floor level of the second storey of the building  B. does not protrude beyond the outer limits of any verandah structure below  C. does not have a sign face that exceeds 1m2 per side.  (d) if located below canopy level, are flush with a wall (e) if located at canopy level, are in the form of a fascia sign if located above a canopy: (i) are flush with a wall (ii) do not have any part rising above parapet height (iii) are not attached to the roof of the building.  (g) if attached to a verandah, no part of the advertisement |
|--|--|
|  | protrudes beyond the outer limits of the verandah structure  (h) if attached to a two-storey building, have no part located above the finished floor level of the second storey of the building  |
|  | (i) where they are flush with a wall, do not, in combination with any other existing sign, cover more than 15% of the building facade to which they are attached.  |
| PO 1.2   | DTS/DPF 1.2  |
| Advertising hoardings do not disfigure the appearance of the land upon which they are situated or the character of the locality. | Where development comprises an advertising hoarding, the supporting structure is:  |
|  | <ul> <li>(a) concealed by the associated advertisement and decorative detailing or</li> <li>(b) not visible from an adjacent public street or thoroughfare, other than a support structure in the form of a single or dual post design.</li> </ul>   |
| PO 1.3   | DTS/DPF 1.3  |
| Advertising does not encroach on public land or the land of an adjacent allotment.   | Advertisements and/or advertising hoardings are contained within the boundaries of the site.   |
| PO 1.4   | DTS/DPF 1.4  |
| Where possible, advertisements on public land are integrated with existing structures and infrastructure.                        | Advertisements on public land that meet at least one of the following:   |
|  | (a) achieves Advertisements DTS/DPF 1.1 (b) are integrated with a bus shelter.   |
| PO 1.5   | DTS/DPF 1.5  |
| Advertisements and/or advertising hoardings are of a scale and size appropriate to the character of the locality.                | None are applicable.   |
| Proliferation of   | Advertisements   |
| 1  | 1  |

Page 24 of 129 Printed on 5/07/2022

| Policy24 - Enquiry  |   |
|---|---|
| PO 2.1  | DTS/DPF 2.1   |
| Proliferation of advertisements is minimised to avoid visual clutter and untidiness.  | No more than one freestanding advertisement is displayed per occupancy.   |
| PO 2.2  | DTS/DPF 2.2   |
| Multiple business or activity advertisements are co-located and coordinated to avoid visual clutter and untidiness.   | Advertising of a multiple business or activity complex is located on a single advertisement fixture or structure.   |
| PO 2.3  | DTS/DPF 2.3   |
| Proliferation of advertisements attached to buildings is minimised to avoid visual clutter and untidiness.  | Advertisements satisfy all of the following:  |
|   | (a) are attached to a building (b) other than in a Neighbourhood-type zone, where they are flush with a wall, cover no more than 15% of the building facade to which they are attached (c) do not result in more than one sign per occupancy that |
|   | is not flush with a wall.   |
| Advertisi   | ng Content  |
| PO 3.1  | DTS/DPF 3.1   |
| Advertisements are limited to information relating to the lawful use of land they are located on to assist in the ready identification of the activity or activities on the land and avoid unrelated content that contributes to visual clutter and untidiness. | Advertisements contain information limited to a lawful existing or proposed activity or activities on the same site as the advertisement.   |
| Amenity   | / Impacts   |
| PO 4.1  | DTS/DPF 4.1   |
| Light spill from advertisement illumination does not unreasonably compromise the amenity of sensitive receivers.  | Advertisements do not incorporate any illumination.   |
| Sa  | fety  |
| PO 5.1  | DTS/DPF 5.1   |
| Advertisements and/or advertising hoardings erected on a verandah or projecting from a building wall are designed and located to allow for safe and convenient pedestrian access.   | Advertisements have a minimum clearance of 2.5m between the top of the footpath and base of the underside of the sign.  |
| PO 5.2  | DTS/DPF 5.2   |
| Advertisements and/or advertising hoardings do not distract or create a hazard to drivers through excessive illumination.   | No advertisement illumination is proposed.  |
| P0 5.3  | DTS/DPF 5.3   |
| Advertisements and/or advertising hoardings do not create a hazard to drivers by:   | Advertisements satisfy all of the following:  |
| (a) being liable to interpretation by drivers as an official traffic sign or signal   | (a) are not located in a public road or rail reserve (b) are located wholly outside the land shown as 'Corner Cut-Off Area' in the following diagram  |

Page 25 of 129 Printed on 5/07/2022

| Policy24 - Enquiry   |   |
|--|---|
| (b) obscuring or impairing drivers' view of official traffic signs or signals (c) obscuring or impairing drivers' view of features of a road that are potentially hazardous (such as junctions, bends, changes in width and traffic control devices) or other road or rail vehicles at/or approaching level crossings. | Corner Cut- Off Area    4.5M   Road Reserve   |
| PO 5.4  Advertisements and/or advertising hoardings do not create a hazard by distracting drivers from the primary driving task at a location where the demands on driver concentration are high.  | DTS/DPF 5.4  Advertisements and/or advertising hoardings are not located along or adjacent to a road having a speed limit of 80km/h or more.  |
| Advertisements and/or advertising hoardings provide sufficient clearance from the road carriageway to allow for safe and convenient movement by all road users.  | Where the advertisement or advertising hoarding is:  (a) on a kerbed road with a speed zone of 60km/h or less, the advertisement or advertising hoarding is located at least 0.6m from the roadside edge of the kerb  (b) on an unkerbed road with a speed zone of 60km/h or less, the advertisement or advertising hoarding is located at least 5.5m from the edge of the seal  (c) on any other kerbed or unkerbed road, the advertisement or advertising hoarding is located a minimum of the following distance from the roadside edge of the kerb or the seal:  (a) 110 km/h road - 14m  (b) 100 km/h road - 13m  (c) 90 km/h road - 10m  (d) 70 or 80 km/h road - 8.5m. |
| PO 5.6 Advertising near signalised intersections does not cause unreasonable distraction to road users through illumination, flashing lights, or moving or changing displays or messages.  | DTS/DPF 5.6  Advertising:  (a) is not illuminated  (b) does not incorporate a moving or changing display or message  (c) does not incorporate a flashing light(s).  |

# **Animal Keeping and Horse Keeping**

## **Assessment Provisions (AP)**

|      | Desired Outcome  |
|------|--|
| DO 1 | Animals are kept at a density that is not beyond the carrying capacity of the land and in a manner that minimises their adverse effects on the environment, local amenity and surrounding development. |

Performance Outcomes (PO) and Deemed-to-Satisfy (DTS) Criteria / Designated Performance Feature (DPF)

Page 26 of 129 Printed on 5/07/2022

| Performance Outcome   | Deemed-to-Satisfy Criteria /<br>Designated Performance<br>Feature   |
|---|---|
| Siting at   | nd Design   |
| PO 1.1  | DTS/DPF 1.1   |
| Animal keeping, horse keeping and associated activities do not create adverse impacts on the environment or the amenity of the locality.  | None are applicable.  |
| P0 1.2  | DTS/DPF 1.2   |
| Animal keeping and horse keeping is located and managed to minimise the potential transmission of disease to other operations where animals are kept.   | None are applicable.  |
| Horse   | Keeping   |
| PO 2.1  | DTS/DPF 2.1   |
| Water from stable wash-down areas is directed to appropriate absorption areas and/or drainage pits to minimise pollution of land and water.   | None are applicable.  |
| P0 2.2  | DTS/DPF 2.2   |
| Stables, horse shelters or associated yards are sited appropriate distances away from sensitive receivers and/or allotments in other ownership to avoid adverse impacts from dust, erosion and odour.                     | Stables, horse shelters and associated yards are sited in accordance with all of the following:  (a) 30m or more from any sensitive receivers (existing or approved) on land in other ownership  (b) where an adjacent allotment is vacant and in other ownership, 30m or more from the boundary of that allotment. |
| PO 2.3  | DTS/DPF 2.3   |
| All areas accessible to horses are separated from septic tank effluent disposal areas to protect the integrity of that system. Stable flooring is constructed with an impervious material to facilitate regular cleaning. | Septic tank effluent disposal areas are enclosed with a horse-<br>proof barrier such as a fence to exclude horses from this area.   |
| PO 2.4  | DTS/DPF 2.4   |
| To minimise environmental harm and adverse impacts on water resources, stables, horse shelters and associated yards are appropriately set back from a watercourse.  | Stables, horse shelters and associated yards are set back 50m or more from a watercourse.   |
| PO 2.5  | DTS/DPF 2.5   |
| Stables, horse shelters and associated yards are located on slopes that are stable to minimise the risk of soil erosion and water runoff.   | Stables, horse shelters and associated yards are not located on land with a slope greater than 10% (1-in-10).   |
| Ker   | nnels   |
| PO 3.1  | DTS/DPF 3.1   |
| Kennel flooring is constructed with an impervious material to facilitate regular cleaning.  | The floors of kennels satisfy all of the following:   |

Page 27 of 129 Printed on 5/07/2022

| 1 Olicy24 - Lilquil y   |  |
|---|--|
|   | (a) are constructed of impervious concrete (b) are designed to be self-draining when washed down.          |
| P0 3.2  | DTS/DPF 3.2  |
| Kennels and exercise yards are designed and sited to minimise noise nuisance to neighbours through measures such as:  | Kennels are sited 500m or more from the nearest sensitive receiver on land in other ownership.             |
| <ul> <li>(a) adopting appropriate separation distances</li> <li>(b) orientating openings away from sensitive receivers.</li> </ul>                                      |  |
| PO 3.3  | DTS/DPF 3.3  |
| Dogs are regularly observed and managed to minimise nuisance impact on adjoining sensitive receivers from animal behaviour.   | Kennels are sited in association with a permanent dwelling on the land.                                    |
| Wa  | stes   |
| PO 4.1  | DTS/DPF 4.1  |
| Storage of manure, used litter and other wastes (other than wastewater lagoons) is designed, constructed and managed to minimise attracting and harbouring vermin.      | None are applicable.   |
| PO 4.2  | DTS/DPF 4.2  |
| Facilities for the storage of manure, used litter and other wastes (other than wastewater lagoons) are located to minimise the potential for polluting water resources. | Waste storage facilities (other than wastewater lagoons) are located outside the 1% AEP flood event areas. |

# Aquaculture

## **Assessment Provisions (AP)**

|      | Desired Outcome   |
|------|---|
| DO 1 | Aquaculture facilities are developed in an ecologically, economically and socially sustainable manner to support an equitable sharing of marine, coastal and inland resources and mitigate conflict with other water-based and land-based uses. |

Performance Outcomes (PO) and Deemed-to-Satisfy (DTS) Criteria / Designated Performance Feature (DPF)

| Performance Outcome  | Deemed-to-Satisfy Criteria / Designated Performance Feature   |
|--|---|
| Land-based   | d Aquaculture   |
| P0 1.1  Land-based aquaculture and associated components are sited and designed to mitigate adverse impacts on nearby sensitive receivers. | DTS/DPF 1.1  Land-based aquaculture and associated components are located to satisfy all of the following:  (a) 200m or more from a sensitive receiver in other |

Page 28 of 129 Printed on 5/07/2022

|  | ownership (b) 500m or more from the boundary of a zone primarily |
|--|--|
|  | intended to accommodate sensitive receivers.                     |
| P0 1.2   | DTS/DPF 1.2  |
| Land-based aquaculture and associated components are sited<br>and designed to prevent surface flows from entering ponds in a<br>1% AEP sea flood level event.  | None are applicable.   |
| PO 1.3   | DTS/DPF 1.3  |
| Land-based aquaculture and associated components are sited and designed to prevent pond leakage that would pollute groundwater.  | None are applicable.   |
| PO 1.4   | DTS/DPF 1.4  |
| Land-based aquaculture and associated components are sited and designed to prevent farmed species escaping and entering into any waters.   | None are applicable.   |
| PO 1.5   | DTS/DPF 1.5  |
| Land-based aquaculture and associated components, including intake and discharge pipes, are designed to minimise the need to traverse sensitive areas to minimise impact on the natural environment. | None are applicable.   |
| PO 1.6   | DTS/DPF 1.6  |
| Pipe inlets and outlets associated with land-based aquaculture are sited and designed to minimise the risk of disease transmission.  | None are applicable.   |
| PO 1.7   | DTS/DPF 1.7  |
| Storage areas associated with aquaculture activity are integrated with the use of the land and sited and designed to minimise their visual impact on the surrounding environment.                    | None are applicable.   |
| Marine Base  | d Aquaculture  |
| PO 2.1   | DTS/DPF 2.1  |
| Marine aquaculture is sited and designed to minimise its adverse impacts on sensitive ecological areas including:  | None are applicable.   |
| <ul> <li>(a) creeks and estuaries</li> <li>(b) wetlands</li> <li>(c) significant seagrass and mangrove communities</li> <li>(d) marine habitats and ecosystems.</li> </ul>                           |  |
| PO 2.2   | DTS/DPF 2.2  |
| Marine aquaculture is sited in areas with adequate water current to disperse sediments and dissolve particulate wastes to prevent the build-up of waste that may cause environmental harm.           | None are applicable.   |
| P0 2.3   | DTS/DPF 2.3  |
| Marine aquaculture is designed to not involve discharge of   | None are applicable.   |

Page 29 of 129 Printed on 5/07/2022

| i Olicy24                | - Eliquily   |  |
|--------------------------|--|--|
| human<br>waters.         | waste on the site, on any adjacent land or into nearby   |  |
| PO 2.4                   |  | DTS/DPF 2.4  |
|                          | aquaculture (other than inter-tidal aquaculture) is located ropriate distance seaward of the high water mark.  | Marine aquaculture development is located 100m or more seaward of the high water mark. |
| PO 2.5                   |  | DTS/DPF 2.5  |
| Marine<br>interfer       | aquaculture is sited and designed to not obstruct or<br>e with:  | None are applicable.   |
| (a)<br>(b)               | areas of high public use<br>areas, including beaches, used for recreational activities<br>such as swimming, fishing, skiing, sailing and other<br>water sports   |  |
| (c)<br>(d)<br>(e)<br>(f) | areas of outstanding visual or environmental value areas of high tourism value areas of important regional or state economic activity, including commercial ports, wharfs and jetties the operation of infrastructure facilities including inlet and outlet pipes associated with the desalination of sea water. |  |
| PO 2.6                   |  | DTS/DPF 2.6  |
| interfer                 | aquaculture is sited and designed to minimise rence and obstruction to the natural processes of the and marine environment.  | None are applicable.   |
| PO 2.7                   |  | DTS/DPF 2.7  |
|                          | aquaculture is designed to be as unobtrusive as able by incorporating measures such as:  | None are applicable.   |
| (a)                      | using feed hoppers painted in subdued colours and suspending them as close as possible to the surface of the water   |  |
| (b)                      | positioning structures to protrude the minimum distance practicable above the surface of the water   |  |
| (c)                      | avoiding the use of shelters and structures above cages and platforms unless necessary to exclude predators and protected species from interacting with the farming structures and/or stock inside the cages, or for safety reasons  |  |
| (d)                      | positioning racks, floats and other farm structures in unobtrusive locations landward from the shoreline.  |  |
| PO 2.8                   |  | DTS/DPF 2.8  |
| establis                 | s, launching and maintenance facilities utilise existing shed roads, tracks, ramps and paths to or from the sea cossible to minimise environmental and amenity impacts.  | None are applicable.   |
| PO 2.9                   |  | DTS/DPF 2.9  |
| commo                    | e, launching and maintenance facilities are developed as<br>on user facilities and are co-located where practicable to<br>e adverse impacts on coastal areas.  | None are applicable.   |
| PO 2.10                  |  | DTS/DPF 2.10   |
|                          |  | •  |

Page 30 of 129 Printed on 5/07/2022

| Folicy24 - Linquity  |   |
|--|---|
| Marine aquaculture is sited to minimise potential impacts on, and to protect the integrity of, reserves under the <i>National Parks and Wildlife Act 1972</i> .  | Marine aquaculture is located 1000m or more seaward of the boundary of any reserve under the <i>National Parks and Wildlife Act</i> 1972. |
| PO 2.11  | DTS/DPF 2.11  |
| Onshore storage, cooling and processing facilities do not impair<br>the coastline and its visual amenity by:   | None are applicable.  |
| (a) being sited, designed, landscaped and of a scale to reduce the overall bulk and appearance of buildings and complement the coastal landscape   |   |
| (b) making provision for appropriately sited and designed vehicular access arrangements, including using existing vehicular access arrangements as far as practicable  |   |
| (c) incorporating appropriate waste treatment and disposal.  |   |
| Navigation   | and Safety  |
| PO 3.1   | DTS/DPF 3.1   |
| Marine aquaculture sites are suitably marked to maintain navigational safety.  | None are applicable.  |
| PO 3.2   | DTS/DPF 3.2   |
| Marine aquaculture is sited to provide adequate separation between farms for safe navigation.  | None are applicable.  |
| Environmenta   | l Management  |
| PO 4.1   | DTS/DPF 4.1   |
| Marine aquaculture is maintained to prevent hazards to people<br>and wildlife, including breeding grounds and habitats of native<br>marine mammals and terrestrial fauna, especially migratory<br>species.                       | None are applicable.  |
| PO 4.2   | DTS/DPF 4.2   |
| Marine aquaculture is designed to facilitate the relocation or removal of structures in the case of emergency such as oil spills, algal blooms and altered water flows.  | None are applicable.  |
| PO 4.3   | DTS/DPF 4.3   |
| Marine aquaculture provides for progressive or future reclamation of disturbed areas ahead of, or upon, decommissioning.   | None are applicable.  |
| PO 4.4   | DTS/DPF 4.4   |
| Aquaculture operations incorporate measures for the removal and disposal of litter, disused material, shells, debris, detritus, dead animals and animal waste to prevent pollution of waters, wetlands, or the nearby coastline. | None are applicable.  |

# **Beverage Production in Rural Areas**

Page 31 of 129 Printed on 5/07/2022

## **Assessment Provisions (AP)**

|      | Desired Outcome  |
|------|--|
| DO 1 | Mitigation of potential amenity and environmental impacts of value-adding beverage production facilities such as wineries, distilleries, cideries and breweries. |

Performance Outcomes (PO) and Deemed-to-Satisfy (DTS) Criteria / Designated Performance Feature (DPF)

| Performance Outcome   | Deemed-to-Satisfy Criteria /<br>Designated Performance<br>Feature  |
|---|--|
| Odour a   | nd Noise   |
| PO 1.1  | DTS/DPF 1.1  |
| Beverage production activities are designed and sited to minimise odour impacts on rural amenity.   | None are applicable.   |
| PO 1.2  | DTS/DPF 1.2  |
| Beverage production activities are designed and sited to minimise noise impacts on sensitive receivers.   | None are applicable.   |
| PO 1.3  | DTS/DPF 1.3  |
| Fermentation, distillation, manufacturing, storage, packaging and bottling activities occur within enclosed buildings to improve the visual appearance within a locality and manage noise associated with these activities. | None are applicable.   |
| PO 1.4  | DTS/DPF 1.4  |
| Breweries are designed to minimise odours emitted during boiling and fermentation stages of production.   | Brew kettles are fitted with a vapour condenser.   |
| PO 1.5  | DTS/DPF 1.5  |
| Beverage production solid wastes are stored in a manner that minimises odour impacts on sensitive receivers in other ownership.   | Solid waste from beverage production is collected and stored in sealed containers and removed from the site within 48 hours. |
| Water Quality   |  |
| PO 2.1  | DTS/DPF 2.1  |
| Beverage production wastewater management systems (including wastewater irrigation) are set back from watercourses to minimise adverse impacts on water resources.  | Wastewater management systems are set back 50m or more from the banks of watercourses and bores.                             |
| PO 2.2  | DTS/DPF 2.2  |
| The storage or disposal of chemicals or hazardous substances is undertaken in a manner to prevent pollution of water resources.   | None are applicable.   |

Page 32 of 129 Printed on 5/07/2022

| Policy24 - Enquiry  |  |  |
|---|--|--|
| PO 2.3  | DTS/DPF 2.3  |  |
| Stormwater runoff from areas that may cause contamination due to beverage production activities (including vehicle movements and machinery operations) is drained to an onsite stormwater treatment system to manage potential environmental impacts.   | None are applicable.   |  |
| PO 2.4  | DTS/DPF 2.4  |  |
| Stormwater runoff from areas unlikely to cause contamination by beverage production and associated activities (such as roof catchments and clean hard-paved surfaces) is diverted away from beverage production areas and wastewater management systems.  | None are applicable.   |  |
| Wastewater Irrigation   |  |  |
| PO 3.1  | DTS/DPF 3.1  |  |
| Beverage production wastewater irrigation systems are designed and located to not contaminate soil and surface and ground water resources or damage crops.  | None are applicable.   |  |
| PO 3.2  | DTS/DPF 3.2  |  |
| Beverage production wastewater irrigation systems are designed and located to minimise impact on amenity and avoid spray drift onto adjoining land.   | Beverage production wastewater is not irrigated within 50m of any dwelling in other ownership. |  |
| P0 3.3  | DTS/DPF 3.3  |  |
| Beverage production wastewater is not irrigated onto areas that pose an undue risk to the environment or amenity such as:  (a) waterlogged areas (b) land within 50m of a creek, swamp or domestic or stock water bore (c) land subject to flooding (d) steeply sloping land (e) rocky or highly permeable soil overlaying an unconfined aquifer. | None are applicable.   |  |

# **Bulk Handling and Storage Facilities**

## **Assessment Provisions (AP)**

| Desired Outcome |   |
|-----------------|---|
| DO 1            | Facilities for the bulk handling and storage of agricultural, mineral, petroleum, rock, ore or other similar commodities are designed to minimise adverse impacts on transport networks, the landscape and surrounding land uses. |

Performance Outcomes (PO) and Deemed-to-Satisfy (DTS) Criteria / Designated Performance Feature (DPF)

Page 33 of 129 Printed on 5/07/2022

## **Performance Outcome**

# Deemed-to-Satisfy Criteria / Designated Performance Feature

Siting and Design

PO 1.1

Bulk handling and storage facilities are sited and designed to minimise risks of adverse air quality and noise impacts on sensitive receivers. DTS/DPF 1.1

Facilities for the handling, storage and dispatch of commodities in bulk (excluding processing) meet the following minimum separation distances from sensitive receivers:

- (a) bulk handling of agricultural crop products, rock, ores, minerals, petroleum products or chemicals at a wharf or wharf side facility (including sea-port grain terminals), where the handling of these materials into or from vessels does not exceed 100 tonnes per day: 300m or more from residential premises not associated with the facility
- (b) bulk handling of agricultural crop products, rock, ores, minerals, petroleum products or chemicals to or from any commercial storage facility: 300m or more from residential premises not associated with the facility
- (c) bulk petroleum storage involving individual containers with a capacity up to 200 litres and a total on-site storage capacity not exceeding 1,000 cubic metres: 500m or more
- (d) coal handling with:

   a. capacity up to 1 tonne per day or a storage capacity up to 50 tonnes: 500m or more
   b. capacity exceeding 1 tonne per day but not exceeding 100 tonnes per day or a storage capacity exceeding 50 tonnes but not exceeding 5000 tonnes: 1000m or more.

**Buffers and Landscaping** 

PO 2.1

DTS/DPF 2.1

Bulk handling and storage facilities incorporate a buffer area for the establishment of dense landscaping adjacent road frontages to enhance the appearance of land and buildings from public thoroughfares. None are applicable.

PO 2.2

DTS/DPF 2.2

Bulk handling and storage facilities incorporate landscaping to assist with screening and dust filtration.

None are applicable.

Access and Parking

PO 3.1

DTS/DPF 3.1

Roadways and vehicle parking areas associated with bulk handling and storage facilities are designed and surfaced to control dust emissions and prevent drag out of material from the site.

Roadways and vehicle parking areas are sealed with an allweather surface.

Slipways, Wharves and Pontoons

PO 4.1

DTS/DPF 4.1

Slipways, wharves and pontoons used for the handling of bulk materials (such as fuel, oil, catch, bait and the like) incorporate None are applicable.

Page 34 of 129 Printed on 5/07/2022

| catchment devices to avoid the release of materials into adjacent |  |
|---|--|
| waters.   |  |
|   |  |

## **Clearance from Overhead Powerlines**

## **Assessment Provisions (AP)**

| Desired Outcome |   |
|-----------------|---|
| DO 1            | Protection of human health and safety when undertaking development in the vicinity of overhead transmission powerlines. |

| Performance Outcome   | Deemed-to-Satisfy Criteria /<br>Designated Performance<br>Feature   |
|---|---|
| PO 1.1  Buildings are adequately separated from aboveground powerlines to minimise potential hazard to people and property. | One of the following is satisfied:  (a) a declaration is provided by or on behalf of the applicant to the effect that the proposal would not be contrary to the regulations prescribed for the purposes of section 86 of the Electricity Act 1996  (b) there are no aboveground powerlines adjoining the site that are the subject of the proposed development. |

## Design

## **Assessment Provisions (AP)**

|      | Desired Outcome |   |  |
|------|-----------------|---|--|
| DO 1 | Develo          | opment is:  |  |
|      | (a)<br>(b)      | contextual - by considering, recognising and carefully responding to its natural surroundings or built environment and positively contributes to the character of the immediate area durable - fit for purpose, adaptable and long lasting  |  |
|      | (c)             | inclusive - by integrating landscape design to optimise pedestrian and cyclist usability, privacy and equitable access, and promoting the provision of quality spaces integrated with the public realm that can be used for access and recreation and help optimise security and safety both internally and within the public realm, for occupants and visitors |  |
|      | (d)             | sustainable - by integrating sustainable techniques into the design and siting of development and landscaping to improve community health, urban heat, water management, environmental performance, biodiversity and local amenity and to minimise energy consumption.  |  |

Page 35 of 129 Printed on 5/07/2022

# **Performance Outcome**

# Deemed-to-Satisfy Criteria / Designated Performance Feature

All development

| All development   |  |  |
|---|--|--|
| External Appearance   |  |  |
| PO 1.1  | DTS/DPF 1.1  |  |
| Buildings reinforce corners through changes in setback, articulation, materials, colour and massing (including height, width, bulk, roof form and slope).   | None are applicable.   |  |
| PO 1.2  | DTS/DPF 1.2  |  |
| Where zero or minor setbacks are desirable, development provides shelter over footpaths (in the form of verandahs, awnings, canopies and the like, with adequate lighting) to positively contribute to the walkability, comfort and safety of the public realm.   | None are applicable.   |  |
| PO 1.3  | DTS/DPF 1.3  |  |
| Building elevations facing the primary street (other than ancillary buildings) are designed and detailed to convey purpose, identify main access points and complement the streetscape.   | None are applicable.   |  |
| PO 1.4  | DTS/DPF 1.4  |  |
| Plant, exhaust and intake vents and other technical equipment is integrated into the building design to minimise visibility from the public realm and negative impacts on residential amenity by:   | Development does not incorporate any structures that protrude beyond the roofline. |  |
| <ul> <li>(a) positioning plant and equipment in unobtrusive locations viewed from public roads and spaces</li> <li>(b) screening rooftop plant and equipment from view</li> <li>(c) when located on the roof of non-residential development, locating the plant and equipment as far as practicable from adjacent sensitive land uses.</li> </ul> |  |  |
| PO 1.5  | DTS/DPF 1.5  |  |
| The negative visual impact of outdoor storage, waste management, loading and service areas is minimised by integrating them into the building design and screening them from public view (such as fencing, landscaping and built form) taking into account the form of development contemplated in the relevant zone.                             | None are applicable.   |  |
| Sa  | fety   |  |
| PO 2.1  | DTS/DPF 2.1  |  |
| Development maximises opportunities for passive surveillance of<br>the public realm by providing clear lines of sight, appropriate<br>lighting and the use of visually permeable screening wherever<br>practicable.   | None are applicable.   |  |
| PO 2.2  | DTS/DPF 2.2  |  |

Page 36 of 129 Printed on 5/07/2022

None are applicable.

Development is designed to differentiate public, communal and

| , , ,   |                      |
|---|----------------------|
| private areas.  |                      |
| PO 2.3  | DTS/DPF 2.3          |
| Buildings are designed with safe, perceptible and direct access from public street frontages and vehicle parking areas.   | None are applicable. |
| PO 2.4  | DTS/DPF 2.4          |
| Development at street level is designed to maximise opportunities for passive surveillance of the adjacent public realm.  | None are applicable. |
| PO 2.5  | DTS/DPF 2.5          |
| Common areas and entry points of buildings (such as the foyer areas of residential buildings), and non-residential land uses at street level, maximise passive surveillance from the public realm to the inside of the building at night.                   | None are applicable. |
| Lands   | caping               |
| PO 3.1  | DTS/DPF 3.1          |
| Soft landscaping and tree planting is incorporated to:  | None are applicable. |
| <ul> <li>(a) minimise heat absorption and reflection</li> <li>(b) maximise shade and shelter</li> <li>(c) maximise stormwater infiltration</li> <li>(d) enhance the appearance of land and streetscapes</li> <li>(e) contribute to biodiversity.</li> </ul> |                      |
| PO 3.2  | DTS/DPF 3.2          |
| Soft landscaping and tree planting maximises the use of locally indigenous plant species, incorporates plant species best suited to current and future climate conditions and avoids pest plant and weed species.   | None are applicable. |
| Environmenta  | I Performance        |
| PO 4.1  | DTS/DPF 4.1          |
| Buildings are sited, oriented and designed to maximise natural sunlight access and ventilation to main activity areas, habitable rooms, common areas and open spaces.   | None are applicable. |
| PO 4.2  | DTS/DPF 4.2          |
| Buildings are sited and designed to maximise passive environmental performance and minimise energy consumption and reliance on mechanical systems, such as heating and cooling.   | None are applicable. |
| PO 4.3  | DTS/DPF 4.3          |
| Buildings incorporate climate-responsive techniques and features such as building and window orientation, use of eaves, verandahs and shading structures, water harvesting, at ground landscaping, green walls, green roofs and photovoltaic cells.         | None are applicable. |
| Water Sens  | itive Design         |
|   |                      |

Page 37 of 129 Printed on 5/07/2022

PO 5.1 DTS/DPF 5.1 Development is sited and designed to maintain natural None are applicable. hydrological systems without negatively impacting: (a) the quantity and quality of surface water and groundwater (b) the depth and directional flow of surface water and aroundwater (c) the quality and function of natural springs. On-site Waste Treatment Systems PO 6.1 DTS/DPF 6.1 Dedicated on-site effluent disposal areas do not include any Effluent disposal drainage areas do not: areas to be used for, or could be reasonably foreseen to be used encroach within an area used as private open space or for, private open space, driveways or car parking. result in less private open space than that specified in Design Table 1 - Private Open Space (b) use an area also used as a driveway (c) encroach within an area used for on-site car parking or result in less on-site car parking than that specified in Transport, Access and Parking Table 1 - General Off-Street Car Parking Requirements or Table 2 - Off-Street Car Parking Requirements in Designated Areas. Carparking Appearance PO 7.1 DTS/DPF 7.1 Development facing the street is designed to minimise the None are applicable. negative impacts of any semi-basement and undercroft car parking on the streetscapes through techniques such as: (a) limiting protrusion above finished ground level (b) screening through appropriate planting, fencing and mounding (c) limiting the width of openings and integrating them into the building structure. PO 7.2 DTS/DPF 7.2 Vehicle parking areas are appropriately located, designed and None are applicable. constructed to minimise impacts on adjacent sensitive receivers through measures such as ensuring they are attractively developed and landscaped, screen fenced and the like. PO 7.3 DTS/DPF 7.3 Safe, legible, direct and accessible pedestrian connections are None are applicable. provided between parking areas and the development. PO 7.4 DTS/DPF 7.4 Street level vehicle parking areas incorporate tree planting to None are applicable. provide shade and reduce solar heat absorption and reflection. PO 7.5 DTS/DPF 7.5 Street level parking areas incorporate soft landscaping to None are applicable. improve visual appearance when viewed from within the site and from public places.

Page 38 of 129 Printed on 5/07/2022

| 1  |
|--|
| DTS/DPF 7.6  |
| None are applicable.   |
| DTS/DPF 7.7  |
| None are applicable.   |
| and sloping land   |
| DTS/DPF 8.1  |
| Development does not involve any of the following:  (a) excavation exceeding a vertical height of 1m  (b) filling exceeding a vertical height of 1m  |
| (c) a total combined excavation and filling vertical height of 2m or more.   |
| DTS/DPF 8.2  |
| Driveways and access tracks on sloping land (with a gradient exceeding 1 in 8) satisfy (a) and (b):  (a) do not have a gradient exceeding 25% (1-in-4) at any point along the driveway  (b) are constructed with an all-weather trafficable surface. |
| DTS/DPF 8.3  |
| None are applicable.   |
|  |
|  |
| DTS/DPF 8.4  |
| None are applicable.   |
| DTS/DPF 8.5  |
| None are applicable.   |
| s and Walls  |
| DTS/DPF 9.1  |
| None are applicable.   |
|  |

Page 39 of 129 Printed on 5/07/2022

| 1 Olicy24 - Litquiry   |  |
|--|--|
| amenity of public places.  |  |
| PO 9.2   | DTS/DPF 9.2  |
| Landscaping incorporated on the low side of retaining walls is visible from public roads and public open space to minimise visual impacts.           | A vegetated landscaped strip 1m wide or more is provided against the low side of a retaining wall.   |
| Overlooking / Visual Privacy   | (in building 3 storeys or less)  |
| PO 10.1  | DTS/DPF 10.1   |
| Development mitigates direct overlooking from upper level windows to habitable rooms and private open spaces of adjoining residential uses.          | Upper level windows facing side or rear boundaries shared with a residential allotment/site satisfy one of the following:  (a) are permanently obscured to a height of 1.5m above finished floor level and are fixed or not capable of being |
|  | opened more than 200mm   |
|  | (b) have sill heights greater than or equal to 1.5m above finished floor level   |
|  | (c) incorporate screening with a maximum of 25% openings, permanently fixed no more than 500mm from the window surface and sited adjacent to any part of the window less than 1.5 m above the finished floor level.                          |
| PO 10.2  | DTS/DPF 10.2   |
| Development mitigates direct overlooking from balconies, terraces and decks to habitable rooms and private open space of adjoining residential uses. | One of the following is satisfied:   |
|  | (a) the longest side of the balcony or terrace will face a public road, public road reserve or public reserve that is at least 15m wide in all places faced by the balcony or terrace  |
|  | (b) all sides of balconies or terraces on upper building levels are permanently obscured by screening with a maximum 25% transparency/openings fixed to a minimum height of:   |
|  | (i) 1.5m above finished floor level where the balcony is located at least 15 metres from the nearest habitable window of a dwelling on adjacent land or  |
|  | (ii) 1.7m above finished floor level in all other cases  |
| All Residentia   | I<br>I development   |
| Front elevations and   | passive surveillance   |
| PO 11.1  | DTS/DPF 11.1   |
| Dwellings incorporate windows along primary street frontages to encourage passive surveillance and make a positive contribution                      | Each dwelling with a frontage to a public street:  |

| All Nesidential development   |  |
|---|--|
| Front elevations and passive surveillance   |  |
| PO 11.1   | DTS/DPF 11.1   |
| Dwellings incorporate windows along primary street frontages to encourage passive surveillance and make a positive contribution to the streetscape. | <ul> <li>(a) includes at least one window facing the primary street from a habitable room that has a minimum internal room dimension of 2.4m</li> <li>(b) has an aggregate window area of at least 2m² facing the primary street.</li> </ul> |
| PO 11.2   | DTS/DPF 11.2   |
| Dwellings incorporate entry doors within street frontages to  | Dwellings with a frontage to a public street have an entry door  |
| 7 10 · f 100  | Drintad on E/07/2022   |

Page 40 of 129 Printed on 5/07/2022

| Policy24 - Enquiry  | .:-::::::::::::::::::::::::::::::::::::   |
|---|---|
| address the street and provide a legible entry point for visitors.  | visible from the primary street boundary.   |
| Outlook a   | nd amenity  |
| P0 12.1   | DTS/DPF 12.1  |
| Living rooms have an external outlook to provide a high standard of amenity for occupants.  | A living room of a dwelling incorporates a window with an outlook towards the street frontage or private open space, public open space, or waterfront areas.  |
| PO 12.2   | DTS/DPF 12.2  |
| Bedrooms are separated or shielded from active communal recreation areas, common access areas and vehicle parking areas and access ways to mitigate noise and artificial light intrusion. | None are applicable.  |
| Ancillary D   | evelopment  |
| Residential ancillary buildings and structures are sited and designed to not detract from the streetscape or appearance of buildings on the site or neighbouring properties.              | DTS/DPF 13.1  Ancillary buildings:  (a) are ancillary to a dwelling erected on the same site (b) have a floor area not exceeding 60m2 (c) are not constructed, added to or altered so that any part is situated:  (i) in front of any part of the building line of the dwelling to which it is ancillary  or  (ii) within 900mm of a boundary of the allotment with a secondary street (if the land has boundaries on two or more roads)  (d) in the case of a garage or carport, the garage or carport:  (i) is set back at least 5.5m from the boundary of the primary street  (ii) when facing a primary street or secondary street, has a total door / opening not exceeding:  A. for dwellings of single building level - 7m in width or 50% of the site frontage, whichever is the lesser  B. for dwellings comprising two or more building levels at the building line fronting the same public street - 7m in width |

(e) if situated on a boundary (not being a boundary with a primary street or secondary street), do not exceed a length of 11.5m unless:

- a longer wall or structure exists on the adjacent site and is situated on the same allotment boundary and
- (ii) the proposed wall or structure will be built along the same length of boundary as the existing adjacent wall or structure to the same or lesser extent

(f) if situated on a boundary of the allotment (not being a boundary with a primary street or secondary street), all walls or structures on the boundary will not exceed 45% of the length of that boundary

Page 41 of 129 Printed on 5/07/2022

- (g) will not be located within 3m of any other wall along the same boundary unless on an adjacent site on that boundary there is an existing wall of a building that would be adjacent to or about the proposed wall or structure
- (h) have a wall height or post height not exceeding 3m above natural ground level (and not including a gable end)
- (i) have a roof height where no part of the roof is more than 5m above the natural ground level
- (j) if clad in sheet metal, is pre-colour treated or painted in a non-reflective colour
- (k) retains a total area of soft landscaping in accordance with (i) or (ii), whichever is less:
  - (i) a total area as determined by the following

| Dwelling site area (or in the case of residential flat building or group dwelling(s), average site area) (m <sup>2</sup> ) | Minimum<br>percentage of<br>site |
|--|----------------------------------|
| <150   | 10%                              |
| 150-200  | 15%                              |
| 201-450  | 20%                              |
| >450   | 25%                              |

(ii) the amount of existing soft landscaping prior to the development occurring.

### PO 13.2

Ancillary buildings and structures do not impede on-site functional requirements such as private open space provision or car parking requirements and do not result in over-development of the site.

### DTS/DPF 13.2

Ancillary buildings and structures do not result in:

- (a) less private open space than specified in Design in Urban Areas Table 1 Private Open Space
- (b) less on-site car parking than specified in Transport, Access and Parking Table 1 - General Off-Street Car Parking Requirements or Table 2 - Off-Street Car Parking Requirements in Designated Areas.

#### PO 13.3

Fixed plant and equipment in the form of pumps and/or filtration systems for a swimming pool or spa is positioned and/or housed to not cause unreasonable noise nuisance to adjacent sensitive receivers.

#### DTS/DPF 13.3

The pump and/or filtration system is ancillary to a dwelling erected on the same site and is:

- enclosed in a solid acoustic structure that is located at least 5m from the nearest habitable room located on an adjoining allotment or
- (b) located at least 12m from the nearest habitable room located on an adjoining allotment.

### Garage appearance

PO 14.1 DTS/DPF 14.1

Page 42 of 129 Printed on 5/07/2022

Garaging is designed to not detract from the streetscape or appearance of a dwelling.

Garages and carports facing a street:

- (a) are situated so that no part of the garage or carport is in front of any part of the building line of the dwelling
- (b) are set back at least 5.5m from the boundary of the primary street
- (c) have a garage door / opening not exceeding 7m in width
- (d) have a garage door /opening width not exceeding 50% of the site frontage unless the dwelling has two or more building levels at the building line fronting the same public street.

### Massing

PO 15.1

The visual mass of larger buildings is reduced when viewed from adjoining allotments or public streets.

DTS/DPF 15.1

None are applicable

#### **Dwelling additions**

PO 16.1

Dwelling additions are sited and designed to not detract from the streetscape or amenity of adjoining properties and do not impede on-site functional requirements.

DTS / DPF 16.1

Dwelling additions:

- (a) are not constructed, added to or altered so that any part is situated closer to a public street
- (b) do not result in:
  - (i) excavation exceeding a vertical height of 1m
  - (ii) filling exceeding a vertical height of 1m
  - (iii) a total combined excavation and filling vertical height of 2m or more
  - (iv) less Private Open Space than specified in Design Table 1 Private Open Space
  - (v) less on-site parking than specified in Transport Access and Parking Table 1 - General Off-Street Car Parking Requirements or Table 2 - Off-Street Car Parking Requirements in Designated Areas
  - (vi) upper level windows facing side or rear boundaries unless:
    - A. they are permanently obscured to a height of 1.5m above finished floor level that is fixed or not capable of being opened more than 200mm or
    - B. have sill heights greater than or equal to 1.5m above finished floor level or
    - C. incorporate screening to a height of 1.5m above finished floor level
  - (vii) all sides of balconies or terraces on upper building levels are permanently obscured by screening with a maximum 25% transparency/openings fixed to a minimum height of:
    - A. 1.5m above finished floor level where the balcony is located at least 15 metres from the nearest habitable window of a dwelling on adjacent land
    - B. 1.7m above finished floor level in all other cases.

Page 43 of 129 Printed on 5/07/2022

| Private 0  | pen Space   |
|--|---|
| P0 17.1  | DTS/DPF 17.1  |
| Dwellings are provided with suitable sized areas of usable private open space to meet the needs of occupants.  | Private open space is provided in accordance with Design Table 1 - Private Open Space.  |
| Water Sens   | itive Design  |
| PO 18.1  | DTS/DPF 18.1  |
| Residential development creating a common driveway / access includes stormwater management systems that minimise the discharge of sediment, suspended solids, organic matter, nutrients, bacteria, litter and other contaminants to the stormwater system, watercourses or other water bodies.     | Residential development creating a common driveway / access that services 5 or more dwellings achieves the following stormwater runoff outcomes:  (a) 80 per cent reduction in average annual total suspended solids (b) 60 per cent reduction in average annual total phosphorus (c) 45 per cent reduction in average annual total nitrogen.   |
| PO 18.2  | DTS/DPF 18.2  |
| Residential development creating a common driveway / access includes a stormwater management system designed to mitigate peak flows and manage the rate and duration of stormwater discharges from the site to ensure that the development does not increase the peak flows in downstream systems. | Development creating a common driveway / access that services 5 or more dwellings:  (a) maintains the pre-development peak flow rate from the site based upon a 0.35 runoff coefficient for the 18.1% AEP 30-minute storm and the stormwater runoff time to peak is not increased or captures and retains the difference in pre-development runoff volume (based upon a 0.35 runoff coefficient) vs post development runoff volume from the site for an 18.1% AEP 30-minute storm; and  (b) manages site generated stormwater runoff up to and including the 1% AEP flood event to avoid flooding of buildings. |
| Car parking, access  | and manoeuvrability   |
| Po 19.1  Enclosed parking spaces are of a size and dimensions to be functional, accessible and convenient.   | Residential car parking spaces enclosed by fencing, walls or other structures have the following internal dimensions (separate from any waste storage area):  (a) single width car parking spaces: (i) a minimum length of 5.4m per space (ii) a minimum width of 3.0m (iii) a minimum garage door width of 2.4m  (b) double width car parking spaces (side by side): (i) a minimum length of 5.4m (ii) a minimum width of 5.4m (iii) minimum garage door width of 2.4m per space.  |
| PO 19.2  | DTS/DPF 19.2  |

Page 44 of 129 Printed on 5/07/2022

| Policy24 - Enquiry   |  |
|--|--|
| Uncovered parking spaces are of a size and dimensions to be functional, accessible and convenient.   | Uncovered car parking spaces have:  (a) a minimum length of 5.4m   |
|  | (b) a minimum width of 2.4m  |
|  | (c) a minimum width between the centre line of the space   |
|  | and any fence, wall or other obstruction of 1.5m   |
| PO 19.3  | DTS/DPF 19.3   |
| Driveways are located and designed to facilitate safe access and egress while maximising land available for street tree planting, landscaped street frontages, domestic waste collection and onstreet parking. | Driveways and access points on sites with a frontage to a public road of 10m or less have a width between 3.0 and 3.2 metres measured at the property boundary and are the only access point provided on the site.       |
| PO 19.4  | DTS/DPF 19.4   |
| Vehicle access is safe, convenient, minimises interruption to the  | Vehicle access to designated car parking spaces satisfy (a) or   |
| operation of public roads and does not interfere with street infrastructure or street trees.   | (b):   |
|  | (a) is provided via a lawfully existing or authorised access point or an access point for which consent has been granted as part of an application for the division of land  |
|  | (b) where newly proposed:  |
|  | (i) is set back 6m or more from the tangent point  |
|  | of an intersection of 2 or more roads  |
|  | (ii) is set back outside of the marked lines or infrastructure dedicating a pedestrian crossing  |
|  | (iii) does not involve the removal, relocation or  |
|  | damage to of mature street trees, street furniture or utility infrastructure services.   |
| PO 19.5  | DTS/DPF 19.5   |
| Driveways are designed to enable safe and convenient vehicle movements from the public road to on-site parking spaces.   | Driveways are designed and sited so that:  |
| movemento nom the public road to on one parking opaces.  | (a) the gradient from the place of access on the boundary of the allotment to the finished floor level at the front of the garage or carport is not steeper than 1:4 on average  |
|  | (b) they are aligned relative to the street boundary so that there is no more than a 20 degree deviation from 90 degrees between the centreline of any dedicated car parking space to which it provides access (measured |
|  | from the front of that space) and the street boundary  |
|  | (c) if located to provide access from an alley, lane or right of way - the alley, land or right or way is at least 6.2m wide along the boundary of the allotment / site  |
| P0 19.6  | DTS/DPF 19.6   |
| Driveways and access points are designed and distributed to  | Where on-street parking is available abutting the site's street  |
| optimise the provision of on-street visitor parking.   | frontage, on-street parking is retained in accordance with the following requirements:   |
|  | (a) minimum 0.33 on-street spaces per dwelling on the site (rounded up to the nearest whole number)  |
|  | (b) minimum car park length of 5.4m where a vehicle can enter or exit a space directly   |
|  | (c) minimum carpark length of 6m for an intermediate space located between two other parking spaces or to  |

Page 45 of 129 Printed on 5/07/2022

an end obstruction where the parking is indented.

|  | 1   |   |
|--|---|---|
| Waste  | storage                                       |   |
| PO 20.1  | DTS/DPF 20.1                                  |   |
| Provision is made for the adequate and convenient storage of waste bins in a location screened from public view.   | None are applicable.                          |   |
| Design of Transp   | oortable Dwellings                            |   |
| PO 21.1  | DTS/DPF 21.1                                  |   |
| The sub-floor space beneath transportable buildings is enclosed to give the appearance of a permanent structure.   |   | ween the building and ground<br>al and finish consistent with the   |
| Group dwelling, residential flat bu  | ldings and battle-axe development             |   |
|  | enity   |   |
| PO 22.1  | DTS/DPF 22.1                                  |   |
| Dwellings are of a suitable size to accommodate a layout that is well organised and provides a high standard of amenity for occupants.                   |   | nal floor area in accordance with   |
|  | Number of bedrooms                            | Minimum internal floor area   |
|  | Studio  | 35m <sup>2</sup>  |
|  | 1 bedroom                                     | 50m <sup>2</sup>  |
|  | 2 bedroom                                     | 65m <sup>2</sup>  |
|  | 3+ bedrooms                                   | 80m <sup>2</sup> and any dwelling over 3<br>bedrooms provides an<br>additional 15m <sup>2</sup> for every<br>additional bedroom |
| PO 22.2  | DTS/DPF 22.2                                  |   |
| The orientation and siting of buildings minimises impacts on the amenity, outlook and privacy of occupants and neighbours.                               | None are applicable.                          |   |
| PO 22.3  | DTS/DPF 22.3                                  |   |
| Development maximises the number of dwellings that face public open space and public streets and limits dwellings oriented towards adjoining properties. | None are applicable.                          |   |
| P0 22.4  | DTS/DPF 22.4                                  |   |
| Battle-axe development is appropriately sited and designed to respond to the existing neighbourhood context.   | Dwelling sites/allotments are no arrangement. | ot in the form of a battle-axe  |
| Communal   | Open Space                                    |   |

Page 46 of 129 Printed on 5/07/2022

| Policy24 - Enquiry   |  |
|--|--|
| P0 23.1  | DTS/DPF 23.1   |
| Private open space provision may be substituted for communal open space which is designed and sited to meet the recreation and amenity needs of residents.   | None are applicable.   |
| P0 23.2  | DTS/DPF 23.2   |
| Communal open space is of sufficient size and dimensions to cater for group recreation.  | Communal open space incorporates a minimum dimension of 5 metres.  |
| PO 23.3  | DTS/DPF 23.3   |
| Communal open space is designed and sited to:  | None are applicable.   |
| (a) be conveniently accessed by the dwellings which it services  |  |
| (b) have regard to acoustic, safety, security and wind effects.  |  |
| P0 23.4  | DTS/DPF 23.4   |
| Communal open space contains landscaping and facilities that are functional, attractive and encourage recreational use.  | None are applicable.   |
| PO 23.5  | DTS/DPF 23.5   |
| Communal open space is designed and sited to:  | None are applicable.   |
| <ul> <li>in relation to rooftop or elevated gardens, minimise overlooking into habitable room windows or onto the useable private open space of other dwellings</li> <li>in relation to ground floor communal space, be overlooked by habitable rooms to facilitate passive surveillance.</li> </ul> |  |
| Carparking, access   | and manoeuvrability  |
| PO 24.1  | DTS/DPF 24.1   |
| Driveways and access points are designed and distributed to optimise the provision of on-street visitor parking.   | Where on-street parking is available directly adjacent the site, on-<br>street parking is retained adjacent the subject site in accordance<br>with the following requirements:               |
|  | (a) minimum 0.33 on-street car parks per proposed dwellings (rounded up to the nearest whole number)  (b) minimum car park length of 5.4m where a vehicle can enter or exit a space directly |
|  | (c) minimum carpark length of 6m for an intermediate space located between two other parking spaces or to an end obstruction where the parking is indented.                                  |
| PO 24.2  | DTS/DPF 24.2   |
| The number of vehicular access points onto public roads is minimised to reduce interruption of the footpath and positively contribute to public safety and walkability.  | Access to group dwellings or dwellings within a residential flat building is provided via a single common driveway.  |
| PO 24.3  | DTS/DPF 24.3   |
| Residential driveways that service more than one dwelling are designed to allow safe and convenient movement.  | Driveways that service more than 1 dwelling or a dwelling on a battle-axe site:  |
|  | (a) have a minimum width of 3m   |

Page 47 of 129 Printed on 5/07/2022

|  | (b) for driveways servicing more than 3 dwellings:  (i) have a width of 5.5m or more and a length of 6m or more at the kerb of the primary street  (ii) where the driveway length exceeds 30m, incorporate a passing point at least every 30 metres with a minimum width of 5.5m and a minimum length of 6m. |
|--|--|
| PO 24.4  | DTS/DPF 24.4   |
| Residential driveways in a battle-axe configuration are designed to allow safe and convenient movement.  | Where in a battle-axe configuration, a driveway servicing one dwelling has a minimum width of 3m.  |
| PO 24.5  | DTS/DPF 24.5   |
| Residential driveways that service more than one dwelling are designed to allow passenger vehicles to enter and exit the site and manoeuvre within the site in a safe and convenient manner. | Driveways providing access to more than one dwelling, or a dwelling on a battle-axe site, allow a B85 passenger vehicle to enter and exit the garages or parking spaces in no more than a three-point turn manoeuvre.  |
| PO 24.6  | DTS/DPF 24.6   |
| Dwellings are adequately separated from common driveways and manoeuvring areas.  | Dwelling walls with entry doors or ground level habitable room windows are set back at least 1.5m from any driveway or area designated for the movement and manoeuvring of vehicles.   |
| Soft Lar   | ndscaping  |
| PO 25.1  | DTS/DPF 25.1   |
| Soft landscaping is provided between dwellings and common driveways to improve the outlook for occupants and appearance of common areas.   | Other than where located directly in front of a garage or a building entry, soft landscaping with a minimum dimension of 1m is provided between a dwelling and common driveway.  |
| PO 25.2  | DTS/DPF 25.2   |
| Soft landscaping is provided that improves the appearance of common driveways.   | Where a common driveway is located directly adjacent the side or rear boundary of the site, soft landscaping with a minimum dimension of 1m is provided between the driveway and site boundary (excluding along the perimeter of a passing point).   |
| Site Facilities  | / Waste Storage  |
| PO 26.1  | DTS/DPF 26.1   |
| Provision is made for suitable mailbox facilities close to the major pedestrian entry to the site or conveniently located considering the nature of accommodation and mobility of occupants. | None are applicable.   |
| PO 26.2  | DTS/DPF 26.2   |
| Provision is made for suitable external clothes drying facilities.   | None are applicable.   |
| P0 26.3  | DTS/DPF 26.3   |
| Provision is made for suitable household waste and recyclable material storage facilities which are:   | None are applicable.   |
| located away, or screened, from public view, and     conveniently located in proximity to dwellings and the waste collection point.  |  |
| PO 26.4  | DTS/DPF 26.4   |

Page 48 of 129 Printed on 5/07/2022

| Waste and recyclable material storage areas are located away from dwellings.   | Dedicated waste and recyclable material storage areas are located at least 3m from any habitable room window. |
|--|---|
| PO 26.5  | DTS/DPF 26.5  |
| Where waste bins cannot be conveniently collected from the street, provision is made for on-site waste collection, designed to accommodate the safe and convenient access, egress and movement of waste collection vehicles.   | None are applicable.  |
| PO 26.6  | DTS/DPF 26.6  |
| Services including gas and water meters are conveniently located and screened from public view.  | None are applicable.  |
| Supported accommodation  | on and retirement facilities  |
| Siting and C   | configuration   |
| PO 27.1  | DTS/DPF 27.1  |
| Supported accommodation and housing for aged persons and people with disabilities is located where on-site movement of residents is not unduly restricted by the slope of the land.  | None are applicable.  |
| Movement   | and Access  |
| PO 28.1  | DTS/DPF 28.1  |
| Development is designed to support safe and convenient access and movement for residents by providing:   | None are applicable.  |
| <ul> <li>(a) ground-level access or lifted access to all units</li> <li>(b) level entry porches, ramps, paths, driveways, passenger loading areas and areas adjacent to footpaths that allow for the passing of wheelchairs and resting places</li> <li>(c) car parks with gradients no steeper than 1-in-40 and of sufficient area to provide for wheelchair manoeuvrability</li> </ul> |   |
| (d) kerb ramps at pedestrian crossing points.  |   |
| Communal   | Open Space  |
| P0 29.1  | DTS/DPF 29.1  |
| Development is designed to provide attractive, convenient and comfortable indoor and outdoor communal areas to be used by residents and visitors.  | None are applicable.  |
| P0 29.2  | DTS/DPF 29.2  |
| Private open space provision may be substituted for communal open space which is designed and sited to meet the recreation and amenity needs of residents.   | None are applicable.  |
| PO 29.3  | DTS/DPF 29.3  |
| Communal open space is of sufficient size and dimensions to cater for group recreation.  | Communal open space incorporates a minimum dimension of 5 metres.   |
| PO 29.4  | DTS/DPF 29.4  |
| Communal open space is designed and sited to:  | None are applicable.  |
| (a) be conveniently accessed by the dwellings which it   |   |

Page 49 of 129 Printed on 5/07/2022

| Policy24 - Enquiry   |   |  |
|--|---|--|
| services (b) have regard to acoustic, safety, security and wind effects.   |   |  |
| PO 29.5  | DTS/DPF 29.5  |  |
| Communal open space contains landscaping and facilities that are functional, attractive and encourage recreational use.  | None are applicable.  |  |
| PO 29.6  | DTS/DPF 29.6  |  |
| Communal open space is designed and sited to:  | None are applicable.  |  |
| <ul> <li>(a) in relation to rooftop or elevated gardens, minimise overlooking into habitable room windows or onto the useable private open space of other dwellings</li> <li>(b) in relation to ground floor communal space, be overlooked by habitable rooms to facilitate passive surveillance.</li> </ul> |   |  |
| Site Facilities ,  | / Waste Storage   |  |
| PO 30.1  | DTS/DPF 30.1  |  |
| Development is designed to provide storage areas for personal items and specialised equipment such as small electric powered vehicles, including facilities for the recharging of small electric powered vehicles.   | None are applicable.  |  |
| PO 30.2  | DTS/DPF 30.2  |  |
| Provision is made for suitable mailbox facilities close to the major pedestrian entry to the site or conveniently located considering the nature of accommodation and mobility of occupants.   | None are applicable.  |  |
| PO 30.3  | DTS/DPF 28.3  |  |
| Provision is made for suitable external clothes drying facilities.   | None are applicable.  |  |
| PO 30.4  | DTS/DPF 30.4  |  |
| Provision is made for suitable household waste and recyclable material storage facilities conveniently located and screened from public view.  | None are applicable.  |  |
| PO 30.5  | DTS/DPF 30.5  |  |
| Waste and recyclable material storage areas are located away from dwellings.   | Dedicated waste and recyclable material storage areas are located at least 3m from any habitable room window. |  |
| PO 30.6  | DTS/DPF 30.6  |  |
| Provision is made for on-site waste collection where 10 or more bins are to be collected at any one time.  | None are applicable.  |  |
| PO 30.7  | DTS/DPF 30.7  |  |
| Services including gas and water meters are conveniently located and screened from public view.  | None are applicable.  |  |
| All non-residential development  |   |  |
| Water Sensitive Design   |   |  |
|  |   |  |

Page 50 of 129 Printed on 5/07/2022

| Policy24 - Enquiry   |                       |  |
|--|-----------------------|--|
| P0 31.1  | DTS/DPF 31.1          |  |
| Development likely to result in significant risk of export of litter, oil or grease includes stormwater management systems designed to minimise pollutants entering stormwater.  | None are applicable.  |  |
| PO 31.2  | DTS/DPF 31.2          |  |
| Water discharged from a development site is of a physical, chemical and biological condition equivalent to or better than its pre-developed state.   | None are applicable.  |  |
| Wash-down and Waste  | Loading and Unloading |  |
| P0 32.1  | DTS/DPF 32.1          |  |
| Areas for activities including loading and unloading, storage of waste refuse bins in commercial and industrial development or wash-down areas used for the cleaning of vehicles, vessels, plant or equipment are:  (a) designed to contain all wastewater likely to pollute stormwater within a bunded and roofed area to exclude the entry of external surface stormwater run-off (b) paved with an impervious material to facilitate wastewater collection (c) of sufficient size to prevent 'splash-out' or 'over-spray' of wastewater from the wash-down area (d) designed to drain wastewater to either:  (i) a treatment device such as a sediment trap and coalescing plate oil separator with subsequent disposal to a sewer, private or Community Wastewater Management Scheme or  (ii) a holding tank and its subsequent removal off-site on a regular basis. | None are applicable.  |  |

Table 1 - Private Open Space

| Dwelling Type                 | Minimum Rate  |
|-------------------------------|---|
| Dwelling (at ground level)    | Total private open space area:  (a) Site area <301m2: 24m2 located behind the building line.  (b) Site area ≥ 301m2: 60m2 located behind the building line.  Minimum directly accessible from a living room: 16m2 / with a minimum dimension 3m.    |
| Dwelling (above ground level) | Studio (no separate bedroom): $4m^2$ with a minimum dimension 1.8m  One bedroom: $8m^2$ with a minimum dimension 2.1m  Two bedroom dwelling: $11m^2$ with a minimum dimension 2.4m  Three + bedroom dwelling: $15m^2$ with a minimum dimension 2.6m |
| Cabin or caravan              | Total area: 16m <sup>2</sup> , which may be used as second car parking space, provided on   |

Page 51 of 129 Printed on 5/07/2022

| (permanently fixed to the     | each site intended for residential occupation. |
|-------------------------------|--|
| ground) in a residential park |  |
| or a caravan and tourist park |  |
|                               |  |

# **Design in Urban Areas**

## **Assessment Provisions (AP)**

| Desired Outcome |                 |  |  |  |
|-----------------|-----------------|--|--|--|
| DO 1            | Development is: |  |  |  |
|                 | (a)             | contextual - by considering, recognising and carefully responding to its natural surroundings or built environment and positively contributing to the character of the locality  |  |  |
|                 | (b)             | durable - fit for purpose, adaptable and long lasting  |  |  |
|                 | (c)             | inclusive - by integrating landscape design to optimise pedestrian and cyclist usability, privacy and equitable access and promoting the provision of quality spaces integrated with the public realm that can be used for access and recreation and help optimise security and safety both internally and within the public realm, for occupants and visitors |  |  |
|                 | (d)             | sustainable - by integrating sustainable techniques into the design and siting of development and landscaping to improve community health, urban heat, water management, environmental performance, biodiversity and local amenity and to minimise energy consumption.   |  |  |

| Performance Outcome   | Deemed-to-Satisfy Criteria /<br>Designated Performance<br>Feature |  |  |  |  |
|---|---|--|--|--|--|
| All Development   |   |  |  |  |  |
| External Appearance   |   |  |  |  |  |
| PO 1.1  | DTS/DPF 1.1   |  |  |  |  |
| Buildings reinforce corners through changes in setback, articulation, materials, colour and massing (including height, width, bulk, roof form and slope).   | None are applicable.  |  |  |  |  |
| P0 1.2  | DTS/DPF 1.2   |  |  |  |  |
| Where zero or minor setbacks are desirable, development provides shelter over footpaths (in the form of verandahs, awnings, canopies and the like, with adequate lighting) to positively contribute to the walkability, comfort and safety of the public realm. | None are applicable.  |  |  |  |  |
| PO 1.3  | DTS/DPF 1.3   |  |  |  |  |
| Building elevations facing the primary street (other than ancillary buildings) are designed and detailed to convey purpose, identify main access points and complement the streetscape.   | None are applicable.  |  |  |  |  |
| PO 1.4  | DTS/DPF 1.4   |  |  |  |  |
| Plant, exhaust and intake vents and other technical equipment are   | Development does not incorporate any structures that protrude     |  |  |  |  |

Page 52 of 129 Printed on 5/07/2022

| integrated into the building design to minimise visibility from the public realm and negative impacts on residential amenity by:   | beyond the roofline. |
|--|----------------------|
| (a) positioning plant and equipment discretely, in unobtrusive locations as viewed from public roads and spaces  |                      |
| (b) screening rooftop plant and equipment from view (c) when located on the roof of non-residential development, locating the plant and equipment as far as practicable from adjacent sensitive land uses.   |                      |
| PO 1.5   | DTS/DPF 1.5          |
| The negative visual impact of outdoor storage, waste management, loading and service areas is minimised by integrating them into the building design and screening them from public view (such as fencing, landscaping and built form), taking into account the form of development contemplated in the relevant zone. | None are applicable. |
| Sa   | fety                 |
| PO 2.1   | DTS/DPF 2.1          |
| Development maximises opportunities for passive surveillance of<br>the public realm by providing clear lines of sight, appropriate<br>lighting and the use of visually permeable screening wherever<br>practicable.  | None are applicable. |
| PO 2.2   | DTS/DPF 2.2          |
| Development is designed to differentiate public, communal and private areas.   | None are applicable. |
| PO 2.3   | DTS/DPF 2.3          |
| Buildings are designed with safe, perceptible and direct access from public street frontages and vehicle parking areas.  | None are applicable. |
| PO 2.4   | DTS/DPF 2.4          |
| Development at street level is designed to maximise opportunities for passive surveillance of the adjacent public realm.   | None are applicable. |
| PO 2.5   | DTS/DPF 2.5          |
| Common areas and entry points of buildings (such as the foyer areas of residential buildings) and non-residential land uses at street level, maximise passive surveillance from the public realm to the inside of the building at night.   | None are applicable. |
| Lands  | caping               |
| PO 3.1   | DTS/DPF 3.1          |
| Soft landscaping and tree planting are incorporated to:  | None are applicable. |
| <ul> <li>(a) minimise heat absorption and reflection</li> <li>(b) maximise shade and shelter</li> <li>(c) maximise stormwater infiltration</li> <li>(d) enhance the appearance of land and streetscapes.</li> </ul>  |                      |
| cilitative the appearance of failu and streetscapes.   |                      |

Page 53 of 129 Printed on 5/07/2022

| Policy24 - Enquiry  Environmenta  | al Performance  |
|---|---|
|   |   |
| PO 4.1  | DTS/DPF 4.1   |
| Buildings are sited, oriented and designed to maximise natural sunlight access and ventilation to main activity areas, habitable rooms, common areas and open spaces.   | None are applicable.  |
| PO 4.2  | DTS/DPF 4.2   |
| Buildings are sited and designed to maximise passive environmental performance and minimise energy consumption and reliance on mechanical systems, such as heating and cooling.   | None are applicable.  |
| PO 4.3  | DTS/DPF 4.3   |
| Buildings incorporate climate responsive techniques and features such as building and window orientation, use of eaves, verandahs and shading structures, water harvesting, at ground landscaping, green walls, green roofs and photovoltaic cells.   | None are applicable.  |
| Water Sens  | sitive Design   |
| PO 5.1  | DTS/DPF 5.1   |
| Development is sited and designed to maintain natural hydrological systems without negatively impacting:  | None are applicable.  |
| (a) the quantity and quality of surface water and groundwater (b) the depth and directional flow of surface water and   |   |
| (b) the depth and directional flow of surface water and groundwater (c) the quality and function of natural springs.  |   |
| On-site Waste Tr  | reatment Systems  |
| P0 6.1  | DTS/DPF 6.1   |
| Dedicated on-site effluent disposal areas do not include any  | Effluent disposal drainage areas do not:  |
| areas to be used for, or could be reasonably foreseen to be used for, private open space, driveways or car parking.   | <ul> <li>(a) encroach within an area used as private open space or result in less private open space than that specified in Design in Urban Areas Table 1 - Private Open Space</li> <li>(b) use an area also used as a driveway</li> <li>(c) encroach within an area used for on-site car parking or result in less on-site car parking than that specified in Transport, Access and Parking Table 1 - General Off-Street Car Parking Requirements or Table 2 - Off-Street Car Parking Requirements in Designated Areas.</li> </ul> |
| Car parking   | appearance  |
| PO 7.1  | DTS/DPF 7.1   |
| Development facing the street is designed to minimise the negative impacts of any semi-basement and undercroft car parking on streetscapes through techniques such as:  (a) limiting protrusion above finished ground level  (b) screening through appropriate planting, fencing and mounding  (c) limiting the width of openings and integrating them into the building structure. | None are applicable.  |
| PO 7.2  | DTS/DPF 7.2   |
| Page 54 of 129  | Printed on 5/07/2022  |

Page 54 of 129 Printed on 5/07/2022

| Vehicle parking areas appropriately located, designed and constructed to minimise impacts on adjacent sensitive receivers through measures such as ensuring they are attractively developed and landscaped, screen fenced and the like. | None are applicable.  |
|---|---|
| P0 7.3  | DTS/DPF 7.3   |
| Safe, legible, direct and accessible pedestrian connections are provided between parking areas and the development.   | None are applicable.  |
| PO 7.4  | DTS/DPF 7.4   |
| Street-level vehicle parking areas incorporate tree planting to provide shade, reduce solar heat absorption and reflection.   | Vehicle parking areas that are open to the sky and comprise 10 or more car parking spaces include a shade tree with a mature canopy of 4m diameter spaced for each 10 car parking spaces provided and a landscaped strip on any road frontage of a minimum dimension of 1m. |
| PO 7.5  | DTS/DPF 7.5   |
| Street level parking areas incorporate soft landscaping to improve visual appearance when viewed from within the site and from public places.   | Vehicle parking areas comprising 10 or more car parking spaces include soft landscaping with a minimum dimension of:  (a) 1m along all public road frontages and allotment  |
|   | boundaries (b) 1m between double rows of car parking spaces.  |
| PO 7.6  | DTS/DPF 7.6   |
| Vehicle parking areas and associated driveways are landscaped to provide shade and positively contribute to amenity.  | None are applicable.  |
| P0 7.7  | DTS/DPF 7.7   |
| Vehicle parking areas and access ways incorporate integrated stormwater management techniques such as permeable or porous surfaces, infiltration systems, drainage swales or rain gardens that integrate with soft landscaping.         | None are applicable.  |
| Earthworks a  | nd sloping land   |
| PO 8.1  | DTS/DPF 8.1   |
| Development, including any associated driveways and access tracks, minimises the need for earthworks to limit disturbance to natural topography.  | Development does not involve any of the following:  (a) excavation exceeding a vertical height of 1m  (b) filling exceeding a vertical height of 1m  (c) a total combined excavation and filling vertical height of 2m or more.   |
| P0 8.2  | DTS/DPF 8.2   |
| Driveways and access tracks designed and constructed to allow safe and convenient access on sloping land.   | Driveways and access tracks on sloping land (with a gradient exceeding 1 in 8) satisfy (a) and (b):  (a) do not have a gradient exceeding 25% (1-in-4) at any point along the driveway  (b) are constructed with an all-weather trafficable surface.                        |
| PO 8.3  | DTS/DPF 8.3   |
| Driveways and access tracks on sloping land (with a gradient  | None are applicable.  |

Page 55 of 129 Printed on 5/07/2022

# exceeding 1 in 8): (a) do not contribute to the instability of embankments and cuttings (b) provide level transition areas for the safe movement of people and goods to and from the development (c) are designed to integrate with the natural topography of the land PO 8.4 DTS/DPF 8.4 Development on sloping land (with a gradient exceeding 1 in 8) None are applicable. avoids the alteration of natural drainage lines and includes on site drainage systems to minimise erosion. PO 8.5 DTS/DPF 8.5 Development does not occur on land at risk of landslip or None are applicable. increase the potential for landslip or land surface instability. Fences and walls PO 9.1 DTS/DPF 9.1 Fences, walls and retaining walls of sufficient height maintain None are applicable. privacy and security without unreasonably impacting visual amenity and adjoining land's access to sunlight or the amenity of public places. DTS/DPF 9.2 PO 9.2 A vegetated landscaped strip 1m wide or more is provided Landscaping is incorporated on the low side of retaining walls that are visible from public roads and public open space to against the low side of a retaining wall. minimise visual impacts. Overlooking / Visual Privacy (low rise buildings) PO 10.1 DTS/DPF 10.1 Development mitigates direct overlooking from upper level Upper level windows facing side or rear boundaries shared with a windows to habitable rooms and private open spaces of residential use in a neighbourhood-type zone: adjoining residential uses in neighbourhood-type zones. are permanently obscured to a height of 1.5m above finished floor level and are fixed or not capable of being opened more than 125mm (b) have sill heights greater than or equal to 1.5m above finished floor level (c) incorporate screening with a maximum of 25% openings, permanently fixed no more than 500mm from the window surface and sited adjacent to any part of the window less than 1.5 m above the finished floor level. PO 10.2 DTS/DPF 10.2 Development mitigates direct overlooking from balconies to One of the following is satisfied: habitable rooms and private open space of adjoining residential uses in neighbourhood type zones. (a) the longest side of the balcony or terrace will face a public road, public road reserve or public reserve that is at least 15m wide in all places faced by the balcony or terrace or (b) all sides of balconies or terraces on upper building levels are permanently obscured by screening with a maximum 25% transparency/openings fixed to a minimum height of:

Page 56 of 129 Printed on 5/07/2022

PO 12.4

PO 12.5

Boundary walls visible from public land include visually

interesting treatments to break up large blank elevations.

External materials and finishes are durable and age well to

minimise ongoing maintenance requirements.

| Policy24 - Enquiry   |  |  |  |
|--|--|--|--|
|  | (i) 1.5m above finished floor level where the balcony is located at least 15 metres from the nearest habitable window of a dwelling on adjacent land or  (ii) 1.7m above finished floor level in all other cases |  |  |
| Site Facilities / Waste Storage (exclu   | ding low rise residential development)   |  |  |
| PO 11.1  | DTS/DPF 11.1   |  |  |
| Development provides a dedicated area for on-site collection and sorting of recyclable materials and refuse, green organic waste and wash bay facilities for the ongoing maintenance of bins that is adequate in size considering the number and nature of the activities they will serve and the frequency of collection. | None are applicable.   |  |  |
| PO 11.2  | DTS/DPF 11.2   |  |  |
| Communal waste storage and collection areas are located, enclosed and designed to be screened from view from the public domain, open space and dwellings.  | None are applicable.   |  |  |
| PO 11.3  | DTS/DPF 11.3   |  |  |
| Communal waste storage and collection areas are designed to be well ventilated and located away from habitable rooms.  | None are applicable.   |  |  |
| PO 11.4  | DTS/DPF 11.4   |  |  |
| Communal waste storage and collection areas are designed to allow waste and recycling collection vehicles to enter and leave the site without reversing.   | None are applicable.   |  |  |
| PO 11.5  | DTS/DPF 11.5   |  |  |
| For mixed use developments, non-residential waste and recycling storage areas and access provide opportunities for on-site management of food waste through composting or other waste recovery as appropriate.   | None are applicable.   |  |  |
| All Development - M  | edium and High Rise  |  |  |
| External A   | ppearance  |  |  |
| PO 12.1  | DTS/DPF 12.1   |  |  |
| Buildings positively contribute to the character of the local area by responding to local context.   | None are applicable.   |  |  |
| PO 12.2  | DTS/DPF 12.2   |  |  |
| Architectural detail at street level and a mixture of materials at lower building levels near the public interface are provided to reinforce a human scale.  | None are applicable.   |  |  |
| PO 12.3  | DTS/DPF 12.3   |  |  |
| Buildings are designed to reduce visual mass by breaking up building elevations into distinct elements.  | None are applicable.   |  |  |

Page 57 of 129 Printed on 5/07/2022

DTS/DPF 12.4

DTS/DPF 12.5

and finishes:

None are applicable.

Buildings utilise a combination of the following external materials

| Policy24 - Enquiry   |  |      |                           |                                |   |
|--|--|------|---------------------------|--------------------------------|---|
|  | (b)  |      | stone                     | that minimise stai<br>oration. | ning,   |
| PO 12.6  | DTS/DPF 1  | 12.6 |                           |                                |   |
| Street-facing building elevations are designed to provide attractive, high quality and pedestrian-friendly street frontages.   | Building street frontages incorporate:  (a) active uses such as shops or offices (b) prominent entry areas for multi-storey buildings (whit is a common entry) (c) habitable rooms of dwellings (d) areas of communal public realm with public art or the like, where consistent with the zone and/or subzone provisions.  |      |                           |                                | blic art or the   |
| PO 12.7  | DTS/DPF 12.7   |      |                           |                                |   |
| Entrances to multi-storey buildings are safe, attractive, welcoming, functional and contribute to streetscape character.  PO 12.8  | <ul> <li>(a) oriented towards the street</li> <li>(b) clearly visible and easily identifiable from the street and vehicle parking areas</li> <li>(c) designed to be prominent, accentuated and a welcoming feature if there are no active or occupied ground floor uses</li> <li>(d) designed to provide shelter, a sense of personal address and transitional space around the entry</li> <li>(e) located as close as practicable to the lift and / or lobby access to minimise the need for long access corridors</li> <li>(f) designed to avoid the creation of potential areas of entrapment.</li> </ul> |      |                           |                                | end a or occupied bersonal ne entry t and / or lobby cess corridors |
| Building services, plant and mechanical equipment are screened   | None are applicable.   |      |                           |                                |   |
| from the public realm.   | попе аге аррисавіе.  |      |                           |                                |   |
| Lands  | scaping  |      |                           |                                |   |
| P0 13.1  | DTS/DPF 1  | 13.1 |                           |                                |   |
| Development facing a street provides a well landscaped area that contains a deep soil space to accommodate a tree of a species and size adequate to provide shade, contribute to tree canopy targets and soften the appearance of buildings. | Buildings provide a 4m by 4m deep soil space in front of the building that accommodates a medium to large tree, except where no building setback from front property boundaries is desired.  |      |                           |                                |   |
| PO 13.2  | DTS/DPF 1  | 13.2 |                           |                                |   |
| Deep soil zones are provided to retain existing vegetation or provide areas that can accommodate new deep root vegetation, including tall trees with large canopies to provide shade and soften the appearance of multi-storey buildings.    | Multi-storey development provides deep soil zones and incorporates trees at not less than the following rates, except in a location or zone where full site coverage is desired.   |      |                           | rates, except in               |   |
|  | Site are   | a    | Minimum<br>deep soil area | Minimum<br>dimension           | Tree / deep<br>soil zones   |

Printed on 5/07/2022 Page 58 of 129

<300 m<sup>2</sup>

 $10 \text{ m}^2$ 

1.5m

1 small tree /

 $10 \; m^2$ 

|   | 11 2   | 70/ -:+                         | 10           | 11   |
|---|--|---------------------------------|--------------|--|
|   | 300-1500 m <sup>2</sup>  | 7% site area                    | 3m           | 1 medium<br>tree / 30 m <sup>2</sup>             |
|   | >1500 m <sup>2</sup>   | 7% site area                    | 6m           | 1 large or<br>medium tree /<br>60 m <sup>2</sup> |
|   | Tree size and site area definitions  |                                 |              |  |
|   | Small tree 4-6m mature height and 2-4m canopy spread  Medium tree 6-12m mature height and 4-8m canopy spread |                                 |              | canopy spread                                    |
|   |  |                                 |              | n canopy spread                                  |
|   | Large tree 12m mature height and >8m canopy spre   |                                 | anopy spread |  |
|   | Site area  | The total area tarea per dwelli |              | t site, not average                              |
| PO 13.3   | DTS/DPF 13.3   |                                 |              |  |
| Deep soil zones with access to natural light are provided to assist in maintaining vegetation health.   | None are applicable.   |                                 |              |  |
| P0 13.4   | DTS/DPF 13.4   |                                 |              |  |
| Unless separated by a public road or reserve, development sites   | Building elements of 3 or more building levels in height are set   |                                 |              |  |
| adjacent to any zone that has a primary purpose of accommodating low-rise residential development incorporate a deep soil zone along the common boundary to enable medium to large trees to be retained or established to assist in screening new buildings of 3 or more building levels in height.                     | back at least 6m from a zone boundary in which a deep soil zone area is incorporated.                        |                                 |              |  |
| Enviror   | nmental  |                                 |              |  |
| PO 14.1   | DTS/DPF 14.1   |                                 |              |  |
| Development minimises detrimental micro-climatic impacts on adjacent land and buildings.  | None are applic  | cable.                          |              |  |
| PO 14.2   | DTS/DPF 14.2   |                                 |              |  |
| Development incorporates sustainable design techniques and features such as window orientation, eaves and shading structures, water harvesting and use, green walls and roof designs that enable the provision of rain water tanks (where they are not provided elsewhere on site), green roofs and photovoltaic cells. | None are applicable.   |                                 |              |  |
| PO 14.3   | DTS/DPF 14.3   |                                 |              |  |
| Development of 5 or more building levels, or 21m or more in height (as measured from natural ground level and excluding roof-mounted mechanical plant and equipment) is designed to minimise the impacts of wind through measures such as:  | None are applic  | cable.                          |              |  |
| (a) a podium at the base of a tall tower and aligned with the street to deflect wind away from the street (b) substantial verandahs around a building to deflect  |  |                                 |              |  |

Page 59 of 129 Printed on 5/07/2022

- downward travelling wind flows over pedestrian areas
  (c) the placement of buildings and use of setbacks to
  deflect the wind at ground level
- (d) avoiding tall shear elevations that create windy conditions at street level.

# Car Parking

#### PO 15.1

Multi-level vehicle parking structures are designed to contribute to active street frontages and complement neighbouring buildings.

DTS/DPF 15.1

Multi-level vehicle parking structures within buildings:

- (a) provide land uses such as commercial, retail or other non-car parking uses along ground floor street frontages
- (b) incorporate facade treatments in building elevations facing along major street frontages that are sufficiently enclosed and detailed to complement adjacent buildings.

PO 15.2

Multi-level vehicle parking structures within buildings complement the surrounding built form in terms of height, massing and scale. DTS/DPF 15.2

None are applicable.

## Overlooking/Visual Privacy

#### PO 16.1

Development mitigates direct overlooking of habitable rooms and private open spaces of adjacent residential uses in neighbourhood-type zones through measures such as:

- (a) appropriate site layout and building orientation
- (b) off-setting the location of balconies and windows of habitable rooms or areas with those of other buildings so that views are oblique rather than direct to avoid direct line of sight
- (c) building setbacks from boundaries (including building boundary to boundary where appropriate) that interrupt views or that provide a spatial separation between balconies or windows of habitable rooms
- (d) screening devices that are integrated into the building design and have minimal negative effect on residents' or neighbours' amenity.

DTS/DPF 16.1

None are applicable.

All residential development

# Front elevations and passive surveillance

## PO 17.1

Dwellings incorporate windows facing primary street frontages to encourage passive surveillance and make a positive contribution to the streetscape. DTS/DPF 17.1

Each dwelling with a frontage to a public street:

- (a) includes at least one window facing the primary street from a habitable room that has a minimum internal room dimension of 2.4m
- (b) has an aggregate window area of at least 2m<sup>2</sup> facing the primary street.

# PO 17.2

Dwellings incorporate entry doors within street frontages to

DTS/DPF 17.2

Dwellings with a frontage to a public street have an entry door

Page 60 of 129 Printed on 5/07/2022

| Policy24 - Enquiry  |  |  |  |
|---|--|--|--|
| address the street and provide a legible entry point for visitors.  | visible from the primary street boundary.  |  |  |
| Outlook and Amenity   |  |  |  |
| PO 18.1   | DTS/DPF 18.1   |  |  |
| Living rooms have an external outlook to provide a high standard of amenity for occupants.  | A living room of a dwelling incorporates a window with an external outlook of the street frontage, private open space, public open space, or waterfront areas. |  |  |
| PO 18.2   | DTS/DPF 18.2   |  |  |
| Bedrooms are separated or shielded from active communal recreation areas, common access areas and vehicle parking areas and access ways to mitigate noise and artificial light intrusion. | None are applicable.   |  |  |
| Ancillary Development   |  |  |  |
| PO 19 1   | DTS/DPF 19 1   |  |  |

#### PO 19.1

Residential ancillary buildings are sited and designed to not detract from the streetscape or appearance of primary residential buildings on the site or neighbouring properties.

**DTS/DPF 19.1** 

Ancillary buildings:

- are ancillary to a dwelling erected on the same site
- (b) have a floor area not exceeding 60m2
- (c) are not constructed, added to or altered so that any part is situated:
  - (i) in front of any part of the building line of the dwelling to which it is ancillary
  - within 900mm of a boundary of the allotment with a secondary street (if the land has boundaries on two or more roads)
- (d) in the case of a garage or carport, the garage or carport:
  - is set back at least 5.5m from the boundary of the primary street
  - when facing a primary street or secondary street, has a total door / opening not exceeding:
    - for dwellings of single building level -7m in width or 50% of the site frontage, whichever is the lesser
    - for dwellings comprising two or more building levels at the building line fronting the same public street - 7m in width
- if situated on a boundary (not being a boundary with a primary street or secondary street), do not exceed a length of 11.5m unless:
  - a longer wall or structure exists on the adjacent site and is situated on the same allotment boundary
    - and
  - the proposed wall or structure will be built along the same length of boundary as the existing adjacent wall or structure to the same or lesser extent
- (f) if situated on a boundary of the allotment (not being a boundary with a primary street or secondary street), all walls or structures on the boundary will not exceed 45% of the length of that boundary

Printed on 5/07/2022 Page 61 of 129

- (g) will not be located within 3m of any other wall along the same boundary unless on an adjacent site on that boundary there is an existing wall of a building that would be adjacent to or about the proposed wall or structure
- (h) have a wall height or post height not exceeding 3m above natural ground level (and not including a gable end)
- (i) have a roof height where no part of the roof is more than 5m above the natural ground level
- (j) if clad in sheet metal, is pre-colour treated or painted in a non-reflective colour
- (k) retains a total area of soft landscaping in accordance with (i) or (ii), whichever is less:
  - a total area as determined by the following table:

| Dwelling site area (or in the case of residential flat building or group dwelling(s), average site area) (m <sup>2</sup> ) | Minimum<br>percentage of<br>site |
|--|----------------------------------|
| <150   | 10%                              |
| 150-200  | 15%                              |
| 201-450  | 20%                              |
| >450   | 25%                              |

(ii) the amount of existing soft landscaping prior to the development occurring.

#### PO 19.2

Ancillary buildings and structures do not impede on-site functional requirements such as private open space provision, car parking requirements or result in over-development of the site.

#### DTS/DPF 19.2

Ancillary buildings and structures do not result in:

- (a) less private open space than specified in Design in Urban Areas Table 1 Private Open Space
- (b) less on-site car parking than specified in Transport, Access and Parking Table 1 - General Off-Street Car Parking Requirements or Table 2 - Off-Street Car Parking Requirements in Designated Areas.

#### PO 19.3

Fixed plant and equipment in the form of pumps and/or filtration systems for a swimming pool or spa positioned and/or housed to not cause unreasonable noise nuisance to adjacent sensitive receivers.

#### DTS/DPF 19.3

The pump and/or filtration system is ancillary to a dwelling erected on the same site and is:

- enclosed in a solid acoustic structure that is located at least 5m from the nearest habitable room located on an adjoining allotment or
- (b) located at least 12m from the nearest habitable room located on an adjoining allotment.

Residential Development - Low Rise

Page 62 of 129 Printed on 5/07/2022

| External a   | ppearance  |
|--|--|
| PO 20 1  | DTS/DPE 20.1   |
| PO 20.1  Garaging is designed to not detract from the streetscape or appearance of a dwelling.  PO 20.2  Dwelling elevations facing public streets and common driveways make a positive contribution to the streetscape and the appearance of common driveway areas. | DTS/DPF 20.1  Garages and carports facing a street:  (a) are situated so that no part of the garage or carport will be in front of any part of the building line of the dwelling (b) are set back at least 5.5m from the boundary of the primary street  (c) have a garage door / opening width not exceeding 7m (d) have a garage door / opening width not exceeding 50% of the site frontage unless the dwelling has two or more building levels at the building line fronting the same public street.  DTS/DPF 20.2  Each dwelling includes at least 3 of the following design features within the building elevation facing a primary street, and at least 2 of the following design features within the building elevation facing any other public road (other than a laneway) or a common driveway:  (a) a minimum of 30% of the building wall is set back an additional 300mm from the building line  (b) a porch or portico projects at least 1m from the building wall  (c) a balcony projects from the building wall  (d) a verandah projects at least 1m from the building wall  (e) eaves of a minimum 400mm width extend along the width of the front elevation  (f) a minimum 30% of the width of the upper level projects forward from the lower level primary building line by at least 300mm  (g) a minimum of two different materials or finishes are incorporated on the walls of the front building elevation, with a maximum of 80% of the building elevation in a single material or finish. |
| PO 20.3  The visual mass of larger buildings is reduced when viewed from adjoining allotments or public streets.   | DTS/DPF 20.3  None are applicable  |
| Private O  | pen Space  |
| PO 21.1  | DTS/DPF 21.1   |
| Dwellings are provided with suitable sized areas of usable private open space to meet the needs of occupants.  |  |
| PO 21.2  | DTS/DPF 21.2   |
| Private open space is positioned to provide convenient access from internal living areas.  | Private open space is directly accessible from a habitable room.   |

Page 63 of 129 Printed on 5/07/2022

#### Landscaping

#### PO 22.1

Soft landscaping is incorporated into development to:

- (a) minimise heat absorption and reflection
- (b) contribute shade and shelter
- (c) provide for stormwater infiltration and biodiversity
- (d) enhance the appearance of land and streetscapes.

DTS/DPF 22.1

Residential development incorporates soft landscaping with a minimum dimension of 700mm provided in accordance with (a) and (b):

(a) a total area as determined by the following table:

| Dwelling site area (or in the case of residential flat building or group dwelling(s), average site area) (m <sup>2</sup> ) | Minimum<br>percentage of<br>site |
|--|----------------------------------|
| <150   | 10%                              |
| 150-200  | 15%                              |
| >200-450   | 20%                              |
| >450   | 25%                              |

(b) at least 30% of any land between the primary street boundary and the primary building line.

#### Car parking, access and manoeuvrability

## PO 23.1

Enclosed car parking spaces are of dimensions to be functional, accessible and convenient.

DTS/DPF 23.1

Residential car parking spaces enclosed by fencing, walls or other structures have the following internal dimensions (separate from any waste storage area):

- (a) single width car parking spaces:
  - (i) a minimum length of 5.4m per space
  - (ii) a minimum width of 3.0m
  - (iii) a minimum garage door width of 2.4m
- (b) double width car parking spaces (side by side):
  - (i) a minimum length of 5.4m
  - (ii) a minimum width of 5.4m
  - (iii) minimum garage door width of 2.4m per space.

## PO 23.2

Uncovered car parking space are of dimensions to be functional, accessible and convenient.

## DTS/DPF 23.2

Uncovered car parking spaces have:

- (a) a minimum length of 5.4m
- (b) a minimum width of 2.4m
- (c) a minimum width between the centre line of the space and any fence, wall or other obstruction of 1.5m.

#### PO 23.3

Driveways and access points are located and designed to facilitate safe access and egress while maximising land available for street tree planting, domestic waste collection, landscaped street frontages and on-street parking.

#### DTS/DPF 23.3

Driveways and access points satisfy (a) or (b):

(a) sites with a frontage to a public road of 10m or less, have a width between 3.0 and 3.2 metres measured at the property boundary and are the only access point

Page 64 of 129 Printed on 5/07/2022

provided on the site (b) sites with a frontage to a public road greater than 10m: have a maximum width of 5m measured at the property boundary and are the only access point provided on the site; (ii) have a width between 3.0 metres and 3.2 metres measured at the property boundary and no more than two access points are provided on site, separated by no less than 1m. PO 23.4 DTS/DPF 23.4 Vehicle access is safe, convenient, minimises interruption to the Vehicle access to designated car parking spaces satisfy (a) or operation of public roads and does not interfere with street infrastructure or street trees. (a) is provided via a lawfully existing or authorised access point or an access point for which consent has been granted as part of an application for the division of land (b) where newly proposed, is set back: 0.5m or more from any street furniture, street pole, infrastructure services pit, or other stormwater or utility infrastructure unless consent is provided from the asset owner 2m or more from the base of the trunk of a street tree unless consent is provided from the tree owner for a lesser distance (iii) 6m or more from the tangent point of an intersection of 2 or more roads (iv) outside of the marked lines or infrastructure dedicating a pedestrian crossing. PO 23.5 **DTS/DPF 23.5** Driveways are designed to enable safe and convenient vehicle Driveways are designed and sited so that: movements from the public road to on-site parking spaces. (a) the gradient from the place of access on the boundary of the allotment to the finished floor level at the front of the garage or carport is not steeper than 1-in-4 on they are aligned relative to the street so that there is no more than a 20 degree deviation from 90 degrees between the centreline of any dedicated car parking space to which it provides access (measured from the front of that space) and the road boundary. if located so as to provide access from an alley, lane or right of way - the alley, lane or right or way is at least 6.2m wide along the boundary of the allotment / site DTS/DPF 23.6 PO 23.6 Driveways and access points are designed and distributed to Where on-street parking is available abutting the site's street optimise the provision of on-street visitor parking. frontage, on-street parking is retained in accordance with the following requirements: minimum 0.33 on-street spaces per dwelling on the site (rounded up to the nearest whole number) (b) minimum car park length of 5.4m where a vehicle can enter or exit a space directly (c) minimum carpark length of 6m for an intermediate

Page 65 of 129 Printed on 5/07/2022

space located between two other parking spaces or to

an end obstruction where the parking is indented. Waste storage PO 24.1 DTS/DPF 24.1 Provision is made for the convenient storage of waste bins in a Where dwellings abut both side boundaries a waste bin storage location screened from public view. area is provided behind the building line of each dwelling that: has a minimum area of 2m<sup>2</sup> with a minimum dimension of 900mm (separate from any designated car parking spaces or private open space); and has a continuous unobstructed path of travel (excluding moveable objects like gates, vehicles and roller doors) with a minimum width of 800mm between the waste bin storage area and the street. Design of Transportable Buildings DTS/DPF 25.1 PO 25.1 The sub-floor space beneath transportable buildings is enclosed Buildings satisfy (a) or (b): to give the appearance of a permanent structure. are not transportable (b) the sub-floor space between the building and ground level is clad in a material and finish consistent with the buildina. Residential Development - Medium and High Rise (including serviced apartments) Outlook and Visual Privacy DTS/DPF 26.1 PO 26.1 Ground level dwellings have a satisfactory short range visual Buildings: outlook to public, communal or private open space. provide a habitable room at ground or first level with a window facing toward the street (b) limit the height / extent of solid walls or fences facing the street to 1.2m high above the footpath level or, where higher, to 50% of the site frontage. PO 26.2 DTS/DPF 26.2 The visual privacy of ground level dwellings within multi-level The finished floor level of ground level dwellings in multi-storey buildings is protected. developments is raised by up to 1.2m. Private Open Space DTS/DPF 27.1 PO 27.1 Dwellings are provided with suitable sized areas of usable private Private open space provided in accordance with Design in Urban open space to meet the needs of occupants. Areas Table 1 - Private Open Space. Residential amenity in multi-level buildings PO 28.1 DTS/DPF 28 1 Residential accommodation within multi-level buildings have Habitable rooms and balconies of independent dwellings and habitable rooms, windows and balconies designed and accommodation are separated by at least 6m from one another where there is a direct line of sight between them and 3m or positioned to be separated from those of other dwellings and accommodation to provide visual and acoustic privacy and allow more from a side or rear property boundary. for natural ventilation and the infiltration of daylight into interior and outdoor spaces.

Page 66 of 129 Printed on 5/07/2022

| Folicy24 - Enquiry  |   |
|---|---|
| PO 28.2   | DTS/DPF 28.2  |
| Balconies are designed, positioned and integrated into the overall architectural form and detail of the development to:   | Balconies utilise one or a combination of the following design elements:  |
| <ul> <li>(a) respond to daylight, wind, and acoustic conditions to maximise comfort and provide visual privacy</li> <li>(b) allow views and casual surveillance of the street while providing for safety and visual privacy of nearby living spaces and private outdoor areas.</li> </ul> | (a) sun screens (b) pergolas (c) louvres (d) green facades (e) openable walls.  |
| PO 28.3   | DTS/DPF 28.3  |
| Balconies are of sufficient size and depth to accommodate outdoor seating and promote indoor / outdoor living.  | Balconies open directly from a habitable room and incorporate a minimum dimension of 2m.  |
| PO 28.4   | DTS/DPF 28.4  |
| Dwellings are provided with sufficient space for storage to meet likely occupant needs.   | Dwellings (not including student accommodation or serviced apartments) are provided with storage at the following rates with at least 50% or more of the storage volume to be provided within the dwelling:   |
|   | (a) studio: not less than 6m <sup>3</sup> (b) 1 bedroom dwelling / apartment: not less than 8m <sup>3</sup> (c) 2 bedroom dwelling / apartment: not less than 10m <sup>3</sup> (d) 3+ bedroom dwelling / apartment: not less than 12m <sup>3</sup> .                                      |
| PO 28.5   | DTS/DPF 28.5  |
| Dwellings that use light wells for access to daylight, outlook and ventilation for habitable rooms, are designed to ensure a reasonable living amenity is provided.   | Light wells:  (a) are not used as the primary source of outlook for living rooms  (b) up to 18m in height have a minimum horizontal dimension of 3m, or 6m if overlooked by bedrooms  (c) above 18m in height have a minimum horizontal dimension of 6m, or 9m if overlooked by bedrooms. |
| PO 28.6   | DTS/DPF 28.6  |
| Attached or abutting dwellings are designed to minimise the transmission of sound between dwellings and, in particular, to protect bedrooms from possible noise intrusions.   | None are applicable.  |
| PO 28.7   | DTS/DPF 28.7  |
| Dwellings are designed so that internal structural columns correspond with the position of internal walls to ensure that the space within the dwelling/apartment is useable.  | None are applicable.  |
| Dwelling Co   | onfiguration  |
| PO 29.1   | DTS/DPF 29.1  |
| Buildings containing in excess of 10 dwellings provide a variety of dwelling sizes and a range in the number of bedrooms per dwelling to contribute to housing diversity.   | Buildings containing in excess of 10 dwellings provide at least one of each of the following:   |
|   | (a) studio (where there is no separate bedroom)   |

Page 67 of 129 Printed on 5/07/2022

(b)

(c)

least 50m<sup>2</sup>

least 65m<sup>2</sup>

1 bedroom dwelling / apartment with a floor area of at

 $2\ \mbox{bedroom}$  dwelling / apartment with a floor area of at

|  | (d) 3+ bedroom dwelling / apartment with a floor area of at least 80m², and any dwelling over 3 bedrooms provides an additional 15m² for every additional bedroom. |
|--|--|
| PO 29.2  | DTS/DPF 29.2   |
| Dwellings located on the ground floor of multi-level buildings with 3 or more bedrooms have the windows of their habitable rooms overlooking internal courtyard space or other public space, where possible. |  |

| The size of lifts, lobbies and corridors is sufficient to  Common corridor or circulation areas:  |  |  |
|---|--|--|
| The size of lifts, lobbies and corridors is sufficient to  Common corridor or circulation areas:  | Commo  | on Areas   |
| visitor waiting areas.  (a) have a minimum ceiling height of 2.7m  (b) provide access to no more than 8 dwellings  (c) incorporate a wider section at apartment entries where the corridors exceed 12m in length from a core. | The size of lifts, lobbies and corridors is sufficient to accommodate movement of bicycles, strollers, mobility aids and | Common corridor or circulation areas:  (a) have a minimum ceiling height of 2.7m (b) provide access to no more than 8 dwellings (c) incorporate a wider section at apartment entries where |

| Group Dwellings, Residential Flat Buildings and Battle axe Development   |  |   |  |
|--|--|---|--|
| Amenity  |  |   |  |
| PO 31.1  | DTS/DPF 31.1   |   |  |
| Dwellings are of a suitable size to provide a high standard of amenity for occupants.  | Dwellings have a minimum internal floor area in accordance with the following table: |   |  |
|  | Number of bedrooms   | Minimum internal floor area   |  |
|  | Studio   | 35m <sup>2</sup>  |  |
|  | 1 bedroom  | 50m <sup>2</sup>  |  |
|  | 2 bedroom  | 65m <sup>2</sup>  |  |
|  | 3+ bedrooms  | 80m <sup>2</sup> and any dwelling over 3<br>bedrooms provides an<br>additional 15m <sup>2</sup> for every<br>additional bedroom |  |
| PO 31.2  | DTS/DPF 31.2   |   |  |
| The orientation and siting of buildings minimises impacts on the amenity, outlook and privacy of occupants and neighbours.                               | None are applicable.   |   |  |
| PO 31.3  | DTS/DPF 31.3   |   |  |
| Development maximises the number of dwellings that face public open space and public streets and limits dwellings oriented towards adjoining properties. | None are applicable.   |   |  |
| PO 31.4  | DTS/DPF 31.4   |   |  |
| Battle-axe development is appropriately sited and designed to respond to the existing neighbourhood context.   | Dwelling sites/allotments are no arrangement.  | ot in the form of a battle-axe  |  |
| Communal Open Space  |  |   |  |

Page 68 of 129 Printed on 5/07/2022

| PO 32.1   | DTS/DPF 32.1   |
|---|--|
| Private open space provision may be substituted for communal open space which is designed and sited to meet the recreation and amenity needs of residents.  | None are applicable.   |
| PO 32.2   | DTS/DPF 32.2   |
| Communal open space is of sufficient size and dimensions to cater for group recreation.   | Communal open space incorporates a minimum dimension of 5 metres.  |
| PO 32.3   | DTS/DPF 32.3   |
| Communal open space is designed and sited to:   | None are applicable.   |
| (a) be conveniently accessed by the dwellings which it services   |  |
| (b) have regard to acoustic, safety, security and wind effects.   |  |
| PO 32.4   | DTS/DPF 32.4   |
| Communal open space contains landscaping and facilities that are functional, attractive and encourage recreational use.   | None are applicable.   |
| PO 32.5   | DTS/DPF 32.5   |
| Communal open space is designed and sited to:   | None are applicable.   |
| in relation to rooftop or elevated gardens, minimise overlooking into habitable room windows or onto the useable private open space of other dwellings     in relation to ground floor communal space, be overlooked by habitable rooms to facilitate passive surveillance. |  |
| Car parking, access   | s and manoeuvrability  |
| PO 33.1   | DTS/DPF 33.1   |
| Driveways and access points are designed and distributed to optimise the provision of on-street visitor parking.  | Where on-street parking is available directly adjacent the site, on-<br>street parking is retained adjacent the subject site in accordance<br>with the following requirements:   |
|   | <ul> <li>(a) minimum 0.33 on-street car parks per proposed dwelling (rounded up to the nearest whole number)</li> <li>(b) minimum car park length of 5.4m where a vehicle can enter or exit a space directly</li> <li>(c) minimum carpark length of 6m for an intermediate space located between two other parking spaces or to an end obstruction where the parking is indented.</li> </ul> |
| PO 33.2   | DTS/DPF 33.2   |
| The number of vehicular access points onto public roads is minimised to reduce interruption of the footpath and positively contribute to public safety and walkability.   | Access to group dwellings or dwellings within a residential flat building is provided via a single common driveway.  |
| PO 33.3   | DTS/DPF 33.3   |
| Residential driveways that service more than one dwelling are designed to allow safe and convenient movement.   | Driveways that service more than 1 dwelling or a dwelling on a battle-axe site:  |
|   | (a) have a minimum width of 3m (b) for driveways servicing more than 3 dwellings: (i) have a width of 5.5m or more and a length of   |

Page 69 of 129 Printed on 5/07/2022

|  | 6m or more at the kerb of the primary street  (ii) where the driveway length exceeds 30m, incorporate a passing point at least every 30 metres with a minimum width of 5.5m and a minimum length of 6m.  |  |  |
|--|--|--|--|
| PO 33.4  Residential driveways that service more than one dwelling or a dwelling on a battle-axe site are designed to allow passenger vehicles to enter and exit and manoeuvre within the site in a safe and convenient manner.                        | DTS/DPF 33.4  Driveways providing access to more than one dwelling, or a dwelling on a battle-axe site, allow a B85 passenger vehicle to enter and exit the garages or parking spaces in no more than a three-point turn manoeuvre.  |  |  |
| PO 33.5  Dwellings are adequately separated from common driveways and manoeuvring areas.   | DTS/DPF 33.5  Dwelling walls with entry doors or ground level habitable room windows are set back at least 1.5m from any driveway or area designated for the movement and manoeuvring of vehicles.   |  |  |
| Soft lan   | dscaping   |  |  |
| PO 34.1  Soft landscaping is provided between dwellings and common driveways to improve the outlook for occupants and appearance of common areas.  | Other than where located directly in front of a garage or building entry, soft landscaping with a minimum dimension of 1m is provided between a dwelling and common driveway.  |  |  |
| P0 34.2  Battle-axe or common driveways incorporate landscaping and permeability to improve appearance and assist in stormwater management.  | Battle-axe or common driveways satisfy (a) and (b):  (a) are constructed of a minimum of 50% permeable or porous material  (b) where the driveway is located directly adjacent the side or rear boundary of the site, soft landscaping with a minimum dimension of 1m is provided between the driveway and site boundary (excluding along the perimeter of a passing point). |  |  |
| Site Facilities  | / Waste Storage  |  |  |
| Provision is made for suitable mailbox facilities close to the major pedestrian entry to the site or conveniently located considering the nature of accommodation and mobility of occupants.   | DTS/DPF 35.1  None are applicable.   |  |  |
| PO 35.2  Provision is made for suitable external clothes drying facilities.  | DTS/DPF 35.2  None are applicable.   |  |  |
| Po 35.3  Provision is made for suitable household waste and recyclable material storage facilities which are:  (a) located away, or screened, from public view, and (b) conveniently located in proximity to dwellings and the waste collection point. | DTS/DPF 35.3  None are applicable.   |  |  |
| PO 35.4  | DTS/DPF 35.4   |  |  |

Page 70 of 129 Printed on 5/07/2022

| Waste and recyclable material storage areas are located away from dwellings.   | Dedicated waste and recyclable material storage areas are located at least 3m from any habitable room window. |
|--|---|
| PO 35.5  | DTS/DPF 35.5  |
| Where waste bins cannot be conveniently collected from the street, provision is made for on-site waste collection, designed to accommodate the safe and convenient access, egress and movement of waste collection vehicles.   | None are applicable.  |
| PO 35.6  | DTS/DPF 35.6  |
| Services including gas and water meters are conveniently located and screened from public view.  | None are applicable.  |
| Water sensitiv   | e urban design  |
| PO 36.1  | DTS/DPF 36.1  |
| Residential development creating a common driveway / access includes stormwater management systems that minimise the discharge of sediment, suspended solids, organic matter, nutrients, bacteria, litter and other contaminants to the stormwater system, watercourses or other water bodies.     | None are applicable.  |
| PO 36.2  | DTS/DPF 36.2  |
| Residential development creating a common driveway / access includes a stormwater management system designed to mitigate peak flows and manage the rate and duration of stormwater discharges from the site to ensure that the development does not increase the peak flows in downstream systems. | None are applicable.  |
| Supported Accommodati  | on and retirement facilities  |
| Siting, Configur   | ation and Design  |
| PO 37.1  | DTS/DPF 37.1  |
| Supported accommodation and housing for aged persons and people with disabilities is located where on-site movement of residents is not unduly restricted by the slope of the land.  | None are applicable.  |
| P0 37.2  | DTS/DPF 37.2  |
| Universal design features are incorporated to provide options for people living with disabilities or limited mobility and / or to facilitate ageing in place.  | None are applicable.  |
| Movement   | and Access  |
| PO 38.1  | DTS/DPF 38.1  |
| Development is designed to support safe and convenient access and movement for residents by providing:   | None are applicable.  |
| ground-level access or lifted access to all units     level entry porches, ramps, paths, driveways, passenger loading areas and areas adjacent to footpaths that allow for the passing of wheelchairs and resting places     car parks with gradients no steeper than 1-in-40, and of              |   |
| sufficient area to provide for wheelchair manoeuvrability (d) kerb ramps at pedestrian crossing points.  |   |

Page 71 of 129 Printed on 5/07/2022

| 39.1   | DTS/DPF 39.1  |
|--|---|
|  | D10/D11 09.1  |
| evelopment is designed to provide attractive, convenient and omfortable indoor and outdoor communal areas to be used by esidents and visitors.   | None are applicable.  |
| 39.2   | DTS/DPF 39.2  |
| rivate open space provision may be substituted for communal pen space which is designed and sited to meet the recreation and amenity needs of residents.   | None are applicable.  |
| 39.3   | DTS/DPF 39.3  |
| ommunal open space is of sufficient size and dimensions to ater for group recreation.  | Communal open space incorporates a minimum dimension of 5 metres. |
| D 39.4   | DTS/DPF 39.4  |
| ommunal open space is designed and sited to:   | None are applicable.  |
| <ul> <li>(a) be conveniently accessed by the dwellings which it services</li> <li>(b) have regard to acoustic, safety, security and wind effects.</li> </ul>   |   |
| 39.5   | DTS/DPF 39.5  |
| ommunal open space contains landscaping and facilities that re functional, attractive and encourage recreational use.  | None are applicable.  |
| O 39.6   | DTS/DPF 39.6  |
| ommunal open space is designed and sited to:   | None are applicable.  |
| <ul> <li>(a) in relation to rooftop or elevated gardens, minimise overlooking into habitable room windows or onto the useable private open space of other dwellings</li> <li>(b) in relation to ground floor communal space, be overlooked by habitable rooms to facilitate passive surveillance.</li> </ul> |   |
| Site Facilities  | s / Waste Storage   |
| O 40.1   | DTS/DPF 40.1  |
| evelopment is designed to provide storage areas for personal ems and specialised equipment such as small electric powered ehicles, including facilities for the recharging of small electricowered vehicles.   | None are applicable.  |
| 0 40.2   | DTS/DPF 40.2  |
| rovision is made for suitable mailbox facilities close to the najor pedestrian entry to the site or conveniently located onsidering the nature of accommodation and mobility of occupants.   | None are applicable.  |
| O 40.3   | DTS/DPF 40.3  |
| rovision is made for suitable external clothes drying facilities.  | None are applicable.  |

Page 72 of 129 Printed on 5/07/2022

pollutants entering stormwater.

| . Siloy2 . Linquity   |   |  |
|---|---|--|
| PO 40.4   | DTS/DPF 40.4  |  |
| Provision is made for suitable household waste and recyclable material storage facilities conveniently located away, or screened, from view.  | None are applicable.  |  |
| PO 40.5   | DTS/DPF 40.5  |  |
| Waste and recyclable material storage areas are located away from dwellings.  | Dedicated waste and recyclable material storage areas are located at least 3m from any habitable room window.   |  |
| PO 40.6   | DTS/DPF 40.6  |  |
| Provision is made for on-site waste collection where 10 or more bins are to be collected at any one time.   | None are applicable.  |  |
| P0 40.7   | DTS/DPF 40.7  |  |
| Services, including gas and water meters, are conveniently located and screened from public view.   | None are applicable.  |  |
| Student Acc   | commodation   |  |
| PO 41.1   | DTS/DPF 41.1  |  |
| Student accommodation is designed to provide safe, secure, attractive, convenient and comfortable living conditions for residents, including an internal layout and facilities that are designed to provide sufficient space and amenity for the requirements of student life and promote social interaction. | (a) a range of living options to meet a variety of accommodation needs, such as one-bedroom, two-bedroom and disability access units (b) common or shared facilities to enable a more efficient use of space, including: (i) shared cooking, laundry and external drying facilities (ii) internal and external communal and private open space provided in accordance with Design in Urban Areas Table 1 - Private Open Space (iii) common storage facilities at the rate of 8m³ for every 2 dwellings or students (iv) common on-site parking in accordance with Transport, Access and Parking Table 1 - General Off-Street Car Parking Requirements or Table 2 - Off-Street Car Parking Requirements in Designated Areas (v) bicycle parking at the rate of one space for every 2 students. |  |
| PO 41.2   | DTS/DPF 41.2  |  |
| Student accommodation is designed to provide easy adaptation of the building to accommodate an alternative use of the building in the event it is no longer required for student housing.   |   |  |
| All non-resider   | tial development  |  |
| Water Sen   | sitive Design   |  |
| PO 42.1   | DTS/DPF 42.1  |  |
| Development likely to result in risk of export of sediment, suspended solids, organic matter, nutrients, oil and grease include stormwater management systems designed to minimise  | None are applicable.  |  |

Page 73 of 129 Printed on 5/07/2022

# Policy24 - Enquiry DTS/DPF 42.2 PO 42.2 Water discharged from a development site is of a physical, None are applicable. chemical and biological condition equivalent to or better than its pre-developed state. PO 42.3 DTS/DPF 42.3 Development includes stormwater management systems to None are applicable. mitigate peak flows and manage the rate and duration of stormwater discharges from the site to ensure that development does not increase peak flows in downstream systems. Wash-down and Waste Loading and Unloading PO 43.1 DTS/DPF 43 1 Areas for activities including loading and unloading, storage of None are applicable. waste refuse bins in commercial and industrial development or wash-down areas used for the cleaning of vehicles, plant or equipment are: (a) designed to contain all wastewater likely to pollute stormwater within a bunded and roofed area to exclude the entry of external surface stormwater run-off (b) paved with an impervious material to facilitate wastewater collection (c) of sufficient size to prevent 'splash-out' or 'over-spray' of wastewater from the wash-down area (d) are designed to drain wastewater to either: a treatment device such as a sediment trap and coalescing plate oil separator with subsequent disposal to a sewer, private or Community Wastewater Management Scheme (ii) a holding tank and its subsequent removal offsite on a regular basis.

Laneway Development

#### Infrastructure and Access

#### PO 44.1

Development with a primary street comprising a laneway, alley, lane, right of way or similar minor thoroughfare only occurs where:

- (a) existing utility infrastructure and services are capable of accommodating the development
- (b) the primary street can support access by emergency and regular service vehicles (such as waste collection)
- (c) it does not require the provision or upgrading of infrastructure on public land (such as footpaths and stormwater management systems)
- (d) safety of pedestrians or vehicle movement is maintained
- (e) any necessary grade transition is accommodated within the site of the development to support an appropriate development intensity and orderly development of land fronting minor thoroughfares.

# DTS/DPF 44.1

Development with a primary street frontage that is not an alley, lane, right of way or similar public thoroughfare.

Page 74 of 129 Printed on 5/07/2022

**Table 1 - Private Open Space** 

| Dwelling Type   | Dwelling / Site Configuration | Minimum Rate   |
|---|-------------------------------|--|
| Dwelling (at ground level, other than<br>a residential flat building that<br>includes above ground dwellings) |                               | Total private open space area:  (a) Site area <301m2: 24m2 located behind the building line.  (b) Site area ≥ 301m2: 60m2 located behind the building line.  Minimum directly accessible from a living room: 16m2 / with a minimum dimension 3m. |
| Cabin or caravan (permanently fixed to the ground) in a residential park or caravan and tourist park          |                               | Total area: 16m <sup>2</sup> , which may be uses as second car parking space, provided on each site intended for residential occupation.   |
| Dwelling in a residential flat building or mixed use building which   | Dwellings at ground level:    | 15m <sup>2</sup> / minimum dimension 3m  |
| incorporate above ground level dwellings  | Dwellings above ground level: |  |
|   | Studio (no separate bedroom)  | 4m <sup>2</sup> / minimum dimension 1.8m   |
|   | One bedroom dwelling          | 8m <sup>2</sup> / minimum dimension 2.1m   |
|   | Two bedroom dwelling          | 11m <sup>2</sup> / minimum dimension 2.4m  |
|   | Three + bedroom dwelling      | 15 m <sup>2</sup> / minimum dimension 2.6m   |

# **Forestry**

# **Assessment Provisions (AP)**

| Desired Outcome |  |  |
|-----------------|--|--|
| DO 1            | Commercial forestry is designed and sited to maximise economic benefits whilst managing potential negative impacts on the environment, transport networks, surrounding land uses and landscapes. |  |

Performance Outcomes (P0) and Deemed-to-Satisfy (DTS) Criteria / Designated Performance Feature (DPF)

| Performance Outcome | Deemed-to-Satisfy Criteria / |
|---------------------|------------------------------|
|                     | Designated Performance       |

Page 75 of 129 Printed on 5/07/2022

|   | Feature  |  |
|---|--|--|
| Si  | ting   |  |
| PO 1.1  | DTS/DPF 1.1  |  |
| Commercial forestry plantations are established where there is no detrimental effect on the physical environment or scenic quality of the rural landscape.  | None are applicable.   |  |
| PO 1.2  | DTS/DPF 1.2  |  |
| Commercial forestry plantations are established on slopes that are stable to minimise the risk of soil erosion.   | Commercial forestry plantations are not located on land with a slope exceeding 20% (1-in-5).   |  |
| PO 1.3  | DTS/DPF 1.3  |  |
| Commercial forestry plantations and operations associated with<br>their establishment, management and harvesting are<br>appropriately set back from any sensitive receiver to minimise<br>fire risk and noise disturbance.        | Commercial forestry plantations and operations associated with their establishment, management and harvesting are set back 50m or more from any sensitive receiver.  |  |
| P0 1.4  | DTS/DPF 1.4  |  |
| Commercial forestry plantations are separated from reserves gazetted under the <i>National Parks and Wildlife Act 1972</i> and/or <i>Wilderness Protection Act 1992</i> to minimise fire risk and potential for weed infestation. | Commercial forestry plantations and operations associated with their establishment, management and harvesting are set back 50m or more from a reserve gazetted under the <i>National Parks</i> and <i>Wildlife Act 1972</i> and/or <i>Wilderness Protection Act 1992</i> .   |  |
| Water P   | Irotection   |  |
| P0 2.1  | DTS/DPF 2.1  |  |
| Commercial forestry plantations incorporate artificial drainage lines (i.e. culverts, runoffs and constructed drains) integrated with natural drainage lines to minimise concentrated water flows onto or from plantation areas.  | None are applicable.   |  |
| PO 2.2  | DTS/DPF 2.2  |  |
| Appropriate siting, layout and design measures are adopted to minimise the impact of commercial forestry plantations on surface water resources.  | Commercial forestry plantations:  (a) do not involve cultivation (excluding spot cultivation) in drainage lines (b) are set back 20m or more from the banks of any major watercourse (a third order or higher watercourse), lake, reservoir, wetland or sinkhole (with direct connection to an aquifer) (c) are set back 10m or more from the banks of any first or second order watercourse or sinkhole ( with no direct connection to an aquifer). |  |
| Fire Mar  | I<br>nagement  |  |
| PO 3.1  | DTS/DPF 3.1  |  |
| Commercial forestry plantations incorporate appropriate firebreaks and fire management design elements.   | Commercial forestry plantations provide:  (a) 7m or more wide external boundary firebreaks for plantations of 40ha or less (b) 10m or more wide external boundary firebreaks for   |  |
|   | plantations of between 40ha and 100ha  (c) 20m or more wide external boundary firebreaks, or 10m with an additional 10m or more of fuel-reduced  |  |

Page 76 of 129 Printed on 5/07/2022

| Policy24 - Enquiry   |   |  |   |
|--|---|--|---|
|  | plantation, for pla   | antations of   | 100ha or greater.   |
| P0 3.2   | DTS/DPF 3.2   |  |   |
| Commercial forestry plantations incorporate appropriate fire management access tracks.                           | (a) are incorporated (b) are 7m or more v more (c) are aligned to pro junctions, or if the appropriately sig turnaround areas   | within all fir<br>wide with a v<br>ovide straigh<br>ey are a no t<br>inposted and<br>s for fire-figh | rertical clearance of 4m or<br>nt through access at<br>through access track are<br>d provide suitable |
| Power-li   | ine Clearances  |  |   |
| Po 4.1  Commercial forestry plantations achieve and maintain appropriate clearances from aboveground powerlines. | DTS/DPF 4.1  Commercial forestry plantations incorporating trees with an expected mature height of greater than 6m meet the clearance requirements listed in the following table: |  |   |
|  | Voltage of transmission line  | Tower or<br>Pole   | Minimum horizontal clearance distance between plantings and transmission lines                        |
|  | 500 kV  | Tower  | 38m   |
|  | 275 kV  | Tower  | 25m   |
|  | 132 kV  | Tower  | 30m   |
|  | 132 kV  | Pole   | 20m   |
|  | 66 kV   | Pole   | 20m   |
|  | Less than 66 kV   | Pole   | 20m   |

# **Housing Renewal**

# **Assessment Provisions (AP)**

| Desired Outcome |   |  |
|-----------------|---|--|
| DO 1            | Renewed residential environments replace older social housing and provide new social housing infrastructure and other housing options and tenures to enhance the residential amenity of the local area. |  |

Performance Outcomes (P0) and Deemed-to-Satisfy (DTS) Criteria / Designated Performance Feature (DPF)

Page 77 of 129 Printed on 5/07/2022

| Performance Outcome  | Deemed-to-Satisfy Criteria /<br>Designated Performance<br>Feature   |  |
|--|---|--|
| Land Use a   | nd Intensity  |  |
| PO 1.1   | DTS/DPF 1.1   |  |
| Residential development provides a range of housing choices.   | Development comprises one or more of the following:  (a) detached dwellings (b) semi-detached dwellings (c) row dwellings (d) group dwellings (e) residential flat buildings.                       |  |
| PO 1.2   | DTS/DPF 1.2   |  |
| Medium-density housing options or higher are located in close proximity to public transit, open space and/or activity centres.   | None are applicable.  |  |
| Building   | g Height  |  |
| PO 2.1   | DTS/DPF 2.1   |  |
| Buildings generally do not exceed 3 building levels unless in locations close to public transport, centres and/or open space.  | Building height (excluding garages, carports and outbuildings) does not exceed 3 building levels and 12m and wall height does not exceed 9m (not including a gable end).                            |  |
| PO 2.2   | DTS/DPF 2.2   |  |
| Medium or high rise residential flat buildings located within or at the interface with zones which restrict heights to a maximum of 2 building levels transition down in scale and height towards the boundary of that zone, other than where it is a street boundary. | • •   |  |
| Primary Str  | I<br>eet Setback  |  |
| PO 3.1   | DTS/DPF 3.1   |  |
| Buildings are set back from the primary street boundary to contribute to an attractive streetscape character.  | Buildings are no closer to the primary street (excluding any balcony, verandah, porch, awning or similar structure) than 3m.  |  |
| Secondary S  | treet Setback   |  |
| PO 4.1   | DTS/DPF 4.1   |  |
| Buildings are set back from secondary street boundaries to maintain separation between building walls and public streets and contribute to a suburban streetscape character.   | Buildings are set back at least 900mm from the boundary of the allotment with a secondary street frontage.  |  |
| Boundary Walls   |   |  |
| PO 5.1   | DTS/DPF 5.1   |  |
| Boundary walls are limited in height and length to manage visual impacts and access to natural light and ventilation.  | Except where the dwelling is located on a central site within a row dwelling or terrace arrangement, dwellings with side boundary walls are sited on only one side boundary and satisfy (a) or (b): |  |

Page 78 of 129 Printed on 5/07/2022

#### (a) adjoin or abut a boundary wall of a building on adjoining land for the same length and height (b) do not: (i) exceed 3.2m in height from the lower of the natural or finished ground level (ii) exceed 11.5m in length when combined with other walls on the boundary of the subject development site, a maximum 45% of the length of the boundary (iv) encroach within 3 metres of any other existing or proposed boundary walls on the subject land. PO 5.2 DTS/DPF 5.2 Dwellings in a semi-detached, row or terrace arrangement Dwellings in a semi-detached or row arrangement are set back maintain space between buildings consistent with a suburban 900mm or more from side boundaries shared with allotments streetscape character. outside the development site, except for a carport or garage. Side Boundary Setback PO 6.1 DTS/DPF 6.1 Buildings are set back from side boundaries to provide: Other than walls located on a side boundary, buildings are set back from side boundaries: (a) separation between dwellings in a way that contributes to a suburban character (a) at least 900mm where the wall height is up to 3m (b) access to natural light and ventilation for neighbours. (b) other than for a wall facing a southern side boundary, at least 900mm plus 1/3 of the wall height above 3m (c) at least 1.9m plus 1/3 of the wall height above 3m for walls facing a southern side boundary. Rear Boundary Setback PO 7.1 DTS/DPF 7.1 Buildings are set back from rear boundaries to provide: Dwellings are set back from the rear boundary: (a) (a) separation between dwellings in a way that contributes 3m or more for the first building level to a suburban character (b) 5m or more for any subsequent building level. (b) access to natural light and ventilation for neighbours (c) private open space (d) space for landscaping and vegetation. Buildings elevation design PO 8.1 DTS/DPF 8.1 Dwelling elevations facing public streets and common driveways Each dwelling includes at least 3 of the following design features make a positive contribution to the streetscape and common within the building elevation facing a primary street, and at least driveway areas. 2 of the following design features within the building elevation facing any other public road (other than a laneway) or a common driveway:

(a) a minimum of 30% of the building elevation is set back an additional 300mm from the building line

(b) a porch or portico projects at least 1m from the building elevation

(c) a balcony projects from the building elevation

(d) a verandah projects at least 1m from the building elevation

(e) eaves of a minimum 400mm width extend along the

Page 79 of 129 Printed on 5/07/2022

|   | width of the front elevation (f) a minimum 30% of the width of the upper level projects  |
|---|--|
|   | forward from the lower level primary building line by at least 300mm.  (g) a minimum of two different materials or finishes are incorporated on the walls of the building elevation, with a maximum of 80% of the building elevation in a single material or finish.           |
| PO 8.2  | DTS/DPF 8.2  |
| Dwellings incorporate windows along primary street frontages to encourage passive surveillance and make a positive contribution to the streetscape.                                       | Each dwelling with a frontage to a public street:  (a) includes at least one window facing the primary street from a habitable room that has a minimum internal room dimension of 2.4m  (b) has an aggregate window area of at least 2m <sup>2</sup> facing the primary street |
| PO 8.3  | DTS/DPF 8.3  |
| The visual mass of larger buildings is reduced when viewed from adjoining allotments or public streets.   | None are applicable.   |
| P0 8.4  | DTS/DPF 8.4  |
| Built form considers local context and provides a quality design response through scale, massing, materials, colours and architectural expression.  | None are applicable.   |
| P0 8.5  | DTS/DPF 8.5  |
| Entrances to multi-storey buildings are:  | None are applicable.   |
| (a) oriented towards the street (b) visible and easily identifiable from the street (c) designed to include a common mail box structure.  |  |
| Outlook a   | nd amenity   |
| PO 9.1  | DTS/DPF 9.1  |
| Living rooms have an external outlook to provide a high standard of amenity for occupants.  | A living room of a dwelling incorporates a window with an external outlook towards the street frontage or private open space.  |
| PO 9.2  | DTS/DPF 9.2  |
| Bedrooms are separated or shielded from active communal recreation areas, common access areas and vehicle parking areas and access ways to mitigate noise and artificial light intrusion. | None are applicable.   |
| Private 0   | pen Space  |
| PO 10.1   | DTS/DPF 10.1   |
| Dwellings are provided with suitable sized areas of usable private open space to meet the needs of occupants.   | Private open space is provided in accordance with the following table:   |
|   | Dwelling Type Dwelling / Site Minimum Rate  Configuration  |

Page 80 of 129 Printed on 5/07/2022

| ĺ  |  |   |  |
|--|--|---|--|
|  | Dwelling (at<br>ground level)                |   | Total area: 24m <sup>2</sup> located behind the building line  Minimum adjacent to a living room: 16m <sup>2</sup> with a minimum dimension 3m |
|  | Dwelling (above ground level)                | Studio  | 4m <sup>2</sup> / minimum<br>dimension 1.8m  |
|  |  | One bedroom<br>dwelling                               | 8m <sup>2</sup> / minimum<br>dimension 2.1m  |
|  |  | Two bedroom<br>dwelling                               | 11m <sup>2</sup> / minimum<br>dimension 2.4m   |
|  |  | Three + bedroom<br>dwelling                           | 15 m <sup>2</sup> / minimum<br>dimension 2.6m  |
| PO 10.2  | DTS/DPF 10.2                                 | •   |  |
| Private open space positioned to provide convenient access from internal living areas.   | At least 50% of the accessible from a        | required area of priva                                | ate open space is  |
| PO 10.3  | DTS/DPF 10.3                                 |   |  |
| Private open space is positioned and designed to:  | None are applicabl                           | e.  |  |
| <ul> <li>(a) provide useable outdoor space that suits the needs of occupants;</li> <li>(b) take advantage of desirable orientation and vistas; and</li> <li>(c) adequately define public and private space.</li> </ul> |  |   |  |
| Visual   | privacy                                      |   |  |
| PO 11.1  | DTS/DPF 11.1                                 |   |  |
| Development mitigates direct overlooking from upper level windows to habitable rooms and private open spaces of adjoining residential uses.  | another residential  (a) are perma           | allotment/site satisf                                 | boundaries shared with y one of the following: height of 1.5m above I or not capable of being  |
|  | opened m<br>(b) have sill he<br>finished fle | ore than 200mm<br>eights greater than or<br>oor level | equal to 1.5m above  |
|  | permanen<br>window su                        | tly fixed no more thar                                | ent to any part of the   |
| P0 11.2  | DTS/DPF 11.2                                 |   |  |
| Development mitigates direct overlooking from upper level  | One of the followin                          | g is satisfied:                                       |  |
| balconies and terraces to habitable rooms and private open space of adjoining residential uses.  |  | t side of the balcony<br>d, public road reserve       | or terrace will face a<br>or public reserve that is  |

Page 81 of 129 Printed on 5/07/2022

Policy24 - Enquiry at least 15m wide in all places faced by the balcony or terrace or (b) all sides of balconies or terraces on upper building levels are permanently obscured by screening with a maximum 25% transparency/openings fixed to a minimum height of: 1.5m above finished floor level where the balcony is located at least 15 metres from the nearest habitable window of a dwelling on adjacent land (ii) 1.7m above finished floor level in all other cases Landscaping DTS/DPF 12.1 PO 12.1 Soft landscaping is incorporated into development to: Residential development incorporates pervious areas for soft landscaping with a minimum dimension of 700mm provided in (a) minimise heat absorption and reflection accordance with (a) and (b): (b) maximise shade and shelter a total area as determined by the following table: (c) maximise stormwater infiltration and biodiversity (d) enhance the appearance of land and streetscapes. Dwelling site area (or in the case of residential Minimum flat building or group dwelling(s), average site percentage area) (m<sup>2</sup>) of site <150 10% <200 15% 200-450 20% >450 25% (b) at least 30% of land between the road boundary and the building line. Water Sensitive Design DTS/DPF 13.1 PO 13.1 Residential development is designed to capture and use None are applicable. stormwater to: (a) maximise efficient use of water resources (b) manage peak stormwater runoff flows and volume to ensure the carrying capacities of downstream systems are not overloaded (c) manage runoff quality to maintain, as close as practical, pre-development conditions. Car Parking DTS/DPF 14.1 PO 14.1 On-site car parking is provided to meet the anticipated demand On-site car parking is provided at the following rates per of residents, with less on-site parking in areas in close proximity dwelling: to public transport. (a) 2 or fewer bedrooms - 1 car parking space

Page 82 of 129 Printed on 5/07/2022

PO 14.2

(b)

DTS/DPF 14.2

3 or more bedrooms - 2 car parking spaces.

| Enclosed car parking spaces are of dimensions to be functional, accessible and convenient.   | Residential parking spaces enclosed by fencing, walls or other obstructions with the following internal dimensions (separate from any waste storage area):  (a) single parking spaces:     (i) a minimum length of 5.4m     (ii) a minimum width of 3.0m     (iii) a minimum garage door width of 2.4m  (b) double parking spaces (side by side):     (i) a minimum length of 5.4m     (ii) a minimum width of 5.5m     (iii) minimum garage door width of 2.4m per space. |
|--|--|
| PO 14.3  | DTS/DPF 14.3   |
| Uncovered car parking spaces are of dimensions to be functional, accessible and convenient.  | Uncovered car parking spaces have:  (a) a minimum length of 5.4m (b) a minimum width of 2.4m (c) a minimum width between the centre line of the space and any fence, wall or other obstruction of 1.5m.  |
| PO 14.4  | DTS/DPF 14.4   |
| Residential flat buildings and group dwelling developments provide sufficient on-site visitor car parking to cater for anticipated demand.   | Visitor car parking for group and residential flat buildings incorporating 4 or more dwellings is provided on-site at a minimum ratio of 0.25 car parking spaces per dwelling.   |
| PO 14.5  | DTS/DPF 14.5   |
| Residential flat buildings provide dedicated areas for bicycle parking.  | Residential flat buildings provide one bicycle parking space per dwelling.   |
| Oversh   | adowing  |
| PO 15.1  | DTS/DPF 15.1   |
| Development minimises overshadowing of the private open spaces of adjoining land by ensuring that ground level open space associated with residential buildings receive direct sunlight for a minimum of 2 hours between 9am and 3pm on 21 June. | None are applicable.   |
| W  | aste   |
| PO 16.1  | DTS/DPF 16.1   |
| Provision is made for the convenient storage of waste bins in a location screened from public view.  | A waste bin storage area is provided behind the primary building line that:  |
| D0.16.2  | (a) has a minimum area of 2m² with a minimum dimension of 900mm (separate from any designated car parking spaces or private open space).; and (b) has a continuous unobstructed path of travel (excluding moveable objects like gates, vehicles and roller doors) with a minimum width of 800mm between the waste bin storage area and the street.   |
| PO 16.2  | DTS/DPF 16.2   |

Page 83 of 129 Printed on 5/07/2022

Residential flat buildings provide a dedicated area for the on-site None are applicable. storage of waste which is: (a) easily and safely accessible for residents and for collection vehicles (b) screened from adjoining land and public roads (c) of sufficient dimensions to be able to accommodate the waste storage needs of the development considering the intensity and nature of the development and the frequency of collection. Vehicle Access PO 17.1 DTS/DPF 17.1 Driveways are located and designed to facilitate safe access and None are applicable. egress while maximising land available for street tree planting, landscaped street frontages and on-street parking. PO 17.2 **DTS/DPF 17.2** Vehicle access is safe, convenient, minimises interruption to the Vehicle access to designated car parking spaces satisfy (a) or operation of public roads and does not interfere with street (b): infrastructure or street trees. is provided via a lawfully existing or authorised access point or an access point for which consent has been granted as part of an application for the division of land (b) where newly proposed, is set back: 0.5m or more from any street furniture, street pole, infrastructure services pit, or other stormwater or utility infrastructure unless consent is provided from the asset owner 2m or more from the base of the trunk of a street tree unless consent is provided from the tree owner for a lesser distance (iii) 6m or more from the tangent point of an intersection of 2 or more roads (iv) outside of the marked lines or infrastructure dedicating a pedestrian crossing. PO 17.3 **DTS/DPF 17.3** Driveways are designed to enable safe and convenient vehicle Driveways are designed and sited so that: movements from the public road to on-site parking spaces. (a) the gradient from the place of access on the boundary of the allotment to the finished floor level at the front of the garage or carport is not more than 1-in-4 on average they are aligned relative to the street so that there is no more than a 20 degree deviation from 90 degrees between the centreline of any dedicated car parking space to which it provides access (measured from the front of that space) and the road boundary. (c) if located so as to provide access from an alley, lane or right of way - the alley, lane or right or way is at least 6.2m wide along the boundary of the allotment / site. PO 17.4 **DTS/DPF 17.4** Driveways and access points are designed and distributed to Where on-street parking is available abutting the site's street optimise the provision of on-street parking. frontage, on-street parking is retained in accordance with the following requirements:

Page 84 of 129 Printed on 5/07/2022

|  | minimum 0.33 on-street spaces per dwelling on the site  (rounded up to the perset whole number)  |
|--|--|
|  | (rounded up to the nearest whole number)  2. Minimum car park length of 5.4m where a vehicle can   |
|  | enter or exit a space directly   |
|  | <ol><li>minimum car park length of 6m for an intermediate<br/>space located between two other parking spaces.</li></ol>  |
| P0 17.5  | DTS/DPF 17.5   |
| Residential driveways that service more than one dwelling of a dimension to allow safe and convenient movement.  | Where on-street parking is available abutting the site's street frontage, on-street parking is retained in accordance with the following requirements:   |
|  | (a) minimum 0.33 on-street spaces per dwelling on the site (rounded up to the nearest whole number)  |
|  | (b) minimum car park length of 5.4m where a vehicle can enter or exit a space directly   |
|  | (c) minimum carpark length of 6m for an intermediate space located between two other parking spaces or to an end obstruction where the parking is indented.  |
| PO 17.6  | DTS/DPF 17.6   |
| Residential driveways that service more than one dwelling are designed to allow passenger vehicles to enter and exit the site and manoeuvre within the site in a safe and convenient manner. | Driveways providing access to more than one dwelling, or a dwelling on a battle-axe site, allow a B85 passenger vehicle to enter and exit the garages or parking spaces in no more than a three-point turn manoeuvre |
| PO 17.7  | DTS/DPF 17.7   |
| Dwellings are adequately separated from common driveways and manoeuvring areas.  | Dwelling walls with entry doors or ground level habitable room windows are set back at least 1.5m from any driveway or area designated for the movement and manoeuvring of vehicles.                                 |
| Sto  | rage   |
| PO 18.1  | DTS/DPF 18.1   |
| Dwellings are provided with sufficient and accessible space for storage to meet likely occupant needs.   | Dwellings are provided with storage at the following rates and 50% or more of the storage volume is provided within the dwelling:  |
|  | (a) studio: not less than 6m <sup>3</sup>  |
|  | (b) 1 bedroom dwelling / apartment: not less than 8m <sup>3</sup>  |
|  | (c) 2 bedroom dwelling / apartment: not less than 10m <sup>3</sup>   |
|  | (d) 3+ bedroom dwelling / apartment: not less than 12m <sup>3</sup> .  |
| Earth  | works  |
| PO 19.1  | DTS/DPF 19.1   |
| Development, including any associated driveways and access tracks, minimises the need for earthworks to limit disturbance to   | The development does not involve:  |
| natural topography.  | (a) excavation exceeding a vertical height of 1m or  |
|  | (b) filling exceeding a vertical height of 1m  |
|  | or   |
|  | (c) a total combined excavation and filling vertical height exceeding 2m.  |
| Service connection   | (c) a total combined excavation and filling vertical height  |

Page 85 of 129 Printed on 5/07/2022

Dwellings are provided with appropriate service connections and infrastructure.

The site and building:

- (a) have the ability to be connected to a permanent potable water supply
- (b) have the ability to be connected to a sewerage system, or a wastewater system approved under the South Australian Public Health Act 2011
- (c) have the ability to be connected to electricity supply
- (d) have the ability to be connected to an adequate water supply (and pressure) for fire-fighting purposes
- (e) would not be contrary to the Regulations prescribed for the purposes of Section 86 of the *Electricity Act 1996*.

Site contamination

### PO 21.1

Land that is suitable for sensitive land uses to provide a safe environment.

#### DTS/DPF 21.1

Development satisfies (a), (b), (c) or (d):

- (a) does not involve a change in the use of land
- (b) involves a change in the use of land that does not constitute a change to a more sensitive use
- (c) involves a change in the use of land to a <u>more sensitive</u> <u>use</u> on land at which <u>site contamination</u> does not exist (as demonstrated in a <u>site contamination declaration</u> form)
- (d) involves a change in the use of land to a <u>more sensitive</u> <u>use</u> on land at which <u>site contamination</u> exists, or may exist (as demonstrated in a site contamination declaration form), and satisfies both of the following:
  - (i) <u>a site contamination audit report</u> has been prepared under Part 10A of the *Environment Protection Act 1993* in relation to the land within the previous 5 years which states that
    - A. <u>site contamination</u> does not exist (or no longer exists) at the land
    - B. the land is suitable for the proposed use or range of uses (without the need for any further <u>remediation</u>)
    - C. where <u>remediation</u> is, or remains, necessary for the proposed use (or range of uses), <u>remediation work</u> has been carried out or will be carried out (and the applicant has provided a written undertaking that the remediation works will be implemented in association with the development)

#### and

(ii) no other <u>class 1 activity</u> or <u>class 2 activity</u> has taken place at the land since the preparation of the site contamination audit report (as demonstrated in a <u>site contamination</u> <u>declaration form</u>).

# Infrastructure and Renewable Energy Facilities

Page 86 of 129 Printed on 5/07/2022

# **Assessment Provisions (AP)**

|      | Desired Outcome   |
|------|---|
| DO 1 | Efficient provision of infrastructure networks and services, renewable energy facilities and ancillary development in a manner that minimises hazard, is environmentally and culturally sensitive and manages adverse visual impacts on natural and rural landscapes and residential amenity. |

Performance Outcomes (PO) and Deemed-to-Satisfy (DTS) Criteria / Designated Performance Feature (DPF)

| Performance Outcome   | Deemed-to-Satisfy Criteria /      |
|---|-----------------------------------|
|   | Designated Performance Feature    |
|   | General                           |
| PO 1.1  | DTS/DPF 1.1                       |
| Development is located and designed to minimise hazard or nuisance to adjacent development and land uses.   | None are applicable.              |
|   | Visual Amenity                    |
| PO 2.1  | DTS/DPF 2.1                       |
| The visual impact of above-ground infrastructure networks and services (excluding high voltage transmission lines), renewable energy facilities (excluding wind farms), energy storage facilities and ancillary development is minimised from townships, scenic routes and public roads by:  (a) utilising features of the natural landscape to obscure views where practicable (b) siting development below ridgelines where practicable (c) avoiding visually sensitive and significant landscapes (d) using materials and finishes with low-reflectivity and colours that complement the surroundings (e) using existing vegetation to screen buildings (f) incorporating landscaping or landscaped mounding around the perimeter of a site and between adjacent allotments accommodating or zoned to primarily accommodate sensitive receivers. | None are applicable.              |
| PO 2.2  Pumping stations, battery storage facilities, maintenance sheds and other ancillary structures incorporate vegetation buffers to reduce adverse visual impacts on adjacent land.  | DTS/DPF 2.2  None are applicable. |

Page 87 of 129 Printed on 5/07/2022

| installation of storage facilities, pipework, penstock, substations and other ancillary plant are reinstated and revegetated to reduce adverse visual impacts on adjacent land.    Rehabilitation  | Policy24 - Enquiry   |                      |
|--|--|----------------------|
| installation of storage facilities, pipework, penstock, substations and other ancillary plant are reinstated and revegetated to reduce adverse visual impacts on adjacent land.  Remahilitation  PO31  Progressive rehabilitation (incorporating revegetation) of disturbed areas, ahead of or upon decommissioning of areas used for renewable energy facilities and transmission corridors.  Hazard Management  PO4.1  Infrastructure and renewable energy facilities and ancillary development located and operated to not adversely impact maritime or air transport safety, including the operation of ports, sirfields and landing strips.  PO4.2  Facilities for energy generation, power storage and transmission are separated as far as practicable from diversity visited public places (such as viewing platforms / lockouts) to reduce risks to public safety from fire or equipment malfunction.  PO4.3  Bushfire hazard risk is minimised for renewable energy facilities by providing appropriate access tracks, safety equipment and water tanks and establishing cleared areas around substations, buttery storage and operations compounds.  Electricity infrastructure is located to minimise visual impacts through techniquese including:  (i) on areas already cleared of native vegetation  (ii) where there is minimal interference or disturbance to existing native vegetation  (iii) where there is minimal interference or disturbance to existing native vegetation or blodiversity  (iv) grouping utility buildings and structures with non-residential development, where practicable. | PO 2.3   | DTS/DPF 2.3          |
| PO3.1 Progressive rehabilitation (incorporating revegetation) of disturbed areas, ahead of or upon decommissioning of areas used for renewable energy facilities and transmission corridors.  Hazard Management PO4.1 Infrastructure and renewable energy facilities and ancillary development located and operated to not adversely impact maritime or aff transport safety, including the operation of ports, airfields and landing strips.  PO4.2 Facilities for energy generation, power storage and transmission are separated as far as practicable from dwellings, tourist accommodation and frequently visited public places (such as viewing platforms / lookouts) to reduce risks to public safety from fire or equipment malfunction.  PO 4.3 Bushfire hazard risk is minimised for renewable energy facilities by providing appropriate access tracks, safety equipment and water tanks and establishing cleared areas around substations, battery storage and operations compounds.  Electricity infrastructure is located to minimise visual impacts through techniques including:  (a) sitting utilities and services:  (b) on areas already cleared of native vegetation  (ii) where there is minimal interference or disturbance to existing native vegetation  (b) grouping utility buildings and structures with non-residential development, where practicable.  | Surfaces exposed by earthworks associated with the installation of storage facilities, pipework, penstock, substations and other ancillary plant are reinstated and revegetated to reduce adverse visual impacts on adjacent land.                 | None are applicable. |
| Progressive rehabilitation (incorporating revegetation) of disturbed areas, ahead of or upon decommissioning of areas used for renewable energy facilities and transmission corridors.    Hazard Management  |  | Rehabilitation       |
| of disturbed areas, ahead of or upon decommissioning of areas used for renewable energy facilities and transmission corridors.  Hazard Management  TS/OPF.4.1  Infrastructure and renewable energy facilities and ancillary development located and operated to not adversely import maritime or air transport safety, including the operation of ports, airfields and landing strips.  DTS/OPF.4.2  Facilities for energy generation, power storage and transmission are separated as far as practicable from dwellings, tourist accommodation and frequently visited public places (such as viewing platforms / lockocuts) to reduce risks to public safety from fire or equipment malfunction.  DTS/OPF.4.3  Bushfire hazard risk is minimised for renewable energy facilities by providing appropriate access tracks, safety equipment and water tanks and establishing cleared areas around substations, battery storage and operations compounds.  Electricity Infrastructure and Battery Storage Facilities  DTS/OPF.5.1  None are applicable.  DTS/OPF.5.1  None are applicable.  DTS/OPF.5.1  None are applicable.  | PO 3.1   | DTS/DPF 3.1          |
| DTS/DPF 4.1 Infrastructure and renewable energy facilities and ancillary development located and operated to not adversely impact maritime or air transport safety, including the operation of ports, airfields and landing strips.  DTS/DPF 4.2 Facilities for energy generation, power storage and transmission are separated as far as practicable from dwellings, tourist accommodation and frequently visited public places (such as viewing platforms / lookouts) to reduce risks to public safety from fire or equipment malfunction.  PO 4.3 Bushfire hazard risk is minimised for renewable energy facilities by providing appropriate access tracks, safety equipment and water tanks and establishing cleared areas around substations, battery storage and operations compounds.  Electricity infrastructure and Battery Storage Facilities  PO 5.1 Electricity infrastructure is located to minimise visual impacts through techniques including:  (a) siting utilities and services:  (b) on areas already cleared of native vegetation  (ii) where there is minimal interference or disturbance to existing native vegetation or biodiversity  (b) grouping utility buildings and structures with non-residential development, where practicable.   | Progressive rehabilitation (incorporating revegetation) of disturbed areas, ahead of or upon decommissioning of areas used for renewable energy facilities and transmission corridors.   | None are applicable. |
| Infrastructure and renewable energy facilities and ancillary development located and operated to not adversely impact maritime or air transport safety, including the operation of ports, airfields and landing strips.  PO 4.2 Facilities for energy generation, power storage and transmission are separated as far as practicable from dwellings, tourist accommodation and frequently visited public places (such as viewing platforms / lookouts) to reduce risks to public safety from fire or equipment malfunction.  PO 4.3  Bushfire hazard risk is minimised for renewable energy facilities by providing appropriate access tracks, safety equipment and water tanks and establishing cleared areas around substations, battery storage and operations compounds.  Electricity infrastructure and Battery Storage Facilities  PO 5.1  Electricity infrastructure is located to minimise visual impacts through techniques including:  (a) siting utilities and services:  (i) on areas already cleared of native vegetation  (ii) where there is minimal interference or disturbance to existing native vegetation or biodiversity  (b) grouping utility buildings and structures with non-residential development, where practicable.  |  | Hazard Management    |
| ancillary development located and operated to not adversely impact maritime or air transport safety, including the operation of ports, airfields and landing strips.  PO 4.2  Facilities for energy generation, power storage and transmission are separated as far as practicable from dwellings, tourist accommodation and frequently visited public places (such as viewing platforms / lookouts) to reduce risks to public safety from fire or equipment malfunction.  PO 4.3  Bushfire hazard risk is minimised for renewable energy facilities by providing appropriate access tracks, safety equipment and water tanks and establishing cleared areas around substations, battery storage and operations compounds.  Electricity Infrastructure and Battery Storage Facilities  DTS/DPF 5.1  Electricity infrastructure is located to minimise visual impacts through techniques including:  (a) siting utilities and services:  (i) on areas already cleared of native vegetation  (ii) where there is minimal interference or disturbance to existing native vegetation or biodiversity  (b) grouping utility buildings and structures with non-residential development, where practicable.   | PO 4.1   | DTS/DPF 4.1          |
| Facilities for energy generation, power storage and transmission are separated as far as practicable from dwellings, tourist accommodation and frequently visited public places (such as viewing platforms / lookouts) to reduce risks to public safety from fire or equipment malfunction.  P0.4.3  Bushfire hazard risk is minimised for renewable energy facilities by providing appropriate access tracks, safety equipment and water tanks and establishing cleared areas around substations, battery storage and operations compounds.  Electricity Infrastructure and Battery Storage Facilities  DTS/DPF.5.1  None are applicable.  P0.5.1  Electricity infrastructure is located to minimise visual impacts through techniques including:  (a) siting utilities and services:  (i) on areas already cleared of native vegetation  (ii) where there is minimal interference or disturbance to existing native vegetation or biodiversity  (b) grouping utility buildings and structures with non-residential development, where practicable.   | Infrastructure and renewable energy facilities and ancillary development located and operated to not adversely impact maritime or air transport safety, including the operation of ports, airfields and landing strips.                            | None are applicable. |
| transmission are separated as far as practicable from dwellings, tourist accommodation and frequently visited public places (such as viewing platforms / lookouts) to reduce risks to public safety from fire or equipment malfunction.  PO 4.3  Bushfire hazard risk is minimised for renewable energy facilities by providing appropriate access tracks, safety equipment and water tanks and establishing cleared areas around substations, battery storage and operations compounds.  Electricity Infrastructure and Battery Storage Facilities  PO 5.1  Electricity infrastructure is located to minimise visual impacts through techniques including:  (a) siting utilities and services:  (i) on areas already cleared of native vegetation  (ii) where there is minimal interference or disturbance to existing native vegetation or biodiversity  (b) grouping utility buildings and structures with non-residential development, where practicable.  | PO 4.2   | DTS/DPF 4.2          |
| Bushfire hazard risk is minimised for renewable energy facilities by providing appropriate access tracks, safety equipment and water tanks and establishing cleared areas around substations, battery storage and operations compounds.    Electricity Infrastructure and Battery Storage Facilities   |  | None are applicable. |
| facilities by providing appropriate access tracks, safety equipment and water tanks and establishing cleared areas around substations, battery storage and operations compounds.    Electricity Infrastructure and Battery Storage Facilities  | PO 4.3   | DTS/DPF 4.3          |
| Electricity infrastructure is located to minimise visual impacts through techniques including:  (a) siting utilities and services:  (i) on areas already cleared of native vegetation  (ii) where there is minimal interference or disturbance to existing native vegetation or biodiversity  (b) grouping utility buildings and structures with non-residential development, where practicable.   | areas around substations, battery storage and  | None are applicable. |
| Electricity infrastructure is located to minimise visual impacts through techniques including:  (a) siting utilities and services:  (i) on areas already cleared of native vegetation  (ii) where there is minimal interference or disturbance to existing native vegetation or biodiversity  (b) grouping utility buildings and structures with non-residential development, where practicable.   | I Electricity Infrastructure and Battery Storage Facilities  |                      |
| impacts through techniques including:  (a) siting utilities and services:  (i) on areas already cleared of native vegetation  (ii) where there is minimal interference or disturbance to existing native vegetation or biodiversity  (b) grouping utility buildings and structures with non-residential development, where practicable.  | PO 5.1   | DTS/DPF 5.1          |
| (i) on areas already cleared of native vegetation  (ii) where there is minimal interference or disturbance to existing native vegetation or biodiversity  (b) grouping utility buildings and structures with non-residential development, where practicable.   | Electricity infrastructure is located to minimise visual impacts through techniques including:   | None are applicable. |
|  | (i) on areas already cleared of native vegetation     (ii) where there is minimal interference or disturbance to existing native vegetation or biodiversity  (b) grouping utility buildings and structures with non-residential development, where |                      |
|  | PO 5.2   | DTS/DPF 5.2          |

Page 88 of 129 Printed on 5/07/2022

| Policy24 - Enquiry  |                             |
|---|-----------------------------|
| Electricity supply (excluding transmission lines) serving new development in urban areas and townships installed underground, excluding lines having a capacity exceeding or equal to 33kV.   | None are applicable.        |
| PO 5.3  | DTS/DPF 5.3                 |
| Battery storage facilities are co-located with substation infrastructure where practicable to minimise the development footprint and reduce environmental impacts.  | None are applicable.        |
| Te  | elecommunication Facilities |
| PO 6.1  | DTS/DPF 6.1                 |
| The proliferation of telecommunications facilities in the form of towers/monopoles in any one locality is managed, where technically feasible, by co-locating a facility with other communications facilities to mitigate impacts from clutter on visual amenity.                     | None are applicable.        |
| PO 6.2  | DTS/DPF 6.2                 |
| Telecommunications antennae are located as close as practicable to support structures to manage overall bulk and mitigate impacts on visual amenity.  | None are applicable.        |
| D0.60   | DTO/DDF CO                  |
| Telecommunications facilities, particularly towers/monopoles, are located and sized to mitigate visual impacts by the following methods:  | None are applicable.        |
| (a) where technically feasible, incorporating the facility within an existing structure that may serve another purpose  |                             |
| or all of the following:  |                             |
| (b) using existing buildings and landscape features to obscure or interrupt views of a facility from nearby public roads, residential areas and places of high public amenity to the extent practical without unduly hindering the effective provision of telecommunications services |                             |
| (c) using materials and finishes that complement  |                             |
| the environment  (d) screening using landscaping and vegetation, particularly for equipment shelters and huts.  |                             |
| Renewable Energy Facilities   |                             |
| PO 7.1  | DTS/DPF 7.1                 |
| Renewable energy facilities are located as close as practicable to existing transmission infrastructure to facilitate connections and minimise environmental impacts as a result of extending transmission infrastructure.  | None are applicable.        |

Page 89 of 129 Printed on 5/07/2022

| PO 8.1   | DTS/DPF 8.1   |
|--|---|
| Visual impact of wind turbine generators on the amenity of residential and tourist development is reduced  | Wind turbine generators are:  |
| through appropriate separation.  | (a) set back at least 2000m from the base of a turbine to any of the following zones:  (i) Rural Settlement Zone  (ii) Township Zone  (iii) Rural Living Zone  (iv) Rural Neighbourhood Zone  with an additional 10m setback per additional metre over 150m overall turbine height (measured from the base of the turbine).  (b) set back at least 1500m from the base of the turbine to non-associated (non-stakeholder) dwellings and tourist accommodation |
| PO 8.2   | DTS/DPF 8.2   |
| The visual impact of wind turbine generators on natural landscapes is managed by:  | None are applicable.  |
| <ul> <li>(a) designing wind turbine generators to be uniform in colour, size and shape</li> <li>(b) coordinating blade rotation and direction</li> <li>(c) mounting wind turbine generators on tubular towers as opposed to lattice towers.</li> </ul> |   |
| PO 8.3   | DTS/DPF 8.3   |
| Wind turbine generators and ancillary development minimise potential for bird and bat strike.  | None are applicable.  |
| PO 8.4   | DTS/DPF 8.4   |
| Wind turbine generators incorporate recognition systems or physical markers to minimise the risk to aircraft operations.   | No Commonwealth air safety (CASA / ASA) or Defence requirement is applicable.   |
| PO 8.5   | DTS/DPF 8.5   |
| Meteorological masts and guidewires are identifiable to aircraft through the use of colour bands, marker balls, high visibility sleeves or flashing strobes.   | None are applicable.  |
| Renewab  | le Energy Facilities (Solar Power)  |
| PO 9.1   | DTS/DPF 9.1   |
| Ground mounted solar power facilities generating 5MW or more are not located on land requiring the clearance of areas of intact native vegetation or on land of high environmental, scenic or cultural value.  | None are applicable.  |
| PO 9.2   | DTS/DPF 9.2   |
| Ground mounted solar power facilities allow for movement of wildlife by:   | None are applicable.  |
| (a) incorporating wildlife corridors and habitat refuges   |   |

Page 90 of 129 Printed on 5/07/2022

avoiding the use of extensive security or perimeter fencing or incorporating fencing that enables the passage of small animals without unreasonably compromising the security of the facility. PO 9.3 DTS/DPF 9.3 Amenity impacts of solar power facilities are minimised Ground mounted solar power facilities are set back from land boundaries, through separation from conservation areas and conservation areas and relevant zones in accordance with the following sensitive receivers in other ownership. criteria: Generation **Approximate** Setback Setback Setback from Capacity size of array from from Township, adjoining conservation Rural land areas Settlement. boundary Rural Neighbourhood and Rural Living Zones<sup>1</sup> 500m 50MW> 80ha+ 30m 2km 10MW<50MW 16ha-<80ha 25m 500m 1.5km 5MW<10MW 8ha to <16ha 20m 500m 1km 1MW<5MW 1.6ha to 15m 500m 500m <8ha 100kW<1MW 0.5ha<1.6ha 10m 500m 100m <100kW <0.5ha 500m 25m 5m Notes: 1. Does not apply when the site of the proposed ground mounted solar power facility is located within one of these zones. PO 9.4 DTS/DPF 9.4 Ground mounted solar power facilities incorporate None are applicable. landscaping within setbacks from adjacent road frontages and boundaries of adjacent allotments accommodating non-host dwellings, where balanced with infrastructure access and bushfire safety considerations. Hydropower / Pumped Hydropower Facilities PO 10.1 DTS/DPF 10.1 Hydropower / pumped hydropower facility storage is None are applicable. designed and operated to minimise the risk of storage dam failure.

Page 91 of 129 Printed on 5/07/2022

#### PO 10.2 DTS/DPF 10.2 Hydropower / pumped hydropower facility storage is None are applicable. designed and operated to minimise water loss through increased evaporation or system leakage, with the incorporation of appropriate liners, dam covers, operational measures or detection systems. PO 10.3 DTS/DPF 10.3 Hydropower / pumped hydropower facilities on existing None are applicable. or former mine sites minimise environmental impacts from site contamination, including from mine operations or water sources subject to such processes, now or in the future. Water Supply PO 11.1 DTS/DPF 11.1 Development is connected to an appropriate water Development is connected, or will be connected, to a reticulated water supply to meet the ongoing requirements of the scheme or mains water supply with the capacity to meet the on-going intended use. requirements of the development. PO 11.2 DTS/DPF 11.2 Dwellings are connected to a reticulated water scheme A dwelling is connected, or will be connected, to a reticulated water or mains water supply with the capacity to meet the scheme or mains water supply with the capacity to meet the requirements requirements of the intended use. Where this is not of the development. Where this is not available it is serviced by a rainwater available an appropriate rainwater tank or storage tank or tanks capable of holding at least 50,000 litres of water which is: system for domestic use is provided. (a) exclusively for domestic use (b) connected to the roof drainage system of the dwelling. Wastewater Services PO 12.1 DTS/DPF 12.1 Development is connected to an approved common Development is connected, or will be connected, to an approved common wastewater disposal service with the capacity to meet wastewater disposal service with the capacity to meet the requirements the requirements of the intended use. Where this is not of the development. Where this is not available it is instead capable of available an appropriate on-site service is provided to being serviced by an on-site waste water treatment system in accordance with the following: meet the ongoing requirements of the intended use in accordance with the following: (a) the system is wholly located and contained within the allotment of (a) it is wholly located and contained within the development it will service; and allotment of the development it will service (b) the system will comply with the requirements of the South Australian Public Health Act 2011. (b) in areas where there is a high risk of contamination of surface, ground, or marine water resources from on-site disposal of liquid wastes, disposal systems are included to minimise the risk of pollution to those water resources (c) septic tank effluent drainage fields and other wastewater disposal areas are located away from watercourses and flood prone, sloping, saline or poorly drained land to minimise environmental harm. PO 12.2 DTS/DPF 12.2 Effluent drainage fields and other wastewater disposal Development is not built on, or encroaches within, an area that is, or will be, required for a sewerage system or waste control system. areas are maintained to ensure the effective operation

Page 92 of 129 Printed on 5/07/2022

| of waste systems and minimise risks to human health and the environment.   |  |
|--|--|
|  | Temporary Facilities   |
| PO 13.1  | DTS/DPF 13.1   |
| In rural and remote locations, development that is likely to generate significant waste material during construction, including packaging waste, makes provision for a temporary on-site waste storage enclosure to minimise the incidence of wind-blown litter. | A waste collection and disposal service is used to dispose of the volume of waste at the rate it is generated. |
| PO 13.2  | DTS/DPF 13.2   |
| Temporary facilities to support the establishment of renewable energy facilities (including borrow pits, concrete batching plants, laydown, storage, access roads and worker amenity areas) are sited and operated to minimise environmental impact.             | None are applicable.   |

# Intensive Animal Husbandry and Dairies

#### **Assessment Provisions (AP)**

| Desired Outcome |   |  |
|-----------------|---|--|
| DO 1            | Development of intensive animal husbandry and dairies in locations that are protected from encroachment by sensitive receivers and in a manner that minimises their adverse effects on amenity and the environment. |  |

Performance Outcomes (PO) and Deemed-to-Satisfy (DTS) Criteria / Designated Performance Feature (DPF)

| Performance Outcome   | Deemed-to-Satisfy Criteria /<br>Designated Performance<br>Feature |
|---|---|
| Siting at   | nd Design   |
| PO 1.1  Intensive animal husbandry, dairies and associated activities are sited, designed, constructed and managed to not unreasonably impact on the environment or amenity of the locality.                    | DTS/DPF 1.1  None are applicable.                                 |
| PO 1.2  Intensive animal husbandry, dairies and associated activities are sited, designed, constructed and managed to prevent the potential transmission of disease to other operations where animals are kept. | DTS/DPF 1.2  None are applicable.                                 |

Page 93 of 129 Printed on 5/07/2022

| Policy24 - Enquiry  |  |  |
|---|--|--|
| P0 1.3  | DTS/DPF 1.3  |  |
| Intensive animal husbandry and associated activities such as wastewater lagoons and liquid/solid waste disposal areas are sited, designed, constructed and managed to not unreasonably impact on sensitive receivers in other ownership in terms of noise and air emissions.  | None are applicable.   |  |
| PO 1.4  | DTS/DPF 1.4  |  |
| Dairies and associated activities such as wastewater lagoons and liquid/solid waste disposal areas are sited, designed, constructed and managed to not unreasonably impact on sensitive receivers in other ownership in terms of noise and air emissions.   | Dairies, associated wastewater lagoon(s) and liquid/solid waste storage and disposal facilities are located 500m or more from the nearest sensitive receiver in other ownership.   |  |
| PO 1.5  | DTS/DPF 1.5  |  |
| Lagoons for the storage or treatment of milking shed effluent is adequately separated from roads to minimise impacts from odour on the general public.  | Lagoons for the storage or treatment of milking shed effluent are set back 20m or more from public roads.  |  |
| Wa  | iste   |  |
| PO 2.1  | DTS/DPF 2.1  |  |
| Storage of manure, used litter and other wastes (other than waste water lagoons) is sited, designed, constructed and managed to:  (a) avoid attracting and harbouring vermin (b) avoid polluting water resources (c) be located outside 1% AEP flood event areas.   | None are applicable.   |  |
| Soil and Wat  | er Protection  |  |
| PO 3.1  | DTS/DPF 3.1  |  |
| To avoid environmental harm and adverse effects on water resources, intensive animal husbandry operations are appropriately set back from:  (a) public water supply reservoirs (b) major watercourses (third order or higher stream) (c) any other watercourse, bore or well used for domestic or stock water supplies. | Intensive animal husbandry operations are set back:  (a) 800m or more from a public water supply reservoir (b) 200m or more from a major watercourse (third order or higher stream)  (c) 100m or more from any other watercourse, bore or well |  |
| PO 3.2  | DTS/DPF 3.2  |  |
| Intensive animal husbandry operations and dairies incorporate appropriately designed effluent and run-off facilities that:  | None are applicable.   |  |
| (a) have sufficient capacity to hold effluent and runoff from the operations on site  |  |  |
| (b) ensure effluent does not infiltrate and pollute<br>groundwater, soil or other water resources.  |  |  |

#### **Interface between Land Uses**

#### **Assessment Provisions (AP)**

Page 94 of 129 Printed on 5/07/2022

# **Desired Outcome**

DO 1

Development is located and designed to mitigate adverse effects on or from neighbouring and proximate land uses.

Deemed-to-Satisfy Criteria /

Performance Outcomes (PO) and Deemed-to-Satisfy (DTS) Criteria / Designated Performance Feature (DPF)

**Performance Outcome** 

#### **Designated Performance Feature** General Land Use Compatibility PO 1.1 DTS/DPF 1.1 Sensitive receivers are designed and sited to protect residents None are applicable. and occupants from adverse impacts generated by lawfully existing land uses (or lawfully approved land uses) and land uses desired in the zone. PO 1.2 DTS/DPF 1.2 Development adjacent to a site containing a sensitive receiver (or None are applicable. lawfully approved sensitive receiver) or zone primarily intended to accommodate sensitive receivers is designed to minimise adverse impacts. Hours of Operation DTS/DPF 2.1 PO 2 1 Non-residential development does not unreasonably impact the Development operating within the following hours: amenity of sensitive receivers (or lawfully approved sensitive receivers) or an adjacent zone primarily for sensitive receivers **Class of Development** Hours of operation through its hours of operation having regard to: (a) the nature of the development Consulting room 7am to 9pm, Monday to Friday (b) measures to mitigate off-site impacts 8am to 5pm, Saturday (c) the extent to which the development is desired in the (d) measures that might be taken in an adjacent zone Office 7am to 9pm, Monday to Friday primarily for sensitive receivers that mitigate adverse impacts without unreasonably compromising the 8am to 5pm, Saturday intended use of that land. Shop, other than any 7am to 9pm, Monday to Friday one or combination of 8am to 5pm, Saturday and Sunday the following: (a) restaurant (b) cellar door in the Productive Rural Landscape Zone, Rural

Page 95 of 129 Printed on 5/07/2022

| Policy24 - Enquiry  |   |
|---|---|
|   | Zone or Rural<br>Horticulture<br>Zone   |
| Oversh  | adowing   |
| PO 3.1  | DTS/DPF 3.1   |
| Overshadowing of habitable room windows of adjacent residential land uses in:  a. a neighbourhood-type zone is minimised to maintain access to direct winter sunlight  b. other zones is managed to enable access to direct winter sunlight.  | North-facing windows of habitable rooms of adjacent residential land uses in a neighbourhood-type zone receive at least 3 hours of direct sunlight between 9.00am and 3.00pm on 21 June.  |
| PO 3.2  | DTS/DPF 3.2   |
| Overshadowing of the primary area of private open space or communal open space of adjacent residential land uses in:  a. a neighbourhood type zone is minimised to maintain access to direct winter sunlight  b. other zones is managed to enable access to direct winter sunlight. | Development maintains 2 hours of direct sunlight between 9.00 am and 3.00 pm on 21 June to adjacent residential land uses in a neighbourhood-type zone in accordance with the following:  a. for ground level private open space, the smaller of the following:  i. half the existing ground level open space or  ii. 35m2 of the existing ground level open space (with at least one of the area's dimensions measuring 2.5m)  b. for ground level communal open space, at least half of the existing ground level open space. |
| PO 3.3  | DTS/DPF 3.3   |
| Development does not unduly reduce the generating capacity of adjacent rooftop solar energy facilities taking into account:  (a) the form of development contemplated in the zone   | None are applicable.  |
| (b) the orientation of the solar energy facilities (c) the extent to which the solar energy facilities are already overshadowed.  |   |
| PO 3.4  | DTS/DPF 3.4   |
| Development that incorporates moving parts, including windmills and wind farms, are located and operated to not cause unreasonable nuisance to nearby dwellings and tourist accommodation caused by shadow flicker.   | None are applicable.  |
| Activities Generatin  | g Noise or Vibration  |
| PO 4.1  | DTS/DPF 4.1   |
| Development that emits noise (other than music) does not unreasonably impact the amenity of sensitive receivers (or lawfully approved sensitive receivers).   | Noise that affects sensitive receivers achieves the relevant Environment Protection (Noise) Policy criteria.  |
| PO 4.2  | DTS/DPF 4.2   |
| Areas for the on-site manoeuvring of service and delivery vehicles, plant and equipment, outdoor work spaces (and the like) are designed and sited to not unreasonably impact the   | None are applicable.  |

Page 96 of 129 Printed on 5/07/2022

amenity of adjacent sensitive receivers (or lawfully approved sensitive receivers) and zones primarily intended to accommodate sensitive receivers due to noise and vibration by adopting techniques including: (a) locating openings of buildings and associated services away from the interface with the adjacent sensitive receivers and zones primarily intended to accommodate sensitive receivers (b) when sited outdoors, locating such areas as far as practicable from adjacent sensitive receivers and zones primarily intended to accommodate sensitive receivers (c) housing plant and equipment within an enclosed structure or acoustic enclosure (d) providing a suitable acoustic barrier between the plant and / or equipment and the adjacent sensitive receiver boundary or zone. PO 4.3 DTS/DPF 4.3 Fixed plant and equipment in the form of pumps and/or filtration The pump and/or filtration system ancillary to a dwelling erected systems for a swimming pool or spa are positioned and/or on the same site is: housed to not cause unreasonable noise nuisance to adjacent enclosed in a solid acoustic structure located at least sensitive receivers (or lawfully approved sensitive receivers). 5m from the nearest habitable room located on an adjoining allotment or (b) located at least 12m from the nearest habitable room located on an adjoining allotment. PO 4.4 DTS/DPF 4.4 External noise into bedrooms is minimised by separating or Adjacent land is used for residential purposes. shielding these rooms from service equipment areas and fixed noise sources located on the same or an adjoining allotment. PO 4.5 DTS/DPF 4.5 Outdoor areas associated with licensed premises (such as beer None are applicable. gardens or dining areas) are designed and/or sited to not cause unreasonable noise impact on existing adjacent sensitive receivers (or lawfully approved sensitive receivers). PO 4.6 DTS/DPF 4.6 Development incorporating music achieves suitable acoustic Development incorporating music includes noise attenuation amenity when measured at the boundary of an adjacent sensitive measures that will achieve the following noise levels: receiver (or lawfully approved sensitive receiver) or zone primarily intended to accommodate sensitive receivers. **Assessment location** Music noise level Externally at the Less than 8dB above the level of nearest existing or background noise (L<sub>90.15min</sub>) in envisaged noise any octave band of the sound sensitive location spectrum (LOCT10,15 < LOCT90,15 + 8dB)Air Quality PO 5.1 DTS/DPF 5.1 Development with the potential to emit harmful or nuisance-None are applicable.

Page 97 of 129 Printed on 5/07/2022

| Policy24 - Enquiry  |  |
|---|--|
| generating air pollution incorporates air pollution control measures to prevent harm to human health or unreasonably impact the amenity of sensitive receivers (or lawfully approved sensitive receivers) within the locality and zones primarily intended to accommodate sensitive receivers.    |  |
| PO 5.2  | DTS/DPF 5.2  |
| Development that includes chimneys or exhaust flues (including cafes, restaurants and fast food outlets) is designed to minimise nuisance or adverse health impacts to sensitive receivers (or lawfully approved sensitive receivers) by:   | None are applicable.   |
| <ul> <li>(a) incorporating appropriate treatment technology before exhaust emissions are released</li> <li>(b) locating and designing chimneys or exhaust flues to maximise the dispersion of exhaust emissions, taking into account the location of sensitive receivers.</li> </ul>              |  |
| Light   | Spill  |
| PO 6.1  External lighting is positioned and designed to not cause unreasonable light spill impact on adjacent sensitive receivers (or lawfully approved sensitive receivers).   | DTS/DPF 6.1  None are applicable.  |
| PO 6.2  | DTS/DPF 6.2  |
| External lighting is not hazardous to motorists and cyclists.   | None are applicable.   |
| Solar Reflec  | tivity / Glare   |
| Development is designed and comprised of materials and finishes that do not unreasonably cause a distraction to adjacent road users and pedestrian areas or unreasonably cause heat loading and micro-climatic impacts on adjacent buildings and land uses as a result of reflective solar glare. | DTS/DPF 7.1  None are applicable.  |
| Electrical In   | nterference  |
| PO 8.1  | DTS/DPF 8.1  |
| Development in rural and remote areas does not unreasonably diminish or result in the loss of existing communication services due to electrical interference.   | (a) is no greater than 10m in height, measured from existing ground level or (b) is not within a line of sight between a fixed transmitter and fixed receiver (antenna) other than where an alternative service is available via a different fixed transmitter or cable. |
| Interface with  | Rural Activities   |
| PO 9.1  | DTS/DPF 9.1  |
| Sensitive receivers are located and designed to mitigate impacts from lawfully existing horticultural and farming activities (or lawfully approved horticultural and farming activities), including spray drift and noise and do not prejudice the continued operation of these activities.       | None are applicable.   |

Page 98 of 129 Printed on 5/07/2022

| PO 9.2   | DTS/DPF 9.2   |  |
|--|---|--|
| Sensitive receivers are located and designed to mitigate potential impacts from lawfully existing intensive animal husbandry activities and do not prejudice the continued operation of these activities.  | None are applicable.  |  |
| PO 9.3   | DTS/DPF 9.3   |  |
| Sensitive receivers are located and designed to mitigate potential impacts from lawfully existing land-based aquaculture activities and do not prejudice the continued operation of these activities.  | Sensitive receivers are located at least 200m from the boundary of a site used for land-based aquaculture and associated components in other ownership.   |  |
| PO 9.4   | DTS/DPF 9.4   |  |
| Sensitive receivers are located and designed to mitigate potential impacts from lawfully existing dairies including associated wastewater lagoons and liquid/solid waste storage and disposal facilities and do not prejudice the continued operation of these activities.   | Sensitive receivers are sited at least 500m from the boundary of a site used for a dairy and associated wastewater lagoon(s) and liquid/solid waste storage and disposal facilities in other ownership.   |  |
| PO 9.5   | DTS/DPF 9.5   |  |
| Sensitive receivers are located and designed to mitigate the potential impacts from lawfully existing facilities used for the handling, transportation and storage of bulk commodities (recognising the potential for extended hours of operation) and do not prejudice the continued operation of these activities. | Sensitive receivers are located away from the boundary of a site used for the handling, transportation and/or storage of bulk commodities in other ownership in accordance with the following:  (a) 300m or more, where it involves the handling of agricultural crop products, rock, ores, minerals, petroleum products or chemicals to or from any commercial storage facility  (b) 300m or more, where it involves the handling of agricultural crop products, rock, ores, minerals, petroleum products or chemicals at a wharf or wharf side facility (including sea-port grain terminals) where the handling of these materials into or from vessels does not exceed 100 tonnes per day  (c) 500m or more, where it involves the storage of bulk petroleum in individual containers with a capacity up to 200 litres and a total on-site storage capacity not exceeding 1000 cubic metres  (d) 500m or more, where it involves the handling of coal with a capacity up to 1 tonne per day or a storage capacity up to 50 tonnes  (e) 1000m or more, where it involves the handling of coal with a capacity exceeding 1 tonne per day but not exceeding 100 tonnes per day or a storage capacity exceeding 50 tonnes but not exceeding 5000 tonnes. |  |
| PO 9.6   | DTS/DPF 9.6   |  |
| Setbacks and vegetation plantings along allotment boundaries should be incorporated to mitigate the potential impacts of spray drift and other impacts associated with agricultural and horticultural activities.  | None are applicable.  |  |
| PO 9.7   | DTS/DPF 9.7   |  |
| Urban development does not prejudice existing agricultural and horticultural activities through appropriate separation and design  | None are applicable.  |  |

Page 99 of 129 Printed on 5/07/2022

| techniques.   |   |  |
|---|---|--|
| Interface with Mines and Quarries (Rural and Remote Areas)  |   |  |
| PO 10.1   | DTS/DPF 10.1  |  |
| Sensitive receivers are separated from existing mines to minimise the adverse impacts from noise, dust and vibration. | Sensitive receivers are located no closer than 500m from the boundary of a Mining Production Tenement under the <i>Mining Act</i> 1971. |  |

# **Land Division**

#### **Assessment Provisions (AP)**

|      | Desired Outcome |   |  |
|------|-----------------|---|--|
| DO 1 | Land o          | livision:   |  |
|      | (a)             | creates allotments with the appropriate dimensions and shape for their intended use   |  |
|      | (b)             | allows efficient provision of new infrastructure and the optimum use of underutilised infrastructure  |  |
|      | (c)             | integrates and allocates adequate and suitable land for the preservation of site features of value, including significant vegetation, watercourses, water bodies and other environmental features |  |
|      | (d)             | facilitates solar access through allotment orientation  |  |
|      | (e)             | creates a compact urban form that supports active travel, walkability and the use of public transport   |  |
|      | (f)             | avoids areas of high natural hazard risk.   |  |

| Performance Outcome  | Deemed-to-Satisfy Criteria /<br>Designated Performance<br>Feature  |
|--|--|
| All land   | division   |
| Allotment of   | configuration  |
| PO 1.1   | DTS/DPF 1.1  |
| Land division creates allotments suitable for their intended use.  | Division of land satisfies (a) or (b):  (a) reflects the site boundaries illustrated and approved in an operative or existing development authorisation for residential development under the Development Act 1993 or Planning, Development and Infrastructure Act 2016 where the allotments are used or are proposed to be used solely for residential purposes  (b) is proposed as part of a combined land division application with deemed-to-satisfy dwellings on the proposed allotments. |
| PO 1.2  Land division considers the physical characteristics of the land, preservation of environmental and cultural features of value and the prevailing context of the locality. | DTS/DPF 1.2  None are applicable.  |

Page 100 of 129 Printed on 5/07/2022

| Design a  | nd Layout            |
|---|----------------------|
| PO 2.1  | DTS/DPF 2.1          |
| Land division results in a pattern of development that minimises the likelihood of future earthworks and retaining walls.                               | None are applicable. |
| PO 2.2  | DTS/DPF 2.2          |
| Land division enables the appropriate management of interface impacts between potentially conflicting land uses and/or zones.                           | None are applicable. |
| PO 2.3  | DTS/DPF 2.3          |
| Land division maximises the number of allotments that face public open space and public streets.  | None are applicable. |
| PO 2.4  | DTS/DPF 2.4          |
| Land division is integrated with site features, adjacent land uses, the existing transport network and available infrastructure.                        | None are applicable. |
| PO 2.5  | DTS/DPF 2.5          |
| Development and infrastructure is provided and staged in a manner that supports an orderly and economic provision of land, infrastructure and services. | None are applicable. |
| PO 2.6  | DTS/DPF 2.6          |
| Land division results in watercourses being retained within open space and development taking place on land not subject to flooding.                    | None are applicable. |
| PO 2.7  | DTS/DPF 2.7          |
| Land division results in legible street patterns connected to the surrounding street network.   | None are applicable. |
| PO 2.8  | DTS/DPF 2.8          |
| Land division is designed to preserve existing vegetation of value including native vegetation and regulated and significant trees.                     | None are applicable. |
| Roads ar  | nd Access            |
| PO 3.1  | DTS/DPF 3.1          |
| Land division provides allotments with access to an all-weather public road.  | None are applicable. |
| P0 3.2  | DTS/DPF 3.2          |
| Street patterns and intersections are designed to enable the safe and efficient movement of pedestrian, cycle and vehicular traffic.                    | None are applicable. |
| PO 3.3  | DTS/DPF 3.3          |
| Land division does not impede access to publicly owned open space and/or recreation facilities.   | None are applicable. |
| PO 3.4  | DTS/DPF 3.4          |
| Road reserves provide for safe and convenient movement and parking of projected volumes of vehicles and allow for the                                   | None are applicable. |

Page 101 of 129 Printed on 5/07/2022

| efficient movement of service and emergency vehicles.  |  |
|--|--|
| PO 3.5   | DTS/DPF 3.5  |
| Road reserves are designed to accommodate pedestrian and cycling infrastructure, street tree planting, landscaping and street furniture.     | None are applicable.   |
| PO 3.6   | DTS/DPF 3.6  |
| Road reserves accommodate stormwater drainage and public utilities.  | None are applicable.   |
| PO 3.7   | DTS/DPF 3.7  |
| Road reserves provide unobstructed vehicular access and egress to and from individual allotments and sites.                                  | None are applicable.   |
| PO 3.8   | DTS/DPF 3.8  |
| Street patterns and intersections are designed to enable the safe and efficient movement of pedestrian, cycle and vehicular traffic.         | None are applicable.   |
| PO 3.9   | DTS/DPF 3.9  |
| Roads, open space and thoroughfares provide safe and convenient linkages to the surrounding open space and transport network.                | None are applicable.   |
| PO 3.10  | DTS/DPF 3.10   |
| Public streets are designed to enable tree planting to provide shade and enhance the amenity of streetscapes.                                | None are applicable.   |
| PO 3.11  | DTS/DPF 3.11   |
| Local streets are designed to create low-speed environments that are safe for cyclists and pedestrians.                                      | None are applicable.   |
| Infras   | tructure   |
| PO 4.1   | DTS/DPF 4.1  |
| Land division incorporates public utility services within road reserves or dedicated easements.  | None are applicable.   |
| PO 4.2   | DTS/DPF 4.2  |
| Waste water, sewage and other effluent is capable of being disposed of from each allotment without risk to public health or the environment. | (a) a waste water treatment plant that has the hydraulic volume and pollutant load treatment and disposal capacity for the maximum predicted wastewater volume generated by subsequent development of the proposed allotment or  (b) a form of on-site waste water treatment and disposal that meets relevant public health and environmental standards. |
| PO 4.3   | DTS/DPF 4.3  |
| Septic tank effluent drainage fields and other waste water disposal areas are maintained to ensure the effective operation                   | Development is not built on, or encroaches within, an area that is or will be, required for a sewerage system or waste control   |

Page 102 of 129 Printed on 5/07/2022

| system.                                       |
|---|
| DTS/DPF 4.4                                   |
| None are applicable.                          |
| DTS/DPF 4.5                                   |
| None are applicable.                          |
| DTS/DPF 4.6                                   |
| None are applicable.                          |
| Jnder 20 Allotments)                          |
| Space   |
| DTS/DPF 5.1                                   |
| None are applicable.                          |
| entation                                      |
| DTS/DPF 6.1                                   |
| None are applicable.                          |
| tive Design                                   |
| DTS/DPF 7.1                                   |
| None are applicable.                          |
|   |
| DTS/DPF 7.2                                   |
| DTS/DPF 7.2  None are applicable.             |
|   |
| None are applicable.                          |
| None are applicable.                          |
| None are applicable.  evelopment  DTS/DPF 8.1 |
|   |

Page 103 of 129 Printed on 5/07/2022

|   | (a) has a minimum width of 4m or (b) where more than 3 allotments are proposed, a minimum  |
|---|--|
|   | width of 5.5m.   |
| PO 8.3  | DTS/DPF 8.3  |
| Battle-axe allotments and/or common land are of a suitable size and dimension to allow passenger vehicles to enter and exit and manoeuvre within the site in a safe and convenient manner.  | Battle-axe development allows a B85 passenger vehicle to enter and exit parking spaces in no more than a three-point turn manoeuvre.   |
| PO 8.4  | DTS/DPF 8.4  |
| Battle-axe or common driveways incorporate landscaping and permeability to improve appearance and assist in stormwater management.  | Battle-axe or common driveways satisfy (a) and (b):  |
| inianagement.   | (a) are constructed of a minimum of 50% permeable or   |
|   | porous material  (b) where the driveway is located directly adjacent the side or rear boundary of the site, soft landscaping with a minimum dimension of 1m is provided between the driveway and site boundary (excluding along the perimeter of a passing point). |
| Major Land Division   | Dr. (20+ Allotments)   |
|   | Space  |
| PO 9.1  | DTS/DPF 9.1  |
|   |  |
| Land division allocates or retains evenly distributed, high quality areas of open space to improve residential amenity and provide urban heat amelioration.   | None are applicable.   |
| PO 9.2  | DTS/DPF 9.2  |
| Land allocated for open space is suitable for its intended active and passive recreational use considering gradient and potential for inundation.   | None are applicable.   |
| PO 9.3  | DTS/DPF 9.3  |
| Land allocated for active recreation has dimensions capable of accommodating a range of active recreational activities.   | None are applicable.   |
| Water Sens  | sitive Design  |
| PO 10.1   | DTS/DPF 10.1   |
| Land division creating 20 or more residential allotments includes a stormwater management system designed to mitigate peak flows and manage the rate and duration of stormwater discharges from the site to ensure that the development does not increase the peak flows in downstream systems.     | None are applicable.   |
| PO 10.2   | DTS/DPF 10.2   |
| Land division creating 20 or more non-residential allotments includes a stormwater management system designed to mitigate peak flows and manage the rate and duration of stormwater discharges from the site to ensure that the development does not increase the peak flows in downstream systems. | None are applicable.   |
| PO 10.3   | DTS/DPF 10.3   |
| Land division creating 20 or more allotments includes   | None are applicable.   |

Page 104 of 129 Printed on 5/07/2022

| stormwater management systems that minimise the discharge of sediment, suspended solids, organic matter, nutrients, bacteria, litter and other contaminants to the stormwater system, watercourses or other water bodies. |                      |  |
|---|----------------------|--|
| Solar Orientation   |                      |  |
| PO 11.1   | DTS/DPF 11.1         |  |
| Land division creating 20 or more allotments for residential purposes facilitates solar access through allotment orientation and allotment dimensions.  | None are applicable. |  |

#### **Marinas and On-Water Structures**

#### **Assessment Provisions (AP)**

|      | Desired Outcome   |
|------|---|
| DO 1 | Marinas and on-water structures are located and designed to minimise the impairment of commercial, recreational and navigational activities and adverse impacts on the environment. |

Performance Outcomes (PO) and Deemed-to-Satisfy (DTS) Criteria / Designated Performance Feature (DPF)

| Performance Outcome   | Deemed-to-Satisfy Criteria /<br>Designated Performance<br>Feature                         |
|---|---|
| Navigation  | and Safety  |
| PO 1.1  | DTS/DPF 1.1   |
| Safe public access is provided or maintained to the waterfront, public infrastructure and recreation areas. | None are applicable.  |
| PO 1.2  | DTS/DPF 1.2   |
| The operation of wharves is not impaired by marinas and onwater structures.                                 | None are applicable.  |
| PO 1.3  | DTS/DPF 1.3   |
| Navigation and access channels are not impaired by marinas and on-water structures.                         | None are applicable.  |
| PO 1.4  | DTS/DPF 1.4   |
| Commercial shipping lanes are not impaired by marinas and onwater structures.                               | Marinas and on-water structures are set back 250m or more from commercial shipping lanes. |
| PO 1.5  | DTS/DPF 1.5   |
| Marinas and on-water structures are located to avoid interfering  | On-water structures are set back:   |

Page 105 of 129 Printed on 5/07/2022

| with the operation or function of a water supply pumping station.  | (a) 3km or more from upstream water supply pumping station take-off points  (b) 500m or more from downstream water supply pumping station take-off points. |
|--|--|
| PO 1.6   | DTS/DPF 1.6  |
| Maintenance of on-water infrastructure, including revetment walls, is not impaired by marinas and on-water structures. | None are applicable.   |
| Environment  | tal Protection   |
| PO 2.1   | DTS/DPF 2.1  |
| Development is sited and designed to facilitate water circulation and exchange.  | None are applicable.   |

# **Open Space and Recreation**

#### **Assessment Provisions (AP)**

|      | Desired Outcome  |
|------|--|
| DO 1 | Pleasant, functional and accessible open space and recreation facilities are provided at State, regional, district, neighbourhood and local levels for active and passive recreation, biodiversity, community health, urban cooling, tree canopy cover, visual amenity, gathering spaces, wildlife and waterway corridors, and a range of other functions and at a range of sizes that reflect the purpose of that open space. |

Performance Outcomes (PO) and Deemed-to-Satisfy (DTS) Criteria / Designated Performance Feature (DPF)

| Performance Outcome  | Deemed-to-Satisfy Criteria /<br>Designated Performance<br>Feature |
|--|---|
| Land Use a   | nd Intensity  |
| PO 1.1   | DTS/DPF 1.1   |
| Recreation facilities are compatible with surrounding land uses and activities.                                  | None are applicable.  |
| PO 1.2   | DTS/DPF 1.2   |
| Open space areas include natural or landscaped areas using locally indigenous plant species and large trees.     | None are applicable.  |
| Design and Siting  |   |
| PO 2.1   | DTS/DPF 2.1   |
| Open space and recreation facilities address adjacent public roads to optimise pedestrian access and visibility. | None are applicable.  |

Page 106 of 129 Printed on 5/07/2022

| Policy24 - Enquiry   |                                   |
|--|-----------------------------------|
| PO 2.2   | DTS/DPF 2.2                       |
| Open space and recreation facilities incorporate park furniture, shaded areas and resting places.  | None are applicable.              |
| PO 2.3   | DTS/DPF 2.3                       |
| Open space and recreation facilities link habitats, wildlife corridors and existing open spaces and recreation facilities.   | None are applicable.              |
| Pedestrians  | s and Cyclists                    |
| P0 3.1   | DTS/DPF 3.1                       |
| Open space incorporates:   | None are applicable.              |
| pedestrian and cycle linkages to other open spaces, centres, schools and public transport nodes;      safe crossing points where pedestrian routes intersect the road network;      easily identified access points. |                                   |
| Usa  | I<br>sbility                      |
| PO 4.1  Land allocated for open space is suitable for its intended active and passive recreational use taking into consideration its gradient and potential for inundation.  | DTS/DPF 4.1  None are applicable. |
| Safety ar  | nd Security                       |
| PO 5.1   | DTS/DPF 5.1                       |
| Open space is overlooked by housing, commercial or other development to provide casual surveillance where possible.  | None are applicable.              |
| PO 5.2   | DTS/DPF 5.2                       |
| Play equipment is located to maximise opportunities for passive surveillance.  | None are applicable.              |
| PO 5.3   | DTS/DPF 5.3                       |
| Landscaping provided in open space and recreation facilities maximises opportunities for casual surveillance throughout the park.  | None are applicable.              |
| P0 5.4   | DTS/DPF 5.4                       |
| Fenced parks and playgrounds have more than one entrance or exit to minimise potential entrapment.   | None are applicable.              |
| PO 5.5   | DTS/DPF 5.5                       |
| Adequate lighting is provided around toilets, telephones, seating, litter bins, bicycle storage, car parks and other such facilities.  | None are applicable.              |
| PO 5.6   | DTS/DPF 5.6                       |
| Pedestrian and bicycle movement after dark is focused along clearly defined, adequately lit routes with observable entries and exits.  | None are applicable.              |
| Sig  | I<br>nage                         |
|  | T                                 |

Page 107 of 129 Printed on 5/07/2022

| Policy24 - Enquiry  |                      |
|---|----------------------|
| PO 6.1  | DTS/DPF 6.1          |
| Signage is provided at entrances to and within the open space and recreation facilities to provide clear orientation to major points of interest such as the location of public toilets, telephones, safe routes, park activities and the like. | None are applicable. |
| Buildings an  | nd Structures        |
| PO 7.1  | DTS/DPF 7.1          |
| Buildings and car parking areas in open space areas are designed, located and of a scale to be unobtrusive.   | None are applicable. |
| PO 7.2  | DTS/DPF 7.2          |
| Buildings and structures in open space areas are clustered where practical to ensure that the majority of the site remains open.  | None are applicable. |
| PO 7.3  | DTS/DPF 7.3          |
| Development in open space is constructed to minimise the extent of impervious surfaces.   | None are applicable. |
| PO 7.4  | DTS/DPF 7.4          |
| Development that abuts or includes a coastal reserve or Crown land used for scenic, conservation or recreational purposes is located and designed to have regard to the purpose, management and amenity of the reserve.                         | None are applicable. |
| Lands   | caping               |
| PO 8.1  | DTS/DPF 8.1          |
| Open space and recreation facilities provide for the planting and retention of large trees and vegetation.  | None are applicable. |
| PO 8.2  | DTS/DPF 8.2          |
| Landscaping in open space and recreation facilities provides shade and windbreaks:  | None are applicable. |
| (a) along cyclist and pedestrian routes; (b) around picnic and barbecue areas; (c) in car parking areas.  |                      |
| PO 8.3  | DTS/DPF 8.3          |
| Landscaping in open space facilitates habitat for local fauna and facilitates biodiversity.   | None are applicable. |
| PO 8.4  | DTS/DPF 8.4          |
| Landscaping including trees and other vegetation passively watered with local rainfall run-off, where practicable.  | None are applicable. |

# **Out of Activity Centre Development**

**Assessment Provisions (AP)** 

# **Desired Outcome**

Page 108 of 129 Printed on 5/07/2022

D01

The role of Activity Centres in contributing to the form and pattern of development and enabling equitable and convenient access to a range of shopping, administrative, cultural, entertainment and other facilities in a single trip is maintained and reinforced.

| Performance Outcome  | Deemed-to-Satisfy Criteria /<br>Designated Performance<br>Feature |
|--|---|
| PO 1.1   | DTS/DPF 1.1   |
| Non-residential development outside Activity Centres of a scale and type that does not diminish the role of Activity Centres:  (a) as primary locations for shopping, administrative, cultural, entertainment and community services (b) as a focus for regular social and business gatherings (c) in contributing to or maintaining a pattern of development that supports equitable community access to services and facilities.               | None are applicable.  |
| PO 1.2   | DTS/DPF 1.2   |
| Out-of-activity centre non-residential development complements  Activity Centres through the provision of services and facilities:  (a) that support the needs of local residents and workers, particularly in underserviced locations  (b) at the edge of Activities Centres where they cannot readily be accommodated within an existing Activity Centre to expand the range of services on offer and support the role of the Activity Centre. | None are applicable.  |

#### **Resource Extraction**

#### **Assessment Provisions (AP)**

|      | Desired Outcome  |
|------|--|
| DO 1 | Resource extraction activities are developed in a manner that minimises human and environmental impacts. |

Performance Outcomes (PO) and Deemed-to-Satisfy (DTS) Criteria / Designated Performance Feature (DPF)

| Performance Outcome    | Deemed-to-Satisfy Criteria /<br>Designated Performance<br>Feature |
|------------------------|---|
| Land Use and Intensity |   |
|                        |   |

Page 109 of 129 Printed on 5/07/2022

| P0 1.1  | DTS/DPF 1.1          |  |
|---|----------------------|--|
| Resource extraction activities minimise landscape damage outside of those areas unavoidably disturbed to access and exploit a resource and provide for the progressive reclamation and betterment of disturbed areas. | None are applicable. |  |
| PO 1.2  | DTS/DPF 1.2          |  |
| Resource extraction activities avoid damage to cultural sites or artefacts.   | None are applicable. |  |
| Water Quality   |                      |  |
| PO 2.1  | DTS/DPF 2.1          |  |
| Stormwater and/or wastewater from resource extraction activities is diverted into appropriately sized treatment and retention systems to enable reuse on site.  | None are applicable. |  |
| Separation Treatments, Buffers and Landscaping  |                      |  |
| PO 3.1  | DTS/DPF 3.1          |  |
| Resource extraction activities minimise adverse impacts upon sensitive receivers through incorporation of separation distances and/or mounding/vegetation.  | None are applicable. |  |
| P0 3.2  | DTS/DPF 3.2          |  |
| Resource extraction activities are screened from view from adjacent land by perimeter landscaping and/or mounding.  | None are applicable. |  |
|   |                      |  |

#### **Site Contamination**

#### **Assessment Provisions (AP)**

| Desired Outcome |  |  |
|-----------------|--|--|
| DO 1            | Ensure land is suitable for the proposed use in circumstances where it is, or may have been, subject to site |  |
|                 | contamination.   |  |

| Performance Outcome   | Deemed-to-Satisfy Criteria /<br>Designated Performance<br>Feature  |
|---|--|
| P0 1.1 Ensure land is suitable for use when land use changes to a more sensitive use. | DTS/DPF 1.1  Development satisfies (a), (b), (c) or (d):  (a) does not involve a change in the use of land (b) involves a change in the use of land that does not constitute a change to a more sensitive use (c) involves a change in the use of land to a more sensitive use on land at which site contamination is unlikely to exist (as demonstrated in a site contamination declaration form) |

Page 110 of 129 Printed on 5/07/2022

- (d) involves a change in the use of land to a more sensitive use on land at which site contamination exists, or may exist (as demonstrated in a site contamination declaration form), and satisfies both of the following:
  - (i) a site contamination audit report has been prepared under Part 10A of the *Environment Protection Act 1993* in relation to the land within the previous 5 years which states that-
    - A. site contamination does not exist (or no longer exists) at the land or
    - B. the land is suitable for the proposed use or range of uses (without the need for any further remediation)

or

C. where remediation is, or remains, necessary for the proposed use (or range of uses), remediation work has been carried out or will be carried out (and the applicant has provided a written undertaking that the remediation works will be implemented in association with the development)

and

(ii) no other class 1 activity or class 2 activity has taken place at the land since the preparation of the site contamination audit report (as demonstrated in a site contamination declaration form).

#### **Tourism Development**

#### **Assessment Provisions (AP)**

| Desired Outcome |  |  |
|-----------------|--|--|
| DO 1            | Tourism development is built in locations that cater to the needs of visitors and positively contributes to South Australia's visitor economy. |  |

Performance Outcomes (PO) and Deemed-to-Satisfy (DTS) Criteria / Designated Performance Feature (DPF)

# Performance Outcome Deemed-to-Satisfy Criteria / Designated Performance Feature General PO 1.1 Tourism development complements and contributes to local, natural, cultural or historical context where: DTS/DPF 1.1 None are applicable.

Page 111 of 129 Printed on 5/07/2022

| it supports immersive natural experiences     it showcases South Australia's landscapes and produce     its events and functions are connected to local food, wine and nature.   |   |  |
|--|---|--|
| PO 1.2   | DTS/DPF 1.2   |  |
| Tourism development comprising multiple accommodation units (including any facilities and activities for use by guests and visitors) is clustered to minimise environmental and contextual impact.   | None are applicable.  |  |
| Caravan and  | Tourist Parks   |  |
| PO 2.1   | DTS/DPF 2.1   |  |
| Potential conflicts between long-term residents and short-term tourists are minimised through suitable siting and design measures.   | None are applicable.  |  |
| PO 2.2   | DTS/DPF 2.2   |  |
| Occupants are provided privacy and amenity through landscaping and fencing.  | None are applicable.  |  |
| PO 2.3   | DTS/DPF 2.3   |  |
| Communal open space and centrally located recreation facilities are provided for guests and visitors.  | 12.5% or more of a caravan park comprises clearly defined communal open space, landscaped areas and areas for recreation. |  |
| PO 2.4   | DTS/DPF 2.4   |  |
| Perimeter landscaping is used to enhance the amenity of the locality.  | None are applicable.  |  |
| PO 2.5   | DTS/DPF 2.5   |  |
| Amenity blocks (showers, toilets, laundry and kitchen facilities) are sufficient to serve the full occupancy of the development.   | None are applicable.  |  |
| PO 2.6   | DTS/DPF 2.6   |  |
| Long-term occupation does not displace tourist accommodation, particularly in important tourist destinations such as coastal and riverine locations.   | None are applicable.  |  |
| Tourist accommodation in areas constituted under the National Parks and Wildlife Act 1972  |   |  |
| PO 3.1   | DTS/DPF 3.1   |  |
| Tourist accommodation avoids delicate or environmentally sensitive areas such as sand dunes, cliff tops, estuaries, wetlands or substantially intact strata of native vegetation (including regenerated areas of native vegetation lost through bushfire). | None are applicable.  |  |
| P0 3.2   | DTS/DPF 3.2   |  |
| Tourist accommodation is sited and designed in a manner that is subservient to the natural environment and where adverse impacts on natural features, landscapes, habitats and cultural  | None are applicable.  |  |

Page 112 of 129 Printed on 5/07/2022

| assets are avoided.  |                      |
|--|----------------------|
| PO 3.3   | DTS/DPF 3.3          |
| Tourist accommodation and recreational facilities, including associated access ways and ancillary structures, are located on cleared (other than where cleared as a result of bushfire) or degraded areas or where environmental improvements can be achieved.     | None are applicable. |
| PO 3.4   | DTS/DPF 3.4          |
| Tourist accommodation is designed to prevent conversion to private dwellings through:  | None are applicable. |
| (a) comprising a minimum of 10 accommodation units   |                      |
| (b) clustering separated individual accommodation units  |                      |
| (c) being of a size unsuitable for a private dwelling  |                      |
| (d) ensuring functional areas that are generally associated<br>with a private dwelling such as kitchens and laundries<br>are excluded from, or physically separated from<br>individual accommodation units, or are of a size<br>unsuitable for a private dwelling. |                      |

# **Transport, Access and Parking**

#### **Assessment Provisions (AP)**

| Desired Outcome |  |
|-----------------|--|
| DO 1            | A comprehensive, integrated and connected transport system that is safe, sustainable, efficient, convenient and accessible to all users. |

Performance Outcomes (PO) and Deemed-to-Satisfy (DTS) Criteria / Designated Performance Feature (DPF)

| Performance Outcome   | Deemed-to-Satisfy Criteria /<br>Designated Performance<br>Feature |
|---|---|
| Movement Systems  |   |
| PO 1.1  | DTS/DPF 1.1   |
| Development is integrated with the existing transport system and designed to minimise its potential impact on the functional performance of the transport system. | None are applicable.  |
| PO 1.2  | DTS/DPF 1.2   |
| Development is designed to discourage commercial and industrial vehicle movements through residential streets and adjacent other sensitive receivers.             | None are applicable.  |

Page 113 of 129 Printed on 5/07/2022

| <u> </u>  |  |
|---|--|
| PO 1.3  | DTS/DPF 1.3  |
| Industrial, commercial and service vehicle movements, loading areas and designated parking spaces are separated from passenger vehicle car parking areas to ensure efficient and safe movement and minimise potential conflict. | None are applicable.   |
| PO 1.4  | DTS/DPF 1.4  |
| Development is sited and designed so that loading, unloading and turning of all traffic avoids interrupting the operation of and queuing on public roads and pedestrian paths.  | All vehicle manoeuvring occurs onsite.   |
| Sigh  | tlines   |
| PO 2.1  | DTS/DPF 2.1  |
| Sightlines at intersections, pedestrian and cycle crossings, and crossovers to allotments for motorists, cyclists and pedestrians are maintained or enhanced to ensure safety for all road users and pedestrians.               | None are applicable.   |
| PO 2.2  | DTS/DPF 2.2  |
| Walls, fencing and landscaping adjacent to driveways and corner sites are designed to provide adequate sightlines between vehicles and pedestrians.   | None are applicable.   |
| Vehicle   | e Access   |
| PO 3.1  | DTS/DPF 3.1  |
| Safe and convenient access minimises impact or interruption on the operation of public roads.   | The access is:  (a) provided via a lawfully existing or authorised driveway or access point or an access point for which consent has been granted as part of an application for the division of land or  (b) not located within 6m of an intersection of 2 or more roads or a pedestrian activated crossing. |
| PO 3.2  | DTS/DPF 3.2  |
| Development incorporating vehicular access ramps ensures vehicles can enter and exit a site safely and without creating a hazard to pedestrians and other vehicular traffic.  | None are applicable.   |
| PO 3.3  | DTS/DPF 3.3  |
| Access points are sited and designed to accommodate the type and volume of traffic likely to be generated by the development or land use.   | None are applicable.   |
| PO 3.4  | DTS/DPF 3.4  |
| Access points are sited and designed to minimise any adverse impacts on neighbouring properties.  | None are applicable.   |
| PO 3.5  | DTS/DPF 3.5  |

Page 114 of 129 Printed on 5/07/2022

| Access points are located so as not to interfere with street trees, existing street furniture (including directional signs, lighting, seating and weather shelters) or infrastructure services to maintain the appearance of the streetscape, preserve local amenity and minimise disruption to utility infrastructure assets. | Vehicle access to designated car parking spaces satisfy (a) or (b):  (a) is provided via a lawfully existing or authorised access point or an access point for which consent has been granted as part of an application for the division of land (b) where newly proposed, is set back:  (i) 0.5m or more from any street furniture, street pole, infrastructure services pit, or other stormwater or utility infrastructure unless consent is provided from the asset owner  (ii) 2m or more from the base of the trunk of a street tree unless consent is provided from the tree owner for a lesser distance  (iii) 6m or more from the tangent point of an intersection of 2 or more roads  (iv) outside of the marked lines or infrastructure dedicating a pedestrian crossing. |
|--|---|
| PO 3.6   | DTS/DPF 3.6   |
| Driveways and access points are separated and minimised in number to optimise the provision of on-street visitor parking (where on-street parking is appropriate).   | (a) for sites with a frontage to a public road of 20m or less, one access point no greater than 3.5m in width is provided (b) for sites with a frontage to a public road greater than 20m:  (i) a single access point no greater than 6m in width is provided or  (ii) not more than two access points with a width of 3.5m each are provided.  |
| PO 3.7   | DTS/DPF 3.7   |
| Access points are appropriately separated from level crossings to avoid interference and ensure their safe ongoing operation.  | Development does not involve a new or modified access or cause an increase in traffic through an existing access that is located within the following distance from a railway crossing:  (a) 80 km/h road - 110m (b) 70 km/h road - 90m (c) 60 km/h road - 70m (d) 50km/h or less road - 50m.   |
| PO 3.8   | DTS/DPF 3.8   |
| Driveways, access points, access tracks and parking areas are designed and constructed to allow adequate movement and manoeuvrability having regard to the types of vehicles that are reasonably anticipated.  | None are applicable.  |
| PO 3.9   | DTS/DPF 3.9   |
| Development is designed to ensure vehicle circulation between activity areas occurs within the site without the need to use public roads.  | None are applicable.  |
| Access for Peop  | le with Disabilities  |
| PO 4.1   | DTS/DPF 4.1   |

Page 115 of 129 Printed on 5/07/2022

| Policy24 - Enquiry  | 1  |
|---|--|
| Development is sited and designed to provide safe, dignified and convenient access for people with a disability.  | None are applicable.   |
| Vehicle Pa  | rking Rates  |
| PO 5.1  | DTS/DPF 5.1  |
| Sufficient on-site vehicle parking and specifically marked accessible car parking places are provided to meet the needs of the development or land use having regard to factors that may support a reduced on-site rate such as:  (a) availability of on-street car parking (b) shared use of other parking areas (c) in relation to a mixed-use development, where the hours of operation of commercial activities complement the residential use of the site, the provision of vehicle parking may be shared (d) the adaptive reuse of a State or Local Heritage Place. | Development provides a number of car parking spaces on-site at a rate no less than the amount calculated using one of the following, whichever is relevant:  (a) Transport, Access and Parking Table 1 - General Off-Street Car Parking Requirements (b) Transport, Access and Parking Table 2 - Off-Street Vehicle Parking Requirements in Designated Areas (c) if located in an area where a lawfully established carparking fund operates, the number of spaces calculated under (a) or (b) less the number of spaces offset by contribution to the fund. |
| Vehicle Pa  | rking Areas  |
| PO 6.1  Vehicle parking areas are sited and designed to minimise impact on the operation of public roads by avoiding the use of public roads when moving from one part of a parking area to another.  | DTS/DPF 6.1  Movement between vehicle parking areas within the site can occur without the need to use a public road.   |
| PO 6.2  | DTS/DPF 6.2  |
| Vehicle parking areas are appropriately located, designed and constructed to minimise impacts on adjacent sensitive receivers through measures such as ensuring they are attractively developed and landscaped, screen fenced, and the like.  | None are applicable.   |
| PO 6.3  | DTS/DPF 6.3  |
| Vehicle parking areas are designed to provide opportunity for integration and shared-use of adjacent car parking areas to reduce the total extent of vehicle parking areas and access points.   | None are applicable.   |
| P0 6.4  | DTS/DPF 6.4  |
| Pedestrian linkages between parking areas and the development are provided and are safe and convenient.   | None are applicable.   |
| PO 6.5  | DTS/DPF 6.5  |
| Vehicle parking areas that are likely to be used during non-<br>daylight hours are provided with sufficient lighting to entry and<br>exit points to ensure clear visibility to users.   | None are applicable.   |
| PO 6.6  | DTS/DPF 6.6  |
| Loading areas and designated parking spaces for service vehicles are provided within the boundary of the site.  | Loading areas and designated parking spaces are wholly located within the site.  |
| PO 6.7  | DTS/DPF 6.7  |
| On-site visitor parking spaces are sited and designed to be accessible to all visitors at all times.  | None are applicable.   |
|   |  |

Page 116 of 129 Printed on 5/07/2022

| Policy24 - Enquiry   |   |
|--|---|
| Undercroft and Below Ground G  | araging and Parking of Vehicles   |
| PO 7.1   | DTS/DPF 7.1   |
| Undercroft and below ground garaging of vehicles is designed to enable safe entry and exit from the site without compromising pedestrian or cyclist safety or causing conflict with other vehicles.  | None are applicable.  |
| Internal Roads and Parking Areas in Resid  | ential Parks and Caravan and Tourist Parks  |
| PO 8.1   | DTS/DPF 8.1   |
| Internal road and vehicle parking areas are surfaced to prevent dust becoming a nuisance to park residents and occupants.  | None are applicable.  |
| PO 8.2   | DTS/DPF 8.2   |
| Traffic circulation and movement within the park is pedestrian friendly and promotes low speed vehicle movement.   | None are applicable.  |
| Bicycle Parking in   | Designated Areas  |
| PO 9.1   | DTS/DPF 9.1   |
| The provision of adequately sized on-site bicycle parking facilities encourages cycling as an active transport mode.   | Areas and / or fixtures are provided for the parking and storage of bicycles at a rate not less than the amount calculated using Transport, Access and Parking Table 3 - Off Street Bicycle Parking Requirements. |
| PO 9.2   | DTS/DPF 9.2   |
| Bicycle parking facilities provide for the secure storage and tethering of bicycles in a place where casual surveillance is possible, is well lit and signed for the safety and convenience of cyclists and deters property theft.                           | None are applicable.  |
| PO 9.3   | DTS/DPF 9.3   |
| Non-residential development incorporates end-of-journey facilities for employees such as showers, changing facilities and secure lockers, and signage indicating the location of the facilities to encourage cycling as a mode of journey-to-work transport. | None are applicable.  |
| Corner   | Cut-Offs  |
| PO 10.1  | DTS/DPF 10.1  |
| Development is located and designed to ensure drivers can safely turn into and out of public road junctions.   | Development does not involve building work, or building work is located wholly outside the land shown as Corner Cut-Off Area in the following diagram:  |
|  | Corner Cut- Off Area  Allotment Boundary  Asserve   |

Table 1 - General Off-Street Car Parking Requirements

Page 117 of 129 Printed on 5/07/2022

The following parking rates apply and if located in an area where a lawfully established carparking fund operates, the number of spaces is reduced by an amount equal to the number of spaces offset by contribution to the fund.

| Class of Development   | Car Parking Rate (unless varied by Table 2 onwards)   |
|--|---|
|  | Where a development comprises more than one development type, then the overall car parking rate will be taken to be the sum of the car parking rates for each development type. |
| Residential Development                                      |   |
| Detached Dwelling  | Dwelling with 1 bedroom (including rooms capable of being used as a bedroom) - 1 space per dwelling.  |
|  | Dwelling with 2 or more bedrooms (including rooms capable of being used as a bedroom) - 2 spaces per dwelling, 1 of which is to be covered.                                     |
| Group Dwelling   | Dwelling with 1 or 2 bedrooms (including rooms capable of being used as a bedroom) - 1 space per dwelling.  |
|  | Dwelling with 3 or more bedrooms (including rooms capable of being used as a bedroom) - 2 spaces per dwelling, 1 of which is to be covered.                                     |
|  | 0.33 spaces per dwelling for visitor parking where development involves 3 or more dwellings.  |
| Residential Flat Building                                    | Dwelling with 1 or 2 bedrooms (including rooms capable of being used as a bedroom) - 1 space per dwelling.  |
|  | Dwelling with 3 or more bedrooms (including rooms capable of being used as a bedroom) - 2 spaces per dwelling, 1 of which is to be covered.                                     |
|  | 0.33 spaces per dwelling for visitor parking where development involves 3 or more dwellings.  |
| Row Dwelling where vehicle access is from the primary street | Dwelling with 1 bedroom (including rooms capable of being used as a bedroom) - 1 space per dwelling.  |
| primary street   | Dwelling with 2 or more bedrooms (including rooms capable of being used as a bedroom) - 2 spaces per dwelling, 1 of which is to be covered.                                     |
| Row Dwelling where vehicle access is not from                | Dwelling with 1 or 2 bedrooms (including rooms capable of being used as a bedroom) - 1 space per dwelling.  |
| the primary street (i.e. rear-loaded)                        | Dwelling with 3 or more bedrooms (including rooms capable of being used as a bedroom) - 2 spaces per dwelling, 1 of which is to be covered.                                     |
| Semi-Detached Dwelling                                       | Dwelling with 1 bedroom (including rooms capable of being used as a bedroom) - 1 space per dwelling.  |
|  | Dwelling with 2 or more bedrooms (including rooms capable of being used as a bedroom) - 2 spaces per dwelling, 1 of which is to be covered.                                     |
| Aged / Supported Accommodation                               |   |
| Retirement village   | Dwelling with 1 or 2 bedrooms (including rooms capable of being used as a bedroom) - 1 space per dwelling.  |
|  | Dwelling with 3 or more bedrooms (including rooms capable of being used as a bedroom) - 2 spaces per dwelling.  |
|  | 0.2 spaces per dwelling for visitor parking.  |
|  |   |

Page 118 of 129 Printed on 5/07/2022

| Supported accommodation         | 0.3 spaces per bed.  |
|---------------------------------|--|
| Residential Development (Other) |  |
| Ancillary accommodation         | No additional requirements beyond those associated with the main dwelling.   |
| Residential park                | Dwelling with 1 or 2 bedrooms (including rooms capable of being used as a bedroom) - 1 space per dwelling.   |
|                                 | Dwelling with 3 or more bedrooms (including rooms capable of being used as a bedroom) - 2 spaces per dwelling.   |
|                                 | 0.2 spaces per dwelling for visitor parking.   |
| Student accommodation           | 0.3 spaces per bed.  |
| Workers' accommodation          | 0.5 spaces per bed plus 0.2 spaces per bed for visitor parking.  |
| Tourist                         |  |
| Caravan park / tourist park     | Parks with 100 sites or less - a minimum of 1 space per 10 sites to be used for accommodation.   |
|                                 | Parks with more than 100 sites - a minimum of 1 space per 15 sites used for accommodation.   |
|                                 | A minimum of 1 space for every caravan (permanently fixed to the ground) or cabin.   |
| Tourist accommodation           | 1 car parking space per accommodation unit / guest room.   |
| Commercial Uses                 |  |
| Auction room/ depot             | 1 space per 100m <sup>2</sup> of building floor area plus an additional 2 spaces.  |
| Automotive collision repair     | 3 spaces per service bay.  |
| Call centre                     | 8 spaces per 100m <sup>2</sup> of gross leasable floor area.   |
| Motor repair station            | 3 spaces per service bay.  |
| Office                          | 4 spaces per 100m <sup>2</sup> of gross leasable floor area.   |
| Retail fuel outlet              | 3 spaces per 100m <sup>2</sup> gross leasable floor area.  |
| Service trade premises          | 2.5 spaces per 100m <sup>2</sup> of gross leasable floor area  |
|                                 | 1 space per 100m <sup>2</sup> of outdoor area used for display purposes.   |
| Shop (no commercial kitchen)    | 5.5 spaces per 100m <sup>2</sup> of gross leasable floor area where not located in an integrated complex containing two or more tenancies (and which may comprise more than one building) where facilities for off-street vehicle parking, vehicle loading and unloading, and the storage and collection of refuse are shared. |

Page 119 of 129 Printed on 5/07/2022

|  | 5 spaces per 100m <sup>2</sup> of gross leasable floor area where located in an integrated complex containing two or more tenancies (and which may comprise more than one building) where facilities for off-street vehicle parking, vehicle loading and unloading, and the storage and collection of refuse are shared. |
|--|--|
| Shop (in the form of a bulky goods outlet)                           | 2.5 spaces per 100m <sup>2</sup> of gross leasable floor area.   |
| Shop (in the form of a restaurant or involving a commercial kitchen) | Premises with a dine-in service only (which may include a take-away component with no drive-through) - 0.4 spaces per seat.  |
|  | Premises with take-away service but with no seats - 12 spaces per 100m <sup>2</sup> of total floor area plus a drive-through queue capacity of ten vehicles measured from the pick-up point.   |
|  | Premises with a dine-in and drive-through take-away service - 0.3 spaces per seat plus a drive through queue capacity of 10 vehicles measured from the pick-up point.  |
| Community and Civic Uses   |  |
| Childcare centre   | 0.25 spaces per child  |
| Library  | 4 spaces per 100m <sup>2</sup> of total floor area.  |
| Community facility   | 10 spaces per 100m <sup>2</sup> of total floor area.   |
| Hall / meeting hall  | 0.2 spaces per seat.   |
| Place of worship   | 1 space for every 3 visitor seats.   |
| Pre-school   | 1 per employee plus 0.25 per child (drop off/pick up bays)   |
| Educational establishment  | For a primary school - 1.1 space per full time equivalent employee plus 0.25 spaces per student for a pickup/set down area either on-site or on the public realm within 300m of the site.  |
|  | For a secondary school - 1.1 per full time equivalent employee plus 0.1 spaces per student for a pickup/set down area either on-site or on the public realm within 300m of the site.   |
|  | For a tertiary institution - 0.4 per student based on the maximum number of students on the site at any time.  |
| Health Related Uses  |  |
| Hospital   | 4.5 spaces per bed for a public hospital.  |
|  | 1.5 spaces per bed for a private hospital.   |

Page 120 of 129 Printed on 5/07/2022

| ,   |  |  |
|---|--|--|
| 4 spaces per consulting room excluding ancillary facilities.  |  |  |
| Recreational and Entertainment Uses   |  |  |
| 0.2 spaces per seat.  |  |  |
| 0.2 spaces per seat.  |  |  |
| 1 space for every 2m <sup>2</sup> of total floor area in a public bar plus 1 space for every 6m <sup>2</sup> of total floor area available to the public in a lounge, beer garden plus 1 space per 2 gaming machines, plus 1 space per 3 seats in a restaurant. |  |  |
| <ul> <li>6.5 spaces per 100m<sup>2</sup> of total floor area for a Fitness Centre</li> <li>4.5 spaces per 100m<sup>2</sup> of total floor area for all other Indoor recreation facilities.</li> </ul>   |  |  |
|   |  |  |
| 1.5 spaces per 100m <sup>2</sup> total floor area   |  |  |
| 1 spaces per 100m <sup>2</sup> of outdoor area used for fuel depot activity purposes.   |  |  |
| 1.5 spaces per 100m <sup>2</sup> of total floor area.   |  |  |
| 0.5 spaces per 100m <sup>2</sup> of total floor area.   |  |  |
| 1.5 spaces per 100m <sup>2</sup> of total floor area  |  |  |
| 1 space per 100m <sup>2</sup> of outdoor area used for display purposes.  |  |  |
| 0.5 spaces per 100m <sup>2</sup> total floor area.  |  |  |
| Other Uses  |  |  |
| 1 space per 5 seats in the chapel plus 1 space for each vehicle operated by the parlour.  |  |  |
| 5 spaces per 100m <sup>2</sup> of total building floor area.  |  |  |
|   |  |  |

#### Table 2 - Off-Street Car Parking Requirements in Designated Areas

The following parking rates apply in any zone, subzone or other area described in the 'Designated Areas' column subject to the following:

- (a) the location of the development is unable to satisfy the requirements of Table 2 Criteria (other than where a location is exempted from the application of those criteria)
- (b) the development satisfies Table 2 Criteria (or is exempt from those criteria) and is located in an area where a lawfully established carparking fund operates, in which case the number of spaces are reduced by an amount equal to the number of spaces offset by contribution to the fund.

Page 121 of 129 Printed on 5/07/2022

| Class of Development  | Car Parking Rate  |   | Designated Areas  |
|---|---|---|---|
|   | Where a development comprises more than one development type, then the overall car parking rate will be taken to be the sum of the car parking rates for each development type. |   |   |
|   | Minimum number of spaces  | Maximum number of spaces  |   |
| Development generally                                       |   |   |   |
| All classes of development                                  | No minimum.   | No maximum except in the Primary Pedestrian Area identified in the Primary Pedestrian Area Concept Plan, where the maximum is:  1 space for each dwelling with a total floor area less than 75 square metres  2 spaces for each dwelling with a total floor area between 75 square metres and 150 square metres  3 spaces for each dwelling with a total floor area greater than 150 square metres.  Residential flat building or Residential component of a multi-storey building: 1 visitor space for each 6 dwellings. | Capital City Zone City Main Street Zone City Riverbank Zone Adelaide Park Lands Zone Business Neighbourhood Zone (within the City of Adelaide) The St Andrews Hospital Precinct Subzone and Women's and Children's Hospital Precinct Subzone of the Community Facilities Zone |
| Non-residential develop                                     | ment  |   |   |
| Non-residential development excluding tourist accommodation | 3 spaces per 100m <sup>2</sup> of gross leasable floor area.  | 5 spaces per 100m <sup>2</sup> of gross leasable floor area.  | City Living Zone  Urban Corridor (Boulevard) Zone  Urban Corridor (Business) Zone  Urban Corridor (Living) Zone  Urban Corridor (Main Street ) Zone  Urban Neighbourhood Zone   |
| Non-residential development excluding tourist accommodation | 3 spaces per 100m <sup>2</sup> of gross leasable floor area.  | 6 spaces per 100m <sup>2</sup> of gross leasable floor area.  | Strategic Innovation Zone Suburban Activity Centre Zone Suburban Business Zone Business Neighbourhood Zone Suburban Main Street Zone  |

Page 122 of 129 Printed on 5/07/2022

|  |   |   | Urban Activity Centre Zone  |
|--|---|---|---|
| Tourist accommodation                                  | 1 space for every 4 bedrooms<br>up to 100 bedrooms plus 1<br>space for every 5 bedrooms<br>over 100 bedrooms  | 1 space per 2 bedrooms up to<br>100 bedrooms and 1 space<br>per 4 bedrooms over 100<br>bedrooms | City Living Zone  Urban Activity Centre Zone  Urban Corridor (Boulevard) Zone  Urban Corridor (Business) Zone  Urban Corridor (Living) Zone  Urban Corridor (Main Street ) Zone  Urban Neighbourhood Zone                     |
| Residential developmen                                 | t   |   |   |
| Residential component<br>of a multi-storey<br>building | Dwelling with no separate bedroom -0.25 spaces per dwelling  1 bedroom dwelling - 0.75 spaces per dwelling  2 bedroom dwelling - 1 space per dwelling  3 or more bedroom dwelling - 1.25 spaces per dwelling  0.25 spaces per dwelling for visitor parking. | None specified.   | City Living Zone Strategic Innovation Zone Urban Activity Centre Zone Urban Corridor (Boulevard) Zone Urban Corridor (Business) Zone Urban Corridor (Living) Zone Urban Corridor (Main Street ) Zone Urban Neighbourhood Zone |
| Residential flat<br>building                           | Dwelling with no separate bedroom -0.25 spaces per dwelling  1 bedroom dwelling - 0.75 spaces per dwelling  2 bedroom dwelling - 1 space per dwelling  3 or more bedroom dwelling - 1.25 spaces per dwelling  0.25 spaces per dwelling for visitor parking. | None specified.   | City Living Zone  Urban Activity Centre Zone  Urban Corridor (Boulevard) Zone  Urban Corridor (Business) Zone  Urban Corridor (Living) Zone  Urban Corridor (Main Street ) Zone  Urban Neighbourhood Zone                     |

#### Table 2 - Criteria:

The following criteria are used in conjunction with Table 2. The 'Exception' column identifies locations where the criteria do not apply and the car parking rates in Table 2 are applicable.

| Criteria | Exceptions |
|----------|------------|
|----------|------------|

Page 123 of 129 Printed on 5/07/2022

# The designated area is wholly located within Metropolitan Adelaide and any part of the development site satisfies one or more of the following:

- (a) is within 200 metres of any section of road reserve along which a bus service operates as a high frequency public transit service<sup>(2)</sup>
- (b) is within 400 metres of a bus interchange<sup>(1)</sup>
- (c) is within 400 metres of an O-Bahn interchange<sup>(1)</sup>
- (d) is within 400 metres of a passenger rail station<sup>(1)</sup>
- (e) is within 400 metres of a passenger tram station<sup>(1)</sup>
- (f) is within 400 metres of the Adelaide Parklands.

- (a) All zones in the City of Adelaide
- (b) Strategic Innovation Zone in the following locations:
  - (i) City of Burnside
  - (ii) City of Marion
  - (iii) City of Mitcham
- (c) Urban Corridor (Boulevard) Zone
- (d) Urban Corridor (Business) Zone
- (e) Urban Corridor (Living) Zone
- (f) Urban Corridor (Main Street ) Zone
- (g) Urban Neighbourhood Zone

[NOTE(S): (1)Measured from an area that contains any platform(s), shelter(s) or stop(s) where people congregate for the purpose waiting to board a bus, tram or train, but does not include areas used for the parking of vehicles. (2) A high frequency public transit service is a route serviced every 15 minutes between 7.30am and 6.30pm Monday to Friday and every 30 minutes at night, Saturday, Sunday and public holidays until 10pm.]

#### **Table 3 - Off-Street Bicycle Parking Requirements**

The bicycle parking rates apply within designated areas located within parts of the State identified in the Schedule to Table 3.

| Class of Development       | Bicycle Parking Rate  |
|----------------------------|---|
|                            | Where a development comprises more than one development type, then the overall bicycle parking rate will be taken to be the sum of the bicycle parking rates for each development type.   |
| Consulting Room            | 1 space per 20 employees plus 1 space per 20 consulting rooms for customers.  |
| Educational establishment  | For a secondary school - 1 space per 20 full-time time employees plus 10 percent of the total number of employee spaces for visitors.  For tertiary education - 1 space per 20 employees plus 1 space per 10 full time students.  |
| Hospital                   | 1 space per 15 beds plus 1 space per 30 beds for visitors.  |
| Indoor recreation facility | 1 space per 4 employees plus 1 space per 200m <sup>2</sup> of gross leasable floor area for visitors.   |
| Licensed Premises          | 1 per 20 employees, plus 1 per 60 square metres total floor area, plus 1 per 40 square metres of bar floor area, plus 1 per 120 square metres lounge and beer garden floor area, plus 1 per 60 square metres dining floor area, plus 1 per 40 square metres gaming room floor area. |
| Office                     | 1 space for every 200m <sup>2</sup> of gross leasable floor area plus 2 spaces plus 1 space   |

Page 124 of 129 Printed on 5/07/2022

|  | 1000 2 6 1 11 6 6 1 11  |
|--|---|
|  | per 1000m <sup>2</sup> of gross leasable floor area for visitors.   |
| Pre-school                                       | 1 space per 20 full time employees plus 1 space per 40 full time children.  |
| Recreation area                                  | 1 per 1500 spectator seats for employees plus 1 per 250 visitor and customers.  |
| Residential flat building                        | Within the City of Adelaide 1 for every dwelling for residents with a total floor area less than 150 square metres, 2 for every dwelling for residents with a total floor area greater than 150 square metres, plus 1 for every 10 dwellings for visitors, and in all other cases 1 space for every 4 dwellings for residents plus 1 for every 10 dwellings for visitors.       |
| Residential component of a multi-storey building | Within the City of Adelaide 1 for every dwelling for residents with a total floor area less than 150 square metres, 2 for every dwelling for residents with a total floor area greater than 150 square metres, plus 1 for every 10 dwellings for visitors, and in all other cases 1 space for every 4 dwellings for residents plus 1 space for every 10 dwellings for visitors. |
| Shop   | 1 space for every 300m <sup>2</sup> of gross leasable floor area plus 1 space for every 600m <sup>2</sup> of gross leasable floor area for customers.   |
| Tourist accommodation                            | 1 space for every 20 employees plus 2 for the first 40 rooms and 1 for every additional 40 rooms for visitors.  |

#### Schedule to Table 3

| Designated Area                    | Relevant part of the State   |
|------------------------------------|--|
|                                    | The bicycle parking rate applies to a designated area located in a relevant part of the State described below. |
| All zones                          | City of Adelaide   |
| Business Neighbourhood Zone        | Metropolitan Adelaide  |
| Strategic Innovation Zone          |  |
| Suburban Activity Centre Zone      |  |
| Suburban Business Zone             |  |
| Suburban Main Street Zone          |  |
| Urban Activity Centre Zone         |  |
| Urban Corridor (Boulevard) Zone    |  |
| Urban Corridor (Business) Zone     |  |
| Urban Corridor (Living) Zone       |  |
| Urban Corridor (Main Street ) Zone |  |
| Urban Neighbourhood Zone           |  |

# **Waste Treatment and Management Facilities**

Page 125 of 129 Printed on 5/07/2022

#### **Assessment Provisions (AP)**

|      | Desired Outcome   |
|------|---|
| DO 1 | Mitigation of the potential environmental and amenity impacts of waste treatment and management facilities. |

Performance Outcomes (PO) and Deemed-to-Satisfy (DTS) Criteria / Designated Performance Feature (DPF)

| Performance Outcome  | Deemed-to-Satisfy Criteria /<br>Designated Performance<br>Feature   |
|--|---|
| Siting   |   |
| P0 1.1   | DTS/DPF 1.1   |
| Waste treatment and management facilities incorporate separation distances and attenuation measures within the site between waste operations areas (including all closed, operating and future cells) and sensitive receivers and sensitive environmental features to mitigate off-site impacts from noise, air and dust emissions.  | None are applicable.  |
| Soil and Water Protection  |   |
| PO 2.1   | DTS/DPF 2.1   |
| Soil, groundwater and surface water are protected from contamination from waste treatment and management facilities through measures such as:  (a) containing potential groundwater and surface water contaminants within waste operations areas (b) diverting clean stormwater away from waste operations areas and potentially contaminated areas (c) providing a leachate barrier between waste operations areas and underlying soil and groundwater. | None are applicable.  |
| PO 2.2   | DTS/DPF 2.2   |
| Wastewater lagoons are set back from watercourses to minimise environmental harm and adverse effects on water resources.   | Wastewater lagoons are set back 50m or more from watercourse banks. |
| PO 2.3   | DTS/DPF 2.3   |
| Wastewater lagoons are designed and sited to:  | None are applicable.  |
| <ul> <li>(a) avoid intersecting underground waters;</li> <li>(b) avoid inundation by flood waters;</li> <li>(c) ensure lagoon contents do not overflow;</li> <li>(d) include a liner designed to prevent leakage.</li> </ul>   |   |
| PO 2.4   | DTS/DPF 2.4   |

Page 126 of 129 Printed on 5/07/2022

| Waste operations areas of landfills and organic waste processing facilities are set back from watercourses to minimise adverse impacts on water resources.     | Waste operations areas are set back 100m or more from watercourse banks.  |
|--|---|
| Am   | enity   |
| PO 3.1   | DTS/DPF 3.1   |
| Waste treatment and management facilities are screened, located and designed to minimise adverse visual impacts on amenity.                                    | None are applicable.  |
| PO 3.2   | DTS/DPF 3.2   |
| Access routes to waste treatment and management facilities via residential streets is avoided.   | None are applicable.  |
| P0 3.3   | DTS/DPF 3.3   |
| Litter control measures minimise the incidence of windblown litter.  | None are applicable.  |
| P0 3.4   | DTS/DPF 3.4   |
| Waste treatment and management facilities are designed to minimise adverse impacts on both the site and surrounding areas from weed and vermin infestation.    | None are applicable.  |
| Acc  | eess  |
| PO 4.1   | DTS/DPF 4.1   |
| Traffic circulation movements within any waste treatment or management site are designed to enable vehicles to enter and exit the site in a forward direction. | None are applicable.  |
| PO 4.2   | DTS/DPF 4.2   |
| Suitable access for emergency vehicles is provided to and within waste treatment or management sites.  | None are applicable.  |
| Fencing a  | nd Security   |
| PO 5.1   | DTS/DPF 5.1   |
| Security fencing provided around waste treatment and management facilities prevents unauthorised access to operations and potential hazard to the public.      | Chain wire mesh or pre-coated painted metal fencing 2m or more in height is erected along the perimeter of the waste treatment or waste management facility site. |
| Lar  | dfill   |
| PO 6.1   | DTS/DPF 6.1   |
| Landfill gas emissions are managed in an environmentally acceptable manner.  | None are applicable.  |
| PO 6.2   | DTS/DPF 6.2   |
| Landfill facilities are separated from areas of environmental significance and land used for public recreation and enjoyment.                                  | Landfill facilities are set back 250m or more from a public open space reserve, forest reserve, national park or Conservation Zone.                               |
| P0 6.3   | DTS/DPF 6.3   |
| Landfill facilities are located on land that is not subject to land  | None are applicable.  |

Page 127 of 129 Printed on 5/07/2022

| Policy24 - Enquiry   |   |
|--|---|
| slip.  |   |
| PO 6.4   | DTS/DPF 6.4   |
| Landfill facilities are separated from areas subject to flooding.  | Landfill facilities are set back 500m or more from land inundated in a 1% AEP flood event.  |
| Organic Waste Pr   | ocessing Facilities   |
| P0 7.1   | DTS/DPF 7.1   |
| Organic waste processing facilities are separated from the coast to avoid potential environment harm.  | Organic waste processing facilities are set back 500m or more from the coastal high water mark.   |
| PO 7.2   | DTS/DPF 7.2   |
| Organic waste processing facilities are located on land where the engineered liner and underlying seasonal water table cannot intersect.   | None are applicable.  |
| PO 7.3   | DTS/DPF 7.3   |
| Organic waste processing facilities are sited away from areas of environmental significance and land used for public recreation and enjoyment.   | Organic waste processing facilities are set back 250m or more from a public open space reserve, forest reserve, national park or a Conservation Zone. |
| PO 7.4   | DTS/DPF 7.4   |
| Organic waste processing facilities are located on land that is not subject to land slip.  | None are applicable.  |
| PO 7.5   | DTS/DPF 7.5   |
| Organic waste processing facilities separated from areas subject to flooding.  | Organic waste processing facilities are set back 500m or more from land inundated in a 1% AEP flood event.  |
| Major Wastewater   | Treatment Facilities  |
| PO 8.1   | DTS/DPF 8.1   |
| Major wastewater treatment and disposal systems, including lagoons, are designed to minimise potential adverse odour impacts on sensitive receivers, minimise public and environmental health risks and protect water quality. | None are applicable.  |
| PO 8.2   | DTS/DPF 8.2   |
| Artificial wetland systems for the storage of treated wastewater are designed and sited to minimise potential public health risks arising from the breeding of mosquitoes.   | None are applicable.  |
|  |   |

# **Workers' accommodation and Settlements**

# **Assessment Provisions (AP)**

| Desired Outcome |  |  |
|-----------------|--|--|
| DO 1            | Appropriately designed and located accommodation for seasonal and short-term workers in rural areas that minimises environmental and social impacts. |  |

Page 128 of 129 Printed on 5/07/2022

| Performance Outcome  | Deemed-to-Satisfy Criteria /<br>Designated Performance<br>Feature |
|--|---|
| PO 1.1   | DTS/DPF 1.1   |
| Workers' accommodation and settlements are obscured from scenic routes, tourist destinations and areas of conservation significance or otherwise designed to complement the surrounding landscape. | None are applicable.  |
| PO 1.2   | DTS/DPF 1.2   |
| Workers' accommodation and settlements are sited and designed to minimise nuisance impacts on the amenity of adjacent users of land.   | None are applicable.  |
| PO 1.3   | DTS/DPF 1.3   |
| Workers' accommodation and settlements are built with materials and colours that blend with the landscape.   | None are applicable.  |
| PO 1.4   | DTS/DPF 1.4   |
| Workers' accommodation and settlements are supplied with service infrastructure such as power, water and effluent disposal sufficient to satisfy the living requirements of workers.               | None are applicable.  |

No criteria applies to this land use. Please check the definition of the land use for further detail.

Page 129 of 129 Printed on 5/07/2022

#### **61 TRISTANIA TCE DERNANCOURT SA 5075**

#### Address:

Click to view a detailed interactive SAILIS in SAILIS

To view a detailed interactive property map in SAPPA click on the map below



#### **Property Zoning Details**

#### Overlay

Airport Building Heights (Regulated) (All structures over 45 metres)

Affordable Housing

Hazards (Flooding - Evidence Required)

Prescribed Wells Area

Regulated and Significant Tree

Stormwater Management

**Urban Tree Canopy** 

#### Zone

General Neighbourhood

#### Selected Development(s)

# Retaining wall

This development may be subject to multiple assessment pathways. Please review the document below to determine which pathway may be applicable based on the proposed development compliances to standards.

If no assessment pathway is shown this mean the proposed development will default to performance assessed. Please contact your local council in this instance. Refer to Part 1 - Rules of Interpretation - Determination of Classes of Development

Property Policy Information for above selection

Retaining wall - Code Assessed - Performance Assessed

## Part 2 - Zones and Sub Zones

#### **General Neighbourhood Zone**

**Assessment Provisions (AP)** 

Page 1 of 4 Printed on 5/07/2022

# Do 1 Low-rise, low and medium-density housing that supports a range of needs and lifestyles located within easy reach of services and facilities. Employment and community service uses contribute to making the neighbourhood a convenient place to live without compromising residential amenity.

#### Table 5 - Procedural Matters (PM) - Notification

dwelling addition

fence

outbuilding

The following table identifies, pursuant to section 107(6) of the *Planning, Development and Infrastructure Act 2016*, classes of performance assessed development that are excluded from notification. The table also identifies any exemptions to the placement of notices when notification is required.

#### Interpretation

Notification tables exclude the classes of development listed in Column A from notification provided that they do not fall within a corresponding exclusion prescribed in Column B.

Where a development or an element of a development falls within more than one class of development listed in Column A, it will be excluded from notification if it is excluded (in its entirety) under any of those classes of development. It need not be excluded under all applicable classes of development.

Where a development involves multiple performance assessed elements, all performance assessed elements will require notification (regardless of whether one or more elements are excluded in the applicable notification table) unless every performance assessed element of the application is excluded in the applicable notification table, in which case the application will not require notification.

| element of the application is excluded in the applicable notification table, in which case the application will not require notification.  |   |   |  |
|--|---|---|--|
| Class of Development   |   | Exceptions  |  |
| (Column  | a A)  | (Column B)  |  |
| Development which, in the opinion of the relevant authority, is of a minor nature only and will not unreasonably impact on the owners or occupiers of land in the locality of the site of the development.   |   | None specified.   |  |
| 2. /   | (a) the South Australian Housing Trust either individually or jointly with other persons or bodies or  (b) a provider registered under the Community Housing National Law participating in a program relating to the renewal of housing endorsed by the South Australian Housing Trust. | <ol> <li>Except development involving any of the following:</li> <li>residential flat building(s) of 3 or more building levels</li> <li>the demolition of a State or Local Heritage Place</li> <li>the demolition of a building (except an ancillary building) in a Historic Area Overlay.</li> </ol> |  |
| 3. Any development involving any of the following (or of any combination of any of the following):  (a) air handling unit, air conditioning system or exhaust fan  (b) ancillary accommodation  (c) building work on railway land  (d) carport  (e) deck  (f) dwelling |   | <ol> <li>does not satisfy General Neighbourhood Zone DTS/DPF 4.1 or</li> <li>involves a building wall (or structure) that is proposed to be situated on (or abut) an allotment boundary (not being a boundary with a primary street or secondary street or an excluded boundary) and:</li> </ol>      |  |

Page 2 of 4 Printed on 5/07/2022

(a) the length of the proposed wall (or structure)

length on the adjoining allotment)

exceeds 11.5m (other than where the proposed

wall abuts an existing wall or structure of greater

pergola (k) private bushfire shelter (b) the height of the proposed wall (or post height) exceeds 3m measured from the top of residential flat building footings (other than where the proposed wall (or (m) retaining wall post) abuts an existing wall or structure of (n) retirement facility greater height on the adjoining allotment). (o) shade sail (p) solar photovoltaic panels (roof mounted) (q) student accommodation (r) supported accommodation (s) swimming pool or spa pool verandah (u) water tank. 4. Any development involving any of the following (or of Except development that: any combination of any of the following): (a) consulting room 1. does not satisfy any of the following: (b) office (a) General Neighbourhood Zone DTS/DPF 1.4 (c) shop. (b) General Neighbourhood Zone DTS/DPF 4.1 or 2. involves a building wall (or structure) that is proposed to be situated on (or abut) an allotment boundary (not being a boundary with a primary street or secondary street or an excluded boundary) and: (a) the length of the proposed wall (or structure) exceeds 11.5m (other than where the proposed wall abuts an existing wall or structure of greater length on the adjoining allotment) (b) the height of the proposed wall (or post height) exceeds 3m measured from the top of footings (other than where the proposed wall (or post) abuts an existing wall or structure of greater height on the adjoining allotment). 5. Any development involving any of the following (or of None specified. any combination of any of the following): (a) internal building works (b) land division (c) recreation area (d) replacement building (e) temporary accommodation in an area affected by bushfire (f) tree damaging activity. 6. Alteration of or addition to any development involving Except development that does not satisfy General Neighbourhood the following (or of any combination of any of the Zone DTS/DPF 1.5. following): (a) community facility (b) educational establishment (c) pre-school. 7. Demolition. Except any of the following:

Page 3 of 4 Printed on 5/07/2022

- 1. the demolition of a State or Local Heritage Place
- 2. the demolition of a building (except an ancillary building) in a Historic Area Overlay.

Placement of Notices - Exemptions for Performance Assessed Development

None specified.

**Placement of Notices - Exemptions for Restricted Development** 

None specified.

# Part 4 - General Development Policies

# **Design in Urban Areas**

**Assessment Provisions (AP)** 

|   | Desired Outcome   |                 |  |  |
|---|---|-----------------|--|--|
|   | DO 1  | Development is: |  |  |
|   | (a) contextual - by considering, recognising and carefully responding to its natural surroundings or built environment and positively contributing to the character of the locality |                 |  |  |
| (b) durable - fit for purpose, adaptable and long lasti |   | (b)             | durable - fit for purpose, adaptable and long lasting  |  |
|   |   | (c)             | inclusive - by integrating landscape design to optimise pedestrian and cyclist usability, privacy and equitable access and promoting the provision of quality spaces integrated with the public realm that can be used for access and recreation and help optimise security and safety both internally and within the public realm, for occupants and visitors |  |
|   |   | (d)             | sustainable - by integrating sustainable techniques into the design and siting of development and landscaping to improve community health, urban heat, water management, environmental performance, biodiversity and local amenity and to minimise energy consumption.   |  |

| Performance Outcome   | Deemed-to-Satisfy Criteria /<br>Designated Performance<br>Feature                                  |
|---|--|
| All Deve  | elopment   |
| Fences  | and walls  |
| PO 9.1  | DTS/DPF 9.1  |
| Fences, walls and retaining walls of sufficient height maintain privacy and security without unreasonably impacting visual amenity and adjoining land's access to sunlight or the amenity of public places. | None are applicable.   |
| PO 9.2  | DTS/DPF 9.2  |
| Landscaping is incorporated on the low side of retaining walls that are visible from public roads and public open space to minimise visual impacts.   | A vegetated landscaped strip 1m wide or more is provided against the low side of a retaining wall. |

Page 4 of 4 Printed on 5/07/2022

#### **59 TRISTANIA TCE DERNANCOURT SA 5075**

#### Address:

Click to view a detailed interactive SAILIS in SAILIS

To view a detailed interactive property map in SAPPA click on the map below



#### **Property Zoning Details**

#### Overlay

Airport Building Heights (Regulated) (All structures over 45 metres)

Affordable Housing

Hazards (Flooding - Evidence Required)

Prescribed Wells Area

Regulated and Significant Tree

Stormwater Management

**Urban Tree Canopy** 

#### Zone

General Neighbourhood

#### Selected Development(s)

# Retaining wall

This development may be subject to multiple assessment pathways. Please review the document below to determine which pathway may be applicable based on the proposed development compliances to standards.

If no assessment pathway is shown this mean the proposed development will default to performance assessed. Please contact your local council in this instance. Refer to Part 1 - Rules of Interpretation - Determination of Classes of Development

Property Policy Information for above selection

Retaining wall - Code Assessed - Performance Assessed

## Part 2 - Zones and Sub Zones

#### **General Neighbourhood Zone**

**Assessment Provisions (AP)** 

Page 1 of 4 Printed on 5/07/2022

# Do 1 Low-rise, low and medium-density housing that supports a range of needs and lifestyles located within easy reach of services and facilities. Employment and community service uses contribute to making the neighbourhood a convenient place to live without compromising residential amenity.

#### Table 5 - Procedural Matters (PM) - Notification

dwelling addition

fence

outbuilding

The following table identifies, pursuant to section 107(6) of the *Planning, Development and Infrastructure Act 2016*, classes of performance assessed development that are excluded from notification. The table also identifies any exemptions to the placement of notices when notification is required.

#### Interpretation

Notification tables exclude the classes of development listed in Column A from notification provided that they do not fall within a corresponding exclusion prescribed in Column B.

Where a development or an element of a development falls within more than one class of development listed in Column A, it will be excluded from notification if it is excluded (in its entirety) under any of those classes of development. It need not be excluded under all applicable classes of development.

Where a development involves multiple performance assessed elements, all performance assessed elements will require notification (regardless of whether one or more elements are excluded in the applicable notification table) unless every performance assessed element of the application is excluded in the applicable notification table, in which case the application will not require notification.

| element of the application is excluded in the applicable notification table, in which case the application will not require notification.  |   |   |  |
|--|---|---|--|
| Class of Development   |   | Exceptions  |  |
| (Column  | a A)  | (Column B)  |  |
| Development which, in the opinion of the relevant authority, is of a minor nature only and will not unreasonably impact on the owners or occupiers of land in the locality of the site of the development.   |   | None specified.   |  |
| 2. /   | (a) the South Australian Housing Trust either individually or jointly with other persons or bodies or  (b) a provider registered under the Community Housing National Law participating in a program relating to the renewal of housing endorsed by the South Australian Housing Trust. | <ol> <li>Except development involving any of the following:</li> <li>residential flat building(s) of 3 or more building levels</li> <li>the demolition of a State or Local Heritage Place</li> <li>the demolition of a building (except an ancillary building) in a Historic Area Overlay.</li> </ol> |  |
| 3. Any development involving any of the following (or of any combination of any of the following):  (a) air handling unit, air conditioning system or exhaust fan  (b) ancillary accommodation  (c) building work on railway land  (d) carport  (e) deck  (f) dwelling |   | <ol> <li>does not satisfy General Neighbourhood Zone DTS/DPF 4.1 or</li> <li>involves a building wall (or structure) that is proposed to be situated on (or abut) an allotment boundary (not being a boundary with a primary street or secondary street or an excluded boundary) and:</li> </ol>      |  |

Page 2 of 4 Printed on 5/07/2022

(a) the length of the proposed wall (or structure)

length on the adjoining allotment)

exceeds 11.5m (other than where the proposed

wall abuts an existing wall or structure of greater

pergola (k) private bushfire shelter (b) the height of the proposed wall (or post height) exceeds 3m measured from the top of residential flat building footings (other than where the proposed wall (or (m) retaining wall post) abuts an existing wall or structure of (n) retirement facility greater height on the adjoining allotment). (o) shade sail (p) solar photovoltaic panels (roof mounted) (q) student accommodation (r) supported accommodation (s) swimming pool or spa pool verandah (u) water tank. 4. Any development involving any of the following (or of Except development that: any combination of any of the following): (a) consulting room 1. does not satisfy any of the following: (b) office (a) General Neighbourhood Zone DTS/DPF 1.4 (c) shop. (b) General Neighbourhood Zone DTS/DPF 4.1 or 2. involves a building wall (or structure) that is proposed to be situated on (or abut) an allotment boundary (not being a boundary with a primary street or secondary street or an excluded boundary) and: (a) the length of the proposed wall (or structure) exceeds 11.5m (other than where the proposed wall abuts an existing wall or structure of greater length on the adjoining allotment) (b) the height of the proposed wall (or post height) exceeds 3m measured from the top of footings (other than where the proposed wall (or post) abuts an existing wall or structure of greater height on the adjoining allotment). 5. Any development involving any of the following (or of None specified. any combination of any of the following): (a) internal building works (b) land division (c) recreation area (d) replacement building (e) temporary accommodation in an area affected by bushfire (f) tree damaging activity. 6. Alteration of or addition to any development involving Except development that does not satisfy General Neighbourhood the following (or of any combination of any of the Zone DTS/DPF 1.5. following): (a) community facility (b) educational establishment (c) pre-school. 7. Demolition. Except any of the following:

Page 3 of 4 Printed on 5/07/2022

- 1. the demolition of a State or Local Heritage Place
- 2. the demolition of a building (except an ancillary building) in a Historic Area Overlay.

Placement of Notices - Exemptions for Performance Assessed Development

None specified.

**Placement of Notices - Exemptions for Restricted Development** 

None specified.

# Part 4 - General Development Policies

# **Design in Urban Areas**

**Assessment Provisions (AP)** 

|   | Desired Outcome   |                 |  |  |
|---|---|-----------------|--|--|
|   | DO 1  | Development is: |  |  |
|   | (a) contextual - by considering, recognising and carefully responding to its natural surroundings or built environment and positively contributing to the character of the locality |                 |  |  |
| (b) durable - fit for purpose, adaptable and long lasti |   | (b)             | durable - fit for purpose, adaptable and long lasting  |  |
|   |   | (c)             | inclusive - by integrating landscape design to optimise pedestrian and cyclist usability, privacy and equitable access and promoting the provision of quality spaces integrated with the public realm that can be used for access and recreation and help optimise security and safety both internally and within the public realm, for occupants and visitors |  |
|   |   | (d)             | sustainable - by integrating sustainable techniques into the design and siting of development and landscaping to improve community health, urban heat, water management, environmental performance, biodiversity and local amenity and to minimise energy consumption.   |  |

| Performance Outcome   | Deemed-to-Satisfy Criteria /<br>Designated Performance<br>Feature                                  |
|---|--|
| All Deve  | elopment   |
| Fences  | and walls  |
| PO 9.1  | DTS/DPF 9.1  |
| Fences, walls and retaining walls of sufficient height maintain privacy and security without unreasonably impacting visual amenity and adjoining land's access to sunlight or the amenity of public places. | None are applicable.   |
| PO 9.2  | DTS/DPF 9.2  |
| Landscaping is incorporated on the low side of retaining walls that are visible from public roads and public open space to minimise visual impacts.   | A vegetated landscaped strip 1m wide or more is provided against the low side of a retaining wall. |

Page 4 of 4 Printed on 5/07/2022

#### **61 TRISTANIA TCE DERNANCOURT SA 5075**

#### Address:

Click to view a detailed interactive SAILIS in SAILIS

To view a detailed interactive property map in SAPPA click on the map below



#### **Property Zoning Details**

#### Overlay

Airport Building Heights (Regulated) (All structures over 45 metres)

Affordable Housing

Hazards (Flooding - Evidence Required)

Prescribed Wells Area

Regulated and Significant Tree

Stormwater Management

**Urban Tree Canopy** 

#### Zone

General Neighbourhood

#### Selected Development(s)

#### **Fence**

This development may be subject to multiple assessment pathways. Please review the document below to determine which pathway may be applicable based on the proposed development compliances to standards.

If no assessment pathway is shown this mean the proposed development will default to performance assessed. Please contact your local council in this instance. Refer to Part 1 - Rules of Interpretation - Determination of Classes of Development

**Property Policy Information for above selection** 

Fence - Code Assessed - Performance Assessed

### Part 2 - Zones and Sub Zones

#### **General Neighbourhood Zone**

**Assessment Provisions (AP)** 

Page 1 of 6 Printed on 5/07/2022

# DO 1 Low-rise, low and medium-density housing that supports a range of needs and lifestyles located within easy reach of services and facilities. Employment and community service uses contribute to making the neighbourhood a convenient place to live without compromising residential amenity.

#### Table 5 - Procedural Matters (PM) - Notification

The following table identifies, pursuant to section 107(6) of the *Planning, Development and Infrastructure Act 2016*, classes of performance assessed development that are excluded from notification. The table also identifies any exemptions to the placement of notices when notification is required.

#### Interpretation

Notification tables exclude the classes of development listed in Column A from notification provided that they do not fall within a corresponding exclusion prescribed in Column B.

Where a development or an element of a development falls within more than one class of development listed in Column A, it will be excluded from notification if it is excluded (in its entirety) under any of those classes of development. It need not be excluded under all applicable classes of development.

Where a development involves multiple performance assessed elements, all performance assessed elements will require notification (regardless of whether one or more elements are excluded in the applicable notification table) unless every performance assessed element of the application is excluded in the applicable notification table, in which case the application will not require notification.

| Class of Development  | Exceptions   |  |
|---|--|--|
| (Column A)  | (Column B)  None specified.  Except development involving any of the following:  1. residential flat building(s) of 3 or more building levels 2. the demolition of a State or Local Heritage Place 3. the demolition of a building (except an ancillary building) in a Historic Area Overlay.  |  |
| <ol> <li>Development which, in the opinion of the relevant<br/>authority, is of a minor nature only and will not<br/>unreasonably impact on the owners or occupiers of land<br/>in the locality of the site of the development.</li> </ol>  |  |  |
| <ul> <li>2. All development undertaken by: <ul> <li>(a) the South Australian Housing Trust either individually or jointly with other persons or bodies or</li> <li>(b) a provider registered under the Community Housing National Law participating in a program relating to the renewal of housing endorsed by the South Australian Housing Trust.</li> </ul> </li> </ul>  |  |  |
| <ul> <li>3. Any development involving any of the following (or of any combination of any of the following): <ul> <li>(a) air handling unit, air conditioning system or exhaust fan</li> <li>(b) ancillary accommodation</li> <li>(c) building work on railway land</li> <li>(d) carport</li> <li>(e) deck</li> <li>(f) dwelling</li> <li>(g) dwelling addition</li> <li>(h) fence</li> <li>(i) outbuilding</li> </ul> </li> </ul> | 1. does not satisfy General Neighbourhood Zone DTS/DPF 4.1 or 2. involves a building wall (or structure) that is proposed to be situated on (or abut) an allotment boundary (not being a boundary with a primary street or secondary street or an excluded boundary) and:  (a) the length of the proposed wall (or structure) exceeds 11.5m (other than where the proposed wall abuts an existing wall or structure of greater length on the adjoining allotment) or |  |

Page 2 of 6 Printed on 5/07/2022

| <ul> <li>(j) pergola</li> <li>(k) private bushfire shelter</li> <li>(l) residential flat building</li> <li>(m) retaining wall</li> <li>(n) retirement facility</li> <li>(o) shade sail</li> <li>(p) solar photovoltaic panels (roof mounted)</li> <li>(q) student accommodation</li> <li>(r) supported accommodation</li> <li>(s) swimming pool or spa pool</li> <li>(t) verandah</li> <li>(u) water tank.</li> </ul> | (b) the height of the proposed wall (or post height)<br>exceeds 3m measured from the top of<br>footings (other than where the proposed wall (or<br>post) abuts an existing wall or structure of greater<br>height on the adjoining allotment).  |
|---|---|
| 4. Any development involving any of the following (or of any combination of any of the following):  (a) consulting room (b) office (c) shop.  | Except development that:  1. does not satisfy any of the following:  (a) General Neighbourhood Zone DTS/DPF 1.4  (b) General Neighbourhood Zone DTS/DPF 4.1  or  2. involves a building wall (or structure) that is proposed to be situated on (or abut) an allotment boundary (not being a boundary with a primary street or secondary street or an excluded boundary) and:  (a) the length of the proposed wall (or structure) exceeds 11.5m (other than where the proposed wall abuts an existing wall or structure of greater length on the adjoining allotment) or  (b) the height of the proposed wall (or post height) exceeds 3m measured from the top of footings (other than where the proposed wall (or post) abuts an existing wall or structure of greater height on the adjoining allotment). |
| <ul> <li>5. Any development involving any of the following (or of any combination of any of the following): <ul> <li>(a) internal building works</li> <li>(b) land division</li> <li>(c) recreation area</li> <li>(d) replacement building</li> <li>(e) temporary accommodation in an area affected by bushfire</li> <li>(f) tree damaging activity.</li> </ul> </li> </ul>   | None specified.   |
| <ul> <li>6. Alteration of or addition to any development involving the following (or of any combination of any of the following):</li> <li>(a) community facility</li> <li>(b) educational establishment</li> <li>(c) pre-school.</li> </ul>  | Except development that does not satisfy General Neighbourhood Zone DTS/DPF 1.5.  |
| 7. Demolition.  | Except any of the following:  |
|   | <ol> <li>the demolition of a State or Local Heritage Place</li> </ol>   |

Page 3 of 6 Printed on 5/07/2022

2. the demolition of a building (except an ancillary building) in a Historic Area Overlay.

Placement of Notices - Exemptions for Performance Assessed Development

None specified.

**Placement of Notices - Exemptions for Restricted Development** 

None specified.

# Part 3 - Overlays

#### Airport Building Heights (Regulated) Overlay

#### **Assessment Provisions (AP)**

| Desired Outcome |   |  |  |
|-----------------|---|--|--|
| DO 1            | Management of potential impacts of buildings and generated emissions to maintain operational and safety requirements of registered and certified commercial and military airfields, airports, airstrips and helicopter landing sites. |  |  |

Performance Outcomes (PO) and Deemed-to-Satisfy (DTS) Criteria / Designated Performance Feature (DPF)

| Performance Outcome   | Deemed-to-Satisfy Criteria / Designated Performance Feature   |
|---|---|
| Built   | Form  |
| PO 1.1  Building height does not pose a hazard to the operation of a certified or registered aerodrome. | DTS/DPF 1.1  Buildings are located outside the area identified as 'All structures' (no height limit is prescribed) and do not exceed the height specified in the Airport Building Heights (Regulated) Overlay which applies to the subject site as shown on the SA Property and Planning Atlas. |
|   | In instances where more than one value applies to the site, the lowest value relevant to the site of the proposed development is applicable.  |

#### Procedural Matters (PM) - Referrals

The following table identifies classes of development / activities that require referral in this Overlay and the applicable referral body. It sets out the purpose of the referral as well as the relevant statutory reference from Schedule 9 of the Planning, Development and Infrastructure (General) Regulations 2017.

| Class of Development / Activity               | Referral Body                                 | Purpose of Referral                        | Statutory Reference                                 |
|---|---|--|---|
| Any of the following classes of development:  | The airport-operator company for the relevant | To provide expert assessment and direction | Development of a class to which Schedule 9 clause 3 |
| (a) building located in an area identified as | airport within the meaning                    | to the relevant authority on               | item 1 of the Planning,                             |

Page 4 of 6 Printed on 5/07/2022

| 'All structures' (no height limit is prescribed) or will exceed the height specified in the Airport Building Heights (Regulated) Overlay  (b) building comprising exhaust stacks that generates plumes, or may cause plumes to be generated, above a height specified in the Airport Building Heights (Regulated) Overlay. | of the Airports Act 1996 of the Commonwealth or, if there is no airport-operator company, the Secretary of the Minister responsible for the administration of the Airports Act 1996 of the Commonwealth. | potential impacts on the safety and operation of aviation activities. | Development and Infrastructure (General) Regulations 2017 applies. |
|--|--|---|--|
|--|--|---|--|

# Part 4 - General Development Policies

#### **Clearance from Overhead Powerlines**

**Assessment Provisions (AP)** 

| Desired Outcome |   |  |  |
|-----------------|---|--|--|
| DO 1            | Protection of human health and safety when undertaking development in the vicinity of overhead transmission powerlines. |  |  |

| Performance Outcome   | Deemed-to-Satisfy Criteria / Designated Performance Feature   |
|---|---|
| PO 1.1  Buildings are adequately separated from aboveground powerlines to minimise potential hazard to people and property. | One of the following is satisfied:  (a) a declaration is provided by or on behalf of the applicant to the effect that the proposal would not be contrary to the regulations prescribed for the purposes of section 86 of the <i>Electricity Act 1996</i> (b) there are no aboveground powerlines adjoining the site that are the subject of the proposed development. |

# **Design in Urban Areas**

## **Assessment Provisions (AP)**

|      | Desired Outcome |  |  |  |
|------|-----------------|--|--|--|
| DO 1 | Development is: |  |  |  |
|      | (a)             | contextual - by considering, recognising and carefully responding to its natural surroundings or built environment and positively contributing to the character of the locality  |  |  |
|      | (b)             | durable - fit for purpose, adaptable and long lasting  |  |  |
|      | (c)             | inclusive - by integrating landscape design to optimise pedestrian and cyclist usability, privacy and equitable access and promoting the provision of quality spaces integrated with the public realm that can be used for access and recreation and help optimise security and safety both internally and within the public realm, for occupants and visitors |  |  |
|      | (d)             | sustainable - by integrating sustainable techniques into the design and siting of development and landscaping to improve community health, urban heat, water management, environmental performance, biodiversity and local amenity and to minimise energy consumption.   |  |  |

Page 5 of 6 Printed on 5/07/2022

# **Performance Outcome**

# Deemed-to-Satisfy Criteria / Designated Performance Feature

All Development

Fences and walls

PO 9.1

DTS/DPF 9.1

Fences, walls and retaining walls of sufficient height maintain privacy and security without unreasonably impacting visual amenity and adjoining land's access to sunlight or the amenity of public places.

None are applicable.

Page 6 of 6 Printed on 5/07/2022

#### **59 TRISTANIA TCE DERNANCOURT SA 5075**

#### Address:

Click to view a detailed interactive SAILIS in SAILIS

To view a detailed interactive property map in SAPPA click on the map below



#### **Property Zoning Details**

#### Overlay

Airport Building Heights (Regulated) (All structures over 45 metres)

Affordable Housing

Hazards (Flooding - Evidence Required)

Prescribed Wells Area

Regulated and Significant Tree

Stormwater Management

**Urban Tree Canopy** 

#### Zone

General Neighbourhood

#### Selected Development(s)

#### **Fence**

This development may be subject to multiple assessment pathways. Please review the document below to determine which pathway may be applicable based on the proposed development compliances to standards.

If no assessment pathway is shown this mean the proposed development will default to performance assessed. Please contact your local council in this instance. Refer to Part 1 - Rules of Interpretation - Determination of Classes of Development

Property Policy Information for above selection

Fence - Code Assessed - Performance Assessed

# Part 2 - Zones and Sub Zones

#### **General Neighbourhood Zone**

**Assessment Provisions (AP)** 

Page 1 of 6 Printed on 5/07/2022

# Do 1 Low-rise, low and medium-density housing that supports a range of needs and lifestyles located within easy reach of services and facilities. Employment and community service uses contribute to making the neighbourhood a convenient place to live without compromising residential amenity.

#### Table 5 - Procedural Matters (PM) - Notification

(g) dwelling addition

outbuilding

fence

The following table identifies, pursuant to section 107(6) of the *Planning, Development and Infrastructure Act 2016*, classes of performance assessed development that are excluded from notification. The table also identifies any exemptions to the placement of notices when notification is required.

#### Interpretation

Notification tables exclude the classes of development listed in Column A from notification provided that they do not fall within a corresponding exclusion prescribed in Column B.

Where a development or an element of a development falls within more than one class of development listed in Column A, it will be excluded from notification if it is excluded (in its entirety) under any of those classes of development. It need not be excluded under all applicable classes of development.

Where a development involves multiple performance assessed elements, all performance assessed elements will require notification (regardless of whether one or more elements are excluded in the applicable notification table) unless every performance assessed element of the application is excluded in the applicable notification table, in which case the application will not require notification.

| element of the application is excluded in the applicable notification table, in which case the application will not require notification.   |  |  |  |
|---|--|--|--|
| Exceptions  |  |  |  |
| (Column B)  |  |  |  |
| None specified.   |  |  |  |
| <ol> <li>residential flat building(s) of 3 or more building levels</li> <li>the demolition of a State or Local Heritage Place</li> <li>the demolition of a building (except an ancillary building) in a Historic Area Overlay.</li> </ol>   |  |  |  |
| Except development that:  1. does not satisfy General Neighbourhood Zone DTS/DPF 4.1 or 2. involves a building wall (or structure) that is proposed to be situated on (or abut) an allotment boundary (not being a boundary with a primary street or secondary street or an excluded boundary) and: |  |  |  |
|   |  |  |  |

Page 2 of 6 Printed on 5/07/2022

(a) the length of the proposed wall (or structure)

length on the adjoining allotment)

exceeds 11.5m (other than where the proposed

wall abuts an existing wall or structure of greater

| <ul> <li>(j) pergola</li> <li>(k) private bushfire shelter</li> <li>(l) residential flat building</li> <li>(m) retaining wall</li> <li>(n) retirement facility</li> <li>(o) shade sail</li> <li>(p) solar photovoltaic panels (roof mounted)</li> <li>(q) student accommodation</li> <li>(r) supported accommodation</li> <li>(s) swimming pool or spa pool</li> <li>(t) verandah</li> <li>(u) water tank.</li> </ul>   | or  (b) the height of the proposed wall (or post height) exceeds 3m measured from the top of footings (other than where the proposed wall (or post) abuts an existing wall or structure of greater height on the adjoining allotment).  |
|---|---|
| <ul> <li>4. Any development involving any of the following (or of any combination of any of the following): <ul> <li>(a) consulting room</li> <li>(b) office</li> <li>(c) shop.</li> </ul> </li> </ul>  | <ol> <li>does not satisfy any of the following:         <ul> <li>(a) General Neighbourhood Zone DTS/DPF 1.4</li> <li>(b) General Neighbourhood Zone DTS/DPF 4.1</li> </ul> </li> <li>or</li> <li>involves a building wall (or structure) that is proposed to be situated on (or abut) an allotment boundary (not being a boundary with a primary street or secondary street or an excluded boundary) and:         <ul> <li>(a) the length of the proposed wall (or structure) exceeds 11.5m (other than where the proposed wall abuts an existing wall or structure of greater length on the adjoining allotment) or</li> <li>(b) the height of the proposed wall (or post height) exceeds 3m measured from the top of footings (other than where the proposed wall (or post) abuts an existing wall or structure of greater height on the adjoining allotment).</li> </ul> </li> </ol> |
| <ul> <li>5. Any development involving any of the following (or of any combination of any of the following): <ul> <li>(a) internal building works</li> <li>(b) land division</li> <li>(c) recreation area</li> <li>(d) replacement building</li> <li>(e) temporary accommodation in an area affected by bushfire</li> <li>(f) tree damaging activity.</li> </ul> </li> <li>6. Alteration of or addition to any development involving the following (or of any combination of any of the</li> </ul> | None specified.  Except development that does not satisfy General Neighbourhood   |
| the following (or of any combination of any of the following):  (a) community facility (b) educational establishment (c) pre-school.  7. Demolition.  | Zone DTS/DPF 1.5.  Except any of the following:   |

Page 3 of 6 Printed on 5/07/2022

- 1. the demolition of a State or Local Heritage Place
- 2. the demolition of a building (except an ancillary building) in a Historic Area Overlay.

Placement of Notices - Exemptions for Performance Assessed Development

None specified.

**Placement of Notices - Exemptions for Restricted Development** 

None specified.

# Part 3 - Overlays

## **Airport Building Heights (Regulated) Overlay**

**Assessment Provisions (AP)** 

| Desired Outcome |   |  |  |
|-----------------|---|--|--|
| DO 1            | Management of potential impacts of buildings and generated emissions to maintain operational and safety requirements of registered and certified commercial and military airfields, airports, airstrips and helicopter landing sites. |  |  |

Performance Outcomes (PO) and Deemed-to-Satisfy (DTS) Criteria / Designated Performance Feature (DPF)

| Performance Outcome   | Deemed-to-Satisfy Criteria / Designated Performance Feature  |
|---|--|
| Built   | Form   |
| PO 1.1  Building height does not pose a hazard to the operation of a certified or registered aerodrome. | DTS/DPF 1.1  Buildings are located outside the area identified as 'All structures' (no height limit is prescribed) and do not exceed the height specified in the Airport Building Heights (Regulated)  Overlay which applies to the subject site as shown on the SA Property and Planning Atlas. |
|   | In instances where more than one value applies to the site, the lowest value relevant to the site of the proposed development is applicable.   |

#### Procedural Matters (PM) - Referrals

The following table identifies classes of development / activities that require referral in this Overlay and the applicable referral body. It sets out the purpose of the referral as well as the relevant statutory reference from Schedule 9 of the Planning, Development and Infrastructure (General) Regulations 2017.

| Class of Development / Activity              | Referral Body                                 | Purpose of Referral              | Statutory Reference                        |
|--|---|----------------------------------|--|
| Any of the following classes of development: | The airport-operator company for the relevant | To provide expert assessment and | Development of a class to which Schedule 9 |

Page 4 of 6 Printed on 5/07/2022

| <ul> <li>(a) building located in an area identified as 'All structures' (no height limit is prescribed) or will exceed the height specified in the Airport Building Heights (Regulated) Overlay</li> <li>(b) building comprising exhaust stacks that generates plumes, or may cause plumes to be generated, above a height specified in the Airport Building Heights (Regulated) Overlay.</li> </ul> | airport within the meaning of the Airports Act 1996 of the Commonwealth or, if there is no airport-operator company, the Secretary of the Minister responsible for the administration of the Airports Act 1996 of the | direction to the relevant<br>authority on potential<br>impacts on the safety<br>and operation of aviation<br>activities. | clause 3 item 1 of the<br>Planning, Development<br>and Infrastructure<br>(General) Regulations<br>2017 applies. |
|--|---|--|---|
|  | Commonwealth.   |  |   |

# Part 4 - General Development Policies

# **Clearance from Overhead Powerlines**

**Assessment Provisions (AP)** 

| Desired Outcome |   |  |  |
|-----------------|---|--|--|
| DO 1            | Protection of human health and safety when undertaking development in the vicinity of overhead transmission powerlines. |  |  |

| Performance Outcome   | Deemed-to-Satisfy Criteria /<br>Designated Performance<br>Feature   |  |
|---|---|--|
| Buildings are adequately separated from aboveground powerlines to minimise potential hazard to people and property. | One of the following is satisfied:  (a) a declaration is provided by or on behalf of the applicant to the effect that the proposal would not be contrary to the regulations prescribed for the purposes of section 86 of the Electricity Act 1996  (b) there are no aboveground powerlines adjoining the site that are the subject of the proposed development. |  |

# **Design in Urban Areas**

**Assessment Provisions (AP)** 

| Desired Outcome |        |  |  |
|-----------------|--------|--|--|
| DO 1            | Develo | ppment is:   |  |
|                 | (a)    | contextual - by considering, recognising and carefully responding to its natural surroundings or built environment and positively contributing to the character of the locality  |  |
|                 | (b)    | durable - fit for purpose, adaptable and long lasting  |  |
|                 | (c)    | inclusive - by integrating landscape design to optimise pedestrian and cyclist usability, privacy and equitable access and promoting the provision of quality spaces integrated with the public realm that can be used for access and recreation and help optimise security and safety both internally and within the public realm, for occupants and visitors |  |
|                 | (d)    | sustainable - by integrating sustainable techniques into the design and siting of development and landscaping to improve community health, urban heat, water management, environmental performance, biodiversity and   |  |

Page 5 of 6 Printed on 5/07/2022

local amenity and to minimise energy consumption.

# Performance Outcome Designated Performance Feature All Development Fences and walls PO 9.1 Fences, walls and retaining walls of sufficient height maintain privacy and security without unreasonably impacting visual amenity and adjoining land's access to sunlight or the amenity of public places. Demed-to-Satisfy Criteria / Designated Performance Feature None are applicable.

Page 6 of 6 Printed on 5/07/2022