228 SMART RD ST AGNES SA 5097

Address:

Click to view a detailed interactive SAILIS in SAILIS

To view a detailed interactive property map in SAPPA click on the map below



Property Zoning Details

Local Variation (TNV)

Maximum Building Height (Metres) (Maximum building height is 9m)

Maximum Building Height (Levels) (Maximum building height is 2 levels)

Overlay

Affordable Housing

Hazards (Flooding)

Hazards (Flooding - Evidence Required)

Prescribed Wells Area

Regulated and Significant Tree

Stormwater Management

Traffic Generating Development

Urban Tree Canopy

Water Resources

Zone

Employment

General Neighbourhood

Development Pathways

Employment

1. Accepted Development

Means that the development type does not require planning consent (planning approval). Please ensure compliance with relevant land use and development controls in the Code.

- Building work on railway land
- Internal building work
- · Partial demolition of a building or structure
- · Shade sail
- Solar photovoltaic panels (roof mounted)
- Water tank (above ground)
- Water tank (underground)

Page 1 of 141 Printed on 19/09/2022

2. Code Assessed - Deemed to Satisfy

Means that the development type requires consent (planning approval). Please ensure compliance with relevant land use and development controls in the Code.

- Advertisement
- · Temporary accommodation in an area affected by bushfire

3. Code Assessed - Performance Assessed

Performance Assessed development types listed below are those for which the Code identifies relevant policies. Additional development types that are not listed as Accepted, Deemed to Satisfy or Restricted default to a Performance assessed Pathway. Please contact your local council for more information.

- Advertisement
- · Consulting room
- Demolition
- · Land division
- · Light industry
- Office
- · Retaining wall
- · Service trade premises
- Shop
- Store
- · Telecommunications facility
- Warehouse

4. Impact Assessed - Restricted

Means that the development type requires approval. Classes of development that are classified as Restricted are listed in Table 4 of the relevant Zones.

General Neighbourhood

1. Accepted Development

Means that the development type does not require planning consent (planning approval). Please ensure compliance with relevant land use and development controls in the Code.

- · Air handling unit, air conditioning system or exhaust fan
- Building work on railway land
- Carport
- · Internal building work
- · Shade sail
- · Solar photovoltaic panels (roof mounted)
- Verandah
- Water tank (above ground)
- Water tank (underground)

2. Code Assessed - Deemed to Satisfy

Means that the development type requires consent (planning approval). Please ensure compliance with relevant land use and development controls in the Code.

- Carport
- Temporary accommodation in an area affected by bushfire
- Verandah

3. Code Assessed - Performance Assessed

Performance Assessed development types listed below are those for which the Code identifies relevant policies. Additional development types that are not listed as Accepted, Deemed to Satisfy or Restricted default to a Performance assessed Pathway. Please contact your local council for more information.

- Ancillary accommodation
- Carport
- Demolition

Page 2 of 141 Printed on 19/09/2022

- · Detached dwelling
- Dwelling addition
- Dwelling or residential flat building undertaken by:
 - (a) the South Australian Housing Trust either individually or jointly with other persons or bodies or
 - (b) a provider registered under the Community Housing National Law participating in a program relating to the renewal of housing endorsed by the South Australian Housing Trust.
- Fence
- · Group dwelling
- · Land division
- Outbuilding
- · Residential flat building
- Retaining wall
- Row dwelling
- · Semi-detached dwelling
- Tree-damaging activity
- Verandah
- 4. Impact Assessed Restricted
 Means that the development type requires approval. Classes of development that are classified as Restricted are listed in
 Table 4 of the relevant Zones.

Property Policy Information for above selection

Part 2 - Zones and Sub Zones

Employment Zone

Assessment Provisions (AP)

	Desired Outcome		
DO 1	A diverse range of low-impact light industrial, commercial and business activities that complement the role of other zones accommodating significant industrial, shopping and business activities.		
DO 2	Distinctive building, landscape and streetscape design to achieve high visual and environmental amenity particularly along arterial roads, zone boundaries and public open spaces.		

Performance Outcomes (PO) and Deemed-to-Satisfy (DTS) Criteria / Designated Performance Feature (DPF)

Performance Outcome	Deemed-to-Satisfy Criteria / Designated Performance Feature	
Land Use and Intensity		
PO 1.1	DTS/DPF 1.1	
A range of employment-generating light industrial, service trade, motor repair and other compatible businesses servicing the local community that do not produce emissions that would detrimentally affect local amenity.	Development comprises one or more of the following: (a) Advertisement (b) Consulting room (c) Indoor recreation facility	

Page 3 of 141 Printed on 19/09/2022

	(d) Light industry (e) Motor repair station (f) Office (g) Place of worship (h) Research facility (i) Retail fuel outlet (j) Service trade premises (k) Shop (l) Store (m) Telecommunications facility (n) Training facility (o) Warehouse.
PO 1.2	DTS/DPF 1.2
Shops provide convenient day-to-day services and amenities to local businesses and workers, support the sale of products manufactured on-site and otherwise complement the role of Activity Centres.	Shop where one of the following applies: (a) with a gross leasable floor area up to 100m² (b) is a bulky goods outlet (c) is a restaurant (d) is ancillary to and located on the same allotment as an industry and primarily involves the sale by retail of goods manufactured by the industry.
PO 1.3	DTS/DPF 1.3
Telecommunication facilities located to mitigate impacts on visual amenity in residential areas.	Telecommunications facility in the form of a monopole: (a) up to a height of 30m (b) no closer than 50m to a neighbourhood-type zone.
PO 1.4	DTS/DPF 1.4
Bulky good outlets and standalone shops are located to provide convenient access.	Bulky goods outlets and standalone shops are located on sites with a frontage to a State Maintained Road.
Built Form a	and Character
PO 2.1	DTS/DPF 2.1
Development achieves distinctive building, landscape and streetscape design to achieve high visual and environmental amenity particularly along arterial roads, zone boundaries and public open spaces.	None are applicable.
PO 2.2	DTS/DPF 2.2
Building facades facing a boundary of a zone primarily intended to accommodate residential development, public roads, or public open space incorporate design elements to add visual interest by considering the following: (a) using a variety of building finishes (b) avoiding elevations that consist solely of metal cladding (c) using materials with a low reflectivity (d) using techniques to add visual interest and reduce large expanses of blank walls including modulation and incorporation of offices and showrooms along elevations visible to a public road.	None are applicable.
Building heigh	nt and setbacks

Page 4 of 141 Printed on 19/09/2022

Policy24 - Enquiry	
PO 3.1	DTS/DPF 3.1
Buildings are set back from the primary street boundary to contribute to the existing/emerging pattern of street setbacks in the streetscape.	The building line of a building set back from the primary street boundary: (a) at least the average setback to the building line of existing buildings on adjoining sites which face the same primary street (including those buildings that would adjoin the site if not separated by a public road or a vacant allotment) (b) where there is only one existing building on adjoining sites which face the same primary street (including those that would adjoin if not separated by a public road or a vacant allotment), not less than the setback to the building line of that building or (c) not less than 3m where no building exists on an adjoining site with the same primary street frontage.
Buildings are set back from a secondary street boundary to	Building walls are no closer than 2m to the secondary street
accommodate the provision of landscaping between buildings and the street to enhance the appearance of land and buildings when viewed from the street.	boundary.
PO 3.3	DTS/DPF 3.3
Buildings are set back from rear access ways to provide	Building walls are set back from the rear access way:
adequate manoeuvrability for vehicles to enter and exit the site.	 (a) where the access way is 6.5m wide or more, no requirement (b) where the access way is less than 6.5m wide, the distance equal to the additional width required to make the access way at least 6.5m wide.
D0.0.4	·
PO 3.4 Buildings are sited to accommodate vehicle access to the rear of a site for deliveries, maintenance and emergency purposes.	Building walls are set back at least 3m from at least one side boundary, unless an alternative means for vehicular access to the rear of the site is available.
PO 3.5	DTS/DPF 3.5
Building height is consistent with the form expressed in any	Building height is not greater than:
relevant Maximum Building Height (Levels) Technical and Numeric Variation layer, and is otherwise generally low-rise to complement the established streetscape and local character.	(a) the following:
	Maximum Building Height (Levels)
	Maximum building height is 2 levels
	Maximum Building Height (Metres) Maximum building height is 9m
	(b) in all other cases (i.e. there are blank fields for both maximum building height (metres) and maximum building height (levels)) - 2 building levels up to a height of 9m.
	In relation to DTS/DPF 3.5, in instances where:
	(c) more than one value is returned in the same field for DTS/DPF 3.5(a) refer to the Maximum Building Height (Levels) Technical and Numeric Variation layer or

Page 5 of 141 Printed on 19/09/2022

Maximum Building Height (Metres) Technical and Numeric Variation layer in the SA planning database to determine the applicable value relevant to the site of the proposed development (d) only one value is returned for DTS/DPF 3.1(a) (i.e. there is one blank field), then the relevant height in metres or building levels applies with no criteria for the other. PO 3.6 DTS/DPF 3.6 Buildings mitigate visual impacts of building massing on Buildings are constructed within a building envelope provided by residential development within a neighbourhood-type zone. a 45 degree plane, measured from a height of 3m above natural ground level at the boundary of an allotment used for residential purposes in a neighbourhood-type zone as shown in the following diagram, except where the relevant boundary is a southern boundary or where this boundary is the primary street boundary. BUILDING ENVELOP PO 3.7 DTS/DPF 3.7 Buildings mitigate overshadowing of residential development Buildings on sites with a southern boundary adjoining an within a neighbourhood-type zone. allotment used for residential purposes within a neighbourhoodtype zone are constructed within a building envelope provided by a 30 degree plane grading north measured from a height of 3m above natural ground level at the southern boundary, as shown in the following diagram: PO 3.8 DTS/DPF 3.8 Buildings on an allotment fronting a road that is not a State None are applicable. maintained road, and where land on the opposite side of the road is within a neighbourhood-type zone, provides an orderly transition to the built form scale envisaged in the adjacent zone to complement the streetscape character. Site Dimensions and Land Division DTS/DPF 4.1 PO 4.1

Page 6 of 141 Printed on 19/09/2022

Land division creates allotments that vary in size and are suitable for a variety of commercial and business activities.	 (a) connected to an approved common wastewater disposal service have an area of 1250m² or more and a frontage width of 20m or more (b) that will require the disposal of wastewater on-site have an area of 2000m² or more and a frontage width of 20m or more.
Lands	scaping
PO 5.1	DTS/DPF 5.1
Landscaping is provided to enhance the visual appearance of development when viewed from public roads and thoroughfares.	Other than to accommodate a lawfully existing or authorised driveway or access point, or an access point for which consent has been granted as part of an application for the division of land, a landscaped area is provided within the development site: (a) where a building is set back less than 3m from the street boundary - 1m wide or the area remaining between the relevant building and the street boundary where the building is less than 1m from the street boundary or (b) in any other case - at least 1.5m wide.
P0 5.2	DTS/DPF 5.2
Development incorporates areas for landscaping to enhance the overall amenity of the site and locality.	(a) not less than 10 percent of the site (b) a dimension of at least 1.5m.
Adverti	sements
PO 6.1 Freestanding advertisements are not visually dominant within the locality.	DTS/DPF 6.1 Freestanding advertisements: (a) do not exceed 6m in height above natural ground level (b) do not have a face that exceeds 8m ² .
Conce	pt Plans
Development is compatible with the outcomes sought by any relevant Concept Plan contained within Part 12 - Concept Plans of the Planning and Design Code to support the orderly development of land through staging of development and provision of infrastructure.	DTS/DPF 7.1 The site of the development is wholly located outside any relevant Concept Plan boundary. The following Concept Plans are relevant: In relation to DTS/DPF 7.1, in instances where: (a) one or more Concept Plan is returned, refer to Part 12 - Concept Plans in the Planning and Design Code to determine if a Concept Plan is relevant to the site of the proposed development. Note: multiple concept plans may be relevant. (b) in instances where 'no value' is returned, there is no relevant concept plan and DTS/DPF 7.1 is met.

Table 5 - Procedural Matters (PM) - Notification

Page 7 of 141 Printed on 19/09/2022

The following table identifies, pursuant to section 107(6) of the *Planning, Development and Infrastructure Act 2016*, classes of performance assessed development that are excluded from notification. The table also identifies any exemptions to the placement of notices when notification is required.

Interpretation

Notification tables exclude the classes of development listed in Column A from notification provided that they do not fall within a corresponding exclusion prescribed in Column B.

Where a development or an element of a development falls within more than one class of development listed in Column A, it will be excluded from notification if it is excluded (in its entirety) under any of those classes of development. It need not be excluded under all applicable classes of development.

Where a development involves multiple performance assessed elements, all performance assessed elements will require notification (regardless of whether one or more elements are excluded in the applicable notification table) unless every performance assessed element of the application is excluded in the applicable notification table, in which case the application will not require notification.

Class	of Development	Exceptions
(Colun	nn A)	(Column B)
1.	Development which, in the opinion of the relevant authority, is of a minor nature only and will not unreasonably impact on the owners or occupiers of land in the locality of the site of the development.	None specified.
2.	Any development involving any of the following (or of any combination of any of the following): (a) advertisement (b) air handling unit, air conditioning system or exhaust fan (c) building on railway land (d) carport (e) fence (f) outbuilding (g) retaining wall (h) shade sail (i) solar photovoltaic panels (roof mounted) (j) temporary public service depot (k) verandah (l) water tank.	Except development that exceeds the maximum building height specified in Employment Zone DTS/DPF 3.5 or does not satisfy any of the following: 1. Employment Zone DTS/DPF 3.6 2. Employment Zone DTS/DPF 3.7.
3.	Any development involving any of the following (or of any combination of any of the following): (a) consulting room (b) light industry (c) office (d) motor repair station (e) retail fuel outlet (f) store (g) warehouse.	Except where the site of the development is adjacent land to a site (or land) used for residential purposes in a neighbourhood-type zone.
4.	Any development involving any of the following (or of any combination of any of the following): (a) internal building works (b) land division	None specified.

Page 8 of 141 Printed on 19/09/2022

olicy24 - Enquiry		
(c)	replacement building	
(d)	temporary accommodation in an area affected by bushfire	
(e)	tree damaging activity.	
5. Demoli	tion.	Except any of the following: 1. the demolition of a State or Local Heritage Place 2. the demolition of a building (except an ancillary building) in a Historic Area Overlay.
	ithin any of the following: Retail Activity Centre Subzone Roadside Service Centre Subzone.	Except shop that exceeds the maximum building height specified in Employment Zone DTS/DPF 3.5 or does not satisfy any of the following: 1. Employment Zone DTS/DPF 3.6 2. Employment Zone DTS/DPF 3.7.
7. Shop.		 Except: where the site of the shop is adjacent land to a site (or land) used for residential purposes in a neighbourhood-type zone or shop that exceeds the maximum building height specified in Employment Zone DTS/DPF 3.5 or shop that does not satisfy Employment Zone DTS/DPF 1.2.
8. Telecor	mmunications facility.	Except telecommunications facility that does not satisfy Employment Zone DTS/DPF 1.3.

Placement of Notices - Exemptions for Performance Assessed Development

None specified.

Placement of Notices - Exemptions for Restricted Development

None specified.

General Neighbourhood Zone

Assessment Provisions (AP)

Desired Outcome		
DO 1		
	Low-rise, low and medium-density housing that supports a range of needs and lifestyles located within easy reach of	
	services and facilities. Employment and community service uses contribute to making the neighbourhood a convenient	

Page 9 of 141 Printed on 19/09/2022

place to live without compromising residential amenity.

Performance Outcomes (PO) and Deemed to Satisfy (DTS) / Designated Performance Feature (DPF) Criteria

Performance Outcome	Deemed-to-Satisfy Criteria / Designated Performance Feature
Land Use a	and Intensity
PO 1.1	DTS/DPF 1.1
Predominantly residential development with complementary non-residential uses that support an active, convenient, and walkable neighbourhood.	Development comprises one or more of the following: (a) Ancillary accommodation (b) Community facility (c) Consulting room (d) Dwelling (e) Educational establishment (f) Office (g) Place of Worship (h) Pre-school (i) Recreation area (j) Residential flat building (k) Retirement facility (l) Shop (m) Student accommodation (n) Supported accommodation
PO 1.2	DTS/DPF 1.2
Non-residential development located and designed to improve community accessibility to services, primarily in the form of:	None are applicable.
(a) small scale commercial uses such as offices, shops and consulting rooms	
(b) community services such as educational establishments, community centres, places of worship, pre-schools, and other health and welfare services	
(c) services and facilities ancillary to the function or operation of supported accommodation or retirement facilities	
(d) open space and recreation facilities.	
PO 1.3	DTS/DPF 1.3
Non-residential development sited and designed to complement the residential character and amenity of the neighbourhood.	None are applicable.
PO 1.4	DTS/DPF 1.4
Commercial activities improve community access to services are of a scale and type to maintain residential amenity.	A shop, consulting room or office (or any combination thereof) satisfies any one of the following:
	(a) it is located on the same allotment and in conjunction with a dwelling where all the following are satisfied: (i) does not exceed 50m ² gross leasable floor

Page 10 of 141 Printed on 19/09/2022

Policy24 - Enquiry (ii) does not involve the display of goods in a window or about the dwelling or its curtilage (b) it reinstates a former shop, consulting room or office in an existing building (or portion of a building) and satisfies one of the following: the building is a State or Local Heritage Place (ii) is in conjunction with a dwelling and there is no increase in the gross leasable floor area previously used for non-residential purposes is located more than 500m from an Activity Centre and satisfies one of the following: does not exceed 100m² gross leasable floor area (individually or combined, in a single building) where the site does not have a frontage to a State Maintained Road (ii) does not exceed 200m² gross leasable floor area (individually or combined, in a single building) where the site has a frontage to a State Maintained Road (d) the development site abuts an Activity Centre and all the following are satisfied: it does not exceed 200m² gross leasable floor area (individually or combined, in a single building) (ii) the proposed development will not result in a combined gross leasable floor area (existing and proposed) of all shops, consulting rooms and offices that abut the Activity Centre in this zone exceeding the lesser of the following: 50% of the existing gross leasable floor area within the Activity Centre B. 1000m². PO 1.5 DTS/DPF 1.5 Expansion of existing community services such as educational Alteration of or addition to existing educational establishments, establishments, community facilities and pre-schools in a community facilities or pre-schools where all the following are manner which complements the scale of development envisaged satisfied: by the desired outcome for the neighbourhood. (a) set back at least 3m from any boundary shared with a residential land use (b) building height not exceeding 1 building level (c) the total floor area of the building not exceeding 150% of the total floor area prior to the addition/alteration (d) off-street vehicular parking exists or will be provided in accordance with the rate(s) specified in Transport, Access and Parking Table 1 - General Off-Street Car Parking Requirements or Table 2 - Off-Street Car Parking Requirements in Designated Areas to the nearest whole number. Site Dimensions and Land Division

Allotments/sites created for residential purposes are of suitable | Development will not result in more than 1 dwelling on an existing

DTS/DPF 2.1

PO 2.1

size and dimension to accommodate the anticipated dwelling form and remain compatible with the pattern of development in a low-rise and predominantly low-density neighbourhood, with higher densities closer to public open space, public transport stations and activity centres.

allotment

10

Allotments/sites for residential purposes accord with the following:

Dwelling Type	Minimum site/allotment area per dwelling	Minimum site/allotment frontage
Detached dwelling (not in a terrace arrangement)	300m ² (exclusive of any battle-axe allotment 'handle')	9m where not on a battle- axe site 5m where on a battle-axe site
Semi-detached dwelling	300m ²	9m
Row dwelling (or detached dwelling in a terrace arrangement)	250m ²	7m (averaged)
Group dwelling	300m ² (average, including common areas)	15m (total)
Dwelling within a residential flat building	300m² (average, including common areas)	15m (total)

PO 2.2

Development creating new allotments/sites in conjunction with retention of an existing dwelling ensures the site of the existing dwelling remains fit for purpose.

DTS/DPF 2.2

Where the site of a dwelling does not comprise an entire allotment:

- (a) the balance of the allotment accords with site area and frontage requirements specified in General Neighbourhood Zone DTS/DPF 2.1
- (b) if there is an existing dwelling on the allotment that will remain on the allotment after completion of the development, it will not contravene:
 - (i) Private open space requirements specified in Design in Urban Areas Table 1 Private Open Space
 - (ii) off-street vehicular parking exists in accordance with the rate(s) specified in Transport, Access and Parking Table 1 - General Off-Street Car Parking Requirements or Table 2 - Off-Street Car Parking Requirements in Designated Areas to the nearest whole number.

PO 2.3

Land division results in sites that are accessible and suitable for their intended purpose.

DTS/DPF 2.3

Division of land satisfies (a), (b) or (c):

- (a) reflects the site boundaries illustrated and approved in an existing development authorisation under the Development Act 1993 or Planning, Development and Infrastructure Act 2016 where the allotments are used or are proposed to be used solely for residential purposes
- is proposed as part of a combined land division application with deemed-to-satisfy dwellings on the proposed allotments
- (c) satisfies all of the following:
 - (i) No more than 5 additional allotments are created

Page 12 of 141 Printed on 19/09/2022

- (ii) Each proposed allotment has a minimum site area of 300m² and frontage of 9m
- (iii) Each proposed allotment has a slope less than 12.5% (1-in-8)
- (iv) There are no regulated trees on or within 20m of the subject land, with the distance measured from the base of the trunk of the tree (or the nearest trunk of the tree) to the subject land
- (v) The division does not involve creation of a public road
- (vi) Vehicle access from a public road can be provided to all proposed allotments which satisfies Design in Urban Areas DTS/DPF 23.3, 23.4 and 23.6, and would be located wholly on one side of the allotment, or located no more than 1m from the side boundary alignment
- (vii) No allotments are in a battle-axe configuration and
- (viii) Each proposed allotment is of a size and dimension capable of containing a rectangle 9m in width and 15m in depth.

Site Coverage

PO 3.1

Building footprints allow sufficient space around buildings to limit visual impact, provide an attractive outlook and access to light and ventilation.

DTS/DPF 3.1

The development does not result in site coverage exceeding 60%.

Building Height

PO 4.1

Buildings contribute to a low-rise suburban character.

DTS/DPF 4.1

Building height (excluding garages, carports and outbuildings) no greater than:

- (a) 2 building levels and 9m
- (b) wall height that is no greater than 7m except in the case of a gable end.

Primary Street Setback

PO 5.1

Buildings are setback from primary street boundaries to contribute to the existing/emerging pattern of street setbacks in the streetscape.

DTS/DPF 5.1

The building line of a building set back from the primary street boundary:

- (a) no more than 1m in front of the average setback to the building line of existing buildings on adjoining sites which face the same primary street (including those buildings that would adjoin the site if not separated by a public road or a vacant allotment)
- (b) where there is only one existing building on adjoining sites which face the same primary street (including those that would adjoin if not separated by a public road or a vacant allotment), no more than 1m in front of the setback to the building line of that building
- (c) not less than 5m where no building exists on an adjoining site with the same primary street frontage.

Page 13 of 141 Printed on 19/09/2022

Secondary 5	Street Setback	
PO 6.1	DTS/DPF 6.1	
Buildings are set back from secondary street boundaries to achieve separation between building walls and public streets and contribute to a suburban streetscape character.	Building walls are set back from the boundary of the allotment with a secondary street frontage: (a) at least 900mm or (b) if a dwelling on any adjoining allotment is closer to the secondary street than 900mm, at least the distance of that dwelling from the boundary with the secondary street.	
Bound	ary Walls	
PO 7.1	DTS/DPF 7.1	
Dwelling boundary walls are limited in height and length to manage visual and overshadowing impacts on adjoining properties.	Except where the dwelling is located on a central site within a row dwelling or terrace arrangement, side boundary walls occur only on one side boundary and satisfy (a) or (b) below: (a) side boundary walls adjoin or abut a boundary wall of a building on adjoining land for the same or lesser length and height (b) side boundary walls do not: (i) exceed 3m in height from the top of footings (ii) exceed 11.5m in length (iii) when combined with other walls on the boundary of the subject development site, exceed a maximum 45% of the length of the boundary (iv) encroach within 3m of any other existing or proposed boundary walls on the subject land.	
P0 7.2	DTS/DPF 7.2	
Dwellings in a semi-detached, row or terrace arrangement maintain space between buildings consistent with a suburban streetscape character.	Dwelling walls in a semi-detached, row or terrace arrangement are setback at least 900mm from side boundaries shared with allotments outside the development site.	
Side boun	dary setback	
PO 8.1	DTS/DPF 8.1	
Building walls are set back from side boundaries to provide: (a) separation between dwellings in a way that contributes to a suburban character and	Other than walls located on a side boundary, building walls are set back from side boundaries: (a) at least 900mm where the wall height is up to 3m (b) other than for a wall facing a southern side boundary, a least 900mm plus 1/3 of the wall height above 3m	
(b) access to natural light and ventilation for neighbours.	and (c) at least 1900mm plus 1/3 of the wall height above 3m for walls facing a southern side boundary.	
Rear boun	dary setback	
PO 9.1	DTS/DPF 9.1	

(a) if the size of the site is less than 301m²—

Dwelling walls are set back from rear boundaries to provide:

Dwelling walls are set back from the rear boundary at least:

- (a) separation between dwellings in a way that contributes to a suburban character
- (b) access to natural light and ventilation for neighbours
- (c) private open space
- (d) space for landscaping and vegetation.

- (i) 3m in relation to the ground floor of the dwelling
- (ii) 5m in relation to any other building level of the dwelling
- (b) if the size of the site is 301m² or more—
 - (i) 4m in relation to the ground floor of the dwelling
 - (ii) 6m in relation to any other building level of the dwelling.

Concept Plans

PO 10.1

Development is compatible with the outcomes sought by any relevant Concept Plan contained within Part 12 - Concept Plans of the Planning and Design Code to support the orderly development of land through staging of development and provision of infrastructure.

DTS/DPF 10.1

The site of the development is wholly located outside any relevant Concept Plan boundary. The following Concept Plans are relevant:

In relation to DTS/DPF 10.1, in instances where:

- (a) one or more Concept Plan is returned, refer to Part 12 -Concept Plans in the Planning and Design Code to determine if a Concept Plan is relevant to the site of the proposed development. Note: multiple concept plans may be relevant.
- (b) in instances where 'no value' is returned, there is no relevant concept plan and DTS/DPF 10.1 is met.

Ancillary Buildings and Structures

PO 11.1

Residential ancillary buildings are sited and designed to not detract from the streetscape or appearance of primary residential buildings on the site or neighbouring properties.

DTS/DPF 11.1

Ancillary buildings:

- (a) are ancillary to a dwelling erected on the same site
- (b) have a floor area not exceeding 60m2
- (c) are not constructed, added to or altered so that any part is situated:
 - (i) in front of any part of the building line of the dwelling to which it is ancillary or
 - (ii) within 900mm of a boundary of the allotment with a secondary street (if the land has boundaries on two or more roads)
- (d) in the case of a garage or carport, the garage or carport:
 - (i) is set back at least 5.5m from the boundary of the primary street
 - (ii) have a door / opening not exceeding:
 - A. for dwellings of single building level 7m in width or 50% of the site frontage, whichever is the lesser
 - B. for dwellings comprising two or more building levels at the building line fronting the same public street 7m in width

Page 15 of 141 Printed on 19/09/2022

- (e) if situated on a boundary (not being a boundary with a primary street or secondary street), do not exceed a length of 11.5m unless:
 - (i) a longer wall or structure exists on the adjacent site and is situated on the same allotment boundary and
 - (ii) the proposed wall or structure will be built along the same length of boundary as the existing adjacent wall or structure to the same or lesser extent
- (f) if situated on a boundary of the allotment (not being a boundary with a primary street or secondary street), all walls or structures on the boundary will not exceed 45% of the length of that boundary
- (g) will not be located within 3m of any other wall along the same boundary unless on an adjacent site on that boundary there is an existing wall of a building that would be adjacent to or about the proposed wall or structure
- (h) have a wall height or post height not exceeding 3m (and not including a gable end)
- (i) have a roof height where no part of the roof is more than 5m above the natural ground level
- (j) if clad in sheet metal, is pre-colour treated or painted in a non-reflective colour
- (k) retains a total area of soft landscaping in accordance with (i) or (ii), whichever is less:
- (i) a total area as determined by the following table:

Dwelling site area (or in the case of residential flat building or group dwelling(s), average site area) (m ²)	Minimum percentage of site
<150	10%
150-200	15%
201-450	20%
>450	25%

(ii) the amount of existing soft landscaping prior to the development occurring.

PO 11.2

Ancillary buildings and structures do not impede on-site functional requirements such as private open space provision, car parking requirements or result in over-development of the site.

DTS/DPF 11.2

Ancillary buildings and structures do not result in:

- (a) less private open space than specified in Design in Urban Areas Table 1 Private Open Space
- (b) less on-site car parking than specified in Transport, Access and Parking Table 1 - General Off-Street Car Parking Requirements or Table 2 - Off-Street Car Parking Requirements in Designated Areas.

Advertisements

Page 16 of 141 Printed on 19/09/2022

P0 12.1	DTS/DPF 12.1
Advertisements identify the associated business activity, and do not detract from the residential character of the locality.	Advertisements relating to a lawful business activity associated with a residential use do not exceed 0.3m2 and mounted flush with a wall or fence.

Table 5 - Procedural Matters (PM) - Notification

The following table identifies, pursuant to section 107(6) of the Planning, Development and Infrastructure Act 2016, classes of

Interpretation

Notification tables exclude the classes of development listed in Column A from notification provided that they do not fall within a corresponding exclusion prescribed in Column B.

Where a development or an element of a development falls within more than one class of development listed in Column A, it will be excluded from notification if it is excluded (in its entirety) under any of those classes of development. It need not be excluded under all applicable classes of development.

Where a development involves multiple performance assessed elements, all performance assessed elements will require notification (regardless of whether one or more elements are excluded in the applicable notification table) unless every performance assessed element of the application is excluded in the applicable notification table, in which case the application will not require notification.

Class	of Development	Exceptions	
(Column A)		(Column B)	
1.	Development which, in the opinion of the relevant authority, is of a minor nature only and will not unreasonably impact on the owners or occupiers of land in the locality of the site of the development.	None specified.	
2.	All development undertaken by: (a) the South Australian Housing Trust either individually or jointly with other persons or bodies or (b) a provider registered under the Community Housing National Law participating in a program relating to the renewal of housing endorsed by the South Australian Housing Trust.	 residential flat building(s) of 3 or more building levels the demolition of a State or Local Heritage Place the demolition of a building (except an ancillary building) in a Historic Area Overlay. 	
3.	Any development involving any of the following (or of any combination of any of the following): (a) air handling unit, air conditioning system or exhaust fan (b) ancillary accommodation (c) building work on railway land	Except development that: 1. does not satisfy General Neighbourhood Zone DTS/DPF 4.1 or 2. involves a building wall (or structure) that is proposed to	

- 2. involves a building wall (or structure) that is proposed to be situated on (or abut) an allotment boundary (not being a boundary with a primary street or secondary street or an excluded boundary) and:
 - (a) the length of the proposed wall (or structure) exceeds 11.5m (other than where the proposed wall abuts an existing wall or structure of greater length on the adjoining allotment) or
 - (b) the height of the proposed wall (or post height)

Printed on 19/09/2022

(d) carport

(f) dwelling

(g) dwelling addition

private bushfire shelter

(e) deck

(h) fence

Page 17 of 141

(i) outbuilding

pergola

performance assessed development that are excluded from notification. The table also identifies any exemptions to the placement of notices when notification is required.

exceeds 3m measured from the top of (I) residential flat building footings (other than where the proposed wall (or (m) retaining wall post) abuts an existing wall or structure of (n) retirement facility greater height on the adjoining allotment). (o) shade sail (p) solar photovoltaic panels (roof mounted) (q) student accommodation (r) supported accommodation (s) swimming pool or spa pool (t) verandah (u) water tank. 4. Any development involving any of the following (or of Except development that: any combination of any of the following): (a) consulting room 1. does not satisfy any of the following: (b) office (a) General Neighbourhood Zone DTS/DPF 1.4 (c) shop. (b) General Neighbourhood Zone DTS/DPF 4.1 or 2. involves a building wall (or structure) that is proposed to be situated on (or abut) an allotment boundary (not being a boundary with a primary street or secondary street or an excluded boundary) and: (a) the length of the proposed wall (or structure) exceeds 11.5m (other than where the proposed wall abuts an existing wall or structure of greater length on the adjoining allotment) (b) the height of the proposed wall (or post height) exceeds 3m measured from the top of footings (other than where the proposed wall (or post) abuts an existing wall or structure of greater height on the adjoining allotment). 5. Any development involving any of the following (or of None specified. any combination of any of the following): (a) internal building works (b) land division (c) recreation area (d) replacement building (e) temporary accommodation in an area affected by bushfire (f) tree damaging activity. 6. Alteration of or addition to any development involving Except development that does not satisfy General Neighbourhood the following (or of any combination of any of the Zone DTS/DPF 1.5. following): (a) community facility (b) educational establishment (c) pre-school. 7. Demolition. Except any of the following: 1. the demolition of a State or Local Heritage Place 2. the demolition of a building (except an ancillary building)

Page 18 of 141 Printed on 19/09/2022

in a Historic Area Overlay.

Placement of Notices - Exemptions for Performance Assessed Development

None specified.

Placement of Notices - Exemptions for Restricted Development

None specified.

Part 3 - Overlays

Affordable Housing Overlay

Assessment Provisions (AP)

	Desired Outcome		
DO 1	Affordable housing is integrated with residential and mixed use development.		
DO 2	Affordable housing caters for a variety of household structures.		

Performance Outcomes (PO) and Deemed-to-Satisfy (DTS) Criteria / Designated Performance Feature (DPF)

Performance Outcome	Deemed-to-Satisfy Criteria / Designated Performance Feature	
Land	Division	
P0 1.1	DTS/DPF 1.1	
Development comprising 20 or more dwellings / allotments incorporates affordable housing.	Development results in 0-19 additional allotments / dwellings.	
PO 1.2	DTS/DPF 1.2	
Development comprising 20 or more dwellings or residential allotments provides housing suited to a range of incomes including households with low to moderate incomes.	Development comprising 20 or more dwellings / or residential allotments includes a minimum of 15% affordable housing except where:	
	(a) it can be demonstrated that any shortfall in affordable housing has been provided in a previous stage of development or	
	(b) it can be demonstrated that any shortfall in affordable housing will be accommodated in a subsequent stage or stages of development.	

Page 19 of 141 Printed on 19/09/2022

PO 1.3	DTS/DPF 1.3	
Affordable housing is distributed throughout the development to avoid an overconcentration.	None are applicable.	
Built Form a	I nd Character	
P0 2.1	DTS/DPF 2.1	
Affordable housing is designed to complement the design and character of residential development within the locality.	None are applicable.	
Affordable Hou	using Incentives	
P0 3.1	DTS/DPF 3.1	
To support the provision of affordable housing, minimum allotment sizes may be reduced below the minimum allotment size specified in a zone while providing allotments of a suitable size and dimension to accommodate dwellings with a high standard of occupant amenity.	The minimum site area specified for a dwelling can be reduced by up to 20%, or the maximum density per hectare increased by up to 20%, where it is to be used to accommodate affordable housing except where the development is located within the Character Area Overlay or Historic Area Overlay.	
PO 3.2	DTS/DPF 3.2	
To support the provision of affordable housing, building heights may be increased above the maximum specified in a zone.	Where a building incorporates dwellings above ground level and includes at least 15% affordable housing, the maximum building height specified in any relevant zone policy can be increased by 1 building level in the: (a) Business Neighbourhood Zone (b) City Living Zone (c) Established Neighbourhood Zone (d) General Neighbourhood Zone (e) Hills Neighbourhood Zone (f) Housing Diversity Neighbourhood Zone (g) Neighbourhood Zone (h) Master Planned Neighbourhood Zone (i) Master Planned Renewal Zone (j) Master Planned Township Zone (k) Rural Neighbourhood Zone (l) Suburban Business Zone (m) Suburban Neighbourhood Zone (n) Township Neighbourhood Zone (o) Township Zone (p) Urban Renewal Neighbourhood Zone (q) Waterfront Neighbourhood Zone	
	and up to 30% in any other zone, except where: (a) the development is located within the Character Area Overlay or Historic Area Overlay or (b) other height incentives already apply to the development.	
Movement ar	nd Car Parking	
P0 4.1	DTS/DPF 4.1	

Page 20 of 141 Printed on 19/09/2022

Dwellings constituting affordable housing are provided with car Sufficient car parking is provided to meet the needs of parking in accordance with the following: occupants of affordable housing. 0.3 carparks per dwelling within a building which incorporates dwellings located above ground level within either: 200 metres of any section of road reserve along which a bus service operates as a high frequency public transit service⁽²⁾ (ii) is within 400 metres of a bus interchange⁽¹⁾ (iii) is within 400 metres of an O-Bahn interchange⁽¹⁾ is within 400 metres of a passenger rail station(1) (v) is within 400 metres of a passenger tram station⁽¹⁾ (vi) is within 400 metres of the Adelaide Parklands. (b) 1 carpark per dwelling for any other dwelling.

[NOTE(S): (1) Measured from an area that contains any platform(s), shelter(s) or stop(s) where people congregate for the purpose waiting to board a bus, tram or train, but does not include areas used for the parking of vehicles. (2) A high frequency public transit service is a route serviced every 15 minutes between 7.30am and 6.30pm Monday to Friday and every 30 minutes at night, Saturday, Sunday and public holidays until 10pm.]

Procedural Matters (PM) - Referrals

The following table identifies classes of development / activities that require referral in this Overlay and the applicable referral body. It sets out the purpose of the referral as well as the relevant statutory reference from Schedule 9 of the Planning, Development and Infrastructure (General) Regulations 2017.

Class of Development / Activity	•	Purpose of Referral	Statutory Reference
Development for the purposes of the provision of affordable housing (applying the criteria determined under regulation 4 of the South Australian Housing Trust Regulations 2010).	Minister responsible for administering the South Australian Housing Trust Act 1995.	To provide direction on the conditions required to secure the provision of dwellings or allotments for affordable housing.	Development of a class to which Schedule 9 clause 3 item 20 of the Planning, Development and Infrastructure (General) Regulations 2017 applies.

Hazards (Flooding) Overlay

Page 21 of 141 Printed on 19/09/2022

Assessment Provisions (AP)

Desired Outcome		
	Impacts on people, property, infrastructure and the environment from high flood risk are minimised by retaining areas free from development, and minimising intensification where development has occurred.	

Performance Outcomes (PO) and Deemed-to-Satisfy (DTS) Criteria / Designated Performance Feature (DPF)

Performance Outcome	Deemed-to-Satisfy Criteria / Designated Performance Feature	
Land I	Division	
PO 1.1	DTS/DPF 1.1	
Land division is limited to areas where the consequences to buildings and safety are low and can be readily managed or overcome.	None are applicable.	
Land	d Use	
PO 2.1	DTS/DPF 2.1	
Development sited and designed to minimise exposure of people and property to unacceptable flood risk.	None are applicable.	
PO 2.2	DTS/DPF 2.2	
Buildings housing vulnerable people, community services facilities, key infrastructure and emergency services are sited away from flood prone areas to enable uninterrupted operation of services and reduce likelihood of entrapment.	Pre-schools, educational establishments, retirement and supported accommodation, emergency services facilities, hospitals and prisons are not located within the Overlay area.	
Flood R	esilience	
PO 3.1	DTS/DPF 3.1	
Development avoids the need for flood protection works.	None are applicable.	
P0 3.2	DTS/DPF 3.2	
Development does not cause unacceptable impacts on any adjoining property by the diversion of flood waters or an increase in flood velocity or flood level.	None are applicable.	
PO 3.3	DTS/DPF 3.3	
Development does not impede the flow of floodwaters through the allotment or the surrounding land, or cause an unacceptable loss of flood storage.	None are applicable.	
PO 3.4	DTS/DPF 3.4	

Page 22 of 141 Printed on 19/09/2022

Development avoids frequently flooded or high velocity areas, other than where it is part of a flood mitigation scheme to reduce flood impact.	Other than a recreation area, development is located outside of the 5% AEP principal flow path.	
PO 3.5	DTS/DPF 3.5	
Buildings are sited, designed and constructed to prevent the entry of floodwaters in a 1% AEP flood event where the entry of floodwaters is likely to result in undue damage to, or compromise ongoing activities within, buildings.	Buildings comprise one of the following: (a) a porch or portico with at least 2 open sides (b) a verandah with at least 3 open sides (c) a carport or outbuilding with at least 2 open sides (whichever elevations face the direction of the flow) (d) any post construction with open sides (e) a building with a finished floor level that is at least 300mm above the height of a 1% AEP flood event.	
PO 3.6	DTS/DPF 3.6	
Fences do not unreasonably impede floodwaters.	A post and wire fence (other than a chain mesh fence).	
Environment	al Protection	
PO 4.1	DTS/DPF 4.1	
Buildings and structures used either partly or wholly to contain or store hazardous materials are designed to prevent spills or leaks leaving the confines of the building during a 1% AEP flood event to avoid potential environmental harm.		
PO 4.2	DTS/DPF 4.2	
Development does not create or aggravate the potential for erosion or siltation or lead to the destruction of vegetation during a flood.	None are applicable.	
Site Ear	thworks	
PO 5.1	DTS/DPF 5.1	
The depth and extent of filling required to raise the finished floor level of a building does not cause unacceptable impact on any adjoining property by diversion of flood waters, an increase in flood velocity or flood level, or an unacceptable loss of flood storage.	None are applicable.	
PO 5.2	DTS/DPF 5.2	
Driveways, access tracks and parking areas are designed and constructed to minimise excavation and filling.	· · · · · · · · · · · · · · · · · · ·	
Acc	cess	
PO 6.1	DTS/DPF 6.1	
Development does not occur on land:	None are applicable.	
 (a) from which evacuation to areas not vulnerable to flood risk is not possible during a 1% AEP flood event (b) which cannot be accessed by emergency services vehicles or essential utility service vehicles during a 1% AEP flood event. 		

Page 23 of 141 Printed on 19/09/2022

PO 6.2	DTS/DPF 6.2
Access driveways and tracks to significant development (i.e. dwellings, places of work, etc.) consist of a safe, all-weather trafficable surface that is accessible during a 1% AEP flood event.	None are applicable.

Procedural Matters (PM) - Referrals

The following table identifies classes of development / activities that require referral in this Overlay and the applicable referral body. It sets out the purpose of the referral as well as the relevant statutory reference from Schedule 9 of the Planning, Development and Infrastructure (General) Regulations 2017.

Class of Development / Activity	Referral Body		Statutory Reference
None	None	None	None

Hazards (Flooding - General) Overlay

Assessment Provisions (AP)

Performance Outcomes (PO) and Deemed-to-Satisfy (DTS) Criteria / Designated Performance Feature (DPF)

Performance Outcome	Deemed-to-Satisfy Criteria / Designated Performance Feature
Flood Resilience	

DTS/DPF 2.1

Habitable buildings, commercial and industrial buildings, and buildings used for animal keeping incorporate a finished ground and floor level not less than:

In instances where no finished floor level value is specified, a building incorporates a finished floor level at least 300mm above the height of a 1% AEP flood event.

Hazards (Flooding - Evidence Required) Overlay

Assessment Provisions (AP)

Desired Outcome		
DO 1	Development adopts a precautionary approach to mitigate potential impacts on people, property, infrastructure and the environment from potential flood risk through the appropriate siting and design of development.	

Performance Outcomes (PO) and Deemed-to-Satisfy (DTS) Criteria / Designated Performance Feature (DPF)

Performance Outcome	Deemed-to-Satisfy Criteria /
	Designated Performance
	Feature

Page 24 of 141 Printed on 19/09/2022

Flood R	esilience	
P01.1 Development is sited, designed and constructed to minimise the risk of entry of potential floodwaters where the entry of flood waters is likely to result in undue damage to or compromise ongoing activities within buildings.	DTS/DPF 1.1	
Environmen	tal Protection	
PO 2.1	DTS/DPF 2.1	
Buildings and structures used either partly or wholly to contain or store hazardous materials are designed to prevent spills or leaks leaving the confines of the building.	· ·	

Procedural Matters (PM) - Referrals

The following table identifies classes of development / activities that require referral in this Overlay and the applicable referral body. It sets out the purpose of the referral as well as the relevant statutory reference from Schedule 9 of the Planning, Development and Infrastructure (General) Regulations 2017.

Class of Development / Activity	Referral Body	Purpose of Referral	Statutory Reference
None	None	None	None

Prescribed Wells Area Overlay

Assessment Provisions (AP)

Desired Outcome		
DO 1	Sustainable water use in prescribed wells areas.	

Performance Outcome	Deemed-to-Satisfy Criteria / Designated Performance Feature
PO 1.1	DTS/DPF 1.1
All development, but in particular involving any of the following:	Development satisfies either of the following:
(a) horticulture	(a) the applicant has a current water licence in which

Page 25 of 141 Printed on 19/09/2022

- (b) activities requiring irrigation
- (c) aquaculture
- (d) industry
- (e) intensive animal husbandry
- (f) commercial forestry

has a lawful, sustainable and reliable water supply that does not place undue strain on water resources in prescribed wells areas.

sufficient spare capacity exists to accommodate the water needs of the proposed use

(b) the proposal does not involve the taking of water for which a licence would be required under the *Landscape South Australia Act 2019*.

Procedural Matters (PM) - Referrals

The following table identifies classes of development / activities that require referral in this Overlay and the applicable referral body. It sets out the purpose of the referral as well as the relevant statutory reference from Schedule 9 of the Planning, Development and Infrastructure (General) Regulations 2017.

Class of Development / Activity	Referral Body	Purpose of Referral	Statutory Reference
Any of the following classes of development that require or may require water to be taken in addition to any allocation that has already been granted under the Landscape South Australia Act 2019: (a) horticulture (b) activities requiring irrigation (c) aquaculture (d) industry (e) intensive animal husbandry (f) commercial forestry. Commercial forestry that requires a forest water licence under Part 8 Division 6 of the Landscape South Australia Act 2019.	The Chief Executive of the Department of the Minister responsible for the administration of the Landscape South Australia Act 2019.	To provide expert technical assessment and direction to the relevant authority on the taking of water to ensure development is undertaken sustainably.	Development of a class to which Schedule 9 clause 3 item 13 of the Planning, Development and Infrastructure (General) Regulations 2017 applies.

Regulated and Significant Tree Overlay

Assessment Provisions (AP)

Desired Outcome			
DO 1	Conservation of regulated and significant trees to provide aesthetic and environmental benefits and mitigate tree loss.		

Performance Outcomes (PO) and Deemed to Satisfy (DTS) / Designated Performance Feature (DPF) Criteria

Performance Outcome	Deemed-to-Satisfy Criteria / Designated Performance
	Feature

Page 26 of 141 Printed on 19/09/2022

i oneyz i	- Enquiry		
		Tree Retent	ion and Health
PO 1.1			DTS/DPF 1.1
Regulat	ted trees	are retained where they:	None are applicable.
(a)	make and am	an important visual contribution to local character nenity	
(b)	Nationa	ligenous to the local area and listed under the all Parks and Wildlife Act 1972 as a rare or gered native species	
(c)		e an important habitat for native fauna.	
PO 1.2			DTS/DPF 1.2
Signific	ant tree	s are retained where they:	None are applicable.
(a)		an important contribution to the character or y of the local area	
(b)	Nationa	ligenous to the local area and are listed under the all Parks and Wildlife Act 1972 as a rare or pered native species	
(c)		ent an important habitat for native fauna	
(d)	are pa vegeta	rt of a wildlife corridor of a remnant area of native tion	
(e)	local e	portant to the maintenance of biodiversity in the nvironment	
(f)	and / o form a local a	notable visual element to the landscape of the	
PO 1.3			DTS/DPF 1.3
	_	g activity not in connection with other atisfies (a) and (b):	None are applicable.
(a)	tree da	maging activity is only undertaken to:	
	(i)	remove a diseased tree where its life expectancy is short	
	(ii)	mitigate an unacceptable risk to public or private safety due to limb drop or the like	
	(iii)	rectify or prevent extensive damage to a building of value as comprising any of the following:	
		A. a Local Heritage Place	
		B. a State Heritage Place C. a substantial building of value	
		C. a substantial building of value	
		and there is no reasonable alternative to rectify or prevent such damage other than to undertake a tree damaging activity	
	(iv)	reduce an unacceptable hazard associated with a tree within 20m of an existing residential, tourist accommodation or other habitable building from bushfire	
	(v)	treat disease or otherwise in the general interests of the health of the tree and / or	
	(vi)	maintain the aesthetic appearance and structural integrity of the tree	

Page 27 of 141 Printed on 19/09/2022

Policy24	I - Enquiry			
(b)	in relation to a significant tree, tree-damaging activity is avoided unless all reasonable remedial treatments and measures have been determined to be ineffective.			
P0 1.4		DTS/DPF 1.4		
	damaging activity in connection with other development es all the following:	None are applicable.		
(a)	it accommodates the reasonable development of land in accordance with the relevant zone or subzone where such development might not otherwise be possible			
(b)	in the case of a significant tree, all reasonable development options and design solutions have been considered to prevent substantial tree-damaging activity occurring.			
	Ground work a	affecting trees		
PO 2.1		DTS/DPF 2.1		
not uno	ated and significant trees, including their root systems, are duly compromised by excavation and / or filling of land, or aling of surfaces within the vicinity of the tree to support etention and health.	None are applicable.		
	Land D	livision		
PO 3.1		DTS/DPF 3.1		
its sub	livision results in an allotment configuration that enables sequent development and the retention of regulated and cant trees as far as is reasonably practicable.	(a) there are no regulated or significant trees located within or adjacent to the plan of division or (b) the application demonstrates that an area exists to accommodate subsequent development of proposed allotments after an allowance has been made for a tree protection zone around any regulated tree within and adjacent to the plan of division.		

Procedural Matters (PM) - Referrals

The following table identifies classes of development / activities that require referral in this Overlay and the applicable referral body. It sets out the purpose of the referral as well as the relevant statutory reference from Schedule 9 of the Planning, Development and Infrastructure (General) Regulations 2017.

Class of Development / Activity	Referral Body	Purpose of Referral	Statutory Reference
None	None	None	None

Stormwater Management Overlay

Assessment Provisions (AP)

Desired Outcome		
DO 1	Development incorporates water sensitive urban design techniques to capture and re-use stormwater.	

Page 28 of 141 Printed on 19/09/2022

Deemed-to-Satisfy Criteria / **Performance Outcome Designated Performance Feature** DTS/DPF 1.1 PO 1.1 Residential development is designed to capture and re-use Residential development comprising detached, semi-detached or stormwater to: row dwellings, or less than 5 group dwellings or dwellings within a residential flat building: (a) maximise conservation of water resources (a) (b) includes rainwater tank storage: manage peak stormwater runoff flows and volume to ensure the carrying capacities of downstream systems connected to at least: are not overloaded in relation to a detached dwelling (not (c) manage stormwater runoff quality. in a battle-axe arrangement), semidetached dwelling or row dwelling, 60% of the roof area B. in all other cases, 80% of the roof area connected to either a toilet, laundry cold water outlets or hot water service for sites less than 200m² connected to one toilet and either the laundry cold water outlets or hot water service for sites of 200m² or greater (iv) with a minimum total capacity in accordance with Table 1 where detention is required, includes a 20-25 mm diameter slow release orifice at the bottom of the detention component of the tank (b) incorporates dwelling roof area comprising at least 80% of the site's impervious area Table 1: Rainwater Tank Site size Minimum Minimum (m^2) retention detention volume volume (Litres) (Litres) <200 1000 1000 200-400 2000 Site perviousness <30%: 1000 Site perviousness ≥30%: N/A >401 4000 Site perviousness <35%: 1000 Site perviousness

Procedural Matters (PM) - Referrals

Page 29 of 141 Printed on 19/09/2022

≥35%: N/A

The following table identifies classes of development / activities that require referral in this Overlay and the applicable referral body. It sets out the purpose of the referral as well as the relevant statutory reference from Schedule 9 of the Planning, Development and Infrastructure (General) Regulations 2017.

Class of Development / Activity	Referral Body	-	Statutory Reference
None	None	None	None

Traffic Generating Development Overlay

Assessment Provisions (AP)

	Desired Outcome		
DO 1	Safe and efficient operation of Urban Transport Routes and Major Urban Transport Routes for all road users.		
DO 2	Provision of safe and efficient access to and from urban transport routes and major urban transport routes.		

Performance Outcomes (PO) and Deemed to Satisfy (DTS) / Designated Performance Feature (DPF) Criteria

Performance Outcome	Deemed-to-Satisfy Criteria / Designated Performance Feature
Traffic General	ing Development
PO 1.1	DTS/DPF 1.1
Development designed to minimise its potential impact on the safety, efficiency and functional performance of the State Maintained Road network.	Access is obtained directly from a State Maintained Road where it involves any of the following types of development: (a) land division creating 50 or more additional allotments (b) commercial development with a gross floor area of 10,000m2 or more (c) retail development with a gross floor area of 2,000m2 or more (d) a warehouse or transport depot with a gross leasable floor area of 8,000m2 or more (e) industry with a gross floor area of 20,000m2 or more (f) educational facilities with a capacity of 250 students or more.
PO 1.2 Access points sited and designed to accommodate the type and volume of traffic likely to be generated by development.	DTS/DPF 1.2 Access is obtained directly from a State Maintained Road where it involves any of the following types of development:
	(a) land division creating 50 or more additional allotments

Page 30 of 141 Printed on 19/09/2022

Policy24 - Enquiry			
	(b) commercial development with a gross floor area of 10,000m2 or more		
	(c) retail development with a gross floor area of 2,000m2 or more		
	(d) a warehouse or transport depot with a gross leasable floor area of 8,000m2 or more		
	(e) industry with a gross floor area of 20,000m2 or more		
	(f) educational facilities with a capacity of 250 students or more.		
P01.3	DTS/DPF 1.3		
Sufficient accessible on-site queuing provided to meet the needs	Access is obtained directly from a State Maintained Road where		
of the development so that queues do not impact on the State Maintained Road network.	it involves any of the following types of development:		
	(a) land division creating 50 or more additional allotments		
	(b) commercial development with a gross floor area of 10,000m2 or more		
	(c) retail development with a gross floor area of 2,000m2 or more		
	(d) a warehouse or transport depot with a gross leasable floor area of 8,000m2 or more		
	(e) industry with a gross floor area of 20,000m2 or more		
	(f) educational facilities with a capacity of 250 students or more.		

Procedural Matters (PM) - Referrals

The following table identifies classes of development / activities that require referral in this Overlay and the applicable referral body. It sets out the purpose of the referral as well as the relevant statutory reference from Schedule 9 of the Planning, Development and Infrastructure (General) Regulations 2017.

Class of Development / Activity	Referral Body	Purpose of Referral	Statutory Reference
Except where all of the relevant deemed-to-satisfy criteria are met, any of the following classes of development that are proposed within 250m of a State Maintained Road: (a) land division creating 50 or more additional allotments (b) commercial development with a gross floor area of 10,000m² or more (c) retail development with a gross floor area of 2,000m² or more (d) a warehouse or transport depot with a gross leasable floor area of 8,000m² or more (e) industry with a gross floor area of 20,000m² or more (f) educational facilities with a capacity of 250 students or more.	Commissioner of Highways.	To provide expert technical assessment and direction to the Relevant Authority on the safe and efficient operation and management of all roads relevant to the Commissioner of Highways as described in the Planning and Design Code.	Development of a class to which Schedule 9 clause 3 item 7 of the Planning, Development and Infrastructure (General) Regulations 2017 applies.

Urban Tree Canopy Overlay

Assessment Provisions (AP)

Page 31 of 141 Printed on 19/09/2022

Desired Outcome

DO 1 Residential development preserves and enhances urban tree canopy through the planting of new trees and retention of existing mature trees where practicable.

Deemed-to-Satisfy Criteria / Performance Outcome Designated Performance Feature PO 1.1 DTS/DPF 1.1 Trees are planted or retained to contribute to an urban tree Tree planting is provided in accordance with the following: canopy. Site size per dwelling Tree size* and number required per dwelling (m²)<450 1 small tree 450-800 1 medium tree or 2 small trees >800 1 large tree or 2 medium trees or 4 small trees *refer Table 1 Tree Size Table 1 Tree Size Tree size Mature Mature Soil area around tree height spread within development (minimum) (minimum) site (minimum) Small 4 m 2m 10m² and min. dimension of 1.5m Medium 6 m 4 m 30m² and min. dimension of 2m Large 12 m 8m 60m² and min. dimension of 4m The discount in Column D of Table 2 discounts the number of trees required to be planted in DTS/DPF 1.1 where existing tree(s) are retained on the subject land that meet the criteria in Columns A, B and C of Table 2, and are not a species identified in Regulation 3F(4)(b) of the Planning Development and

Page 32 of 141 Printed on 19/09/2022

Infrastructure (General) Regulations 2017.

Table 2 Tree Discounts

Retained tree height (Column A)	Retained tree spread (Column B)	Retained soil area around tree within development site (Column C)	Discount applied (Column D)
4-6m	2-4m	10m ² and min. dimension of 1.5m	2 small trees (or 1 medium tree)
6-12m	4-8m	30m ² and min. dimension of 3m	2 medium trees (or 4 small trees)
>12m	>8m	60m ² and min. dimension of 6m	2 large trees (or 4 medium trees, or 8 small trees)

Note: In order to satisfy DTS/DPF 1.1, payment may be made in accordance with a relevant off-set scheme established by the Minister under section 197 of the Planning, Development and Infrastructure Act 2016, provided the provisions and requirements of that scheme are satisfied. For the purposes of section 102(4) of the Planning, Development and Infrastructure Act 2016, an applicant may elect for any of the matters in DTS/DPF 1.1 to be reserved.

Procedural Matters (PM) - Referrals

The following table identifies classes of development / activities that require referral in this Overlay and the applicable referral body. It sets out the purpose of the referral as well as the relevant statutory reference from Schedule 9 of the Planning, Development and Infrastructure (General) Regulations 2017.

Class of Development / Activity	Referral Body	Purpose of Referral	Statutory Reference
None	None	None	None

Water Resources Overlay

Assessment Provisions (AP)

	Desired Outcome
DO 1	Protection of the quality of surface waters considering adverse water quality impacts associated with projected

Page 33 of 141 Printed on 19/09/2022

	reductions in rainfall and warmer air temperatures as a result of climate change.
DO 2	Maintain the conveyance function and natural flow paths of watercourses to assist in the management of flood waters and stormwater runoff.

Performance Outcomes (PO) and Deemed-to-Satisfy (DTS) Criteria / Designated Performance Feature (DPF)

Performance Outcome	Deemed-to-Satisfy Criteria / Designated Performance Feature			
Water Catchment				
P0 1.1	DTS/DPF 1.1			
Watercourses and their beds, banks, wetlands and floodplains (1% AEP flood extent) are not damaged or modified and are retained in their natural state, except where modification is required for essential access or maintenance purposes.	None are applicable.			
PO 1.2	DTS/DPF 1.2			
Development avoids interfering with the existing hydrology or water regime of swamps and wetlands other than to improve the existing conditions to enhance environmental values.	None are applicable.			
PO 1.3	DTS/DPF 1.3			
Wetlands and low-lying areas providing habitat for native flora and fauna are not drained, except temporarily for essential management purposes to enhance environmental values.	None are applicable.			
PO 1.4	DTS/DPF 1.4			
Watercourses, areas of remnant native vegetation, or areas prone to erosion that are capable of natural regeneration are fenced off to limit stock access.	None are applicable.			
PO 1.5	DTS/DPF 1.5			
Development that increases surface water run-off includes a suitably sized strip of vegetated land on each side of a watercourse to filter runoff to: (a) reduce the impacts on native aquatic ecosystems (b) minimise soil loss eroding into the watercourse.	A strip of land 20m or more wide measured from the top of existing banks on each side of the watercourse is free from development, livestock use and revegetated with locally indigenous vegetation.			
PO 1.6	DTS/DPF 1.6			
Development resulting in the depositing or placing of an object or solid material in a watercourse or lake occurs only where it involves any of the following:	None are applicable.			
(a) the construction of an erosion control structure				
(b) devices or structures used to extract or regulate water flowing in a watercourse				
devices used for scientific purposes (d) the rehabilitation of watercourses.				

Page 34 of 141 Printed on 19/09/2022

PO 1.7	DTS/DPF 1.7
Watercourses, floodplains (1% AEP flood extent) and wetlands protected and enhanced by retaining and protecting existing native vegetation.	None are applicable.
PO 1.8	DTS/DPF 1.8
Watercourses, floodplains (1% AEP flood extent) and wetlands are protected and enhanced by stabilising watercourse banks and reducing sediments and nutrients entering the watercourse.	None are applicable.
PO 1.9	DTS/DPF 1.9
Dams, water tanks and diversion drains are located and constructed to maintain the quality and quantity of flows required to meet environmental and downstream needs.	None are applicable.

Procedural Matters (PM) - Referrals

The following table identifies classes of development / activities that require referral in this Overlay and the applicable referral body. It sets out the purpose of the referral as well as the relevant statutory reference from Schedule 9 of the Planning, Development and Infrastructure (General) Regulations 2017.

Class of Development / Activity	Referral Body	Purpose of Referral	Statutory Reference
None	None	None	None

Part 4 - General Development Policies

Advertisements

Assessment Provisions (AP)

Desired Outcome			
DO 1	Advertisements and advertising hoardings are appropriate to context, efficient and effective in communicating with the public, limited in number to avoid clutter, and do not create hazard.		

Performance Outcomes (PO) and Deemed-to-Satisfy (DTS) Criteria / Designated Performance Feature (DPF)

Performance Outcome	Deemed-to-Satisfy Criteria / Designated Performance Feature	
Appearance		

Page 35 of 141 Printed on 19/09/2022

PO 1.1	DTS/DPF 1.1	
Advertisements are compatible and integrated with the design of the building and/or land they are located on.	Advertisements attached to a building satisfy all of the following: (a) are not located in a Neighbourhood-type zone (b) where they are flush with a wall: (i) if located at canopy level, are in the form of a fascia sign	
	(ii) if located above canopy level: A. do not have any part rising above parapet height B. are not attached to the roof of the building	
	(c) where they are not flush with a wall: (i) if attached to a verandah, no part of the advertisement protrudes beyond the outer limits of the verandah structure	
	(ii) if attached to a two-storey building: A. has no part located above the finished floor level of the second storey of the building	
	B. does not protrude beyond the outer limits of any verandah structure below C. does not have a sign face that exceeds 1m2 per side.	
	(d) if located below canopy level, are flush with a wall (e) if located at canopy level, are in the form of a fascia sign (f) if located above a canopy: (i) are flush with a wall (ii) do not have any part rising above parapet height (iii) are not attached to the roof of the building.	
	(g) if attached to a verandah, no part of the advertisement protrudes beyond the outer limits of the verandah structure	
	(h) if attached to a two-storey building, have no part located above the finished floor level of the second storey of the building	
	(i) where they are flush with a wall, do not, in combination with any other existing sign, cover more than 15% of the building facade to which they are attached.	
P0 1.2	DTS/DPF 1.2	
Advertising hoardings do not disfigure the appearance of the land upon which they are situated or the character of the locality.	Where development comprises an advertising hoarding, the supporting structure is:	
	(a) concealed by the associated advertisement and decorative detailing or	
	(b) not visible from an adjacent public street or thoroughfare, other than a support structure in the form of a single or dual post design.	
PO 1.3	DTS/DPF 1.3	
Advertising does not encroach on public land or the land of an	Advertisements and/or advertising hoardings are contained	

Page 36 of 141 Printed on 19/09/2022

adjacent allotment.	within the boundaries of the site.
P0 1.4	DTS/DPF 1.4
Where possible, advertisements on public land are integrated with existing structures and infrastructure.	Advertisements on public land that meet at least one of the following:
	(a) achieves Advertisements DTS/DPF 1.1 (b) are integrated with a bus shelter.
PO 1.5	DTS/DPF 1.5
Advertisements and/or advertising hoardings are of a scale and size appropriate to the character of the locality.	None are applicable.
Proliferation of	f Advertisements
P0 2.1	DTS/DPF 2.1
Proliferation of advertisements is minimised to avoid visual clutter and untidiness.	No more than one freestanding advertisement is displayed per occupancy.
PO 2.2	DTS/DPF 2.2
Multiple business or activity advertisements are co-located and coordinated to avoid visual clutter and untidiness.	Advertising of a multiple business or activity complex is located on a single advertisement fixture or structure.
PO 2.3 Proliferation of advertisements attached to buildings is minimised to avoid visual clutter and untidiness.	DTS/DPF 2.3 Advertisements satisfy all of the following:
	(a) are attached to a building (b) other than in a Neighbourhood-type zone, where they are flush with a wall, cover no more than 15% of the building facade to which they are attached
	(c) do not result in more than one sign per occupancy that is not flush with a wall.
Advertisi	ng Content
PO 3.1	DTS/DPF 3.1
Advertisements are limited to information relating to the lawful use of land they are located on to assist in the ready identification of the activity or activities on the land and avoid unrelated content that contributes to visual clutter and untidiness.	Advertisements contain information limited to a lawful existing or proposed activity or activities on the same site as the advertisement.
Amenity	y Impacts
P0 4.1	DTS/DPF 4.1
Light spill from advertisement illumination does not unreasonably compromise the amenity of sensitive receivers.	Advertisements do not incorporate any illumination.
Sa	fety
PO 5.1	DTS/DPF 5.1
Advertisements and/or advertising hoardings erected on a verandah or projecting from a building wall are designed and located to allow for safe and convenient pedestrian access.	Advertisements have a minimum clearance of 2.5m between the top of the footpath and base of the underside of the sign.

Page 37 of 141 Printed on 19/09/2022

Advertisements and/or advertising hoardings do not distract or create a hazard to drivers through excessive illumination.	No advertisement illumination is proposed.
Advertisements and/or advertising hoardings do not create a hazard to drivers by: (a) being liable to interpretation by drivers as an official traffic sign or signal (b) obscuring or impairing drivers' view of official traffic signs or signals (c) obscuring or impairing drivers' view of features of a road that are potentially hazardous (such as junctions, bends, changes in width and traffic control devices) or other road or rail vehicles at/or approaching level crossings.	Advertisements satisfy all of the following: (a) are not located in a public road or rail reserve (b) are located wholly outside the land shown as 'Corner Cut-Off Area' in the following diagram Corner Cut-Off Area Allotment Boundary Road Reserve
P0 5.4 Advertisements and/or advertising hoardings do not create a hazard by distracting drivers from the primary driving task at a location where the demands on driver concentration are high.	DTS/DPF 5.4 Advertisements and/or advertising hoardings are not located along or adjacent to a road having a speed limit of 80km/h or more.
Advertisements and/or advertising hoardings provide sufficient clearance from the road carriageway to allow for safe and convenient movement by all road users.	DTS/DPF 5.5 Where the advertisement or advertising hoarding is: (a) on a kerbed road with a speed zone of 60km/h or less, the advertisement or advertising hoarding is located at least 0.6m from the roadside edge of the kerb (b) on an unkerbed road with a speed zone of 60km/h or less, the advertisement or advertising hoarding is located at least 5.5m from the edge of the seal (c) on any other kerbed or unkerbed road, the advertisement or advertising hoarding is located a minimum of the following distance from the roadside edge of the kerb or the seal: (a) 110 km/h road - 14m (b) 100 km/h road - 13m (c) 90 km/h road - 10m (d) 70 or 80 km/h road - 8.5m.
P0 5.6 Advertising near signalised intersections does not cause unreasonable distraction to road users through illumination, flashing lights, or moving or changing displays or messages.	DTS/DPF 5.6 Advertising: (a) is not illuminated (b) does not incorporate a moving or changing display or message (c) does not incorporate a flashing light(s).

Animal Keeping and Horse Keeping

Assessment Provisions (AP)

Page 38 of 141 Printed on 19/09/2022

Desired Outcome

DO 1

Animals are kept at a density that is not beyond the carrying capacity of the land and in a manner that minimises their adverse effects on the environment, local amenity and surrounding development.

Performance Outcomes (PO) and Deemed-to-Satisfy (DTS) Criteria / Designated Performance Feature (DPF)

Performance Outcome	Deemed-to-Satisfy Criteria / Designated Performance Feature
Siting ar	nd Design
PO 1.1	DTS/DPF 1.1
Animal keeping, horse keeping and associated activities do not create adverse impacts on the environment or the amenity of the locality.	None are applicable.
PO 1.2	DTS/DPF 1.2
Animal keeping and horse keeping is located and managed to minimise the potential transmission of disease to other operations where animals are kept.	None are applicable.
Horse	Keeping
PO 2.1	DTS/DPF 2.1
Water from stable wash-down areas is directed to appropriate absorption areas and/or drainage pits to minimise pollution of land and water.	None are applicable.
PO 2.2	DTS/DPF 2.2
Stables, horse shelters or associated yards are sited appropriate distances away from sensitive receivers and/or allotments in other ownership to avoid adverse impacts from dust, erosion and odour.	Stables, horse shelters and associated yards are sited in accordance with all of the following: (a) 30m or more from any sensitive receivers (existing or approved) on land in other ownership (b) where an adjacent allotment is vacant and in other ownership, 30m or more from the boundary of that allotment.
PO 2.3	DTS/DPF 2.3
All areas accessible to horses are separated from septic tank effluent disposal areas to protect the integrity of that system. Stable flooring is constructed with an impervious material to facilitate regular cleaning.	Septic tank effluent disposal areas are enclosed with a horse- proof barrier such as a fence to exclude horses from this area.
PO 2.4	DTS/DPF 2.4
To minimise environmental harm and adverse impacts on water resources, stables, horse shelters and associated yards are appropriately set back from a watercourse.	Stables, horse shelters and associated yards are set back 50m or more from a watercourse.
PO 2.5	DTS/DPF 2.5

Page 39 of 141 Printed on 19/09/2022

Policy24 - Enquiry	
Stables, horse shelters and associated yards are located on slopes that are stable to minimise the risk of soil erosion and water runoff.	Stables, horse shelters and associated yards are not located on land with a slope greater than 10% (1-in-10).
Ker	nnels
PO 3.1	DTS/DPF 3.1
Kennel flooring is constructed with an impervious material to facilitate regular cleaning.	The floors of kennels satisfy all of the following: (a) are constructed of impervious concrete (b) are designed to be self-draining when washed down.
PO 3.2	DTS/DPF 3.2
Kennels and exercise yards are designed and sited to minimise noise nuisance to neighbours through measures such as: (a) adopting appropriate separation distances (b) orientating openings away from sensitive receivers.	Kennels are sited 500m or more from the nearest sensitive receiver on land in other ownership.
P0 3.3	DTS/DPF 3.3
Dogs are regularly observed and managed to minimise nuisance impact on adjoining sensitive receivers from animal behaviour.	Kennels are sited in association with a permanent dwelling on the land.
Wastes	
P0 4.1 Storage of manure, used litter and other wastes (other than wastewater lagoons) is designed, constructed and managed to minimise attracting and harbouring vermin.	DTS/DPF 4.1 None are applicable.
PO 4.2 Facilities for the storage of manure, used litter and other wastes (other than wastewater lagoons) are located to minimise the potential for polluting water resources.	DTS/DPF 4.2 Waste storage facilities (other than wastewater lagoons) are located outside the 1% AEP flood event areas.

Aquaculture

Assessment Provisions (AP)

Desired Outcome	
DO 1	Aquaculture facilities are developed in an ecologically, economically and socially sustainable manner to support an equitable sharing of marine, coastal and inland resources and mitigate conflict with other water-based and land-based uses.

Performance Outcomes (PO) and Deemed-to-Satisfy (DTS) Criteria / Designated Performance Feature (DPF)

Performance Outcome	Deemed-to-Satisfy Criteria /
	Designated Performance

Page 40 of 141 Printed on 19/09/2022

	Feature
Land-based	Aquaculture
PO 1.1	DTS/DPF 1.1
Land-based aquaculture and associated components are sited and designed to mitigate adverse impacts on nearby sensitive receivers.	Land-based aquaculture and associated components are located to satisfy all of the following: (a) 200m or more from a sensitive receiver in other ownership (b) 500m or more from the boundary of a zone primarily intended to accommodate sensitive receivers.
	intended to accommodate sensitive receivers.
PO 1.2	DTS/DPF 1.2
Land-based aquaculture and associated components are sited and designed to prevent surface flows from entering ponds in a 1% AEP sea flood level event.	None are applicable.
P0 1.3	DTS/DPF 1.3
Land-based aquaculture and associated components are sited and designed to prevent pond leakage that would pollute groundwater.	None are applicable.
P0 1.4	DTS/DPF 1.4
Land-based aquaculture and associated components are sited and designed to prevent farmed species escaping and entering into any waters.	None are applicable.
PO 1.5	DTS/DPF 1.5
Land-based aquaculture and associated components, including intake and discharge pipes, are designed to minimise the need to traverse sensitive areas to minimise impact on the natural environment.	None are applicable.
PO 1.6	DTS/DPF 1.6
Pipe inlets and outlets associated with land-based aquaculture are sited and designed to minimise the risk of disease transmission.	None are applicable.
PO 1.7	DTS/DPF 1.7
Storage areas associated with aquaculture activity are integrated with the use of the land and sited and designed to minimise their visual impact on the surrounding environment.	None are applicable.
Marine Base	d Aquaculture
PO 2.1	DTS/DPF 2.1
Marine aquaculture is sited and designed to minimise its adverse impacts on sensitive ecological areas including:	None are applicable.
(a) creeks and estuaries (b) wetlands (c) significant seagrass and mangrove communities (d) marine habitats and ecosystems.	

Page 41 of 141 Printed on 19/09/2022

PO 2.2	. ,	DTS/DPF 2.2
to disp	aquaculture is sited in areas with adequate water current erse sediments and dissolve particulate wastes to t the build-up of waste that may cause environmental	None are applicable.
PO 2.3		DTS/DPF 2.3
	aquaculture is designed to not involve discharge of waste on the site, on any adjacent land or into nearby .	None are applicable.
PO 2.4		DTS/DPF 2.4
	aquaculture (other than inter-tidal aquaculture) is located ropriate distance seaward of the high water mark.	Marine aquaculture development is located 100m or more seaward of the high water mark.
PO 2.5		DTS/DPF 2.5
Marine interfer	aquaculture is sited and designed to not obstruct or re with:	None are applicable.
(a) (b)	areas of high public use areas, including beaches, used for recreational activities such as swimming, fishing, skiing, sailing and other water sports	
(c) (d)	areas of outstanding visual or environmental value	
(e)	areas of high tourism value areas of important regional or state economic activity, including commercial ports, wharfs and jetties	
(f)	the operation of infrastructure facilities including inlet and outlet pipes associated with the desalination of sea water.	
PO 2.6		DTS/DPF 2.6
interfer	aquaculture is sited and designed to minimise rence and obstruction to the natural processes of the land marine environment.	None are applicable.
PO 2.7		DTS/DPF 2.7
	aquaculture is designed to be as unobtrusive as able by incorporating measures such as:	None are applicable.
(a)	using feed hoppers painted in subdued colours and suspending them as close as possible to the surface of the water	
(b)	positioning structures to protrude the minimum distance practicable above the surface of the water	
(c)	avoiding the use of shelters and structures above cages and platforms unless necessary to exclude predators and protected species from interacting with the farming structures and/or stock inside the cages, or for safety reasons	
(d)	positioning racks, floats and other farm structures in unobtrusive locations landward from the shoreline.	
PO 2.8		DTS/DPF 2.8
	s, launching and maintenance facilities utilise existing shed roads, tracks, ramps and paths to or from the sea	None are applicable.

Page 42 of 141 Printed on 19/09/2022

Policy24 - Enquiry	
where possible to minimise environmental and amenity impacts.	
PO 2.9	DTS/DPF 2.9
Access, launching and maintenance facilities are developed as common user facilities and are co-located where practicable to mitigate adverse impacts on coastal areas.	None are applicable.
PO 2.10	DTS/DPF 2.10
Marine aquaculture is sited to minimise potential impacts on, and to protect the integrity of, reserves under the <i>National Parks and Wildlife Act 1972</i> .	Marine aquaculture is located 1000m or more seaward of the boundary of any reserve under the <i>National Parks and Wildlife Act</i> 1972.
PO 2.11	DTS/DPF 2.11
Onshore storage, cooling and processing facilities do not impair the coastline and its visual amenity by:	None are applicable.
(a) being sited, designed, landscaped and of a scale to reduce the overall bulk and appearance of buildings and complement the coastal landscape	
(b) making provision for appropriately sited and designed vehicular access arrangements, including using existing vehicular access arrangements as far as practicable	
(c) incorporating appropriate waste treatment and disposal.	
Navigation	and Safety
PO 3.1	DTS/DPF 3.1
Marine aquaculture sites are suitably marked to maintain navigational safety.	None are applicable.
PO 3.2	DTS/DPF 3.2
Marine aquaculture is sited to provide adequate separation between farms for safe navigation.	None are applicable.
Environmenta	l Management
PO 4.1	DTS/DPF 4.1
Marine aquaculture is maintained to prevent hazards to people and wildlife, including breeding grounds and habitats of native marine mammals and terrestrial fauna, especially migratory species.	None are applicable.
PO 4.2	DTS/DPF 4.2
Marine aquaculture is designed to facilitate the relocation or removal of structures in the case of emergency such as oil spills, algal blooms and altered water flows.	None are applicable.
PO 4.3	DTS/DPF 4.3
Marine aquaculture provides for progressive or future reclamation of disturbed areas ahead of, or upon, decommissioning.	None are applicable.
PO 4.4	DTS/DPF 4.4
Aquaculture operations incorporate measures for the removal	None are applicable.

Page 43 of 141 Printed on 19/09/2022

and disposal of litter, disused material, shells, debris, detritus,	
dead animals and animal waste to prevent pollution of waters,	
wetlands, or the nearby coastline.	

Beverage Production in Rural Areas

Assessment Provisions (AP)

Desired Outcome	
DO 1	Mitigation of potential amenity and environmental impacts of value-adding beverage production facilities such as wineries, distilleries, cideries and breweries.

Performance Outcomes (PO) and Deemed-to-Satisfy (DTS) Criteria / Designated Performance Feature (DPF)

Performance Outcome	Deemed-to-Satisfy Criteria / Designated Performance Feature
Odour a	nd Noise
PO 1.1	DTS/DPF 1.1
Beverage production activities are designed and sited to minimise odour impacts on rural amenity.	None are applicable.
PO 1.2	DTS/DPF 1.2
Beverage production activities are designed and sited to minimise noise impacts on sensitive receivers.	None are applicable.
PO 1.3	DTS/DPF 1.3
Fermentation, distillation, manufacturing, storage, packaging and bottling activities occur within enclosed buildings to improve the visual appearance within a locality and manage noise associated with these activities.	None are applicable.
PO 1.4	DTS/DPF 1.4
Breweries are designed to minimise odours emitted during boiling and fermentation stages of production.	Brew kettles are fitted with a vapour condenser.
PO 1.5	DTS/DPF 1.5
Beverage production solid wastes are stored in a manner that minimises odour impacts on sensitive receivers in other ownership.	Solid waste from beverage production is collected and stored in sealed containers and removed from the site within 48 hours.
Water	Quality
PO 2.1	DTS/DPF 2.1

Page 44 of 141 Printed on 19/09/2022

Wastewater management systems are set back 50m or more from the banks of watercourses and bores.
DTS/DPF 2.2
None are applicable.
DTS/DPF 2.3
None are applicable.
DTS/DPF 2.4
None are applicable.
er Irrigation
DTS/DPF 3.1
None are applicable.
DTS/DPF 3.2
Beverage production wastewater is not irrigated within 50m of any dwelling in other ownership.
DTS/DPF 3.3
None are applicable.

Bulk Handling and Storage Facilities

Assessment Provisions (AP)

Desired Outcome

Page 45 of 141 Printed on 19/09/2022

DO 1

Facilities for the bulk handling and storage of agricultural, mineral, petroleum, rock, ore or other similar commodities are designed to minimise adverse impacts on transport networks, the landscape and surrounding land uses.

Performance Outcomes (PO) and Deemed-to-Satisfy (DTS) Criteria / Designated Performance Feature (DPF)

Deemed-to-Satisfy Criteria / Performance Outcome Designated Performance Feature Siting and Design PO 1.1 DTS/DPF 1.1 Bulk handling and storage facilities are sited and designed to Facilities for the handling, storage and dispatch of commodities minimise risks of adverse air quality and noise impacts on in bulk (excluding processing) meet the following minimum separation distances from sensitive receivers: sensitive receivers. bulk handling of agricultural crop products, rock, ores, minerals, petroleum products or chemicals at a wharf or wharf side facility (including sea-port grain terminals), where the handling of these materials into or from vessels does not exceed 100 tonnes per day: 300m or more from residential premises not associated with the facility (b) bulk handling of agricultural crop products, rock, ores, minerals, petroleum products or chemicals to or from any commercial storage facility: 300m or more from residential premises not associated with the facility bulk petroleum storage involving individual containers with a capacity up to 200 litres and a total on-site storage capacity not exceeding 1,000 cubic metres: 500m or more (d) coal handling with: a. capacity up to 1 tonne per day or a storage capacity up to 50 tonnes: 500m or more b. capacity exceeding 1 tonne per day but not exceeding 100 tonnes per day or a storage capacity exceeding 50 tonnes but not exceeding 5000 tonnes: 1000m or more. Buffers and Landscaping PO 2.1 DTS/DPF 2.1 Bulk handling and storage facilities incorporate a buffer area for None are applicable. the establishment of dense landscaping adjacent road frontages to enhance the appearance of land and buildings from public thoroughfares. PO 2.2 DTS/DPF 2.2 Bulk handling and storage facilities incorporate landscaping to None are applicable. assist with screening and dust filtration. Access and Parking PO 3.1 Roadways and vehicle parking areas associated with bulk Roadways and vehicle parking areas are sealed with an allhandling and storage facilities are designed and surfaced to weather surface.

Page 46 of 141 Printed on 19/09/2022

control dust emissions and prevent drag out of material from the	
site.	
Slipways, Wharv	es and Pontoons
PO 4.1	DTS/DPF 4.1
Slipways, wharves and pontoons used for the handling of bulk materials (such as fuel, oil, catch, bait and the like) incorporate catchment devices to avoid the release of materials into adjacent waters.	None are applicable.

Clearance from Overhead Powerlines

Assessment Provisions (AP)

	Desired Outcome
DO 1	Protection of human health and safety when undertaking development in the vicinity of overhead transmission powerlines.

Performance Outcome	Deemed-to-Satisfy Criteria / Designated Performance Feature
PO 1.1 Buildings are adequately separated from aboveground powerlines to minimise potential hazard to people and property.	One of the following is satisfied: (a) a declaration is provided by or on behalf of the applicant to the effect that the proposal would not be contrary to the regulations prescribed for the purposes of section 86 of the Electricity Act 1996 (b) there are no aboveground powerlines adjoining the site that are the subject of the proposed development.

Design

Assessment Provisions (AP)

Desired Outcome		
DO 1	Development is:	
	 (a) contextual - by considering, recognising and carefully responding to its natural surroundings or built environment and positively contributes to the character of the immediate area (b) durable - fit for purpose, adaptable and long lasting 	

Page 47 of 141 Printed on 19/09/2022

- (c) inclusive by integrating landscape design to optimise pedestrian and cyclist usability, privacy and equitable access, and promoting the provision of quality spaces integrated with the public realm that can be used for access and recreation and help optimise security and safety both internally and within the public realm, for occupants and visitors
- (d) sustainable by integrating sustainable techniques into the design and siting of development and landscaping to improve community health, urban heat, water management, environmental performance, biodiversity and local amenity and to minimise energy consumption.

Performance Outcome Deemed-to-Satisfy Criteria / **Designated Performance Feature** All development **External Appearance** PO 1.1 DTS/DPF 1.1 Buildings reinforce corners through changes in setback, None are applicable. articulation, materials, colour and massing (including height, width, bulk, roof form and slope). PO 1.2 DTS/DPF 1.2 Where zero or minor setbacks are desirable, development None are applicable. provides shelter over footpaths (in the form of verandahs, awnings, canopies and the like, with adequate lighting) to positively contribute to the walkability, comfort and safety of the public realm. PO 1.3 DTS/DPF 1.3 Building elevations facing the primary street (other than ancillary None are applicable. buildings) are designed and detailed to convey purpose, identify main access points and complement the streetscape. PO 1.4 DTS/DPF 1.4 Plant, exhaust and intake vents and other technical equipment is Development does not incorporate any structures that protrude integrated into the building design to minimise visibility from the beyond the roofline. public realm and negative impacts on residential amenity by: (a) positioning plant and equipment in unobtrusive locations viewed from public roads and spaces (b) screening rooftop plant and equipment from view (c) when located on the roof of non-residential development, locating the plant and equipment as far as practicable from adjacent sensitive land uses. DTS/DPF 1.5 PO 1.5 The negative visual impact of outdoor storage, waste None are applicable. management, loading and service areas is minimised by integrating them into the building design and screening them from public view (such as fencing, landscaping and built form) taking into account the form of development contemplated in the relevant zone. Safety DTS/DPF 2.1 PO 2.1

Page 48 of 141 Printed on 19/09/2022

Development maximises opportunities for passive surveillance of the public realm by providing clear lines of sight, appropriate lighting and the use of visually permeable screening wherever practicable.	None are applicable.
PO 2.2	DTS/DPF 2.2
Development is designed to differentiate public, communal and private areas.	None are applicable.
PO 2.3	DTS/DPF 2.3
Buildings are designed with safe, perceptible and direct access from public street frontages and vehicle parking areas.	None are applicable.
PO 2.4	DTS/DPF 2.4
Development at street level is designed to maximise opportunities for passive surveillance of the adjacent public realm.	None are applicable.
PO 2.5	DTS/DPF 2.5
Common areas and entry points of buildings (such as the foyer areas of residential buildings), and non-residential land uses at street level, maximise passive surveillance from the public realm to the inside of the building at night.	None are applicable.
Lands	caping
PO 3.1	DTS/DPF 3.1
Soft landscaping and tree planting is incorporated to:	None are applicable.
(a) minimise heat absorption and reflection (b) maximise shade and shelter (c) maximise stormwater infiltration (d) enhance the appearance of land and streetscapes (e) contribute to biodiversity.	
PO 3.2	DTS/DPF 3.2
Soft landscaping and tree planting maximises the use of locally indigenous plant species, incorporates plant species best suited to current and future climate conditions and avoids pest plant and weed species.	None are applicable.
Environmenta	l Performance
PO 4.1	DTS/DPF 4.1
Buildings are sited, oriented and designed to maximise natural sunlight access and ventilation to main activity areas, habitable rooms, common areas and open spaces.	None are applicable.
PO 4.2	DTS/DPF 4.2
Buildings are sited and designed to maximise passive environmental performance and minimise energy consumption and reliance on mechanical systems, such as heating and cooling.	None are applicable.

Page 49 of 141 Printed on 19/09/2022

Policy24 - Enquiry PO 4.3 DTS/DPF 4.3 Buildings incorporate climate-responsive techniques and None are applicable. features such as building and window orientation, use of eaves, verandahs and shading structures, water harvesting, at ground landscaping, green walls, green roofs and photovoltaic cells. Water Sensitive Design PO 5.1 DTS/DPF 5.1 Development is sited and designed to maintain natural None are applicable. hydrological systems without negatively impacting: (a) the quantity and quality of surface water and groundwater (b) the depth and directional flow of surface water and groundwater (c) the quality and function of natural springs. On-site Waste Treatment Systems PO 6.1 DTS/DPF 6.1 Dedicated on-site effluent disposal areas do not include any Effluent disposal drainage areas do not: areas to be used for, or could be reasonably foreseen to be used (a) encroach within an area used as private open space or for, private open space, driveways or car parking. result in less private open space than that specified in Design Table 1 - Private Open Space (b) use an area also used as a driveway encroach within an area used for on-site car parking or result in less on-site car parking than that specified in Transport, Access and Parking Table 1 - General Off-Street Car Parking Requirements or Table 2 - Off-Street Car Parking Requirements in Designated Areas. Carparking Appearance PO 7.1 DTS/DPF 7.1 Development facing the street is designed to minimise the None are applicable. negative impacts of any semi-basement and undercroft car parking on the streetscapes through techniques such as: (a) limiting protrusion above finished ground level (b) screening through appropriate planting, fencing and mounding (c) limiting the width of openings and integrating them into the building structure. PO 7.2 DTS/DPF 7.2

Vehicle parking areas are appropriately located, designed and constructed to minimise impacts on adjacent sensitive receivers through measures such as ensuring they are attractively developed and landscaped, screen fenced and the like.

None are applicable.

PO 7.3

DTS/DPF 7.3

Safe, legible, direct and accessible pedestrian connections are provided between parking areas and the development.

None are applicable.

PO 7.4

DTS/DPF 7.4

Page 50 of 141 Printed on 19/09/2022

Street level vehicle parking areas incorporate tree planting to provide shade and reduce solar heat absorption and reflection.	None are applicable.	
PO 7.5	DTS/DPF 7.5	
Street level parking areas incorporate soft landscaping to improve visual appearance when viewed from within the site and from public places.	None are applicable.	
PO 7.6	DTS/DPF 7.6	
Vehicle parking areas and associated driveways are landscaped to provide shade and positively contribute to amenity.	None are applicable.	
PO 7.7	DTS/DPF 7.7	
Vehicle parking areas and access ways incorporate integrated stormwater management techniques such as permeable or porous surfaces, infiltration systems, drainage swales or rain gardens that integrate with soft landscaping.	None are applicable.	
Earthworks a	nd sloping land	
P0 8.1	DTS/DPF 8.1	
Development, including any associated driveways and access tracks, minimises the need for earthworks to limit disturbance to natural topography.	Development does not involve any of the following: (a) excavation exceeding a vertical height of 1m	
	(b) filling exceeding a vertical height of 1m	
	(c) a total combined excavation and filling vertical height of 2m or more.	
PO 8.2	DTS/DPF 8.2	
Driveways and access tracks are designed and constructed to allow safe and convenient access on sloping land (with a gradient exceeding 1 in 8).	Driveways and access tracks on sloping land (with a gradient exceeding 1 in 8) satisfy (a) and (b): (a) do not have a gradient exceeding 25% (1-in-4) at any point along the driveway (b) are constructed with an all-weather trafficable surface.	
PO 8.3	DTS/DPF 8.3	
Driveways and access tracks on sloping land (with a gradient exceeding 1 in 8):	None are applicable.	
(a) do not contribute to the instability of embankments and cuttings		
(b) provide level transition areas for the safe movement of people and goods to and from the development		
(c) are designed to integrate with the natural topography of the land.		
PO 8.4	DTS/DPF 8.4	
Development on sloping land (with a gradient exceeding 1 in 8)	None are applicable.	
avoids the alteration of natural drainage lines and includes onsite drainage systems to minimise erosion.		

Page 51 of 141 Printed on 19/09/2022

Development does not occur on land at risk of landslip nor None are applicable. increases the potential for landslip or land surface instability. Fences and Walls DTS/DPF 9.1 PO 9.1 Fences, walls and retaining walls are of sufficient height to None are applicable. maintain privacy and security without unreasonably impacting the visual amenity and adjoining land's access to sunlight or the amenity of public places. PO 9.2 DTS/DPF 9.2 Landscaping incorporated on the low side of retaining walls is A vegetated landscaped strip 1m wide or more is provided visible from public roads and public open space to minimise against the low side of a retaining wall. visual impacts. Overlooking / Visual Privacy (in building 3 storeys or less) PO 10.1 DTS/DPF 10.1 Development mitigates direct overlooking from upper level Upper level windows facing side or rear boundaries shared with a windows to habitable rooms and private open spaces of residential allotment/site satisfy one of the following: adjoining residential uses. are permanently obscured to a height of 1.5m above finished floor level and are fixed or not capable of being opened more than 200mm (b) have sill heights greater than or equal to 1.5m above finished floor level (c) incorporate screening with a maximum of 25% openings, permanently fixed no more than 500mm from the window surface and sited adjacent to any part of the window less than 1.5 m above the finished floor level. PO 10.2 DTS/DPF 10.2 Development mitigates direct overlooking from balconies, One of the following is satisfied: terraces and decks to habitable rooms and private open space of the longest side of the balcony or terrace will face a adjoining residential uses. public road, public road reserve or public reserve that is at least 15m wide in all places faced by the balcony or terrace (b) all sides of balconies or terraces on upper building levels are permanently obscured by screening with a maximum 25% transparency/openings fixed to a minimum height of: (i) 1.5m above finished floor level where the balcony is located at least 15 metres from the nearest habitable window of a dwelling on adjacent land (ii) 1.7m above finished floor level in all other cases

All Residential development

Front elevations and passive surveillance	
PO 11.1	DTS/DPF 11.1
Dwellings incorporate windows along primary street frontages to	Each dwelling with a frontage to a public street:

Printed on 19/09/2022 Page 52 of 141

onoy2 i Ziiqan y	
encourage passive surveillance and make a positive contribution to the streetscape.	 (a) includes at least one window facing the primary street from a habitable room that has a minimum internal room dimension of 2.4m (b) has an aggregate window area of at least 2m² facing the primary street.
PO 11.2	DTS/DPF 11.2
Dwellings incorporate entry doors within street frontages to address the street and provide a legible entry point for visitors.	Dwellings with a frontage to a public street have an entry door visible from the primary street boundary.
Outlook a	nd amenity
PO 12.1	DTS/DPF 12.1
Living rooms have an external outlook to provide a high standard of amenity for occupants.	A living room of a dwelling incorporates a window with an outlook towards the street frontage or private open space, public open space, or waterfront areas.
PO 12.2	DTS/DPF 12.2
Bedrooms are separated or shielded from active communal recreation areas, common access areas and vehicle parking areas and access ways to mitigate noise and artificial light intrusion.	None are applicable.
Ancillary D	Development
Residential ancillary buildings and structures are sited and designed to not detract from the streetscape or appearance of buildings on the site or neighbouring properties.	Ancillary buildings: (a) are ancillary to a dwelling erected on the same site (b) have a floor area not exceeding 60m2 (c) are not constructed, added to or altered so that any part is situated: (i) in front of any part of the building line of the dwelling to which it is ancillary or (ii) within 900mm of a boundary of the allotment with a secondary street (if the land has boundaries on two or more roads) (d) in the case of a garage or carport, the garage or carport: (i) is set back at least 5.5m from the boundary of the primary street (ii) when facing a primary street or secondary street, has a total door / opening not exceeding: A. for dwellings of single building level - 7m in width or 50% of the site frontage, whichever is the lesser B. for dwellings comprising two or more building levels at the building line fronting the same public street - 7m in width (e) if situated on a boundary (not being a boundary with a primary street or secondary street), do not exceed a length of 11.5m unless: (i) a longer wall or structure exists on the adjacent

Page 53 of 141 Printed on 19/09/2022

boundary

and

- (ii) the proposed wall or structure will be built along the same length of boundary as the existing adjacent wall or structure to the same or lesser extent
- (f) if situated on a boundary of the allotment (not being a boundary with a primary street or secondary street), all walls or structures on the boundary will not exceed 45% of the length of that boundary
- (g) will not be located within 3m of any other wall along the same boundary unless on an adjacent site on that boundary there is an existing wall of a building that would be adjacent to or about the proposed wall or structure
- (h) have a wall height or post height not exceeding 3m above natural ground level (and not including a gable end)
- (i) have a roof height where no part of the roof is more than 5m above the natural ground level
- (j) if clad in sheet metal, is pre-colour treated or painted in a non-reflective colour
- (k) retains a total area of soft landscaping in accordance with (i) or (ii), whichever is less:
 - a total area as determined by the following table:

Dwelling site area (or in the case of residential flat building or group dwelling(s), average site area) (m ²)	Minimum percentage of site
<150	10%
150-200	15%
201-450	20%
>450	25%

(ii) the amount of existing soft landscaping prior to the development occurring.

PO 13.2

Ancillary buildings and structures do not impede on-site functional requirements such as private open space provision or car parking requirements and do not result in over-development of the site.

DTS/DPF 13.2

Ancillary buildings and structures do not result in:

- (a) less private open space than specified in Design in Urban Areas Table 1 Private Open Space
- (b) less on-site car parking than specified in Transport, Access and Parking Table 1 - General Off-Street Car Parking Requirements or Table 2 - Off-Street Car Parking Requirements in Designated Areas.

PO 13.3

Fixed plant and equipment in the form of pumps and/or filtration systems for a swimming pool or spa is positioned and/or housed to not cause unreasonable noise nuisance to adjacent

DTS/DPF 13.3

The pump and/or filtration system is ancillary to a dwelling erected on the same site and is:

Page 54 of 141 Printed on 19/09/2022

Policy24 - Enquiry (a) enclosed in a solid acoustic structure that is located at sensitive receivers. least 5m from the nearest habitable room located on an adjoining allotment or (b) located at least 12m from the nearest habitable room located on an adjoining allotment. Garage appearance PO 14.1 DTS/DPF 14.1 Garaging is designed to not detract from the streetscape or Garages and carports facing a street: appearance of a dwelling. are situated so that no part of the garage or carport is in front of any part of the building line of the dwelling (b) are set back at least 5.5m from the boundary of the primary street (c) have a garage door / opening not exceeding 7m in width (d) have a garage door /opening width not exceeding 50% of the site frontage unless the dwelling has two or more building levels at the building line fronting the same public street. Massing **DTS/DPF 15.1** PO 15.1

The visual mass of larger buildings is reduced when viewed from adjoining allotments or public streets.

None are applicable

Dwelling additions

PO 16.1

Dwelling additions are sited and designed to not detract from the streetscape or amenity of adjoining properties and do not impede on-site functional requirements.

DTS / DPF 16.1

Dwelling additions:

- (a) are not constructed, added to or altered so that any part is situated closer to a public street
- (b) do not result in:
 - (i) excavation exceeding a vertical height of 1m
 - (ii) filling exceeding a vertical height of 1m
 - iii) a total combined excavation and filling vertical height of 2m or more
 - (iv) less Private Open Space than specified in Design Table 1 Private Open Space
 - (v) less on-site parking than specified in Transport Access and Parking Table 1 - General Off-Street Car Parking Requirements or Table 2 - Off-Street Car Parking Requirements in Designated Areas
 - (vi) upper level windows facing side or rear boundaries unless:
 - A. they are permanently obscured to a height of 1.5m above finished floor level that is fixed or not capable of being opened more than 200mm or
 - B. have sill heights greater than or equal to 1.5m above finished floor level
 - C. incorporate screening to a height of 1.5m above finished floor level

Page 55 of 141 Printed on 19/09/2022

- (vii) all sides of balconies or terraces on upper building levels are permanently obscured by screening with a maximum 25% transparency/openings fixed to a minimum height of:
 - A. 1.5m above finished floor level where the balcony is located at least 15 metres from the nearest habitable window of a dwelling on adjacent land
 - B. 1.7m above finished floor level in all other cases.

Private Open Space

PO 17.1

DTS/DPF 17.1

Dwellings are provided with suitable sized areas of usable private open space to meet the needs of occupants.

Private open space is provided in accordance with Design Table 1 - Private Open Space.

Water Sensitive Design

PO 18.1

DTS/DPF 18.1

Residential development creating a common driveway / access includes stormwater management systems that minimise the discharge of sediment, suspended solids, organic matter, nutrients, bacteria, litter and other contaminants to the stormwater system, watercourses or other water bodies.

Residential development creating a common driveway / access that services 5 or more dwellings achieves the following stormwater runoff outcomes:

- (a) 80 per cent reduction in average annual total suspended solids
- (b) 60 per cent reduction in average annual total phosphorus
- (c) 45 per cent reduction in average annual total nitrogen.

PO 18.2

DTS/DPF 18.2

Residential development creating a common driveway / access includes a stormwater management system designed to mitigate peak flows and manage the rate and duration of stormwater discharges from the site to ensure that the development does not increase the peak flows in downstream systems.

Development creating a common driveway / access that services 5 or more dwellings:

- (a) maintains the pre-development peak flow rate from the site based upon a 0.35 runoff coefficient for the 18.1% AEP 30-minute storm and the stormwater runoff time to peak is not increased
 - captures and retains the difference in pre-development runoff volume (based upon a 0.35 runoff coefficient) vs post development runoff volume from the site for an 18.1% AEP 30-minute storm; and
- (b) manages site generated stormwater runoff up to and including the 1% AEP flood event to avoid flooding of buildings.

Car parking, access and manoeuvrability

PO 19.1

DTS/DPF 19.1

Enclosed parking spaces are of a size and dimensions to be functional, accessible and convenient.

Residential car parking spaces enclosed by fencing, walls or other structures have the following internal dimensions (separate from any waste storage area):

- (a) single width car parking spaces:
 - (i) a minimum length of 5.4m per space
 - (ii) a minimum width of 3.0m

Page 56 of 141 Printed on 19/09/2022

(iii) a minimum garage door width of 2.4m (b) double width car parking spaces (side by side): (i) a minimum length of 5.4m (ii) a minimum width of 5.4m (iii) minimum garage door width of 2.4m per sp DTS/DPF 19.2 Uncovered parking spaces are of a size and dimensions to be functional, accessible and convenient. DTS/DPF 19.2 Uncovered car parking spaces have: (a) a minimum length of 5.4m (b) a minimum width of 2.4m (c) a minimum width of 2.4m (d) a minimum width of 2.4m (e) a minimum width of 2.4m (f) a minimum width of 5.4m (g) a minimum width of 2.4m (g) a minimum width of 5.4m (g) a minimum width of 2.4m (g) a minimum valdh of 2.4m (g) a minimum width of 2.4m (g) a minimum valdh of 2.4m (g) a minimum valdh of 2.4m (g) a minimum valdh of 2.4m
(i) a minimum length of 5.4m (ii) a minimum width of 5.4m (iii) minimum garage door width of 2.4m per sp PD 19.2 Uncovered parking spaces are of a size and dimensions to be functional, accessible and convenient. DTS/DPF 19.2 Uncovered car parking spaces have: (a) a minimum length of 5.4m (b) a minimum width of 2.4m (c) a minimum width of 2.4m (d) a minimum width of 2.4m (e) a minimum width of 2.4m (f) a minimum width of 2.4m (g) a minimum width of 2.4m (h) a minimum width of 2.4m (g) a minimum width of 2.4m (g) a minimum length of 5.4m (h) a minimum width of 2.4m (g) a minimum length of 5.4m (h) a minimum length of 5.4m (g) a minimum length of 5.4m (h) a minimum length of 2.4m (h) a minimum length
(i) a minimum width of 5.4m (iii) minimum garage door width of 2.4m per sp (iii) minimum garage door width of 2.4m per sp (iii) minimum garage door width of 2.4m per sp (iii) minimum garage door width of 2.4m per sp (iii) minimum garage door width of 2.4m per sp (iii) minimum garage door width of 2.4m per sp (iii) a minimum garage door width of 2.4m per sp (iii) a minimum garage door width of 2.4m per sp (iii) a minimum garage door width of 2.4m per sp (iii) a minimum garage door width of 2.4m per sp (iii) a minimum garage door width of 2.4m per sp (iii) a minimum garage door width of 2.4m per sp (iii) a minimum garage door width of 2.4m per sp (iii) a minimum garage door width of 2.4m per sp (iii) a minimum garage door width of 2.4m per sp (iii) a minimum garage door width of 2.4m per sp (iii) a minimum garage door width of 2.4m per sp (iii) a minimum garage door width of 2.4m per sp (iii) a minimum garage door width of 2.4m per sp (iii) a minimum garage door width of 2.4m per sp (iii) a minimum garage door width of 2.4m per sp (iii) a minimum garage door width of 2.4m per sp (iii) a minimum garage door width of 2.4m per sp (iii) a minimum garage door width of 2.4m per sp (iii) a minimum width of 2.4m (iii)
DTS/DPF 19.2 Uncovered parking spaces are of a size and dimensions to be functional, accessible and convenient. DTS/DPF 19.2 Uncovered car parking spaces have: (a) a minimum width of 2.4m (b) a minimum width of 2.4m (c) a minimum width of 2.4m (d) a minimum width of 2.4m (e) a minimum width of 2.4m (f) a minimum width of 2.4m (g) a minimum length of 5.4m (h) a minimum length of 2.4m (h) a minimum width etues length peaces length
PO 19.2 Uncovered parking spaces are of a size and dimensions to be functional, accessible and convenient. (a) a minimum length of 5.4m (b) a minimum width of 2.4m (c) a minimum width between the centre line of the spa and any fence, wall or other obstruction of 1.5m DTS/DPF 19.3 Driveways are located and designed to facilitate safe access and egress while maximising land available for street tree planting, landscaped street frontages, domestic waste collection and onstreet parking. DTS/DPF 19.3 DTS/DPF 19.3 DTS/DPF 19.3 DTS/DPF 19.4 Vehicle access is safe, convenient, minimises interruption to the operation of public roads and does not interfere with street infrastructure or street trees. DTS/DPF 19.4 Vehicle access to designated car parking spaces satisfy (a) (b): (a) is provided via a lawfully existing or authorised accepoint or an access point for which consent has beer granted as part of an application for the division of low where newly proposed: (i) is set back outside of the marked lines or infrastructure dedicating a pedestrian crossing damage to of mature street trees, street lines or infrastructure dedicating a pedestrian crossing damage to of mature street trees, street lines or infrastructure dedicating a pedestrian crossing damage to of mature street trees, street lines, street lines, street lines or infrastructure dedicating a pedestrian crossing damage to of mature street trees, street lines,
Uncovered parking spaces are of a size and dimensions to be functional, accessible and convenient. (a) a minimum length of 5.4m (b) a minimum width of 2.4m (c) a minimum width between the centre line of the spa and any fence, wall or other obstruction of 1.5m DTS/DPF 19.3 DTIVEWAYS are located and designed to facilitate safe access and egress while maximising land available for street tree planting, landscaped street frontages, domestic waste collection and onstreet parking. DTS/DPF 19.3 DTIVEWAYS and access points on sites with a frontage to a provided on the site. DTS/DPF 19.4 Vehicle access is safe, convenient, minimises interruption to the operation of public roads and does not interfere with street infrastructure or street trees. (a) a minimum width of 2.4m (b) a minimum width of 2.4m (c) a minimum width between the centre line of the spa and any fence, wall or other obstruction of 1.5m DTS/DPF 19.3 DTIVEWAYS and access points on sites with a frontage to a provided of 10m or less have a width between 3.0 and 3.2 metre measured at the property boundary and are the only access provided on the site. DTS/DPF 19.4 Vehicle access to designated car parking spaces satisfy (a) (b): (a) Is provided via a lawfully existing or authorised accepoint or an access point for which consent has been granted as part of an application for the division of infrastructure dedicating a pedestrian cross. (ii) is set back 6m or more from the tangent poof an intersection of 2 or more roads (ii) is set back outside of the marked lines or infrastructure dedicating a pedestrian cross. (iii) does not involve the removal, relocation or damage to of mature street trees, street
functional, accessible and convenient. (a) a minimum length of 5.4m (b) a minimum width of 2.4m (c) a minimum width between the centre line of the spa and any fence, wall or other obstruction of 1.5m PO 19.3 Driveways are located and designed to facilitate safe access and egress while maximising land available for street tree planting, landscaped street frontages, domestic waste collection and onstreet parking. DTS/DPF 19.3 Driveways and access points on sites with a frontage to a purcoad of 10m or less have a width between 3.0 and 3.2 metre measured at the property boundary and are the only access provided on the site. DTS/DPF 19.4 Vehicle access is safe, convenient, minimises interruption to the operation of public roads and does not interfere with street infrastructure or street trees. (a) is provided via a lawfully existing or authorised accepoint or an access point for which consent has been granted as part of an application for the division of low where newly proposed: (i) is set back 6m or more from the tangent per of an intersection of 2 or more roads (ii) is set back outside of the marked lines or infrastructure dedicating a pedestrian cross infrastructure dedicating a pedestrian cross damage to of mature street trees, street
(a) a minimum length of 5.4m (b) a minimum width of 2.4m (c) a minimum width between the centre line of the spa and any fence, wall or other obstruction of 1.5m PO 19.3 Driveways are located and designed to facilitate safe access and egress while maximising land available for street tree planting, landscaped street frontages, domestic waste collection and onstreet parking. DTS/DPF 19.3 Driveways and access points on sites with a frontage to a period of 10m or less have a width between 3.0 and 3.2 metre measured at the property boundary and are the only access provided on the site. DTS/DPF 19.4 Vehicle access is safe, convenient, minimises interruption to the operation of public roads and does not interfere with street infrastructure or street trees. (a) is provided via a lawfully existing or authorised accepoint or an access point for which consent has been granted as part of an application for the division of line in tersection of 2 or more roads (b) where newly proposed: (i) is set back 6m or more from the tangent period of an intersection of 2 or more roads (ii) is set back outside of the marked lines or infrastructure dedicating a pedestrian cross. (iii) does not involve the removal, relocation or damage to of mature street trees, street
(b) a minimum width of 2.4m (c) a minimum width between the centre line of the spa and any fence, wall or other obstruction of 1.5m DTS/DPF 19.3 Diveways are located and designed to facilitate safe access and egress while maximising land available for street tree planting, landscaped street frontages, domestic waste collection and onstreet parking. DTS/DPF 19.3 Driveways and access points on sites with a frontage to a proad of 10m or less have a width between 3.0 and 3.2 metre measured at the property boundary and are the only access provided on the site. DTS/DPF 19.4 Vehicle access is safe, convenient, minimises interruption to the operation of public roads and does not interfere with street infrastructure or street trees. DTS/DPF 19.4 Vehicle access to designated car parking spaces satisfy (a) (b): (a) is provided via a lawfully existing or authorised accepoint or an access point for which consent has beer granted as part of an application for the division of line is set back 6m or more from the tangent poof an intersection of 2 or more roads (i) is set back outside of the marked lines or infrastructure dedicating a pedestrian cross (iii) does not involve the removal, relocation or damage to of mature street trees, street
(c) a minimum width between the centre line of the spa and any fence, wall or other obstruction of 1.5m DTS/DPF 19.3 Driveways are located and designed to facilitate safe access and egress while maximising land available for street tree planting, landscaped street frontages, domestic waste collection and onstreet parking. DTS/DPF 19.3 Driveways and access points on sites with a frontage to a purple of 10m or less have a width between 3.0 and 3.2 metre measured at the property boundary and are the only access provided on the site. DTS/DPF 19.4 Vehicle access is safe, convenient, minimises interruption to the operation of public roads and does not interfere with street infrastructure or street trees. (a) is provided via a lawfully existing or authorised accepoint or an access point for which consent has beer granted as part of an application for the division of 10m or less have a width between 3.0 and 3.2 metre measured at the property boundary and are the only access provided on the site. (b): (a) is provided via a lawfully existing or authorised accepoint or an access point for which consent has beer granted as part of an application for the division of 10m or less have a width between 3.0 and 3.2 metre measured at the property boundary and are the only access provided on the site. (b): (a) is provided via a lawfully existing or authorised accepoint or an access point for which consent has beer granted as part of an application for the division of 10m or less have a width between 3.0 and 3.2 metre measured at the property boundary and are the only access provided on the site. (b): (a) is provided via a lawfully existing or authorised accepoint or an access point for which consent has beer granted as part of an application of 2 or more roads (i) is set back 6m or more from the tangent point or an access point for which consent has been granted as part of an application of 2 or more roads (ii) is set back 0m or more from the tangent point and the property beautiful the property beautiful the proper
po 19.3 Driveways are located and designed to facilitate safe access and egress while maximising land available for street tree planting, landscaped street frontages, domestic waste collection and onstreet parking. DTS/DPF 19.3 Driveways and access points on sites with a frontage to a proad of 10m or less have a width between 3.0 and 3.2 metre measured at the property boundary and are the only access provided on the site. DTS/DPF 19.4 Vehicle access is safe, convenient, minimises interruption to the operation of public roads and does not interfere with street infrastructure or street trees. (a) is provided via a lawfully existing or authorised accepoint or an access point for which consent has been granted as part of an application for the division of limits as part of an application for the division of limits set back 6m or more from the tangent poor of an intersection of 2 or more roads (ii) is set back outside of the marked lines or infrastructure dedicating a pedestrian cross (iii) does not involve the removal, relocation or damage to of mature street trees, street
Driveways are located and designed to facilitate safe access and egress while maximising land available for street tree planting, landscaped street frontages, domestic waste collection and onstreet parking. PO 19.4 Vehicle access is safe, convenient, minimises interruption to the operation of public roads and does not interfere with street infrastructure or street trees. Driveways and access points on sites with a frontage to a proad of 10m or less have a width between 3.0 and 3.2 metre measured at the property boundary and are the only access provided on the site. Driveways and access points on sites with a frontage to a proad of 10m or less have a width between 3.0 and 3.2 metre measured at the property boundary and are the only access provided on the site. Driveways and access points on sites with a frontage to a proad of 10m or less have a width between 3.0 and 3.2 metre measured at the property boundary and are the only access provided on the site. Driveways and access points on sites with a frontage to a proad of 10m or less have a width between 3.0 and 3.2 metre measured at the property boundary and are the only access provided on the site. Driveways and access points on sites with a frontage to a proad of 10m or less have a width between 3.0 and 3.2 metre measured at the property boundary and are the only access provided on the site. Driveways and access points on sites with a frontage to a proad of 10m or less have a width between 3.0 and 3.2 metre measured at the property boundary and are the only access provided on the site. Driveways and access point so width between 3.0 and 3.2 metre measured at the property boundary and are the only access provided on the site. Driveways and access point so width between 3.0 and 3.2 metre measured at the property boundary and are the only access provided on the site. (b): (a) is provided via a lawfully existing or authorised accepoint or an access point for which consent has been granted as part of an application for the division of interfere with stre
egress while maximising land available for street tree planting, landscaped street frontages, domestic waste collection and onstreet parking. PO 19.4 Vehicle access is safe, convenient, minimises interruption to the operation of public roads and does not interfere with street infrastructure or street trees. (a) is provided via a lawfully existing or authorised accepoint or an access point for which consent has been granted as part of an application for the division of the of an intersection of 2 or more roads (ii) is set back 6m or more from the tangent poof an intersection of 2 or more roads (iii) does not involve the removal, relocation or damage to of mature street trees, street
landscaped street frontages, domestic waste collection and onstreet parking. PO 19.4 Vehicle access is safe, convenient, minimises interruption to the operation of public roads and does not interfere with street infrastructure or street trees. (a) is provided via a lawfully existing or authorised accepoint or an access point for which consent has been granted as part of an application for the division of (i) is set back 6m or more from the tangent poof an intersection of 2 or more roads (ii) is set back outside of the marked lines or infrastructure dedicating a pedestrian cross (iii) does not involve the removal, relocation or damage to of mature street trees, street
street parking. provided on the site. DTS/DPF 19.4 Vehicle access is safe, convenient, minimises interruption to the operation of public roads and does not interfere with street infrastructure or street trees. (a) is provided via a lawfully existing or authorised accepoint or an access point for which consent has been granted as part of an application for the division of (i) where newly proposed: (i) is set back 6m or more from the tangent poof an intersection of 2 or more roads (ii) is set back outside of the marked lines or infrastructure dedicating a pedestrian cross (iii) does not involve the removal, relocation or damage to of mature street trees, street
Vehicle access is safe, convenient, minimises interruption to the operation of public roads and does not interfere with street infrastructure or street trees. (a) is provided via a lawfully existing or authorised access point or an access point for which consent has been granted as part of an application for the division of an intersection of 2 or more roads (i) is set back 6m or more from the tangent poof an intersection of 2 or more roads (ii) is set back outside of the marked lines or infrastructure dedicating a pedestrian cross (iii) does not involve the removal, relocation or damage to of mature street trees, street
operation of public roads and does not interfere with street infrastructure or street trees. (a) is provided via a lawfully existing or authorised access point or an access point for which consent has been granted as part of an application for the division of long where newly proposed: (b) where newly proposed: (i) is set back 6m or more from the tangent poor of an intersection of 2 or more roads (ii) is set back outside of the marked lines or infrastructure dedicating a pedestrian cross dimensional does not involve the removal, relocation or damage to of mature street trees, street
infrastructure or street trees. (a) is provided via a lawfully existing or authorised access point or an access point for which consent has been granted as part of an application for the division of lower newly proposed: (b) where newly proposed: (i) is set back 6m or more from the tangent poor of an intersection of 2 or more roads (ii) is set back outside of the marked lines or infrastructure dedicating a pedestrian cross (iii) does not involve the removal, relocation or damage to of mature street trees, street
(a) is provided via a lawfully existing or authorised access point or an access point for which consent has been granted as part of an application for the division of low where newly proposed: (i) is set back 6m or more from the tangent poor of an intersection of 2 or more roads (ii) is set back outside of the marked lines or infrastructure dedicating a pedestrian cross (iii) does not involve the removal, relocation or damage to of mature street trees, street
point or an access point for which consent has beer granted as part of an application for the division of (b) where newly proposed: (i) is set back 6m or more from the tangent poor of an intersection of 2 or more roads (ii) is set back outside of the marked lines or infrastructure dedicating a pedestrian cross (iii) does not involve the removal, relocation or damage to of mature street trees, street
(i) is set back 6m or more from the tangent poor of an intersection of 2 or more roads (ii) is set back outside of the marked lines or infrastructure dedicating a pedestrian cross (iii) does not involve the removal, relocation or damage to of mature street trees, street
of an intersection of 2 or more roads (ii) is set back outside of the marked lines or infrastructure dedicating a pedestrian cross (iii) does not involve the removal, relocation or damage to of mature street trees, street
infrastructure dedicating a pedestrian cross (iii) does not involve the removal, relocation or damage to of mature street trees, street
damage to of mature street trees, street
PO 19.5 DTS/DPF 19.5
Driveways are designed to enable safe and convenient vehicle Driveways are designed and sited so that:
movements from the public road to on-site parking spaces. (a) the gradient from the place of access on the bounds
of the allotment to the finished floor level at the from
the garage or carport is not steeper than 1:4 on ave (b) they are aligned relative to the street boundary so the
(b) they are aligned relative to the street boundary so the there is no more than a 20 degree deviation from 90
degrees between the centreline of any dedicated ca
parking space to which it provides access (measure from the front of that space) and the street boundar
(c) if located to provide access from an alley, lane or rig
of way - the alley, land or right or way is at least 6.2r wide along the boundary of the allotment / site
PO 19.6 DTS/DPF 19.6
Driveways and access points are designed and distributed to Where on-street parking is available abutting the site's street

Page 57 of 141 Printed on 19/09/2022

optimise the provision of on-street visitor parking. frontage, on-street parking is retained in accordance with the following requirements: minimum 0.33 on-street spaces per dwelling on the site (rounded up to the nearest whole number) (b) minimum car park length of 5.4m where a vehicle can enter or exit a space directly (c) minimum carpark length of 6m for an intermediate space located between two other parking spaces or to an end obstruction where the parking is indented. Waste storage PO 20.1 DTS/DPF 20.1 Provision is made for the adequate and convenient storage of None are applicable. waste bins in a location screened from public view. Design of Transportable Dwellings PO 21.1 DTS/DPF 21.1 The sub-floor space beneath transportable buildings is enclosed Buildings satisfy (a) or (b): to give the appearance of a permanent structure. (a) are not transportable (b) the sub-floor space between the building and ground level is clad in a material and finish consistent with the building. Group dwelling, residential flat buildings and battle-axe development Amenity PO 22.1 DTS/DPF 22.1 Dwellings are of a suitable size to accommodate a layout that is Dwellings have a minimum internal floor area in accordance with well organised and provides a high standard of amenity for the following table: occupants. **Number of bedrooms** Minimum internal floor area Studio 35m²1 bedroom 50m² 2 bedroom 65m² 3+ bedrooms 80m² and any dwelling over 3 bedrooms provides an additional 15m² for every additional bedroom PO 22.2 DTS/DPF 22.2 The orientation and siting of buildings minimises impacts on the None are applicable. amenity, outlook and privacy of occupants and neighbours. PO 22.3 DTS/DPF 22.3

Page 58 of 141 Printed on 19/09/2022

Policy24 - Enquiry	
Development maximises the number of dwellings that face public open space and public streets and limits dwellings oriented towards adjoining properties.	None are applicable.
PO 22.4	DTS/DPF 22.4
Battle-axe development is appropriately sited and designed to respond to the existing neighbourhood context.	Dwelling sites/allotments are not in the form of a battle-axe arrangement.
Communal	Open Space
PO 23.1	DTS/DPF 23.1
Private open space provision may be substituted for communal open space which is designed and sited to meet the recreation and amenity needs of residents.	None are applicable.
PO 23.2	DTS/DPF 23.2
Communal open space is of sufficient size and dimensions to cater for group recreation.	Communal open space incorporates a minimum dimension of 5 metres.
PO 23.3	DTS/DPF 23.3
Communal open space is designed and sited to:	None are applicable.
(a) be conveniently accessed by the dwellings which it services (b) have regard to acoustic, safety, security and wind effects.	
PO 23.4	DTS/DPF 23.4
Communal open space contains landscaping and facilities that are functional, attractive and encourage recreational use.	None are applicable.
P0 23.5	DTS/DPF 23.5
Communal open space is designed and sited to:	None are applicable.
in relation to rooftop or elevated gardens, minimise overlooking into habitable room windows or onto the useable private open space of other dwellings in relation to ground floor communal space, be overlooked by habitable rooms to facilitate passive surveillance.	
Carparking, access	and manoeuvrability
PO 24.1	DTS/DPF 24.1
Driveways and access points are designed and distributed to optimise the provision of on-street visitor parking.	Where on-street parking is available directly adjacent the site, on- street parking is retained adjacent the subject site in accordance with the following requirements:
P0 24.2	 (a) minimum 0.33 on-street car parks per proposed dwellings (rounded up to the nearest whole number) (b) minimum car park length of 5.4m where a vehicle can enter or exit a space directly (c) minimum carpark length of 6m for an intermediate space located between two other parking spaces or to an end obstruction where the parking is indented.

Page 59 of 141 Printed on 19/09/2022

The number of vehicular access points onto public roads is minimised to reduce interruption of the footpath and positively contribute to public safety and walkability.	Access to group dwellings or dwellings within a residential flat building is provided via a single common driveway.
PO 24.3	DTS/DPF 24.3
Residential driveways that service more than one dwelling are designed to allow safe and convenient movement.	Driveways that service more than 1 dwelling or a dwelling on a battle-axe site: (a) have a minimum width of 3m (b) for driveways servicing more than 3 dwellings: (i) have a width of 5.5m or more and a length of 6m or more at the kerb of the primary street (ii) where the driveway length exceeds 30m, incorporate a passing point at least every 30 metres with a minimum width of 5.5m and a minimum length of 6m.
PO 24.4	DTS/DPF 24.4
Residential driveways in a battle-axe configuration are designed to allow safe and convenient movement.	Where in a battle-axe configuration, a driveway servicing one dwelling has a minimum width of 3m.
PO 24.5	DTS/DPF 24.5
Residential driveways that service more than one dwelling are designed to allow passenger vehicles to enter and exit the site and manoeuvre within the site in a safe and convenient manner.	Driveways providing access to more than one dwelling, or a dwelling on a battle-axe site, allow a B85 passenger vehicle to enter and exit the garages or parking spaces in no more than a three-point turn manoeuvre.
PO 24.6	DTS/DPF 24.6
Dwellings are adequately separated from common driveways and manoeuvring areas.	Dwelling walls with entry doors or ground level habitable room windows are set back at least 1.5m from any driveway or area designated for the movement and manoeuvring of vehicles.
Soft Lar	ndscaping
PO 25.1	DTS/DPF 25.1
Soft landscaping is provided between dwellings and common driveways to improve the outlook for occupants and appearance of common areas.	Other than where located directly in front of a garage or a building entry, soft landscaping with a minimum dimension of 1m is provided between a dwelling and common driveway.
PO 25.2	DTS/DPF 25.2
Soft landscaping is provided that improves the appearance of common driveways.	Where a common driveway is located directly adjacent the side or rear boundary of the site, soft landscaping with a minimum dimension of 1m is provided between the driveway and site boundary (excluding along the perimeter of a passing point).
Site Facilities	/ Waste Storage
Provision is made for suitable mailbox facilities close to the major pedestrian entry to the site or conveniently located considering the nature of accommodation and mobility of occupants.	DTS/DPF 26.1 None are applicable.
PO 26.2	DTS/DPF 26.2
Provision is made for suitable external clothes drying facilities.	None are applicable.

Page 60 of 141 Printed on 19/09/2022

PO 26.3	DTS/DPF 26.3
Provision is made for suitable household waste and recyclable material storage facilities which are:	None are applicable.
located away, or screened, from public view, and conveniently located in proximity to dwellings and the waste collection point.	
PO 26.4	DTS/DPF 26.4
Waste and recyclable material storage areas are located away from dwellings.	Dedicated waste and recyclable material storage areas are located at least 3m from any habitable room window.
P0 26.5	DTS/DPF 26.5
Where waste bins cannot be conveniently collected from the street, provision is made for on-site waste collection, designed to accommodate the safe and convenient access, egress and movement of waste collection vehicles.	None are applicable.
PO 26.6	DTS/DPF 26.6
Services including gas and water meters are conveniently located and screened from public view.	None are applicable.
Supported accommodation	on and retirement facilities
Siting and C	Configuration
PO 27.1	DTS/DPF 27.1
Supported accommodation and housing for aged persons and people with disabilities is located where on-site movement of residents is not unduly restricted by the slope of the land.	None are applicable.
Movement	and Access
PO 28.1	DTS/DPF 28.1
Development is designed to support safe and convenient access and movement for residents by providing:	None are applicable.
(a) ground-level access or lifted access to all units (b) level entry porches, ramps, paths, driveways, passenger loading areas and areas adjacent to footpaths that allow for the passing of wheelchairs and resting places	
(c) car parks with gradients no steeper than 1-in-40 and of sufficient area to provide for wheelchair manoeuvrability	
(d) kerb ramps at pedestrian crossing points.	
Communal	Open Space
PO 29.1	DTS/DPF 29.1
Development is designed to provide attractive, convenient and comfortable indoor and outdoor communal areas to be used by residents and visitors.	None are applicable.
PO 29.2	DTS/DPF 29.2
Private open space provision may be substituted for communal open space which is designed and sited to meet the recreation and amenity needs of residents.	None are applicable.

Page 61 of 141 Printed on 19/09/2022

PO 29.3	DTS/DPF 29.3
Communal open space is of sufficient size and dimensions to cater for group recreation.	Communal open space incorporates a minimum dimension of 5 metres.
PO 29.4	DTS/DPF 29.4
Communal open space is designed and sited to:	None are applicable.
(a) be conveniently accessed by the dwellings which it services (b) have regard to acoustic, safety, security and wind effects.	
PO 29.5	DTS/DPF 29.5
Communal open space contains landscaping and facilities that are functional, attractive and encourage recreational use.	None are applicable.
PO 29.6	DTC/DDF 20.6
Communal open space is designed and sited to:	DTS/DPF 29.6 None are applicable.
 (a) in relation to rooftop or elevated gardens, minimise overlooking into habitable room windows or onto the useable private open space of other dwellings (b) in relation to ground floor communal space, be overlooked by habitable rooms to facilitate passive surveillance. 	
Site Facilities	Waste Storage
PO 30.1	DTS/DPF 30.1
PO 30.1 Development is designed to provide storage areas for personal items and specialised equipment such as small electric powered vehicles, including facilities for the recharging of small electric powered vehicles.	DTS/DPF 30.1 None are applicable.
Development is designed to provide storage areas for personal items and specialised equipment such as small electric powered vehicles, including facilities for the recharging of small electric	
Development is designed to provide storage areas for personal items and specialised equipment such as small electric powered vehicles, including facilities for the recharging of small electric powered vehicles.	None are applicable.
Development is designed to provide storage areas for personal items and specialised equipment such as small electric powered vehicles, including facilities for the recharging of small electric powered vehicles. PO 30.2 Provision is made for suitable mailbox facilities close to the major pedestrian entry to the site or conveniently located considering the nature of accommodation and mobility of	None are applicable. DTS/DPF 30.2
Development is designed to provide storage areas for personal items and specialised equipment such as small electric powered vehicles, including facilities for the recharging of small electric powered vehicles. PO 30.2 Provision is made for suitable mailbox facilities close to the major pedestrian entry to the site or conveniently located considering the nature of accommodation and mobility of occupants.	None are applicable. DTS/DPF 30.2 None are applicable.
Development is designed to provide storage areas for personal items and specialised equipment such as small electric powered vehicles, including facilities for the recharging of small electric powered vehicles. PO 30.2 Provision is made for suitable mailbox facilities close to the major pedestrian entry to the site or conveniently located considering the nature of accommodation and mobility of occupants. PO 30.3	None are applicable. DTS/DPF 30.2 None are applicable. DTS/DPF 28.3
Development is designed to provide storage areas for personal items and specialised equipment such as small electric powered vehicles, including facilities for the recharging of small electric powered vehicles. PO 30.2 Provision is made for suitable mailbox facilities close to the major pedestrian entry to the site or conveniently located considering the nature of accommodation and mobility of occupants. PO 30.3 Provision is made for suitable external clothes drying facilities.	None are applicable. DTS/DPF 30.2 None are applicable. DTS/DPF 28.3 None are applicable.
Development is designed to provide storage areas for personal items and specialised equipment such as small electric powered vehicles, including facilities for the recharging of small electric powered vehicles. PO 30.2 Provision is made for suitable mailbox facilities close to the major pedestrian entry to the site or conveniently located considering the nature of accommodation and mobility of occupants. PO 30.3 Provision is made for suitable external clothes drying facilities. PO 30.4 Provision is made for suitable household waste and recyclable material storage facilities conveniently located and screened	None are applicable. DTS/DPF 30.2 None are applicable. DTS/DPF 28.3 None are applicable. DTS/DPF 30.4
Development is designed to provide storage areas for personal items and specialised equipment such as small electric powered vehicles, including facilities for the recharging of small electric powered vehicles. PO 30.2 Provision is made for suitable mailbox facilities close to the major pedestrian entry to the site or conveniently located considering the nature of accommodation and mobility of occupants. PO 30.3 Provision is made for suitable external clothes drying facilities. PO 30.4 Provision is made for suitable household waste and recyclable material storage facilities conveniently located and screened from public view.	None are applicable. DTS/DPF 30.2 None are applicable. DTS/DPF 28.3 None are applicable. DTS/DPF 30.4 None are applicable.

Page 62 of 141 Printed on 19/09/2022

Policy24 - Enquiry	
Provision is made for on-site waste collection where 10 or more bins are to be collected at any one time.	None are applicable.
PO 30.7	DTS/DPF 30.7
Services including gas and water meters are conveniently located and screened from public view.	None are applicable.
All non-reside	ntial development
Water Ser	sitive Design
PO 31.1	DTS/DPF 31.1
Development likely to result in significant risk of export of litter, oil or grease includes stormwater management systems designed to minimise pollutants entering stormwater.	None are applicable.
P0 31.2	DTS/DPF 31.2
Water discharged from a development site is of a physical, chemical and biological condition equivalent to or better than its pre-developed state.	None are applicable.
Wash-down and Wast	e Loading and Unloading
	o zodamig dna omodamig
PO 32.1	DTS/DPF 32.1
	DTS/DPF 32.1 None are applicable.
PO 32.1 Areas for activities including loading and unloading, storage of waste refuse bins in commercial and industrial development or wash-down areas used for the cleaning of vehicles, vessels, plant or equipment are: (a) designed to contain all wastewater likely to pollute stormwater within a bunded and roofed area to exclude the entry of external surface stormwater run-off	DTS/DPF 32.1 None are applicable.
PO 32.1 Areas for activities including loading and unloading, storage of waste refuse bins in commercial and industrial development or wash-down areas used for the cleaning of vehicles, vessels, plant or equipment are: (a) designed to contain all wastewater likely to pollute stormwater within a bunded and roofed area to exclude	DTS/DPF 32.1 None are applicable.
PO 32.1 Areas for activities including loading and unloading, storage of waste refuse bins in commercial and industrial development or wash-down areas used for the cleaning of vehicles, vessels, plant or equipment are: (a) designed to contain all wastewater likely to pollute stormwater within a bunded and roofed area to exclude the entry of external surface stormwater run-off (b) paved with an impervious material to facilitate	DTS/DPF 32.1 None are applicable.
PO 32.1 Areas for activities including loading and unloading, storage of waste refuse bins in commercial and industrial development or wash-down areas used for the cleaning of vehicles, vessels, plant or equipment are: (a) designed to contain all wastewater likely to pollute stormwater within a bunded and roofed area to exclude the entry of external surface stormwater run-off (b) paved with an impervious material to facilitate wastewater collection (c) of sufficient size to prevent 'splash-out' or 'over-spray' or	DTS/DPF 32.1 None are applicable.

Table 1 - Private Open Space

Dwelling Type	Minimum Rate
Dwelling (at ground level)	Total private open space area: (a) Site area <301m2: 24m2 located behind the building line. (b) Site area ≥ 301m2: 60m2 located behind the building line. Minimum directly accessible from a living room: 16m2 / with a minimum dimension 3m.

Page 63 of 141 Printed on 19/09/2022

Dwelling (above ground level)	Studio (no separate bedroom): 4m ² with a minimum dimension 1.8m
	One bedroom: 8m ² with a minimum dimension 2.1m
	Two bedroom dwelling: 11m ² with a minimum dimension 2.4m
	Three + bedroom dwelling: 15m ² with a minimum dimension 2.6m
Cabin or caravan (permanently fixed to the ground) in a residential park or a caravan and tourist park	Total area: 16m ² , which may be used as second car parking space, provided on each site intended for residential occupation.

Design in Urban Areas

Assessment Provisions (AP)

		Desired Outcome
DO 1	Develo	opment is:
	(a) (b)	contextual - by considering, recognising and carefully responding to its natural surroundings or built environment and positively contributing to the character of the locality durable - fit for purpose, adaptable and long lasting
	(c)	inclusive - by integrating landscape design to optimise pedestrian and cyclist usability, privacy and equitable access and promoting the provision of quality spaces integrated with the public realm that can be used for access and recreation and help optimise security and safety both internally and within the public realm, for occupants and visitors
	(d)	sustainable - by integrating sustainable techniques into the design and siting of development and landscaping to improve community health, urban heat, water management, environmental performance, biodiversity and local amenity and to minimise energy consumption.

Performance Outcome	Deemed-to-Satisfy Criteria / Designated Performance Feature
All Deve	lopment
External A	ppearance
PO 1.1	DTS/DPF 1.1
Buildings reinforce corners through changes in setback, articulation, materials, colour and massing (including height, width, bulk, roof form and slope).	None are applicable.
PO 1.2	DTS/DPF 1.2
Where zero or minor setbacks are desirable, development provides shelter over footpaths (in the form of verandahs, awnings, canopies and the like, with adequate lighting) to positively contribute to the walkability, comfort and safety of the	None are applicable.

Page 64 of 141 Printed on 19/09/2022

public realm.	
PO 1.3	DTS/DPF 1.3
Building elevations facing the primary street (other than ancillary buildings) are designed and detailed to convey purpose, identify main access points and complement the streetscape.	None are applicable.
PO 1.4	DTS/DPF 1.4
Plant, exhaust and intake vents and other technical equipment are integrated into the building design to minimise visibility from the public realm and negative impacts on residential amenity by:	Development does not incorporate any structures that protrude beyond the roofline.
(a) positioning plant and equipment discretely, in unobtrusive locations as viewed from public roads and spaces	
(b) screening rooftop plant and equipment from view (c) when located on the roof of non-residential development, locating the plant and equipment as far as practicable from adjacent sensitive land uses.	
PO 1.5	DTS/DPF 1.5
The negative visual impact of outdoor storage, waste management, loading and service areas is minimised by integrating them into the building design and screening them from public view (such as fencing, landscaping and built form), taking into account the form of development contemplated in the relevant zone.	None are applicable.
Sa	fety
PO 2.1	DTS/DPF 2.1
Development maximises opportunities for passive surveillance of the public realm by providing clear lines of sight, appropriate lighting and the use of visually permeable screening wherever practicable.	None are applicable.
PO 2.2	DTS/DPF 2.2
Development is designed to differentiate public, communal and private areas.	None are applicable.
PO 2.3	DTS/DPF 2.3
Buildings are designed with safe, perceptible and direct access from public street frontages and vehicle parking areas.	None are applicable.
PO 2.4	DTS/DPF 2.4
Development at street level is designed to maximise opportunities for passive surveillance of the adjacent public	None are applicable.
realm.	
PO 2.5	DTS/DPF 2.5

Page 65 of 141 Printed on 19/09/2022

Policy24 - Enquiry	
Lands	caping
PO 3.1	DTS/DPF 3.1
Soft landscaping and tree planting are incorporated to:	None are applicable.
(a) minimise heat absorption and reflection	
(b) maximise shade and shelter	
(c) maximise stormwater infiltration	
(d) enhance the appearance of land and streetscapes.	
Environmenta	Il Performance
PO 4.1	DTS/DPF 4.1
Buildings are sited, oriented and designed to maximise natural sunlight access and ventilation to main activity areas, habitable rooms, common areas and open spaces.	None are applicable.
PO 4.2	DTS/DPF 4.2
Buildings are sited and designed to maximise passive	None are applicable.
environmental performance and minimise energy consumption and reliance on mechanical systems, such as heating and cooling.	
PO 4.3	DTS/DPF 4.3
Buildings incorporate climate responsive techniques and features such as building and window orientation, use of eaves, verandahs and shading structures, water harvesting, at ground landscaping, green walls, green roofs and photovoltaic cells.	None are applicable.
Water Sens	itive Design
PO 5.1	DTS/DPF 5.1
Development is sited and designed to maintain natural hydrological systems without negatively impacting:	None are applicable.
(a) the quantity and quality of surface water and groundwater	
(b) the depth and directional flow of surface water and	
groundwater	
(c) the quality and function of natural springs.	
On-site Waste Tr	eatment Systems
PO 6.1	DTS/DPF 6.1
Dedicated on-site effluent disposal areas do not include any	Effluent disposal drainage areas do not:
areas to be used for, or could be reasonably foreseen to be used	(3)
for, private open space, driveways or car parking.	(a) encroach within an area used as private open space or result in less private open space than that specified in Design in Urban Areas Table 1 - Private Open Space
	(b) use an area also used as a driveway
	(c) encroach within an area used for on-site car parking or result in less on-site car parking than that specified in Transport, Access and Parking Table 1 - General Off-Street Car Parking Requirements or Table 2 - Off-Street Car Parking Requirements in Designated Areas.
Car parking	appearance
P0 7.1	DTS/DPF 7.1

Page 66 of 141 Printed on 19/09/2022

Development facing the street is designed to minimise the negative impacts of any semi-basement and undercroft car parking on streetscapes through techniques such as: (a) limiting protrusion above finished ground level (b) screening through appropriate planting, fencing and mounding (c) limiting the width of openings and integrating them into the building structure.	None are applicable.
P0 7.2	DTS/DPF 7.2
Vehicle parking areas appropriately located, designed and constructed to minimise impacts on adjacent sensitive receivers through measures such as ensuring they are attractively developed and landscaped, screen fenced and the like.	None are applicable.
P0 7.3	DTS/DPF 7.3
Safe, legible, direct and accessible pedestrian connections are provided between parking areas and the development.	None are applicable.
P0 7.4	DTS/DPF 7.4
Street-level vehicle parking areas incorporate tree planting to provide shade, reduce solar heat absorption and reflection.	Vehicle parking areas that are open to the sky and comprise 10 or more car parking spaces include a shade tree with a mature canopy of 4m diameter spaced for each 10 car parking spaces provided and a landscaped strip on any road frontage of a minimum dimension of 1m.
PO 7.5	DTS/DPF 7.5
Street level parking areas incorporate soft landscaping to improve visual appearance when viewed from within the site and from public places.	Vehicle parking areas comprising 10 or more car parking spaces include soft landscaping with a minimum dimension of: (a) 1m along all public road frontages and allotment boundaries (b) 1m between double rows of car parking spaces.
P0 7.6	DTS/DPF 7.6
Vehicle parking areas and associated driveways are landscaped to provide shade and positively contribute to amenity.	None are applicable.
PO 7.7	DTS/DPF 7.7
Vehicle parking areas and access ways incorporate integrated stormwater management techniques such as permeable or porous surfaces, infiltration systems, drainage swales or rain gardens that integrate with soft landscaping.	None are applicable.
Earthworks at	nd sloping land
PO 8.1	DTS/DPF 8.1
Development, including any associated driveways and access tracks, minimises the need for earthworks to limit disturbance to natural topography.	Development does not involve any of the following: (a) excavation exceeding a vertical height of 1m (b) filling exceeding a vertical height of 1m (c) a total combined excavation and filling vertical height of 2m or more.
PO 8.2	DTS/DPF 8.2

Page 67 of 141 Printed on 19/09/2022

	1
Driveways and access tracks designed and constructed to allow safe and convenient access on sloping land.	Driveways and access tracks on sloping land (with a gradient exceeding 1 in 8) satisfy (a) and (b): (a) do not have a gradient exceeding 25% (1-in-4) at any point along the driveway (b) are constructed with an all-weather trafficable surface.
PO 8.3	DTS/DPF 8.3
Driveways and access tracks on sloping land (with a gradient exceeding 1 in 8):	None are applicable.
 (a) do not contribute to the instability of embankments and cuttings (b) provide level transition areas for the safe movement of people and goods to and from the development (c) are designed to integrate with the natural topography of the land. 	
PO 8.4	DTS/DPF 8.4
Development on sloping land (with a gradient exceeding 1 in 8) avoids the alteration of natural drainage lines and includes on site drainage systems to minimise erosion.	None are applicable.
PO 8.5	DTS/DPF 8.5
Development does not occur on land at risk of landslip or increase the potential for landslip or land surface instability.	None are applicable.
Fences	and walls
PO 9.1	DTS/DPF 9.1
Fences, walls and retaining walls of sufficient height maintain privacy and security without unreasonably impacting visual amenity and adjoining land's access to sunlight or the amenity of public places.	None are applicable.
PO 9.2	DTS/DPF 9.2
Landscaping is incorporated on the low side of retaining walls that are visible from public roads and public open space to minimise visual impacts.	A vegetated landscaped strip 1m wide or more is provided against the low side of a retaining wall.
Overlooking / Visual Pr	ivacy (low rise buildings)
	DTS/DPF 10.1
PO 10.1	510,511 10.1
Development mitigates direct overlooking from upper level windows to habitable rooms and private open spaces of adjoining residential uses in neighbourhood-type zones.	Upper level windows facing side or rear boundaries shared with a residential use in a neighbourhood-type zone: (a) are permanently obscured to a height of 1.5m above finished floor level and are fixed or not capable of being opened more than 125mm (b) have sill heights greater than or equal to 1.5m above finished floor level (c) incorporate screening with a maximum of 25% openings, permanently fixed no more than 500mm from the window surface and sited adjacent to any part of the window less than 1.5 m above the finished floor level.

Page 68 of 141 Printed on 19/09/2022

Development mitigates direct overlooking from balconies to habitable rooms and private open space of adjoining residential uses in neighbourhood type zones.

One of the following is satisfied:

(a) the longest side of the balcony or terrace will face a public road, public road reserve or public reserve that is at least 15m wide in all places faced by the balcony or terrace

or

- (b) all sides of balconies or terraces on upper building levels are permanently obscured by screening with a maximum 25% transparency/openings fixed to a minimum height of:
 - (i) 1.5m above finished floor level where the balcony is located at least 15 metres from the nearest habitable window of a dwelling on adjacent land
 - (ii) 1.7m above finished floor level in all other cases

Site Facilities / Waste Storage (excluding low rise residential development)

Development provides a dedicated area for on-site collection and sorting of recyclable materials and refuse, green organic waste and wash bay facilities for the ongoing maintenance of bins that is adequate in size considering the number and nature of the activities they will serve and the frequency of collection.

None are applicable.

PO 11.2

PO 11.1

Communal waste storage and collection areas are located, enclosed and designed to be screened from view from the public domain, open space and dwellings.

DTS/DPF 11.2

DTS/DPF 11.1

None are applicable.

PO 11.3

Communal waste storage and collection areas are designed to be well ventilated and located away from habitable rooms.

DTS/DPF 11.3

None are applicable.

PO 11.4

DTS/DPF 11.4

Communal waste storage and collection areas are designed to allow waste and recycling collection vehicles to enter and leave the site without reversing.

None are applicable.

PO 11.5

DTS/DPF 11.5

For mixed use developments, non-residential waste and recycling storage areas and access provide opportunities for on-site management of food waste through composting or other waste recovery as appropriate.

None are applicable.

All Development - Medium and High Rise

External Appearance

Buildings positively contribute to the character of the local area by responding to local context. None are applicable.

PO 12.2

PO 12.1

DTS/DPF 12.2

DTS/DPF 12.1

Architectural detail at street level and a mixture of materials at lower building levels near the public interface are provided to reinforce a human scale.

None are applicable.

PO 12.3

DTS/DPF 12.3

Buildings are designed to reduce visual mass by breaking up building elevations into distinct elements.

None are applicable.

Page 69 of 141 Printed on 19/09/2022

Policy24 - Enquiry	
PO 12.4	DTS/DPF 12.4
Boundary walls visible from public land include visually interesting treatments to break up large blank elevations.	None are applicable.
P0 12.5	DTS/DPF 12.5
External materials and finishes are durable and age well to minimise ongoing maintenance requirements.	Buildings utilise a combination of the following external materials and finishes:
	(a) masonry (b) natural stone (c) pre-finished materials that minimise staining, discolouring or deterioration.
PO 12.6	DTS/DPF 12.6
Street-facing building elevations are designed to provide attractive, high quality and pedestrian-friendly street frontages.	Building street frontages incorporate:
	(a) active uses such as shops or offices (b) prominent entry areas for multi-storey buildings (where it is a common entry)
	(c) habitable rooms of dwellings
	(d) areas of communal public realm with public art or the like, where consistent with the zone and/or subzone provisions.
PO 12.7	DTS/DPF 12.7
Entrances to multi-storey buildings are safe, attractive, welcoming, functional and contribute to streetscape character.	(a) oriented towards the street (b) clearly visible and easily identifiable from the street and vehicle parking areas (c) designed to be prominent, accentuated and a welcoming feature if there are no active or occupied ground floor uses (d) designed to provide shelter, a sense of personal address and transitional space around the entry (e) located as close as practicable to the lift and / or lobby access to minimise the need for long access corridors (f) designed to avoid the creation of potential areas of entrapment.
P0 12.8	DTS/DPF 12.8
Building services, plant and mechanical equipment are screened from the public realm.	None are applicable.
Lands	scaping
P0 13.1	DTS/DPF 13.1
Development facing a street provides a well landscaped area that contains a deep soil space to accommodate a tree of a species and size adequate to provide shade, contribute to tree canopy targets and soften the appearance of buildings.	Buildings provide a 4m by 4m deep soil space in front of the building that accommodates a medium to large tree, except where no building setback from front property boundaries is desired.
PO 13.2	DTS/DPF 13.2
Deep soil zones are provided to retain existing vegetation or provide areas that can accommodate new deep root vegetation,	Multi-storey development provides deep soil zones and incorporates trees at not less than the following rates, except in

Page 70 of 141 Printed on 19/09/2022

cells.

including tall trees with large canopies to provide shade and

soften the appearance of multi-storey buildings.

Site area **Minimum Minimum** Tree / deep dimension soil zones deep soil area <300 m² 1.5m 1 small tree / 10 m^2 $10 \, \text{m}^2$ 7% site area 3m 1 medium 300-1500 m² tree / 30 m² 7% site area 6m 1 large or >1500 m² medium tree / 60 m^2 Tree size and site area definitions Small tree 4-6m mature height and 2-4m canopy spread Medium tree 6-12m mature height and 4-8m canopy spread Large tree 12m mature height and >8m canopy spread Site area The total area for development site, not average area per dwelling PO 13.3 DTS/DPF 13.3 Deep soil zones with access to natural light are provided to None are applicable. assist in maintaining vegetation health. PO 13.4 DTS/DPF 13.4 Unless separated by a public road or reserve, development sites Building elements of 3 or more building levels in height are set adjacent to any zone that has a primary purpose of back at least 6m from a zone boundary in which a deep soil zone accommodating low-rise residential development incorporate a area is incorporated. deep soil zone along the common boundary to enable medium to large trees to be retained or established to assist in screening new buildings of 3 or more building levels in height. Environmental PO 14.1 DTS/DPF 14.1 Development minimises detrimental micro-climatic impacts on None are applicable. adjacent land and buildings. PO 14.2 DTS/DPF 14.2 Development incorporates sustainable design techniques and None are applicable. features such as window orientation, eaves and shading structures, water harvesting and use, green walls and roof designs that enable the provision of rain water tanks (where they are not provided elsewhere on site), green roofs and photovoltaic

a location or zone where full site coverage is desired.

Page 71 of 141 Printed on 19/09/2022

PO 14.3

Development of 5 or more building levels, or 21m or more in height (as measured from natural ground level and excluding roof-mounted mechanical plant and equipment) is designed to minimise the impacts of wind through measures such as:

- (a) a podium at the base of a tall tower and aligned with the street to deflect wind away from the street
- (b) substantial verandahs around a building to deflect downward travelling wind flows over pedestrian areas
- (c) the placement of buildings and use of setbacks to deflect the wind at ground level
- avoiding tall shear elevations that create windy conditions at street level.

DTS/DPF 14.3

None are applicable.

Car Parking

PO 15.1

Multi-level vehicle parking structures are designed to contribute to active street frontages and complement neighbouring buildings.

DTS/DPF 15.1

Multi-level vehicle parking structures within buildings:

- (a) provide land uses such as commercial, retail or other non-car parking uses along ground floor street frontages
- (b) incorporate facade treatments in building elevations facing along major street frontages that are sufficiently enclosed and detailed to complement adjacent buildings.

PO 15.2

Multi-level vehicle parking structures within buildings complement the surrounding built form in terms of height, massing and scale.

DTS/DPF 15.2

None are applicable.

Overlooking/Visual Privacy

PO 16.1

Development mitigates direct overlooking of habitable rooms and private open spaces of adjacent residential uses in neighbourhood-type zones through measures such as:

- (a) appropriate site layout and building orientation
- (b) off-setting the location of balconies and windows of habitable rooms or areas with those of other buildings so that views are oblique rather than direct to avoid direct line of sight
- (c) building setbacks from boundaries (including building boundary to boundary where appropriate) that interrupt views or that provide a spatial separation between balconies or windows of habitable rooms
- (d) screening devices that are integrated into the building design and have minimal negative effect on residents' or neighbours' amenity.

DTS/DPF 16.1

None are applicable.

All residential development

Front elevations and passive surveillance

PO 17.1

DTS/DPF 17.1

Dwellings incorporate windows facing primary street frontages

Each dwelling with a frontage to a public street:

Page 72 of 141 Printed on 19/09/2022

to encourage passive surveillance and make a positive contribution to the streetscape. PO 17.2 Dwellings incorporate entry doors within street frontages to address the street and provide a legible entry point for visitors.	(a) includes at least one window facing the primary street from a habitable room that has a minimum internal room dimension of 2.4m (b) has an aggregate window area of at least 2m² facing the primary street. DTS/DPF 17.2 Dwellings with a frontage to a public street have an entry door visible from the primary street boundary.
Outlook a	nd Amenity
PO 18.1	DTS/DPF 18.1
Living rooms have an external outlook to provide a high standard of amenity for occupants.	A living room of a dwelling incorporates a window with an external outlook of the street frontage, private open space, public open space, or waterfront areas.
PO 18.2	DTS/DPF 18.2
Bedrooms are separated or shielded from active communal recreation areas, common access areas and vehicle parking areas and access ways to mitigate noise and artificial light intrusion.	None are applicable.
Ancillary D	evelopment
PO 19.1	DTS/DPF 19.1
Residential ancillary buildings are sited and designed to not detract from the streetscape or appearance of primary residential buildings on the site or neighbouring properties.	Ancillary buildings: (a) are ancillary to a dwelling erected on the same site (b) have a floor area not exceeding 60m2 (c) are not constructed, added to or altered so that any part is situated: (i) in front of any part of the building line of the dwelling to which it is ancillary or (ii) within 900mm of a boundary of the allotment with a secondary street (if the land has boundaries on two or more roads) (d) in the case of a garage or carport, the garage or carport: (i) is set back at least 5.5m from the boundary of the primary street (ii) when facing a primary street or secondary street, has a total door / opening not exceeding: A. for dwellings of single building level - 7m in width or 50% of the site frontage, whichever is the lesser B. for dwellings comprising two or more building levels at the building line fronting the same public street - 7m in width
	(e) if situated on a boundary (not being a boundary with a primary street or secondary street), do not exceed a length of 11.5m unless: (i) a longer wall or structure exists on the adjacent site and is situated on the same allotment boundary

Page 73 of 141 Printed on 19/09/2022

and

- (ii) the proposed wall or structure will be built along the same length of boundary as the existing adjacent wall or structure to the same or lesser extent
- (f) if situated on a boundary of the allotment (not being a boundary with a primary street or secondary street), all walls or structures on the boundary will not exceed 45% of the length of that boundary
- (g) will not be located within 3m of any other wall along the same boundary unless on an adjacent site on that boundary there is an existing wall of a building that would be adjacent to or about the proposed wall or structure
- (h) have a wall height or post height not exceeding 3m above natural ground level (and not including a gable end)
- (i) have a roof height where no part of the roof is more than 5m above the natural ground level
- (j) if clad in sheet metal, is pre-colour treated or painted in a non-reflective colour
- (k) retains a total area of soft landscaping in accordance with (i) or (ii), whichever is less:
 - a total area as determined by the following table:

Dwelling site area (or in the case of residential flat building or group dwelling(s), average site area) (m ²)	Minimum percentage of site
<150	10%
150-200	15%
201-450	20%
>450	25%

(ii) the amount of existing soft landscaping prior to the development occurring.

PO 19.2

Ancillary buildings and structures do not impede on-site functional requirements such as private open space provision, car parking requirements or result in over-development of the site.

DTS/DPF 19.2

Ancillary buildings and structures do not result in:

- (a) less private open space than specified in Design in Urban Areas Table 1 Private Open Space
- (b) less on-site car parking than specified in Transport, Access and Parking Table 1 - General Off-Street Car Parking Requirements or Table 2 - Off-Street Car Parking Requirements in Designated Areas.

PO 19.3

Fixed plant and equipment in the form of pumps and/or filtration systems for a swimming pool or spa positioned and/or housed

DTS/DPF 19.3

The pump and/or filtration system is ancillary to a dwelling erected on the same site and is:

Page 74 of 141 Printed on 19/09/2022

to not cause unreasonable noise nuisance to adjacent sensitive (a) enclosed in a solid acoustic structure that is located at receivers. least 5m from the nearest habitable room located on an adjoining allotment or (b) located at least 12m from the nearest habitable room located on an adjoining allotment. Residential Development - Low Rise External appearance PO 20.1 DTS/DPF 20.1 Garaging is designed to not detract from the streetscape or Garages and carports facing a street: appearance of a dwelling. are situated so that no part of the garage or carport will be in front of any part of the building line of the dwelling (b) are set back at least 5.5m from the boundary of the primary street (c) have a garage door / opening width not exceeding 7m (d) have a garage door / opening width not exceeding 50% of the site frontage unless the dwelling has two or more building levels at the building line fronting the same public street. PO 20.2 DTS/DPF 20.2 Dwelling elevations facing public streets and common driveways Each dwelling includes at least 3 of the following design features make a positive contribution to the streetscape and the within the building elevation facing a primary street, and at least 2 of the following design features within the building elevation appearance of common driveway areas. facing any other public road (other than a laneway) or a common driveway: (a) a minimum of 30% of the building wall is set back an additional 300mm from the building line (b) a porch or portico projects at least 1m from the building (c) a balcony projects from the building wall (d) a verandah projects at least 1m from the building wall (e) eaves of a minimum 400mm width extend along the width of the front elevation a minimum 30% of the width of the upper level projects forward from the lower level primary building line by at least 300mm a minimum of two different materials or finishes are incorporated on the walls of the front building elevation, with a maximum of 80% of the building elevation in a single material or finish. PO 20.3 DTS/DPF 20.3 The visual mass of larger buildings is reduced when viewed from None are applicable adjoining allotments or public streets.

Page 75 of 141 Printed on 19/09/2022

Policy24 - Enquiry Private 0	pen Space	
	DTS/DPF 21.1	
P0 21.1		
Dwellings are provided with suitable sized areas of usable private open space to meet the needs of occupants.	Private open space is provided in accordance with Design in Urban Areas Table 1 - Private Open Space.	
PO 21.2	DTS/DPF 21.2	
Private open space is positioned to provide convenient access from internal living areas.	Private open space is directly accessible from a habitable room.	
Lands	caping	
PO 22.1	DTS/DPF 22.1	
Soft landscaping is incorporated into development to:	Residential development incorporates soft landscaping with a minimum dimension of 700mm provided in accordance with (a	
 (a) minimise heat absorption and reflection (b) contribute shade and shelter 	and (b):	
(c) provide for stormwater infiltration and biodiversity (d) enhance the appearance of land and streetscapes.	(a) a total area as determined by the following table:	
	Dwelling site area (or in the case of residential flat building or group percentage of	
	dwelling(s), average site area) (m²) site	
	<150 10%	
	150-200 15%	
	>200-450 20%	
	>450 25%	
	(b) at least 30% of any land between the primary street boundary and the primary building line.	
Car parking, access	and manoeuvrability	
P0 23.1	DTS/DPF 23.1	
Enclosed car parking spaces are of dimensions to be functional, accessible and convenient.	Residential car parking spaces enclosed by fencing, walls or other structures have the following internal dimensions (separa from any waste storage area):	
	(a) single width car parking spaces: (i) a minimum length of 5.4m per space (ii) a minimum width of 3.0m (iii) a minimum garage door width of 2.4m	
	(b) double width car parking spaces (side by side): (i) a minimum length of 5.4m (ii) a minimum width of 5.4m (iii) minimum garage door width of 2.4m per space	
PO 23.2	DTS/DPF 23.2	
Uncovered car parking space are of dimensions to be functional, accessible and convenient.	Uncovered car parking spaces have:	
	(a) a minimum length of 5.4m	

Page 76 of 141 Printed on 19/09/2022

Policy24 - Enquiry	
	(b) a minimum width of 2.4m
	(c) a minimum width between the centre line of the space and any fence, wall or other obstruction of 1.5m.
PO 23.3	DTS/DPF 23.3
Driveways and access points are located and designed to facilitate safe access and egress while maximising land available for street tree planting, domestic waste collection, landscaped street frontages and on-street parking.	Driveways and access points satisfy (a) or (b): (a) sites with a frontage to a public road of 10m or less, have a width between 3.0 and 3.2 metres measured at the property boundary and are the only access point provided on the site (b) sites with a frontage to a public road greater than 10m: (i) have a maximum width of 5m measured at the
	property boundary and are the only access point provided on the site; (ii) have a width between 3.0 metres and 3.2 metres measured at the property boundary and no more than two access points are provided on site, separated by no less than 1m.
PO 23.4	DTS/DPF 23.4
Vehicle access is safe, convenient, minimises interruption to the operation of public roads and does not interfere with street infrastructure or street trees.	Vehicle access to designated car parking spaces satisfy (a) or (b):
annuoliuolule or oli eet ti eeo.	(a) is provided via a lawfully existing or authorised access point or an access point for which consent has been granted as part of an application for the division of land
	(b) where newly proposed, is set back: (i) 0.5m or more from any street furniture, street pole, infrastructure services pit, or other stormwater or utility infrastructure unless consent is provided from the asset owner
	(ii) 2m or more from the base of the trunk of a street tree unless consent is provided from the tree owner for a lesser distance
	(iii) 6m or more from the tangent point of an intersection of 2 or more roads
	(iv) outside of the marked lines or infrastructure dedicating a pedestrian crossing.
PO 23.5	DTS/DPF 23.5
Driveways are designed to enable safe and convenient vehicle	Driveways are designed and sited so that:
movements from the public road to on-site parking spaces.	(a) the gradient from the place of access on the boundary of the allotment to the finished floor level at the front of the garage or carport is not steeper than 1-in-4 on average
	(b) they are aligned relative to the street so that there is no more than a 20 degree deviation from 90 degrees between the centreline of any dedicated car parking space to which it provides access (measured from the front of that space) and the road boundary.
	(c) if located so as to provide access from an alley, lane or right of way - the alley, lane or right or way is at least 6.2m wide along the boundary of the allotment / site
PO 23.6	DTS/DPF 23.6

Page 77 of 141 Printed on 19/09/2022

Driveways and access points are designed and distributed to optimise the provision of on-street visitor parking.

Where on-street parking is available abutting the site's street frontage, on-street parking is retained in accordance with the following requirements:

- (a) minimum 0.33 on-street spaces per dwelling on the site (rounded up to the nearest whole number)
- (b) minimum car park length of 5.4m where a vehicle can enter or exit a space directly
- (c) minimum carpark length of 6m for an intermediate space located between two other parking spaces or to an end obstruction where the parking is indented.

Waste storage

PO 24.1

Provision is made for the convenient storage of waste bins in a location screened from public view.

DTS/DPF 24.1

Where dwellings abut both side boundaries a waste bin storage area is provided behind the building line of each dwelling that:

- (a) has a minimum area of 2m² with a minimum dimension of 900mm (separate from any designated car parking spaces or private open space); and
- (b) has a continuous unobstructed path of travel (excluding moveable objects like gates, vehicles and roller doors) with a minimum width of 800mm between the waste bin storage area and the street.

Design of Transportable Buildings

PO 25 1

The sub-floor space beneath transportable buildings is enclosed to give the appearance of a permanent structure.

DTS/DPF 25.1

Buildings satisfy (a) or (b):

- (a) are not transportable
- (b) the sub-floor space between the building and ground level is clad in a material and finish consistent with the building.

Residential Development - Medium and High Rise (including serviced apartments)

Outlook and Visual Privacy

PO 26.1

Ground level dwellings have a satisfactory short range visual outlook to public, communal or private open space.

DTS/DPF 26.1

Buildings:

- (a) provide a habitable room at ground or first level with a window facing toward the street
- (b) limit the height / extent of solid walls or fences facing the street to 1.2m high above the footpath level or, where higher, to 50% of the site frontage.

PO 26.2

DTS/DPF 26.2

The visual privacy of ground level dwellings within multi-level buildings is protected.

The finished floor level of ground level dwellings in multi-storey developments is raised by up to 1.2m.

Private Open Space

PO 27.1

DTS/DPF 27.1

Dwellings are provided with suitable sized areas of usable private open space to meet the needs of occupants.

Private open space provided in accordance with Design in Urban Areas Table 1 - Private Open Space.

Residential amenity in multi-level buildings

Page 78 of 141 Printed on 19/09/2022

PO 28.1 DTS/DPF 28.1 Residential accommodation within multi-level buildings have Habitable rooms and balconies of independent dwellings and habitable rooms, windows and balconies designed and accommodation are separated by at least 6m from one another positioned to be separated from those of other dwellings and where there is a direct line of sight between them and 3m or accommodation to provide visual and acoustic privacy and allow more from a side or rear property boundary. for natural ventilation and the infiltration of daylight into interior and outdoor spaces. PO 28.2 DTS/DPF 28.2 Balconies are designed, positioned and integrated into the overall Balconies utilise one or a combination of the following design architectural form and detail of the development to: elements: (a) (a) respond to daylight, wind, and acoustic conditions to sun screens maximise comfort and provide visual privacy (b) pergolas (b) allow views and casual surveillance of the street while (c) louvres providing for safety and visual privacy of nearby living (d) green facades spaces and private outdoor areas. (e) openable walls. PO 28.3 DTS/DPF 28.3 Balconies are of sufficient size and depth to accommodate Balconies open directly from a habitable room and incorporate a outdoor seating and promote indoor / outdoor living. minimum dimension of 2m. PO 28.4 **DTS/DPF 28.4** Dwellings are provided with sufficient space for storage to meet Dwellings (not including student accommodation or serviced likely occupant needs. apartments) are provided with storage at the following rates with at least 50% or more of the storage volume to be provided within the dwelling: (a) studio: not less than 6m³ (b) 1 bedroom dwelling / apartment: not less than 8m³ (c) 2 bedroom dwelling / apartment: not less than 10m³ (d) 3+ bedroom dwelling / apartment: not less than 12m³. PO 28.5 **DTS/DPF 28.5** Dwellings that use light wells for access to daylight, outlook and Light wells: ventilation for habitable rooms, are designed to ensure a reasonable living amenity is provided. (a) are not used as the primary source of outlook for living (b) up to 18m in height have a minimum horizontal dimension of 3m, or 6m if overlooked by bedrooms above 18m in height have a minimum horizontal dimension of 6m, or 9m if overlooked by bedrooms. PO 28.6 DTS/DPF 28.6 None are applicable. Attached or abutting dwellings are designed to minimise the transmission of sound between dwellings and, in particular, to protect bedrooms from possible noise intrusions. DTS/DPF 28.7 PO 28 7 None are applicable. Dwellings are designed so that internal structural columns correspond with the position of internal walls to ensure that the space within the dwelling/apartment is useable. **Dwelling Configuration**

Page 79 of 141 Printed on 19/09/2022

PO 29.1

Buildings containing in excess of 10 dwellings provide a variety of dwelling sizes and a range in the number of bedrooms per dwelling to contribute to housing diversity.

DTS/DPF 29.1

Buildings containing in excess of 10 dwellings provide at least one of each of the following:

- (a) studio (where there is no separate bedroom)
- (b) 1 bedroom dwelling / apartment with a floor area of at least 50m²
- (c) 2 bedroom dwelling / apartment with a floor area of at least 65m²
- (d) 3+ bedroom dwelling / apartment with a floor area of at least 80m², and any dwelling over 3 bedrooms provides an additional 15m² for every additional bedroom.

PO 29.2

Dwellings located on the ground floor of multi-level buildings with 3 or more bedrooms have the windows of their habitable rooms overlooking internal courtyard space or other public space, where possible.

DTS/DPF 29.2

None are applicable.

Common Areas

PO 30.1

The size of lifts, lobbies and corridors is sufficient to accommodate movement of bicycles, strollers, mobility aids and visitor waiting areas.

DTS/DPF 30.1

Common corridor or circulation areas:

- (a) have a minimum ceiling height of 2.7m
- (b) provide access to no more than 8 dwellings
- (c) incorporate a wider section at apartment entries where the corridors exceed 12m in length from a core.

Group Dwellings, Residential Flat Buildings and Battle axe Development

Amenity

PO 31.1

Dwellings are of a suitable size to provide a high standard of amenity for occupants.

DTS/DPF 31.1

Dwellings have a minimum internal floor area in accordance with the following table:

Number of bedrooms	Minimum internal floor area
Studio	35m ²
1 bedroom	50m ²
2 bedroom	65m ²
3+ bedrooms	80m ² and any dwelling over 3 bedrooms provides an additional 15m ² for every additional bedroom

PO 31.2

The orientation and siting of buildings minimises impacts on the amenity, outlook and privacy of occupants and neighbours.

DTS/DPF 31.2

None are applicable.

Page 80 of 141 Printed on 19/09/2022

Policy24 - Enquiry	
PO 31.3	DTS/DPF 31.3
Development maximises the number of dwellings that face publ open space and public streets and limits dwellings oriented towards adjoining properties.	c None are applicable.
PO 31.4	DTS/DPF 31.4
Battle-axe development is appropriately sited and designed to respond to the existing neighbourhood context.	Dwelling sites/allotments are not in the form of a battle-axe arrangement.
Commun	al Open Space
PO 32.1	DTS/DPF 32.1
Private open space provision may be substituted for communal open space which is designed and sited to meet the recreation and amenity needs of residents.	None are applicable.
PO 32.2	DTS/DPF 32.2
Communal open space is of sufficient size and dimensions to cater for group recreation.	Communal open space incorporates a minimum dimension of 5 metres.
PO 32.3	DTS/DPF 32.3
Communal open space is designed and sited to:	None are applicable.
(a) be conveniently accessed by the dwellings which it services (b) have regard to acoustic, safety, security and wind	
(b) have regard to acoustic, safety, security and wind effects.	
PO 32.4	DTS/DPF 32.4
Communal open space contains landscaping and facilities that are functional, attractive and encourage recreational use.	None are applicable.
PO 32.5	DTS/DPF 32.5
Communal open space is designed and sited to:	None are applicable.
(a) in relation to rooftop or elevated gardens, minimise overlooking into habitable room windows or onto the useable private open space of other dwellings	
(b) in relation to ground floor communal space, be overlooked by habitable rooms to facilitate passive surveillance.	
Car parking, acce	ss and manoeuvrability
PO 33.1	DTS/DPF 33.1
Driveways and access points are designed and distributed to optimise the provision of on-street visitor parking.	Where on-street parking is available directly adjacent the site, on- street parking is retained adjacent the subject site in accordance with the following requirements:
	 (a) minimum 0.33 on-street car parks per proposed dwelling (rounded up to the nearest whole number) (b) minimum car park length of 5.4m where a vehicle can enter or exit a space directly (c) minimum carpark length of 6m for an intermediate space located between two other parking spaces or to an end obstruction where the parking is indented.
PO 33.2	DTS/DPF 33.2
The number of vehicular access points onto public roads is minimised to reduce interruption of the footpath and positively	Access to group dwellings or dwellings within a residential flat building is provided via a single common driveway.

Page 81 of 141 Printed on 19/09/2022

contribute to public safety and walkability.	
PO 33.3	DTS/DPF 33.3
Residential driveways that service more than one dwelling are designed to allow safe and convenient movement.	Driveways that service more than 1 dwelling or a dwelling on a battle-axe site: (a) have a minimum width of 3m (b) for driveways servicing more than 3 dwellings: (i) have a width of 5.5m or more and a length of 6m or more at the kerb of the primary street (ii) where the driveway length exceeds 30m, incorporate a passing point at least every 30 metres with a minimum width of 5.5m and a minimum length of 6m.
PO 33.4	DTS/DPF 33.4
Residential driveways that service more than one dwelling or a dwelling on a battle-axe site are designed to allow passenger vehicles to enter and exit and manoeuvre within the site in a safe and convenient manner.	Driveways providing access to more than one dwelling, or a dwelling on a battle-axe site, allow a B85 passenger vehicle to enter and exit the garages or parking spaces in no more than a three-point turn manoeuvre.
PO 33.5	DTS/DPF 33.5
Dwellings are adequately separated from common driveways and manoeuvring areas.	Dwelling walls with entry doors or ground level habitable room windows are set back at least 1.5m from any driveway or area designated for the movement and manoeuvring of vehicles.
Soft lan	dscaping
DO 24.1	
P0 34.1	DTS/DPF 34.1
Soft landscaping is provided between dwellings and common driveways to improve the outlook for occupants and appearance of common areas.	Other than where located directly in front of a garage or building entry, soft landscaping with a minimum dimension of 1m is provided between a dwelling and common driveway.
Soft landscaping is provided between dwellings and common driveways to improve the outlook for occupants and appearance	Other than where located directly in front of a garage or building entry, soft landscaping with a minimum dimension of 1m is
Soft landscaping is provided between dwellings and common driveways to improve the outlook for occupants and appearance of common areas.	Other than where located directly in front of a garage or building entry, soft landscaping with a minimum dimension of 1m is provided between a dwelling and common driveway.
Soft landscaping is provided between dwellings and common driveways to improve the outlook for occupants and appearance of common areas. PO 34.2 Battle-axe or common driveways incorporate landscaping and permeability to improve appearance and assist in stormwater management.	Other than where located directly in front of a garage or building entry, soft landscaping with a minimum dimension of 1m is provided between a dwelling and common driveway. DTS/DPF 34.2 Battle-axe or common driveways satisfy (a) and (b): (a) are constructed of a minimum of 50% permeable or porous material (b) where the driveway is located directly adjacent the side or rear boundary of the site, soft landscaping with a minimum dimension of 1m is provided between the driveway and site boundary (excluding along the
Soft landscaping is provided between dwellings and common driveways to improve the outlook for occupants and appearance of common areas. PO 34.2 Battle-axe or common driveways incorporate landscaping and permeability to improve appearance and assist in stormwater management.	Other than where located directly in front of a garage or building entry, soft landscaping with a minimum dimension of 1m is provided between a dwelling and common driveway. DTS/DPF 34.2 Battle-axe or common driveways satisfy (a) and (b): (a) are constructed of a minimum of 50% permeable or porous material (b) where the driveway is located directly adjacent the side or rear boundary of the site, soft landscaping with a minimum dimension of 1m is provided between the driveway and site boundary (excluding along the perimeter of a passing point).
Soft landscaping is provided between dwellings and common driveways to improve the outlook for occupants and appearance of common areas. PO 34.2 Battle-axe or common driveways incorporate landscaping and permeability to improve appearance and assist in stormwater management. Site Facilities PO 35.1 Provision is made for suitable mailbox facilities close to the major pedestrian entry to the site or conveniently located considering the nature of accommodation and mobility of	Other than where located directly in front of a garage or building entry, soft landscaping with a minimum dimension of 1m is provided between a dwelling and common driveway. DTS/DPF 34.2 Battle-axe or common driveways satisfy (a) and (b): (a) are constructed of a minimum of 50% permeable or porous material (b) where the driveway is located directly adjacent the side or rear boundary of the site, soft landscaping with a minimum dimension of 1m is provided between the driveway and site boundary (excluding along the perimeter of a passing point). Waste Storage DTS/DPF 35.1
Soft landscaping is provided between dwellings and common driveways to improve the outlook for occupants and appearance of common areas. P0 34.2 Battle-axe or common driveways incorporate landscaping and permeability to improve appearance and assist in stormwater management. Site Facilities P0 35.1 Provision is made for suitable mailbox facilities close to the major pedestrian entry to the site or conveniently located considering the nature of accommodation and mobility of occupants.	Other than where located directly in front of a garage or building entry, soft landscaping with a minimum dimension of 1m is provided between a dwelling and common driveway. DTS/DPF 34.2 Battle-axe or common driveways satisfy (a) and (b): (a) are constructed of a minimum of 50% permeable or porous material (b) where the driveway is located directly adjacent the side or rear boundary of the site, soft landscaping with a minimum dimension of 1m is provided between the driveway and site boundary (excluding along the perimeter of a passing point). Waste Storage DTS/DPF 35.1 None are applicable.

Page 82 of 141 Printed on 19/09/2022

Provision is made for suitable household waste and recyclable material storage facilities which are:	None are applicable.
(a) located away, or screened, from public view, and (b) conveniently located in proximity to dwellings and the waste collection point.	
PO 35.4	DTS/DPF 35.4
Waste and recyclable material storage areas are located away from dwellings.	Dedicated waste and recyclable material storage areas are located at least 3m from any habitable room window.
PO 35.5	DTS/DPF 35.5
Where waste bins cannot be conveniently collected from the street, provision is made for on-site waste collection, designed to accommodate the safe and convenient access, egress and movement of waste collection vehicles.	None are applicable.
PO 35.6	DTS/DPF 35.6
Services including gas and water meters are conveniently located and screened from public view.	None are applicable.
Water sensitiv	e urban design
PO 36.1	DTS/DPF 36.1
Residential development creating a common driveway / access includes stormwater management systems that minimise the discharge of sediment, suspended solids, organic matter, nutrients, bacteria, litter and other contaminants to the stormwater system, watercourses or other water bodies.	None are applicable.
PO 36.2	DTS/DPF 36.2
Residential development creating a common driveway / access includes a stormwater management system designed to mitigate peak flows and manage the rate and duration of stormwater discharges from the site to ensure that the development does not increase the peak flows in downstream systems.	None are applicable.
Supported Accommodation	I on and retirement facilities
Siting, Configur	ation and Design
PO 37.1	DTS/DPF 37.1
Supported accommodation and housing for aged persons and people with disabilities is located where on-site movement of residents is not unduly restricted by the slope of the land.	None are applicable.
PO 37.2	DTS/DPF 37.2
Universal design features are incorporated to provide options for people living with disabilities or limited mobility and / or to facilitate ageing in place.	None are applicable.
Movement	and Access
PO 38.1	DTS/DPF 38.1
Development is designed to support safe and convenient access and movement for residents by providing:	None are applicable.

Page 83 of 141 Printed on 19/09/2022

PO 40.2

(a) ground-level access or lifted access to all units (b) level entry porches, ramps, paths, driveways, passenger loading areas and areas adjacent to footpaths that allow for the passing of wheelchairs and resting places (c) car parks with gradients no steeper than 1-in-40, and of sufficient area to provide for wheelchair manoeuvrability (d) kerb ramps at pedestrian crossing points. Communal Open Space PO 39.1 DTS/DPF 39.1 Development is designed to provide attractive, convenient and None are applicable. comfortable indoor and outdoor communal areas to be used by residents and visitors. PO 39.2 DTS/DPF 39.2 Private open space provision may be substituted for communal None are applicable. open space which is designed and sited to meet the recreation and amenity needs of residents. PO 39.3 DTS/DPF 39.3 Communal open space is of sufficient size and dimensions to Communal open space incorporates a minimum dimension of 5 cater for group recreation. metres. PO 39.4 DTS/DPF 39.4 Communal open space is designed and sited to: None are applicable. be conveniently accessed by the dwellings which it services (b) have regard to acoustic, safety, security and wind effects. PO 39.5 DTS/DPF 39.5 Communal open space contains landscaping and facilities that None are applicable. are functional, attractive and encourage recreational use. PO 39.6 DTS/DPF 39.6 Communal open space is designed and sited to: None are applicable. (a) in relation to rooftop or elevated gardens, minimise overlooking into habitable room windows or onto the useable private open space of other dwellings (b) in relation to ground floor communal space, be overlooked by habitable rooms to facilitate passive surveillance. Site Facilities / Waste Storage PO 40.1 DTS/DPF 40.1 Development is designed to provide storage areas for personal None are applicable. items and specialised equipment such as small electric powered vehicles, including facilities for the recharging of small electricpowered vehicles.

Page 84 of 141 Printed on 19/09/2022

DTS/DPF 40.2

Provision is made for suitable mailbox facilities close to the major pedestrian entry to the site or conveniently located considering the nature of accommodation and mobility of occupants.	None are applicable.
PO 40.3	DTS/DPF 40.3
Provision is made for suitable external clothes drying facilities.	None are applicable.
PO 40.4	DTS/DPF 40.4
Provision is made for suitable household waste and recyclable material storage facilities conveniently located away, or screened, from view.	None are applicable.
PO 40.5	DTS/DPF 40.5
Waste and recyclable material storage areas are located away from dwellings.	Dedicated waste and recyclable material storage areas are located at least 3m from any habitable room window.
PO 40.6	DTS/DPF 40.6
Provision is made for on-site waste collection where 10 or more bins are to be collected at any one time.	None are applicable.
PO 40.7	DTS/DPF 40.7
Services, including gas and water meters, are conveniently located and screened from public view.	None are applicable.
Student Acc	commodation
PO 41.1	DTS/DPF 41.1
Student accommodation is designed to provide safe, secure, attractive, convenient and comfortable living conditions for residents, including an internal layout and facilities that are designed to provide sufficient space and amenity for the requirements of student life and promote social interaction.	(a) a range of living options to meet a variety of accommodation needs, such as one-bedroom, two-bedroom and disability access units (b) common or shared facilities to enable a more efficient use of space, including: (i) shared cooking, laundry and external drying facilities (ii) internal and external communal and private open space provided in accordance with Design in Urban Areas Table 1 - Private Open Space (iii) common storage facilities at the rate of 8m³ for every 2 dwellings or students (iv) common on-site parking in accordance with Transport, Access and Parking Table 1 - General Off-Street Car Parking Requirements or Table 2 - Off-Street Car Parking Requirements in Designated Areas (v) bicycle parking at the rate of one space for every 2 students.
PO 41.2 Student accommodation is designed to provide easy adaptation of the building to accommodate an alternative use of the building in the event it is no longer required for student housing.	DTS/DPF 41.2 None are applicable.

Page 85 of 141 Printed on 19/09/2022

	y	
All non-residential development		
Water Sensitive Design		
PO 42.1		DTS/DPF 42.1
suspended soli	ikely to result in risk of export of sediment, ids, organic matter, nutrients, oil and grease vater management systems designed to minimise ering stormwater.	None are applicable.
PO 42.2		DTS/DPF 42.2
_	ged from a development site is of a physical, piological condition equivalent to or better than its state.	None are applicable.
PO 42.3		DTS/DPF 42.3
mitigate peak f stormwater dis	ncludes stormwater management systems to flows and manage the rate and duration of scharges from the site to ensure that development ase peak flows in downstream systems.	None are applicable.
	Wash-down and Waste	Loading and Unloading
PO 43.1		DTS/DPF 43.1
waste refuse b	ities including loading and unloading, storage of ins in commercial and industrial development or eas used for the cleaning of vehicles, plant or	None are applicable.
storm	ned to contain all wastewater likely to pollute water within a bunded and roofed area to exclude try of external surface stormwater run-off	
	with an impervious material to facilitate water collection	
	ficient size to prevent 'splash-out' or 'over-spray' of water from the wash-down area	
(d) are de (i)	signed to drain wastewater to either: a treatment device such as a sediment trap and coalescing plate oil separator with subsequent disposal to a sewer, private or Community Wastewater Management Scheme or a holding tank and its subsequent removal offsite on a regular basis.	

Laneway Development

Infrastructure and Access

PO 44.1

Development with a primary street comprising a laneway, alley, lane, right of way or similar minor thoroughfare only occurs where:

- (a) existing utility infrastructure and services are capable of accommodating the development
- (b) the primary street can support access by emergency and regular service vehicles (such as waste collection)

DTS/DPF 44.1

Development with a primary street frontage that is not an alley, lane, right of way or similar public thoroughfare.

Page 86 of 141 Printed on 19/09/2022

(c) it does not require the provision or upgrading of infrastructure on public land (such as footpaths and stormwater management systems)

(d) safety of pedestrians or vehicle movement is maintained any necessary grade transition is accommodated within the site of the development to support an appropriate

development intensity and orderly development of land

Table 1 - Private Open Space

fronting minor thoroughfares.

Dwelling Type	Dwelling / Site Configuration	Minimum Rate
Dwelling (at ground level, other than a residential flat building that includes above ground dwellings)		Total private open space area: (a) Site area <301m2: 24m2 located behind the building line. (b) Site area ≥ 301m2: 60m2 located behind the building line. Minimum directly accessible from a living room: 16m2 / with a minimum dimension 3m.
Cabin or caravan (permanently fixed to the ground) in a residential park or caravan and tourist park		Total area: 16m ² , which may be uses as second car parking space, provided on each site intended for residential occupation.
Dwelling in a residential flat building or mixed use building which	Dwellings at ground level:	15m ² / minimum dimension 3m
incorporate above ground level dwellings	Dwellings above ground level:	
	Studio (no separate bedroom)	4m ² / minimum dimension 1.8m
	One bedroom dwelling	8m ² / minimum dimension 2.1m
	Two bedroom dwelling	11m ² / minimum dimension 2.4m
	Three + bedroom dwelling	15 m ² / minimum dimension 2.6m

Forestry

Assessment Provisions (AP)

Desired Outcome	
DO 1	Commercial forestry is designed and sited to maximise economic benefits whilst managing potential negative impacts

Page 87 of 141 Printed on 19/09/2022

on the environment, transport networks, surrounding land uses and landscapes.

Performance Outcomes (PO) and Deemed-to-Satisfy (DTS) Criteria / Designated Performance Feature (DPF)

Performance Outcome	Deemed-to-Satisfy Criteria / Designated Performance Feature		
Sit	ing		
PO 1.1	DTS/DPF 1.1		
Commercial forestry plantations are established where there is no detrimental effect on the physical environment or scenic quality of the rural landscape.	None are applicable.		
PO 1.2	DTS/DPF 1.2		
Commercial forestry plantations are established on slopes that are stable to minimise the risk of soil erosion.	Commercial forestry plantations are not located on land with a slope exceeding 20% (1-in-5).		
PO 1.3	DTS/DPF 1.3		
Commercial forestry plantations and operations associated with their establishment, management and harvesting are appropriately set back from any sensitive receiver to minimise fire risk and noise disturbance.	Commercial forestry plantations and operations associated with their establishment, management and harvesting are set back 50m or more from any sensitive receiver.		
PO 1.4	DTS/DPF 1.4		
Commercial forestry plantations are separated from reserves gazetted under the <i>National Parks and Wildlife Act 1972</i> and/or <i>Wilderness Protection Act 1992</i> to minimise fire risk and potential for weed infestation.	Commercial forestry plantations and operations associated with their establishment, management and harvesting are set back 50m or more from a reserve gazetted under the <i>National Parks</i> and <i>Wildlife Act 1972</i> and/or <i>Wilderness Protection Act 1992</i> .		
Water P	rotection		
PO 2.1	DTS/DPF 2.1		
Commercial forestry plantations incorporate artificial drainage lines (i.e. culverts, runoffs and constructed drains) integrated with natural drainage lines to minimise concentrated water flows onto or from plantation areas.	None are applicable.		
PO 2.2	DTS/DPF 2.2		
Appropriate siting, layout and design measures are adopted to minimise the impact of commercial forestry plantations on surface water resources.	(a) do not involve cultivation (excluding spot cultivation) in drainage lines (b) are set back 20m or more from the banks of any major watercourse (a third order or higher watercourse), lake, reservoir, wetland or sinkhole (with direct connection to an aquifer) (c) are set back 10m or more from the banks of any first or second order watercourse or sinkhole (with no direct connection to an aquifer).		
Fire Management			

Page 88 of 141 Printed on 19/09/2022

PO 3.1 DTS/DPF 3.1 Commercial forestry plantations incorporate appropriate Commercial forestry plantations provide: firebreaks and fire management design elements. 7m or more wide external boundary firebreaks for plantations of 40ha or less 10m or more wide external boundary firebreaks for plantations of between 40ha and 100ha (c) 20m or more wide external boundary firebreaks, or 10m with an additional 10m or more of fuel-reduced plantation, for plantations of 100ha or greater. PO 3.2 DTS/DPF 3.2 Commercial forestry plantations incorporate appropriate fire Commercial forestry plantation fire management access tracks: management access tracks. (a) are incorporated within all firebreaks (b) are 7m or more wide with a vertical clearance of 4m or (c) are aligned to provide straight through access at junctions, or if they are a no through access track are appropriately signposted and provide suitable turnaround areas for fire-fighting vehicles (d) partition the plantation into units of 40ha or less in area. Power-line Clearances DTS/DPF 4.1 PO 4.1 Commercial forestry plantations achieve and maintain Commercial forestry plantations incorporating trees with an appropriate clearances from aboveground powerlines. expected mature height of greater than 6m meet the clearance requirements listed in the following table: Voltage of transmission Minimum horizontal Tower or line Pole clearance distance between plantings and transmission lines 500 kV 38m Tower 275 kV Tower 25m 132 kV Tower 30m Pole 132 kV 20m 66 kV 20m Pole

Housing Renewal

Assessment Provisions (AP)

Page 89 of 141 Printed on 19/09/2022

Less than 66 kV

Pole

20m

Desired Outcome

DO 1

Renewed residential environments replace older social housing and provide new social housing infrastructure and other housing options and tenures to enhance the residential amenity of the local area.

Performance Outcomes (PO) and Deemed-to-Satisfy (DTS) Criteria / Designated Performance Feature (DPF)

Performance Outcome	Deemed-to-Satisfy Criteria / Designated Performance Feature	
Land Use a	nd Intensity	
P0 1.1	DTS/DPF 1.1	
Residential development provides a range of housing choices.	Development comprises one or more of the following: (a) detached dwellings (b) semi-detached dwellings (c) row dwellings (d) group dwellings (e) residential flat buildings.	
PO 1.2	DTS/DPF 1.2	
Medium-density housing options or higher are located in close proximity to public transit, open space and/or activity centres.	None are applicable.	
Building	g Height	
PO 2.1	DTS/DPF 2.1	
Buildings generally do not exceed 3 building levels unless in locations close to public transport, centres and/or open space.	Building height (excluding garages, carports and outbuildings) does not exceed 3 building levels and 12m and wall height does not exceed 9m (not including a gable end).	
PO 2.2	DTS/DPF 2.2	
Medium or high rise residential flat buildings located within or at the interface with zones which restrict heights to a maximum of 2 building levels transition down in scale and height towards the boundary of that zone, other than where it is a street boundary.		
Primary Str	eet Setback	
PO 3.1	DTS/DPF 3.1	
Buildings are set back from the primary street boundary to contribute to an attractive streetscape character.	Buildings are no closer to the primary street (excluding any balcony, verandah, porch, awning or similar structure) than 3m.	
Secondary S	treet Setback	
PO 4.1	DTS/DPF 4.1	
Buildings are set back from secondary street boundaries to maintain separation between building walls and public streets and contribute to a suburban streetscape character.	Buildings are set back at least 900mm from the boundary of the allotment with a secondary street frontage.	

Page 90 of 141 Printed on 19/09/2022

	Bounda	ry Walls		
PO 5.1		DTS/DPF 5.1		
Boundary walls are limited in height and length to manage visual impacts and access to natural light and ventilation.		Except where the dwelling is located on a central site within a row dwelling or terrace arrangement, dwellings with side boundary walls are sited on only one side boundary and satisfy (a) or (b):		
		la (b) do	-	exceed 3.2m in height from the lower of the natural or finished ground level exceed 11.5m in length when combined with other walls on the boundary of the subject development site, a maximum 45% of the length of the boundary encroach within 3 metres of any other existing or proposed boundary walls on the subject land.
PO 5.2		DTS/DPF 5.2	!	
=	d, row or terrace arrangement dings consistent with a suburban	900mm or	r more	emi-detached or row arrangement are set back from side boundaries shared with allotments elopment site, except for a carport or garage.
	Side Bound	ary Setback		
to a suburban chara	dwellings in a way that contributes	(a) at (b) ot le	n walls side l t least ther theast 90	s located on a side boundary, buildings are set boundaries: 900mm where the wall height is up to 3m can for a wall facing a southern side boundary, at 30mm plus 1/3 of the wall height above 3m 1.9m plus 1/3 of the wall height above 3m for
				cing a southern side boundary.
	Rear Bound	ary Setback		
P0 7.1 Buildings are set back from r	ear boundaries to provide:	DTS/DPF 7.1 Dwellings		et back from the rear boundary:
to a suburban chara	ht and ventilation for neighbours	4		nore for the first building level nore for any subsequent building level.
	Buildings ele	vation design		
PO 8.1		DTS/DPF 8.1		
	ablic streets and common driveways to the streetscape and common		-	cludes at least 3 of the following design features ng elevation facing a primary street, and at least

driveway areas.

2 of the following design features within the building elevation facing any other public road (other than a laneway) or a common driveway:

Page 91 of 141 Printed on 19/09/2022

PO 8.2 Dwellings incorporate windows along primary street frontages to	 (a) a minimum of 30% of the building elevation is set back an additional 300mm from the building line (b) a porch or portico projects at least 1m from the building elevation (c) a balcony projects from the building elevation (d) a verandah projects at least 1m from the building elevation (e) eaves of a minimum 400mm width extend along the width of the front elevation (f) a minimum 30% of the width of the upper level projects forward from the lower level primary building line by at least 300mm. (g) a minimum of two different materials or finishes are incorporated on the walls of the building elevation, with a maximum of 80% of the building elevation in a single material or finish. DTS/DPF 8.2 Each dwelling with a frontage to a public street:		
encourage passive surveillance and make a positive contribution to the streetscape.	(a) includes at least one window facing the primary street from a habitable room that has a minimum internal room dimension of 2.4m (b) has an aggregate window area of at least 2m² facing the primary street		
PO 8.3	DTS/DPF 8.3		
The visual mass of larger buildings is reduced when viewed from adjoining allotments or public streets.	None are applicable.		
PO 8.4	DTS/DPF 8.4		
Built form considers local context and provides a quality design response through scale, massing, materials, colours and architectural expression.	None are applicable.		
PO 8.5	DTS/DPF 8.5		
Entrances to multi-storey buildings are:	None are applicable.		
(a) oriented towards the street (b) visible and easily identifiable from the street (c) designed to include a common mail box structure.			
Outlook a	nd amenity		
PO 9.1	DTS/DPF 9.1		
Living rooms have an external outlook to provide a high standard of amenity for occupants.	A living room of a dwelling incorporates a window with an external outlook towards the street frontage or private open space.		
PO 9.2	DTS/DPF 9.2		
Bedrooms are separated or shielded from active communal recreation areas, common access areas and vehicle parking areas and access ways to mitigate noise and artificial light	None are applicable.		

Page 92 of 141 Printed on 19/09/2022

Private Open Space PO 10.1 DTS/DPF 10.1 Dwellings are provided with suitable sized areas of usable private Private open space is provided in accordance with the following open space to meet the needs of occupants. **Dwelling Type Dwelling / Site Minimum Rate** Configuration Dwelling (at Total area: 24m² ground level) located behind the building line Minimum adjacent to a living room: 16m² with a minimum dimension 3m Dwelling (above 4m² / minimum Studio ground level) dimension 1.8m 8m² / minimum One bedroom dimension 2.1m dwelling 11m² / minimum Two bedroom dimension 2.4m dwelling 15 m² / minimum Three + bedroom dimension 2.6m dwelling PO 10.2 DTS/DPF 10.2 Private open space positioned to provide convenient access At least 50% of the required area of private open space is from internal living areas. accessible from a habitable room. PO 10.3 DTS/DPF 10.3 Private open space is positioned and designed to: None are applicable. (a) provide useable outdoor space that suits the needs of occupants; (b) take advantage of desirable orientation and vistas; and (c) adequately define public and private space. Visual privacy PO 11.1 DTS/DPF 11.1 Development mitigates direct overlooking from upper level Upper level windows facing side or rear boundaries shared with another residential allotment/site satisfy one of the following: windows to habitable rooms and private open spaces of adjoining residential uses. are permanently obscured to a height of 1.5m above finished floor level and are fixed or not capable of being opened more than 200mm (b) have sill heights greater than or equal to 1.5m above finished floor level (c) incorporate screening with a maximum of 25% openings,

Page 93 of 141 Printed on 19/09/2022

permanently fixed no more than 500mm from the window surface and sited adjacent to any part of the window less than 1.5m above the finished floor. PO 11.2 DTS/DPF 11.2 Development mitigates direct overlooking from upper level One of the following is satisfied: balconies and terraces to habitable rooms and private open the longest side of the balcony or terrace will face a space of adjoining residential uses. public road, public road reserve or public reserve that is at least 15m wide in all places faced by the balcony or terrace or (b) all sides of balconies or terraces on upper building levels are permanently obscured by screening with a maximum 25% transparency/openings fixed to a minimum height of: 1.5m above finished floor level where the balcony is located at least 15 metres from the nearest habitable window of a dwelling on adjacent land or (ii) 1.7m above finished floor level in all other cases Landscaping DTS/DPF 12.1 PO 12.1 Soft landscaping is incorporated into development to: Residential development incorporates pervious areas for soft landscaping with a minimum dimension of 700mm provided in (a) minimise heat absorption and reflection accordance with (a) and (b): (b) maximise shade and shelter (a) (c) a total area as determined by the following table: maximise stormwater infiltration and biodiversity (d) enhance the appearance of land and streetscapes. Dwelling site area (or in the case of residential Minimum percentage flat building or group dwelling(s), average site area) (m2) of site <150 10% <200 15% 200-450 20% >450 25% (b) at least 30% of land between the road boundary and the building line. Water Sensitive Design PO 13.1 DTS/DPF 13.1 Residential development is designed to capture and use None are applicable. stormwater to: (a) maximise efficient use of water resources (b) manage peak stormwater runoff flows and volume to ensure the carrying capacities of downstream systems are not overloaded (c) manage runoff quality to maintain, as close as practical, pre-development conditions. Car Parking

Page 94 of 141 Printed on 19/09/2022

Policy24 - Enquiry			
PO 14.1	DTS/DPF 14.1		
On-site car parking is provided to meet the anticipated demand of residents, with less on-site parking in areas in close proximity to public transport.	On-site car parking is provided at the following rates per dwelling: (a) 2 or fewer bedrooms - 1 car parking space		
	(b) 3 or more bedrooms - 2 car parking spaces.		
PO 14.2	DTS/DPF 14.2		
Enclosed car parking spaces are of dimensions to be functional, accessible and convenient.	Residential parking spaces enclosed by fencing, walls or other obstructions with the following internal dimensions (separate from any waste storage area):		
	(a) single parking spaces:		
	(i) a minimum length of 5.4m (ii) a minimum width of 3.0m		
	(iii) a minimum width of 3.0m		
	a minimum garage door width or 2.4m		
	(b) double parking spaces (side by side):		
	(i) a minimum length of 5.4m		
	(ii) a minimum width of 5.5m (iii) minimum garage door width of 2.4m per space.		
	(iii) minimum garage door width of 2.4m per space.		
PO 14.3	DTS/DPF 14.3		
Uncovered car parking spaces are of dimensions to be functional, accessible and convenient.	Uncovered car parking spaces have:		
	(a) a minimum length of 5.4m		
	(b) a minimum width of 2.4m		
	(c) a minimum width between the centre line of the space and any fence, wall or other obstruction of 1.5m.		
PO 14.4	DTS/DPF 14.4		
Residential flat buildings and group dwelling developments provide sufficient on-site visitor car parking to cater for anticipated demand.	Visitor car parking for group and residential flat buildings incorporating 4 or more dwellings is provided on-site at a minimum ratio of 0.25 car parking spaces per dwelling.		
PO 14.5	DTS/DPF 14.5		
Residential flat buildings provide dedicated areas for bicycle parking.	Residential flat buildings provide one bicycle parking space per dwelling.		
Oversh	adowing		
PO 15.1	DTS/DPF 15.1		
Development minimises overshadowing of the private open spaces of adjoining land by ensuring that ground level open space associated with residential buildings receive direct sunlight for a minimum of 2 hours between 9am and 3pm on 21 June.	None are applicable.		
W	aste		
PO 16.1	DTS/DPF 16.1		
Provision is made for the convenient storage of waste bins in a location screened from public view.	A waste bin storage area is provided behind the primary building line that:		
	(a) has a minimum area of 2m ² with a minimum dimension		

Page 95 of 141 Printed on 19/09/2022

of 900mm (separate from any designated car parking spaces or private open space).; and (b) has a continuous unobstructed path of travel (excluding moveable objects like gates, vehicles and roller doors) with a minimum width of 800mm between the waste bin storage area and the street. PO 16.2 DTS/DPF 16.2 Residential flat buildings provide a dedicated area for the on-site None are applicable. storage of waste which is: (a) easily and safely accessible for residents and for collection vehicles (b) screened from adjoining land and public roads (c) of sufficient dimensions to be able to accommodate the waste storage needs of the development considering the intensity and nature of the development and the frequency of collection. Vehicle Access DTS/DPF 17.1 PO 17.1 Driveways are located and designed to facilitate safe access and None are applicable. egress while maximising land available for street tree planting, landscaped street frontages and on-street parking. PO 17.2 **DTS/DPF 17.2** Vehicle access is safe, convenient, minimises interruption to the Vehicle access to designated car parking spaces satisfy (a) or operation of public roads and does not interfere with street infrastructure or street trees. (a) is provided via a lawfully existing or authorised access point or an access point for which consent has been granted as part of an application for the division of land (b) where newly proposed, is set back: 0.5m or more from any street furniture, street pole, infrastructure services pit, or other stormwater or utility infrastructure unless consent is provided from the asset owner 2m or more from the base of the trunk of a street tree unless consent is provided from the tree owner for a lesser distance (iii) 6m or more from the tangent point of an intersection of 2 or more roads (iv) outside of the marked lines or infrastructure dedicating a pedestrian crossing. PO 17.3 **DTS/DPF 17.3** Driveways are designed to enable safe and convenient vehicle Driveways are designed and sited so that: movements from the public road to on-site parking spaces. the gradient from the place of access on the boundary of the allotment to the finished floor level at the front of the garage or carport is not more than 1-in-4 on average (b) they are aligned relative to the street so that there is no more than a 20 degree deviation from 90 degrees between the centreline of any dedicated car parking space to which it provides access (measured from the front of that space) and the road boundary. (c) if located so as to provide access from an alley, lane or

Page 96 of 141 Printed on 19/09/2022

	right of way - the alley, lane or right or way is at least 6.2m wide along the boundary of the allotment / site.
PO 17.4	DTS/DPF 17.4
Driveways and access points are designed and distributed to optimise the provision of on-street parking.	Where on-street parking is available abutting the site's street frontage, on-street parking is retained in accordance with the following requirements:
	 minimum 0.33 on-street spaces per dwelling on the site (rounded up to the nearest whole number) Minimum car park length of 5.4m where a vehicle can enter or exit a space directly minimum car park length of 6m for an intermediate space located between two other parking spaces.
PO 17.5	DTS/DPF 17.5
Residential driveways that service more than one dwelling of a dimension to allow safe and convenient movement.	Where on-street parking is available abutting the site's street frontage, on-street parking is retained in accordance with the following requirements:
	(a) minimum 0.33 on-street spaces per dwelling on the site (rounded up to the nearest whole number)
	(b) minimum car park length of 5.4m where a vehicle can enter or exit a space directly
	(c) minimum carpark length of 6m for an intermediate space located between two other parking spaces or to an end obstruction where the parking is indented.
PO 17.6	DTS/DPF 17.6
Residential driveways that service more than one dwelling are designed to allow passenger vehicles to enter and exit the site and manoeuvre within the site in a safe and convenient manner.	Driveways providing access to more than one dwelling, or a dwelling on a battle-axe site, allow a B85 passenger vehicle to enter and exit the garages or parking spaces in no more than a three-point turn manoeuvre
PO 17.7	DTS/DPF 17.7
Dwellings are adequately separated from common driveways and manoeuvring areas.	Dwelling walls with entry doors or ground level habitable room windows are set back at least 1.5m from any driveway or area designated for the movement and manoeuvring of vehicles.
Sto	prage
PO 18.1	DTS/DPF 18.1
Dwellings are provided with sufficient and accessible space for storage to meet likely occupant needs.	Dwellings are provided with storage at the following rates and 50% or more of the storage volume is provided within the dwelling:
	^(a) studio: not less than 6m ³
	(b) 1 bedroom dwelling / apartment: not less than 8m ³
	(c) 2 bedroom dwelling / apartment: not less than 10m ³ (d) 3+ bedroom dwelling / apartment: not less than 12m ³ .
Eartl	nworks
PO 19.1	DTS/DPF 19.1
Development, including any associated driveways and access	The development does not involve:
tracks, minimises the need for earthworks to limit disturbance to natural topography.	(a) excavation exceeding a vertical height of 1m or

Page 97 of 141 Printed on 19/09/2022

- (b) filling exceeding a vertical height of 1m or
 - (c) a total combined excavation and filling vertical height exceeding 2m.

Service connections and infrastructure

PO 20.1

Dwellings are provided with appropriate service connections and infrastructure.

DTS/DPF 20.1

The site and building:

- (a) have the ability to be connected to a permanent potable water supply
- (b) have the ability to be connected to a sewerage system, or a wastewater system approved under the South Australian Public Health Act 2011
- (c) have the ability to be connected to electricity supply
- (d) have the ability to be connected to an adequate water supply (and pressure) for fire-fighting purposes
- (e) would not be contrary to the Regulations prescribed for the purposes of Section 86 of the *Electricity Act* 1996.

Site contamination

PO 21.1

Land that is suitable for sensitive land uses to provide a safe environment.

DTS/DPF 21.1

Development satisfies (a), (b), (c) or (d):

- (a) does not involve a change in the use of land
- (b) involves a change in the use of land that does not constitute a change to a more sensitive use
- (c) involves a change in the use of land to a more sensitive use on land at which site contamination does not exist (as demonstrated in a site contamination declaration form)
- (d) involves a change in the use of land to a <u>more sensitive</u> <u>use</u> on land at which <u>site contamination</u> exists, or may exist (as demonstrated in a site contamination declaration form), and satisfies both of the following:
 - (i) <u>a site contamination audit report</u> has been prepared under Part 10A of the *Environment Protection Act 1993* in relation to the land within the previous 5 years which states that
 - A. <u>site contamination</u> does not exist (or no longer exists) at the land
 - B. the land is suitable for the proposed use or range of uses (without the need for any further <u>remediation</u>)
 - C. where <u>remediation</u> is, or remains, necessary for the proposed use (or range of uses), <u>remediation work</u> has been carried out or will be carried out (and the applicant has provided a written undertaking that the remediation works will be implemented in association with the development)

and

(ii) no other <u>class 1 activity</u> or <u>class 2 activity</u> has taken place at the land since the preparation of the site contamination audit report (as

Page 98 of 141 Printed on 19/09/2022

demonstrated in a site contamination
declaration form).

Infrastructure and Renewable Energy Facilities

Assessment Provisions (AP)

Desired Outcome			
DO 1	Efficient provision of infrastructure networks and services, renewable energy facilities and ancillary development in a manner that minimises hazard, is environmentally and culturally sensitive and manages adverse visual impacts on natural and rural landscapes and residential amenity.		

Performance Outcomes (PO) and Deemed-to-Satisfy (DTS) Criteria / Designated Performance Feature (DPF)

	Performance Outcome	Deemed-to-Satisfy Criteria / Designated Performance Feature
		General
PO 1.1		DTS/DPF 1.1
Development is located and designed to minimise hazard or nuisance to adjacent development and land uses.		None are applicable.
		Visual Amenity
PO 2.1		DTS/DPF 2.1
network transm (exclude ancilla	sual impact of above-ground infrastructure rks and services (excluding high voltage nission lines), renewable energy facilities ding wind farms), energy storage facilities and ry development is minimised from townships, routes and public roads by:	None are applicable.
(a)	utilising features of the natural landscape to obscure views where practicable	
(b)	siting development below ridgelines where practicable	
(c)	avoiding visually sensitive and significant landscapes	
(d)	using materials and finishes with low- reflectivity and colours that complement the surroundings	
(e)	using existing vegetation to screen buildings	
(f)	incorporating landscaping or landscaped mounding around the perimeter of a site and between adjacent allotments accommodating or zoned to primarily accommodate sensitive receivers.	

Page 99 of 141 Printed on 19/09/2022

	1
PO 2.2	DTS/DPF 2.2
Pumping stations, battery storage facilities, maintenance sheds and other ancillary structures incorporate vegetation buffers to reduce adverse visual impacts on adjacent land.	None are applicable.
PO 2.3	DTS/DPF 2.3
Surfaces exposed by earthworks associated with the installation of storage facilities, pipework, penstock, substations and other ancillary plant are reinstated and revegetated to reduce adverse visual impacts on adjacent land.	None are applicable.
	Rehabilitation
P0 3.1	DTS/DPF 3.1
Progressive rehabilitation (incorporating revegetation) of disturbed areas, ahead of or upon decommissioning of areas used for renewable energy facilities and transmission corridors.	None are applicable.
	Hazard Management
PO 4.1	DTS/DPF 4.1
Infrastructure and renewable energy facilities and ancillary development located and operated to not adversely impact maritime or air transport safety, including the operation of ports, airfields and landing strips.	None are applicable.
PO 4.2	DTS/DPF 4.2
Facilities for energy generation, power storage and transmission are separated as far as practicable from dwellings, tourist accommodation and frequently visited public places (such as viewing platforms / lookouts) to reduce risks to public safety from fire or equipment malfunction.	None are applicable.
PO 4.3	DTS/DPF 4.3
Bushfire hazard risk is minimised for renewable energy facilities by providing appropriate access tracks, safety equipment and water tanks and establishing cleared areas around substations, battery storage and operations compounds.	None are applicable.
Electricity Infra	structure and Battery Storage Facilities
PO 5.1	DTS/DPF 5.1
Electricity infrastructure is located to minimise visual impacts through techniques including:	None are applicable.
(a) siting utilities and services: (i) on areas already cleared of native vegetation (ii) where there is minimal interference or	

Page 100 of 141 Printed on 19/09/2022

Policy24	- Enquiry	
	disturbance to existing native vegetation or biodiversity	
(b)	grouping utility buildings and structures with non-residential development, where practicable.	
PO 5.2		DTS/DPF 5.2
new de installe	rity supply (excluding transmission lines) serving velopment in urban areas and townships d underground, excluding lines having a capacity ing or equal to 33kV.	None are applicable.
PO 5.3		DTS/DPF 5.3
infrastr	storage facilities are co-located with substation ucture where practicable to minimise the oment footprint and reduce environmental s.	None are applicable.
	Te	lecommunication Facilities
PO 6.1		DTS/DPF 6.1
form of manage facility	oliferation of telecommunications facilities in the fowers/monopoles in any one locality is ed, where technically feasible, by co-locating a with other communications facilities to mitigate is from clutter on visual amenity.	None are applicable.
PO 6.2		DTS/DPF 6.2
practic	mmunications antennae are located as close as able to support structures to manage overall d mitigate impacts on visual amenity.	None are applicable.
PO 6.3		DTS/DPF 6.3
towers	mmunications facilities, particularly /monopoles, are located and sized to mitigate mpacts by the following methods:	None are applicable.
(a)	where technically feasible, incorporating the facility within an existing structure that may serve another purpose	
	or all of the following:	
(b)	using existing buildings and landscape features to obscure or interrupt views of a facility from nearby public roads, residential areas and places of high public amenity to the extent practical without unduly hindering the effective provision of telecommunications services	
(c)	using materials and finishes that complement the environment	
(d)	screening using landscaping and vegetation, particularly for equipment shelters and huts.	
	Re	enewable Energy Facilities

Page 101 of 141 Printed on 19/09/2022

PO 7.1 DTS/DPF 7.1 Renewable energy facilities are located as close as None are applicable. practicable to existing transmission infrastructure to facilitate connections and minimise environmental impacts as a result of extending transmission infrastructure. Renewable Energy Facilities (Wind Farm) PO 8.1 DTS/DPF 8.1 Visual impact of wind turbine generators on the amenity Wind turbine generators are: of residential and tourist development is reduced (a) set back at least 2000m from the base of a turbine to any of the through appropriate separation. following zones: (i) Rural Settlement Zone (ii) Township Zone (iii) Rural Living Zone (iv) Rural Neighbourhood Zone with an additional 10m setback per additional metre over 150m overall turbine height (measured from the base of the turbine). (b) set back at least 1500m from the base of the turbine to nonassociated (non-stakeholder) dwellings and tourist accommodation PO 8.2 DTS/DPF 8.2 The visual impact of wind turbine generators on natural None are applicable. landscapes is managed by: (a) designing wind turbine generators to be uniform in colour, size and shape (b) coordinating blade rotation and direction (c) mounting wind turbine generators on tubular towers as opposed to lattice towers. PO 8.3 DTS/DPF 8.3 Wind turbine generators and ancillary development None are applicable. minimise potential for bird and bat strike. PO 8.4 DTS/DPF 8.4 Wind turbine generators incorporate recognition No Commonwealth air safety (CASA / ASA) or Defence requirement is systems or physical markers to minimise the risk to applicable. aircraft operations. PO 8.5 DTS/DPF 8.5 Meteorological masts and guidewires are identifiable to None are applicable. aircraft through the use of colour bands, marker balls, high visibility sleeves or flashing strobes. Renewable Energy Facilities (Solar Power) PO 9.1 DTS/DPF 9.1 Ground mounted solar power facilities generating 5MW None are applicable. or more are not located on land requiring the clearance of areas of intact native vegetation or on land of high environmental, scenic or cultural value.

Page 102 of 141 Printed on 19/09/2022

PO 9.2

Ground mounted solar power facilities allow for movement of wildlife by:

- (a) incorporating wildlife corridors and habitat refuges
- (b) avoiding the use of extensive security or perimeter fencing or incorporating fencing that enables the passage of small animals without unreasonably compromising the security of the facility.

DTS/DPF 9.2

None are applicable.

PO 9.3

Amenity impacts of solar power facilities are minimised through separation from conservation areas and sensitive receivers in other ownership.

DTS/DPF 9.3

Ground mounted solar power facilities are set back from land boundaries, conservation areas and relevant zones in accordance with the following criteria:

Generation Capacity	Approximate size of array	Setback from adjoining land boundary	Setback from conservation areas	Setback from Township, Rural Settlement, Rural Neighbourhood and Rural Living Zones ¹
50MW>	80ha+	30m	500m	2km
10MW<50MW	16ha-<80ha	25m	500m	1.5km
5MW<10MW	8ha to <16ha	20m	500m	1km
1MW<5MW	1.6ha to <8ha	15m	500m	500m
100kW<1MW	0.5ha<1.6ha	10m	500m	100m
<100kW	<0.5ha	5m	500m	25m

Notes:

1. Does not apply when the site of the proposed ground mounted solar power facility is located within one of these zones.

PO 9.4

Ground mounted solar power facilities incorporate landscaping within setbacks from adjacent road frontages and boundaries of adjacent allotments accommodating non-host dwellings, where balanced with infrastructure access and bushfire safety considerations.

DTS/DPF 9.4

None are applicable.

Page 103 of 141 Printed on 19/09/2022

Policy24 - Enquiry		
Hydropowe	er / Pumped Hydropower Facilities	
PO 10.1	DTS/DPF 10.1	
Hydropower / pumped hydropower facility storage is designed and operated to minimise the risk of storage dam failure.	None are applicable.	
PO 10.2	DTS/DPF 10.2	
Hydropower / pumped hydropower facility storage is designed and operated to minimise water loss through increased evaporation or system leakage, with the incorporation of appropriate liners, dam covers, operational measures or detection systems.	None are applicable.	
PO 10.3	DTS/DPF 10.3	
Hydropower / pumped hydropower facilities on existing or former mine sites minimise environmental impacts from site contamination, including from mine operations or water sources subject to such processes, now or in the future.	None are applicable.	
	Water Supply	
P0 11.1	DTS/DPF 11.1	
Development is connected to an appropriate water supply to meet the ongoing requirements of the intended use.	Development is connected, or will be connected, to a reticulated water scheme or mains water supply with the capacity to meet the on-going requirements of the development.	
P0 11.2	DTS/DPF 11.2	
Dwellings are connected to a reticulated water scheme or mains water supply with the capacity to meet the requirements of the intended use. Where this is not available an appropriate rainwater tank or storage system for domestic use is provided.	A dwelling is connected, or will be connected, to a reticulated water scheme or mains water supply with the capacity to meet the requirement of the development. Where this is not available it is serviced by a rainward tank or tanks capable of holding at least 50,000 litres of water which is: (a) exclusively for domestic use (b) connected to the roof drainage system of the dwelling.	
	Wastewater Services	
PO 12.1	DTS/DPF 12.1	
Development is connected to an approved common wastewater disposal service with the capacity to meet the requirements of the intended use. Where this is not available an appropriate on-site service is provided to meet the ongoing requirements of the intended use in accordance with the following:	Development is connected, or will be connected, to an approved common wastewater disposal service with the capacity to meet the requirements of the development. Where this is not available it is instead capable of being serviced by an on-site waste water treatment system in accordance with the following: (a) the system is wholly located and contained within the allotment	
(a) it is wholly located and contained within the allotment of the development it will service (b) in areas where there is a high risk of contamination of surface, ground, or marine water resources from on-site disposal of liquid wastes, disposal systems are included to minimise the risk of pollution to those water resources (c) septic tank effluent drainage fields and other wastewater disposal areas are located away.	 (a) the system is wholly located and contained within the allotment of development it will service; and (b) the system will comply with the requirements of the South Australian Public Health Act 2011. 	

Page 104 of 141 Printed on 19/09/2022

1 olloy24 Eliquily	
saline or poorly drained land to minimise environmental harm.	
PO 12.2	DTS/DPF 12.2
Effluent drainage fields and other wastewater disposal areas are maintained to ensure the effective operation of waste systems and minimise risks to human health and the environment.	Development is not built on, or encroaches within, an area that is, or will be, required for a sewerage system or waste control system.
	Temporary Facilities
PO 13.1	DTS/DPF 13.1
In rural and remote locations, development that is likely to generate significant waste material during construction, including packaging waste, makes provision for a temporary on-site waste storage enclosure to minimise the incidence of wind-blown litter.	A waste collection and disposal service is used to dispose of the volume of waste at the rate it is generated.
PO 13.2	DTS/DPF 13.2
Temporary facilities to support the establishment of renewable energy facilities (including borrow pits, concrete batching plants, laydown, storage, access roads and worker amenity areas) are sited and operated to minimise environmental impact.	None are applicable.

Intensive Animal Husbandry and Dairies

Assessment Provisions (AP)

Desired Outcome	
	Development of intensive animal husbandry and dairies in locations that are protected from encroachment by sensitive receivers and in a manner that minimises their adverse effects on amenity and the environment.

Performance Outcomes (PO) and Deemed-to-Satisfy (DTS) Criteria / Designated Performance Feature (DPF)

Performance Outcome	Deemed-to-Satisfy Criteria / Designated Performance Feature
Siting and Design	
PO 1.1	DTS/DPF 1.1
Intensive animal husbandry, dairies and associated activities are sited, designed, constructed and managed to not unreasonably impact on the environment or amenity of the locality.	None are applicable.

Page 105 of 141 Printed on 19/09/2022

Policy24 - Enquiry	
PO 1.2	DTS/DPF 1.2
Intensive animal husbandry, dairies and associated activities are sited, designed, constructed and managed to prevent the potential transmission of disease to other operations where animals are kept.	None are applicable.
PO 1.3	DTS/DPF 1.3
Intensive animal husbandry and associated activities such as wastewater lagoons and liquid/solid waste disposal areas are sited, designed, constructed and managed to not unreasonably impact on sensitive receivers in other ownership in terms of noise and air emissions.	None are applicable.
PO 1.4	DTS/DPF 1.4
Dairies and associated activities such as wastewater lagoons and liquid/solid waste disposal areas are sited, designed, constructed and managed to not unreasonably impact on sensitive receivers in other ownership in terms of noise and air emissions.	Dairies, associated wastewater lagoon(s) and liquid/solid waste storage and disposal facilities are located 500m or more from the nearest sensitive receiver in other ownership.
PO 1.5	DTS/DPF 1.5
Lagoons for the storage or treatment of milking shed effluent is adequately separated from roads to minimise impacts from odour on the general public.	Lagoons for the storage or treatment of milking shed effluent are set back 20m or more from public roads.
W	/aste
P0 2.1	DTS/DPF 2.1
Storage of manure, used litter and other wastes (other than waste water lagoons) is sited, designed, constructed and managed to: (a) avoid attracting and harbouring vermin (b) avoid polluting water resources (c) be located outside 1% AEP flood event areas.	None are applicable.
Soil and Wa	ater Protection
PO 3.1	DTS/DPF 3.1
To avoid environmental harm and adverse effects on water resources, intensive animal husbandry operations are appropriately set back from: (a) public water supply reservoirs (b) major watercourses (third order or higher stream) (c) any other watercourse, bore or well used for domestic or stock water supplies.	Intensive animal husbandry operations are set back: (a) 800m or more from a public water supply reservoir (b) 200m or more from a major watercourse (third order or higher stream) (c) 100m or more from any other watercourse, bore or well
P0 3.2	DTS/DPF 3.2
Intensive animal husbandry operations and dairies incorporate appropriately designed effluent and run-off facilities that:	None are applicable.
 (a) have sufficient capacity to hold effluent and runoff from the operations on site (b) ensure effluent does not infiltrate and pollute groundwater, soil or other water resources. 	

Page 106 of 141 Printed on 19/09/2022

Interface between Land Uses

Assessment Provisions (AP)

Desired Outcome		
DO 1	Development is located and designed to mitigate adverse effects on or from neighbouring and proximate land uses.	

Performance Outcomes (PO) and Deemed-to-Satisfy (DTS) Criteria / Designated Performance Feature (DPF)

Performance Outcome	Deemed-to-Satisfy Criteria / Designated Performance Feature
General Land Use Compatibility	
PO 1.1	DTS/DPF 1.1
Sensitive receivers are designed and sited to protect residents and occupants from adverse impacts generated by lawfully existing land uses (or lawfully approved land uses) and land uses desired in the zone.	None are applicable.
PO 1.2	DTS/DPF 1.2
Development adjacent to a site containing a sensitive receiver (or lawfully approved sensitive receiver) or zone primarily intended to accommodate sensitive receivers is designed to minimise adverse impacts.	None are applicable.
Hours of Operation	
D0.0.1	DTO/DDF 0.1

PO 2.1

Non-residential development does not unreasonably impact the amenity of sensitive receivers (or lawfully approved sensitive receivers) or an adjacent zone primarily for sensitive receivers through its hours of operation having regard to:

- (a) the nature of the development
- (b) measures to mitigate off-site impacts
- (c) the extent to which the development is desired in the zone
- (d) measures that might be taken in an adjacent zone primarily for sensitive receivers that mitigate adverse impacts without unreasonably compromising the intended use of that land.

DTS/DPF 2.1

Development operating within the following hours:

Class of Development	Hours of operation
Consulting room	7am to 9pm, Monday to Friday
	8am to 5pm, Saturday
Office	7am to 9pm, Monday to Friday
	8am to 5pm, Saturday
Shop, other than any	7am to 9pm, Monday to Friday
one or combination of the following:	8am to 5pm, Saturday and Sunday

Page 107 of 141 Printed on 19/09/2022

,=-:	
	(a) restaurant (b) cellar door in the Productive Rural Landscape Zone, Rural Zone or Rural Horticulture Zone
Oversh	adowing
PO 3.1	DTS/DPF 3.1
Overshadowing of habitable room windows of adjacent residential land uses in:	North-facing windows of habitable rooms of adjacent residential land uses in a neighbourhood-type zone receive at least 3 hours of direct sunlight between 9.00am and 3.00pm on 21 June.
 a. a neighbourhood-type zone is minimised to maintain access to direct winter sunlight b. other zones is managed to enable access to direct winter sunlight. 	
PO 3.2	DTS/DPF 3.2
Overshadowing of the primary area of private open space or communal open space of adjacent residential land uses in: a. a neighbourhood type zone is minimised to maintain access to direct winter sunlight b. other zones is managed to enable access to direct winter sunlight.	Development maintains 2 hours of direct sunlight between 9.00 am and 3.00 pm on 21 June to adjacent residential land uses in a neighbourhood-type zone in accordance with the following: a. for ground level private open space, the smaller of the following: i. half the existing ground level open space or ii. 35m2 of the existing ground level open space (with at least one of the area's dimensions measuring 2.5m) b. for ground level communal open space, at least half of the existing ground level open space.
PO 3.3 Development does not unduly reduce the generating capacity of adjacent rooftop solar energy facilities taking into account: (a) the form of development contemplated in the zone (b) the orientation of the solar energy facilities (c) the extent to which the solar energy facilities are already overshadowed.	DTS/DPF 3.3 None are applicable.
P0 3.4	DTS/DPF 3.4
Development that incorporates moving parts, including windmills and wind farms, are located and operated to not cause unreasonable nuisance to nearby dwellings and tourist accommodation caused by shadow flicker.	None are applicable.
Activities Generatin	g Noise or Vibration
PO 4.1	DTS/DPF 4.1
Development that emits noise (other than music) does not unreasonably impact the amenity of sensitive receivers (or	Noise that affects sensitive receivers achieves the relevant Environment Protection (Noise) Policy criteria.

Page 108 of 141 Printed on 19/09/2022

Policy24 - Enquiry	
lawfully approved sensitive receivers).	
PO 4.2	DTS/DPF 4.2
Areas for the on-site manoeuvring of service and delivery vehicles, plant and equipment, outdoor work spaces (and the like) are designed and sited to not unreasonably impact the amenity of adjacent sensitive receivers (or lawfully approved sensitive receivers) and zones primarily intended to accommodate sensitive receivers due to noise and vibration by adopting techniques including:	None are applicable.
(a) locating openings of buildings and associated services away from the interface with the adjacent sensitive receivers and zones primarily intended to accommodat sensitive receivers	e
(b) when sited outdoors, locating such areas as far as practicable from adjacent sensitive receivers and zones primarily intended to accommodate sensitive receivers	
(c) housing plant and equipment within an enclosed structure or acoustic enclosure	
(d) providing a suitable acoustic barrier between the plant and / or equipment and the adjacent sensitive receiver boundary or zone.	
P0 4.3	DTS/DPF 4.3
Fixed plant and equipment in the form of pumps and/or filtration systems for a swimming pool or spa are positioned and/or housed to not cause unreasonable noise nuisance to adjacent sensitive receivers (or lawfully approved sensitive receivers).	The pump and/or filtration system ancillary to a dwelling erected on the same site is: (a) enclosed in a solid acoustic structure located at least 5m from the nearest habitable room located on an adjoining allotment or (b) located at least 12m from the nearest habitable room located on an adjoining allotment.
PO 4.4	DTS/DPF 4.4
External noise into bedrooms is minimised by separating or shielding these rooms from service equipment areas and fixed noise sources located on the same or an adjoining allotment.	Adjacent land is used for residential purposes.
PO 4.5	DTS/DPF 4.5
Outdoor areas associated with licensed premises (such as beer gardens or dining areas) are designed and/or sited to not cause unreasonable noise impact on existing adjacent sensitive receivers (or lawfully approved sensitive receivers).	None are applicable.
PO 4.6	DTS/DPF 4.6
Development incorporating music achieves suitable acoustic amenity when measured at the boundary of an adjacent sensitive receiver (or lawfully approved sensitive receiver) or zone	Development incorporating music includes noise attenuation measures that will achieve the following noise levels:
primarily intended to accommodate sensitive receivers.	Assessment location Music noise level
	Externally at the nearest existing or envisaged noise sensitive location Less than 8dB above the level of background noise (L _{90,15min}) in any octave band of the sound spectrum (LOCT10,15 <

Page 109 of 141 Printed on 19/09/2022

Policy24 - Enquiry	11 1
	LOCT90,15 + 8dB)
Air C	Quality
P0 5.1	DTS/DPF 5.1
Development with the potential to emit harmful or nuisance- generating air pollution incorporates air pollution control measures to prevent harm to human health or unreasonably impact the amenity of sensitive receivers (or lawfully approved sensitive receivers) within the locality and zones primarily intended to accommodate sensitive receivers.	None are applicable.
PO 5.2	DTS/DPF 5.2
Development that includes chimneys or exhaust flues (including cafes, restaurants and fast food outlets) is designed to minimise nuisance or adverse health impacts to sensitive receivers (or lawfully approved sensitive receivers) by: (a) incorporating appropriate treatment technology before	None are applicable.
exhaust emissions are released (b) locating and designing chimneys or exhaust flues to maximise the dispersion of exhaust emissions, taking into account the location of sensitive receivers.	
Ligh	t Spill
PO 6.1	DTS/DPF 6.1
External lighting is positioned and designed to not cause unreasonable light spill impact on adjacent sensitive receivers (or lawfully approved sensitive receivers).	None are applicable.
PO 6.2	DTS/DPF 6.2
External lighting is not hazardous to motorists and cyclists.	None are applicable.
Solar Reflec	ctivity / Glare
P0 7.1	DTS/DPF 7.1
Development is designed and comprised of materials and finishes that do not unreasonably cause a distraction to adjacent road users and pedestrian areas or unreasonably cause heat loading and micro-climatic impacts on adjacent buildings and land uses as a result of reflective solar glare.	None are applicable.
Electrical	nterference
PO 8.1	DTS/DPF 8.1
Development in rural and remote areas does not unreasonably diminish or result in the loss of existing communication services due to electrical interference.	The building or structure: (a) is no greater than 10m in height, measured from existing ground level or (b) is not within a line of sight between a fixed transmitter and fixed receiver (antenna) other than where an alternative service is available via a different fixed transmitter or cable.
Interface with	Rural Activities
PO 9.1	DTS/DPF 9.1

Page 110 of 141 Printed on 19/09/2022

Sensitive receivers are located and designed to mitigate impacts from lawfully existing horticultural and farming activities (or lawfully approved horticultural and farming activities), including spray drift and noise and do not prejudice the continued operation of these activities.	None are applicable.
PO 9.2	DTS/DPF 9.2
Sensitive receivers are located and designed to mitigate potential impacts from lawfully existing intensive animal husbandry activities and do not prejudice the continued operation of these activities.	None are applicable.
PO 9.3	DTS/DPF 9.3
Sensitive receivers are located and designed to mitigate potential impacts from lawfully existing land-based aquaculture activities and do not prejudice the continued operation of these activities.	Sensitive receivers are located at least 200m from the boundary of a site used for land-based aquaculture and associated components in other ownership.
PO 9.4	DTS/DPF 9.4
Sensitive receivers are located and designed to mitigate potential impacts from lawfully existing dairies including associated wastewater lagoons and liquid/solid waste storage and disposal facilities and do not prejudice the continued operation of these activities.	Sensitive receivers are sited at least 500m from the boundary of a site used for a dairy and associated wastewater lagoon(s) and liquid/solid waste storage and disposal facilities in other ownership.
PO 9.5	DTS/DPF 9.5
Sensitive receivers are located and designed to mitigate the potential impacts from lawfully existing facilities used for the handling, transportation and storage of bulk commodities (recognising the potential for extended hours of operation) and do not prejudice the continued operation of these activities.	Sensitive receivers are located away from the boundary of a site used for the handling, transportation and/or storage of bulk commodities in other ownership in accordance with the following: (a) 300m or more, where it involves the handling of agricultural crop products, rock, ores, minerals, petroleum products or chemicals to or from any commercial storage facility (b) 300m or more, where it involves the handling of agricultural crop products, rock, ores, minerals, petroleum products or chemicals at a wharf or wharf side facility (including sea-port grain terminals) where the handling of these materials into or from vessels does not exceed 100 tonnes per day (c) 500m or more, where it involves the storage of bulk petroleum in individual containers with a capacity up to 200 litres and a total on-site storage capacity not exceeding 1000 cubic metres (d) 500m or more, where it involves the handling of coal with a capacity up to 1 tonne per day or a storage capacity up to 50 tonnes (e) 1000m or more, where it involves the handling of coal with a capacity exceeding 1 tonne per day but not exceeding 100 tonnes per day or a storage capacity exceeding 50 tonnes but not exceeding 5000 tonnes.
PO 9.6	DTS/DPF 9.6
Setbacks and vegetation plantings along allotment boundaries should be incorporated to mitigate the potential impacts of	None are applicable.

Page 111 of 141 Printed on 19/09/2022

spray drift and other impacts associated with agricultural and horticultural activities.		
P0 9.7	DTS/DPF 9.7	
Urban development does not prejudice existing agricultural and horticultural activities through appropriate separation and design techniques.	None are applicable.	
Interface with Mines and Quarries (Rural and Remote Areas)		
PO 10.1	DTS/DPF 10.1	
Sensitive receivers are separated from existing mines to minimise the adverse impacts from noise, dust and vibration.	Sensitive receivers are located no closer than 500m from the boundary of a Mining Production Tenement under the <i>Mining Act</i> 1971.	

Land Division

Assessment Provisions (AP)

	Desired Outcome
DO 1	Land division:
	 (a) creates allotments with the appropriate dimensions and shape for their intended use (b) allows efficient provision of new infrastructure and the optimum use of underutilised infrastructure (c) integrates and allocates adequate and suitable land for the preservation of site features of value, including significant vegetation, watercourses, water bodies and other environmental features (d) facilitates solar access through allotment orientation (e) creates a compact urban form that supports active travel, walkability and the use of public transport (f) avoids areas of high natural hazard risk.

Performance Outcome	Deemed-to-Satisfy Criteria / Designated Performance Feature
All land	division
Allotment o	onfiguration
P0 1.1	DTS/DPF 1.1
Land division creates allotments suitable for their intended use.	Division of land satisfies (a) or (b): (a) reflects the site boundaries illustrated and approved in an operative or existing development authorisation for residential development under the Development Act 1993 or Planning, Development and Infrastructure Act 2016 where the allotments are used or are proposed to be used solely for residential purposes (b) is proposed as part of a combined land division
	application with deemed-to-satisfy dwellings on the proposed allotments.

Page 112 of 141 Printed on 19/09/2022

, ,	
PO 1.2	DTS/DPF 1.2
Land division considers the physical characteristics of the land, preservation of environmental and cultural features of value and the prevailing context of the locality.	None are applicable.
Design a	nd Layout
PO 2.1	DTS/DPF 2.1
Land division results in a pattern of development that minimises the likelihood of future earthworks and retaining walls.	None are applicable.
PO 2.2	DTS/DPF 2.2
Land division enables the appropriate management of interface impacts between potentially conflicting land uses and/or zones.	None are applicable.
PO 2.3	DTS/DPF 2.3
Land division maximises the number of allotments that face public open space and public streets.	None are applicable.
PO 2.4	DTS/DPF 2.4
Land division is integrated with site features, adjacent land uses, the existing transport network and available infrastructure.	None are applicable.
PO 2.5	DTS/DPF 2.5
Development and infrastructure is provided and staged in a manner that supports an orderly and economic provision of land, infrastructure and services.	None are applicable.
PO 2.6	DTS/DPF 2.6
Land division results in watercourses being retained within open space and development taking place on land not subject to flooding.	None are applicable.
PO 2.7	DTS/DPF 2.7
Land division results in legible street patterns connected to the surrounding street network.	None are applicable.
PO 2.8	DTS/DPF 2.8
Land division is designed to preserve existing vegetation of value including native vegetation and regulated and significant trees.	None are applicable.
Roads ar	nd Access
PO 3.1	DTS/DPF 3.1
Land division provides allotments with access to an all-weather public road.	None are applicable.
PO 3.2	DTS/DPF 3.2
Street patterns and intersections are designed to enable the safe and efficient movement of pedestrian, cycle and vehicular traffic.	None are applicable.
PO 3.3	DTS/DPF 3.3
	·

Page 113 of 141 Printed on 19/09/2022

None are applicable.
DTS/DPF 3.4
None are applicable.
DTS/DPF 3.5
None are applicable.
DTS/DPF 3.6
None are applicable.
DTS/DPF 3.7
None are applicable.
DTS/DPF 3.8
None are applicable.
DTS/DPF 3.9
None are applicable.
DTS/DPF 3.10
None are applicable.
DTS/DPF 3.11
None are applicable.
tructure
DTS/DPF 4.1
None are applicable.
DTS/DPF 4.2
Each allotment can be connected to: (a) a waste water treatment plant that has the hydraulic volume and pollutant load treatment and disposal capacity for the maximum predicted wastewater volume generated by subsequent development of the proposed allotment

Page 114 of 141 Printed on 19/09/2022

, , ,			
	that meets relevant public health and environmental standards.		
PO 4.3	DTS/DPF 4.3		
Septic tank effluent drainage fields and other waste water disposal areas are maintained to ensure the effective operation of waste systems and minimise risks to human health and the environment.	Development is not built on, or encroaches within, an area that is or will be, required for a sewerage system or waste control system.		
PO 4.4	DTS/DPF 4.4		
Constructed wetland systems, including associated detention and retention basins, are sited and designed to ensure public health and safety is protected, including by minimising potential public health risks arising from the breeding of mosquitoes.	None are applicable.		
PO 4.5	DTS/DPF 4.5		
Constructed wetland systems, including associated detention and retention basins, are sited and designed to allow sediments to settle prior to discharge into watercourses or the marine environment.	None are applicable.		
PO 4.6	DTS/DPF 4.6		
Constructed wetland systems, including associated detention and retention basins, are sited and designed to function as a landscape feature.	None are applicable.		
Minor Land Division	(Under 20 Allotments)		
Oper	Space		
PO 5.1	DTS/DPF 5.1		
Land division proposing an additional allotment under 1 hectare provides or supports the provision of open space.	None are applicable.		
Solar O	Solar Orientation		
P0 6.1	nentation		
	DTS/DPF 6.1		
Land division for residential purposes facilitates solar access through allotment orientation.			
through allotment orientation.	DTS/DPF 6.1		
through allotment orientation.	DTS/DPF 6.1 None are applicable.		
through allotment orientation. Water Sen	DTS/DPF 6.1 None are applicable. sitive Design DTS/DPF 7.1 None are applicable.		
through allotment orientation. Water Sen P0 7.1 Land division creating a new road or common driveway includes stormwater management systems that minimise the discharge of sediment, suspended solids, organic matter, nutrients, bacteria, litter and other contaminants to the stormwater system,	DTS/DPF 6.1 None are applicable. sitive Design DTS/DPF 7.1 None are applicable.		
through allotment orientation. Water Sen P0 7.1 Land division creating a new road or common driveway includes stormwater management systems that minimise the discharge of sediment, suspended solids, organic matter, nutrients, bacteria, litter and other contaminants to the stormwater system, watercourses or other water bodies.	DTS/DPF 6.1 None are applicable. sitive Design DTS/DPF 7.1 None are applicable.		

Page 115 of 141 Printed on 19/09/2022

Policy24 - Enquiry	
P0 8.1	DTS/DPF 8.1
Battle-axe development appropriately responds to the existing neighbourhood context.	Allotments are not in the form of a battle-axe arrangement.
PO 8.2	DTS/DPF 8.2
Battle-axe development designed to allow safe and convenient movement.	The handle of a battle-axe development:
	(a) has a minimum width of 4m
	or (b) where more than 3 allotments are proposed, a minimum width of 5.5m.
PO 8.3	DTS/DPF 8.3
Battle-axe allotments and/or common land are of a suitable size and dimension to allow passenger vehicles to enter and exit and manoeuvre within the site in a safe and convenient manner.	Battle-axe development allows a B85 passenger vehicle to enter and exit parking spaces in no more than a three-point turn manoeuvre.
PO 8.4	DTS/DPF 8.4
Battle-axe or common driveways incorporate landscaping and permeability to improve appearance and assist in stormwater	Battle-axe or common driveways satisfy (a) and (b):
management.	(a) are constructed of a minimum of 50% permeable or porous material
	(b) where the driveway is located directly adjacent the side or rear boundary of the site, soft landscaping with a minimum dimension of 1m is provided between the driveway and site boundary (excluding along the perimeter of a passing point).
Major Land Division	Don (20+ Allotments)
Open	Space
PO 9.1	DTS/DPF 9.1
Land division allocates or retains evenly distributed, high quality areas of open space to improve residential amenity and provide urban heat amelioration.	None are applicable.
P0 9.2	DTS/DPF 9.2
Land allocated for open space is suitable for its intended active and passive recreational use considering gradient and potential for inundation.	None are applicable.
PO 9.3	DTS/DPF 9.3
Land allocated for active recreation has dimensions capable of accommodating a range of active recreational activities.	None are applicable.
Water Sen:	sitive Design
PO 10.1	DTS/DPF 10.1
Land division creating 20 or more residential allotments includes a stormwater management system designed to mitigate peak flows and manage the rate and duration of stormwater discharges from the site to ensure that the development does not increase the peak flows in downstream systems.	None are applicable.
PO 10.2	DTS/DPF 10.2
Land division creating 20 or more non-residential allotments includes a stormwater management system designed to mitigate peak flows and manage the rate and duration of	None are applicable.

Page 116 of 141 Printed on 19/09/2022

, , ,	
stormwater discharges from the site to ensure that the development does not increase the peak flows in downstream systems.	
PO 10.3	DTS/DPF 10.3
Land division creating 20 or more allotments includes stormwater management systems that minimise the discharge of sediment, suspended solids, organic matter, nutrients, bacteria, litter and other contaminants to the stormwater system, watercourses or other water bodies.	None are applicable.
Solar Orientation	
PO 11.1	DTS/DPF 11.1
Land division creating 20 or more allotments for residential purposes facilitates solar access through allotment orientation and allotment dimensions.	None are applicable.

Marinas and On-Water Structures

Assessment Provisions (AP)

	Desired Outcome
DO 1	Marinas and on-water structures are located and designed to minimise the impairment of commercial, recreational and navigational activities and adverse impacts on the environment.

Performance Outcomes (PO) and Deemed-to-Satisfy (DTS) Criteria / Designated Performance Feature (DPF)

Performance Outcome	Deemed-to-Satisfy Criteria / Designated Performance Feature
Navigation	and Safety
PO 1.1	DTS/DPF 1.1
Safe public access is provided or maintained to the waterfront, public infrastructure and recreation areas.	None are applicable.
PO 1.2	DTS/DPF 1.2
The operation of wharves is not impaired by marinas and onwater structures.	None are applicable.
PO 1.3	DTS/DPF 1.3
Navigation and access channels are not impaired by marinas and on-water structures.	None are applicable.
PO 1.4	DTS/DPF 1.4

Page 117 of 141 Printed on 19/09/2022

Commercial shipping lanes are not impaired by marinas and onwater structures.	Marinas and on-water structures are set back 250m or more from commercial shipping lanes.
PO 1.5	DTS/DPF 1.5
Marinas and on-water structures are located to avoid interfering with the operation or function of a water supply pumping station.	On-water structures are set back: (a) 3km or more from upstream water supply pumping station take-off points (b) 500m or more from downstream water supply pumping station take-off points.
PO 1.6	DTS/DPF 1.6
Maintenance of on-water infrastructure, including revetment walls, is not impaired by marinas and on-water structures.	None are applicable.
Environment	al Protection
PO 2.1	DTS/DPF 2.1
Development is sited and designed to facilitate water circulation and exchange.	None are applicable.

Open Space and Recreation

Assessment Provisions (AP)

	Desired Outcome
DO 1	Pleasant, functional and accessible open space and recreation facilities are provided at State, regional, district, neighbourhood and local levels for active and passive recreation, biodiversity, community health, urban cooling, tree canopy cover, visual amenity, gathering spaces, wildlife and waterway corridors, and a range of other functions and at a range of sizes that reflect the purpose of that open space.

Performance Outcomes (PO) and Deemed-to-Satisfy (DTS) Criteria / Designated Performance Feature (DPF)

Performance Outcome	Deemed-to-Satisfy Criteria / Designated Performance Feature
Land Use a	nd Intensity
PO 1.1	DTS/DPF 1.1
Recreation facilities are compatible with surrounding land uses and activities.	None are applicable.
PO 1.2	DTS/DPF 1.2
Open space areas include natural or landscaped areas using locally indigenous plant species and large trees.	None are applicable.

Page 118 of 141 Printed on 19/09/2022

Policy24 - Enquiry	<u> </u>
Design a	and Siting
PO 2.1	DTS/DPF 2.1
Open space and recreation facilities address adjacent public roads to optimise pedestrian access and visibility.	None are applicable.
PO 2.2	DTS/DPF 2.2
Open space and recreation facilities incorporate park furniture, shaded areas and resting places.	None are applicable.
PO 2.3	DTS/DPF 2.3
Open space and recreation facilities link habitats, wildlife corridors and existing open spaces and recreation facilities.	None are applicable.
Pedestrians	and Cyclists
PO 3.1	DTS/DPF 3.1
Open space incorporates:	None are applicable.
 (a) pedestrian and cycle linkages to other open spaces, centres, schools and public transport nodes; (b) safe crossing points where pedestrian routes intersect the road network; 	
(c) easily identified access points.	
Usa	bility
PO 4.1 Land allocated for open space is suitable for its intended active and passive recreational use taking into consideration its gradient and potential for inundation.	DTS/DPF 4.1 None are applicable.
·	d Security
PO 5.1	DTS/DPF 5.1
Open space is overlooked by housing, commercial or other development to provide casual surveillance where possible.	None are applicable.
PO 5.2	DTS/DPF 5.2
Play equipment is located to maximise opportunities for passive surveillance.	None are applicable.
PO 5.3	DTS/DPF 5.3
Landscaping provided in open space and recreation facilities maximises opportunities for casual surveillance throughout the park.	None are applicable.
PO 5.4	DTS/DPF 5.4
Fenced parks and playgrounds have more than one entrance or exit to minimise potential entrapment.	None are applicable.
P0 5.5	DTS/DPF 5.5
Adequate lighting is provided around toilets, telephones, seating, litter bins, bicycle storage, car parks and other such facilities.	None are applicable.
PO 5.6	DTS/DPF 5.6

Page 119 of 141 Printed on 19/09/2022

Folicy24 - Eriquity	
Pedestrian and bicycle movement after dark is focused along clearly defined, adequately lit routes with observable entries and exits.	None are applicable.
Sign	I nage
P0 6.1	DTS/DPF 6.1
Signage is provided at entrances to and within the open space and recreation facilities to provide clear orientation to major points of interest such as the location of public toilets, telephones, safe routes, park activities and the like.	None are applicable.
Buildings ar	nd Structures
PO 7.1	DTS/DPF 7.1
Buildings and car parking areas in open space areas are designed, located and of a scale to be unobtrusive.	None are applicable.
P0 7.2	DTS/DPF 7.2
Buildings and structures in open space areas are clustered where practical to ensure that the majority of the site remains open.	None are applicable.
PO 7.3	DTS/DPF 7.3
Development in open space is constructed to minimise the extent of impervious surfaces.	None are applicable.
PO 7.4	DTS/DPF 7.4
Development that abuts or includes a coastal reserve or Crown land used for scenic, conservation or recreational purposes is located and designed to have regard to the purpose, management and amenity of the reserve.	None are applicable.
Lands	ccaping
PO 8.1	DTS/DPF 8.1
Open space and recreation facilities provide for the planting and retention of large trees and vegetation.	None are applicable.
PO 8.2	DTS/DPF 8.2
Landscaping in open space and recreation facilities provides shade and windbreaks:	None are applicable.
(a) along cyclist and pedestrian routes; (b) around picnic and barbecue areas; (c) in car parking areas.	
PO 8.3	DTS/DPF 8.3
Landscaping in open space facilitates habitat for local fauna and facilitates biodiversity.	None are applicable.
PO 8.4	DTS/DPF 8.4
Landscaping including trees and other vegetation passively watered with local rainfall run-off, where practicable.	None are applicable.
t.	,

Page 120 of 141 Printed on 19/09/2022

Out of Activity Centre Development

Assessment Provisions (AP)

	Desired Outcome
DO1	The role of Activity Centres in contributing to the form and pattern of development and enabling equitable and convenient access to a range of shopping, administrative, cultural, entertainment and other facilities in a single trip is maintained and reinforced.

Performance Outcome	Deemed-to-Satisfy Criteria / Designated Performance Feature
PO 1.1 Non-residential development outside Activity Centres of a scale and type that does not diminish the role of Activity Centres: (a) as primary locations for shopping, administrative, cultural, entertainment and community services (b) as a focus for regular social and business gatherings (c) in contributing to or maintaining a pattern of development that supports equitable community access to services and facilities.	DTS/DPF 1.1 None are applicable.
PO 1.2 Out-of-activity centre non-residential development complements Activity Centres through the provision of services and facilities: (a) that support the needs of local residents and workers, particularly in underserviced locations (b) at the edge of Activities Centres where they cannot readily be accommodated within an existing Activity Centre to expand the range of services on offer and support the role of the Activity Centre.	DTS/DPF 1.2 None are applicable.

Resource Extraction

Assessment Provisions (AP)

Desired Outcome	
DO 1	Resource extraction activities are developed in a manner that minimises human and environmental impacts.

Performance Outcomes (PO) and Deemed-to-Satisfy (DTS) Criteria / Designated Performance Feature (DPF)

Performance Outcome	Deemed-to-Satisfy Criteria /
	becined to eatisty criteria,

Page 121 of 141 Printed on 19/09/2022

	Designated Performance
	Feature
Land Use a	nd Intensity
PO 1.1	DTS/DPF 1.1
Resource extraction activities minimise landscape damage outside of those areas unavoidably disturbed to access and exploit a resource and provide for the progressive reclamation and betterment of disturbed areas.	None are applicable.
PO 1.2	DTS/DPF 1.2
Resource extraction activities avoid damage to cultural sites or artefacts.	None are applicable.
Water	Quality
PO 2.1	DTS/DPF 2.1
Stormwater and/or wastewater from resource extraction activities is diverted into appropriately sized treatment and retention systems to enable reuse on site.	None are applicable.
Separation Treatments,	Buffers and Landscaping
PO 3.1	DTS/DPF 3.1
Resource extraction activities minimise adverse impacts upon sensitive receivers through incorporation of separation distances and/or mounding/vegetation.	None are applicable.
PO 3.2	DTS/DPF 3.2
Resource extraction activities are screened from view from adjacent land by perimeter landscaping and/or mounding.	None are applicable.

Site Contamination

Assessment Provisions (AP)

	Desired Outcome
DO 1	Ensure land is suitable for the proposed use in circumstances where it is, or may have been, subject to site contamination.

Performance Outcome	Deemed-to-Satisfy Criteria / Designated Performance Feature
PO 1.1	DTS/DPF 1.1
Ensure land is suitable for use when land use changes to a more sensitive use.	Development satisfies (a), (b), (c) or (d): (a) does not involve a change in the use of land

Page 122 of 141 Printed on 19/09/2022

- (b) involves a change in the use of land that does not constitute a change to a more sensitive use
- (c) involves a change in the use of land to a more sensitive use on land at which site contamination is unlikely to exist (as demonstrated in a site contamination declaration form)
- (d) involves a change in the use of land to a more sensitive use on land at which site contamination exists, or may exist (as demonstrated in a site contamination declaration form), and satisfies both of the following:
 - a site contamination audit report has been prepared under Part 10A of the *Environment Protection Act 1993* in relation to the land within the previous 5 years which states that-
 - A. site contamination does not exist (or no longer exists) at the land
 - B. the land is suitable for the proposed use or range of uses (without the need for any further remediation)
 - C. where remediation is, or remains, necessary for the proposed use (or range of uses), remediation work has been carried out or will be carried out (and the applicant has provided a written undertaking that the remediation works will be implemented in association with the development)

and

(ii) no other class 1 activity or class 2 activity has taken place at the land since the preparation of the site contamination audit report (as demonstrated in a site contamination declaration form).

Tourism Development

Assessment Provisions (AP)

Desired Outcome	
DO 1	Tourism development is built in locations that cater to the needs of visitors and positively contributes to South Australia's visitor economy.

Performance Outcomes (PO) and Deemed-to-Satisfy (DTS) Criteria / Designated Performance Feature (DPF)

Performance Outcome	Deemed-to-Satisfy Criteria /
	Designated Performance

Page 123 of 141 Printed on 19/09/2022

	Feature
General	
PO 1.1	DTS/DPF 1.1
Tourism development complements and contributes to local, natural, cultural or historical context where:	None are applicable.
(a) it supports immersive natural experiences (b) it showcases South Australia's landscapes and produce (c) its events and functions are connected to local food, wine and nature.	
PO 1.2	DTS/DPF 1.2
Tourism development comprising multiple accommodation units (including any facilities and activities for use by guests and visitors) is clustered to minimise environmental and contextual impact.	None are applicable.
Caravan and	Tourist Parks
PO 2.1	DTS/DPF 2.1
Potential conflicts between long-term residents and short-term tourists are minimised through suitable siting and design measures.	None are applicable.
PO 2.2	DTS/DPF 2.2
Occupants are provided privacy and amenity through landscaping and fencing.	None are applicable.
PO 2.3	DTS/DPF 2.3
Communal open space and centrally located recreation facilities are provided for guests and visitors.	12.5% or more of a caravan park comprises clearly defined communal open space, landscaped areas and areas for recreation.
P0 2.4	DTS/DPF 2.4
Perimeter landscaping is used to enhance the amenity of the locality.	None are applicable.
PO 2.5	DTS/DPF 2.5
Amenity blocks (showers, toilets, laundry and kitchen facilities) are sufficient to serve the full occupancy of the development.	None are applicable.
PO 2.6	DTS/DPF 2.6
Long-term occupation does not displace tourist accommodation, particularly in important tourist destinations such as coastal and riverine locations.	None are applicable.
Tourist accommodation in areas constituted	I under the National Parks and Wildlife Act 1972
PO 3.1	DTS/DPF 3.1
Tourist accommodation avoids delicate or environmentally sensitive areas such as sand dunes, cliff tops, estuaries, wetlands or substantially intact strata of native vegetation (including regenerated areas of native vegetation lost through	None are applicable.

Page 124 of 141 Printed on 19/09/2022

bushfire).	
P0 3.2	DTS/DPF 3.2
Tourist accommodation is sited and designed in a manner that is subservient to the natural environment and where adverse impacts on natural features, landscapes, habitats and cultural assets are avoided.	None are applicable.
PO 3.3	DTS/DPF 3.3
Tourist accommodation and recreational facilities, including associated access ways and ancillary structures, are located on cleared (other than where cleared as a result of bushfire) or degraded areas or where environmental improvements can be achieved.	None are applicable.
PO 3.4	DTS/DPF 3.4
Tourist accommodation is designed to prevent conversion to private dwellings through:	None are applicable.
 (a) comprising a minimum of 10 accommodation units (b) clustering separated individual accommodation units (c) being of a size unsuitable for a private dwelling (d) ensuring functional areas that are generally associated with a private dwelling such as kitchens and laundries are excluded from, or physically separated from individual accommodation units, or are of a size unsuitable for a private dwelling. 	

Transport, Access and Parking

Assessment Provisions (AP)

Desired Outcome	
DO 1	A comprehensive, integrated and connected transport system that is safe, sustainable, efficient, convenient and accessible to all users.

Performance Outcomes (PO) and Deemed-to-Satisfy (DTS) Criteria / Designated Performance Feature (DPF)

Performance Outcome	Deemed-to-Satisfy Criteria / Designated Performance Feature
Movement Systems	
PO 1.1	DTS/DPF 1.1
Development is integrated with the existing transport system and designed to minimise its potential impact on the functional	None are applicable.

Page 125 of 141 Printed on 19/09/2022

Policy24 - Enquiry		
performance of the transport system.		
PO 1.2	DTS/DPF 1.2	
Development is designed to discourage commercial and industrial vehicle movements through residential streets and adjacent other sensitive receivers.	None are applicable.	
PO 1.3	DTS/DPF 1.3	
Industrial, commercial and service vehicle movements, loading areas and designated parking spaces are separated from passenger vehicle car parking areas to ensure efficient and safe movement and minimise potential conflict. None are applicable.		
PO 1.4	DTS/DPF 1.4	
Development is sited and designed so that loading, unloading and turning of all traffic avoids interrupting the operation of and queuing on public roads and pedestrian paths.	All vehicle manoeuvring occurs onsite.	
Sigh	tlines	
PO 2.1	DTS/DPF 2.1	
Sightlines at intersections, pedestrian and cycle crossings, and crossovers to allotments for motorists, cyclists and pedestrians are maintained or enhanced to ensure safety for all road users and pedestrians.	None are applicable.	
PO 2.2	DTS/DPF 2.2	
Walls, fencing and landscaping adjacent to driveways and corner sites are designed to provide adequate sightlines between vehicles and pedestrians.	None are applicable.	
Vehicle	e Access	
PO 3.1	DTS/DPF 3.1	
Safe and convenient access minimises impact or interruption on the operation of public roads.	The access is: (a) provided via a lawfully existing or authorised driveway or access point or an access point for which consent has been granted as part of an application for the division of land or (b) not located within 6m of an intersection of 2 or more roads or a pedestrian activated crossing.	
PO 3.2	DTS/DPF 3.2	
1	None are applicable.	
Development incorporating vehicular access ramps ensures vehicles can enter and exit a site safely and without creating a hazard to pedestrians and other vehicular traffic.	None are applicable.	
vehicles can enter and exit a site safely and without creating a	DTS/DPF 3.3	
vehicles can enter and exit a site safely and without creating a hazard to pedestrians and other vehicular traffic.		

Page 126 of 141 Printed on 19/09/2022

Access points are sited and designed to minimise any adverse impacts on neighbouring properties.	None are applicable.
PO 3.5 Access points are located so as not to interfere with street trees, existing street furniture (including directional signs, lighting, seating and weather shelters) or infrastructure services to maintain the appearance of the streetscape, preserve local amenity and minimise disruption to utility infrastructure assets.	DTS/DPF 3.5 Vehicle access to designated car parking spaces satisfy (a) or (b): (a) is provided via a lawfully existing or authorised access point or an access point for which consent has been granted as part of an application for the division of land (b) where newly proposed, is set back: (i) 0.5m or more from any street furniture, street pole, infrastructure services pit, or other stormwater or utility infrastructure unless consent is provided from the asset owner (ii) 2m or more from the base of the trunk of a street tree unless consent is provided from the tree owner for a lesser distance (iii) 6m or more from the tangent point of an intersection of 2 or more roads (iv) outside of the marked lines or infrastructure dedicating a pedestrian crossing.
PO 3.6 Driveways and access points are separated and minimised in number to optimise the provision of on-street visitor parking (where on-street parking is appropriate).	DTS/DPF 3.6 Driveways and access points: (a) for sites with a frontage to a public road of 20m or less, one access point no greater than 3.5m in width is provided (b) for sites with a frontage to a public road greater than 20m: (i) a single access point no greater than 6m in width is provided or (ii) not more than two access points with a width of 3.5m each are provided.
PO 3.7 Access points are appropriately separated from level crossings to avoid interference and ensure their safe ongoing operation.	DTS/DPF 3.7 Development does not involve a new or modified access or cause an increase in traffic through an existing access that is located within the following distance from a railway crossing: (a) 80 km/h road - 110m (b) 70 km/h road - 90m (c) 60 km/h road - 70m (d) 50km/h or less road - 50m.
PO 3.8 Driveways, access points, access tracks and parking areas are designed and constructed to allow adequate movement and manoeuvrability having regard to the types of vehicles that are reasonably anticipated.	DTS/DPF 3.8 None are applicable.
PO 3.9 Development is designed to ensure vehicle circulation between activity areas occurs within the site without the need to use	DTS/DPF 3.9 None are applicable.

Page 127 of 141 Printed on 19/09/2022

public roads.		
Access for Peopl	e with Disabilities	
PO 4.1	DTS/DPF 4.1	
Development is sited and designed to provide safe, dignified and convenient access for people with a disability.	None are applicable.	
Vehicle Pa	rking Rates	
PO 5.1	DTS/DPF 5.1	
Sufficient on-site vehicle parking and specifically marked accessible car parking places are provided to meet the needs of the development or land use having regard to factors that may support a reduced on-site rate such as: (a) availability of on-street car parking (b) shared use of other parking areas (c) in relation to a mixed-use development, where the hours of operation of commercial activities complement the residential use of the site, the provision of vehicle parking may be shared (d) the adaptive reuse of a State or Local Heritage Place.	Development provides a number of car parking spaces on-site at a rate no less than the amount calculated using one of the following, whichever is relevant: (a) Transport, Access and Parking Table 1 - General Off-Street Car Parking Requirements (b) Transport, Access and Parking Table 2 - Off-Street Vehicle Parking Requirements in Designated Areas (c) if located in an area where a lawfully established carparking fund operates, the number of spaces calculated under (a) or (b) less the number of spaces offset by contribution to the fund.	
Vehicle Par	rking Areas	
P0 6.1	DTS/DPF 6.1	
Vehicle parking areas are sited and designed to minimise impact on the operation of public roads by avoiding the use of public roads when moving from one part of a parking area to another.	Movement between vehicle parking areas within the site can occur without the need to use a public road.	
Po 6.2 Vehicle parking areas are appropriately located, designed and constructed to minimise impacts on adjacent sensitive receivers	DTS/DPF 6.2 None are applicable.	
through measures such as ensuring they are attractively developed and landscaped, screen fenced, and the like.		
PO 6.3	DTS/DPF 6.3	
Vehicle parking areas are designed to provide opportunity for integration and shared-use of adjacent car parking areas to reduce the total extent of vehicle parking areas and access points.	None are applicable.	
PO 6.4	DTS/DPF 6.4	
Pedestrian linkages between parking areas and the development are provided and are safe and convenient.	None are applicable.	
PO 6.5	DTS/DPF 6.5	
Vehicle parking areas that are likely to be used during non- daylight hours are provided with sufficient lighting to entry and exit points to ensure clear visibility to users.	None are applicable.	
PO 6.6	DTS/DPF 6.6	
Loading areas and designated parking spaces for service vehicles are provided within the boundary of the site.	Loading areas and designated parking spaces are wholly locate within the site.	
	 	

Page 128 of 141 Printed on 19/09/2022

Policy24 - Enquiry	
P0 6.7	DTS/DPF 6.7
On-site visitor parking spaces are sited and designed to be accessible to all visitors at all times.	None are applicable.
Undercroft and Below Ground G	Garaging and Parking of Vehicles
P0 7.1	DTS/DPF 7.1
Undercroft and below ground garaging of vehicles is designed to enable safe entry and exit from the site without compromising pedestrian or cyclist safety or causing conflict with other vehicles.	None are applicable.
Internal Roads and Parking Areas in Resid	ential Parks and Caravan and Tourist Parks
PO 8.1	DTS/DPF 8.1
Internal road and vehicle parking areas are surfaced to prevent dust becoming a nuisance to park residents and occupants.	None are applicable.
PO 8.2	DTS/DPF 8.2
Traffic circulation and movement within the park is pedestrian friendly and promotes low speed vehicle movement.	None are applicable.
Bicycle Parking in	n Designated Areas
PO 9.1	DTS/DPF 9.1
The provision of adequately sized on-site bicycle parking facilities encourages cycling as an active transport mode.	Areas and / or fixtures are provided for the parking and storage of bicycles at a rate not less than the amount calculated using Transport, Access and Parking Table 3 - Off Street Bicycle Parking Requirements.
P0 9.2	DTS/DPF 9.2
Bicycle parking facilities provide for the secure storage and tethering of bicycles in a place where casual surveillance is possible, is well lit and signed for the safety and convenience of cyclists and deters property theft.	None are applicable.
P0 9.3	DTS/DPF 9.3
Non-residential development incorporates end-of-journey facilities for employees such as showers, changing facilities and secure lockers, and signage indicating the location of the facilities to encourage cycling as a mode of journey-to-work transport.	None are applicable.
Corner Cut-Offs	
PO 10.1	DTS/DPF 10.1
Development is located and designed to ensure drivers can safely turn into and out of public road junctions.	Development does not involve building work, or building work is located wholly outside the land shown as Corner Cut-Off Area in the following diagram:

Page 129 of 141 Printed on 19/09/2022




Table 1 - General Off-Street Car Parking Requirements

The following parking rates apply and if located in an area where a lawfully established carparking fund operates, the number of spaces is reduced by an amount equal to the number of spaces offset by contribution to the fund.

Class of Development	Car Parking Rate (unless varied by Table 2 onwards)
	Where a development comprises more than one development type, then the overall car parking rate will be taken to be the sum of the car parking rates for each development type.
Residential Development	
Detached Dwelling	Dwelling with 1 bedroom (including rooms capable of being used as a bedroom) - 1 space per dwelling.
	Dwelling with 2 or more bedrooms (including rooms capable of being used as a bedroom) - 2 spaces per dwelling, 1 of which is to be covered.
Group Dwelling	Dwelling with 1 or 2 bedrooms (including rooms capable of being used as a bedroom) - 1 space per dwelling.
	Dwelling with 3 or more bedrooms (including rooms capable of being used as a bedroom) - 2 spaces per dwelling, 1 of which is to be covered.
	0.33 spaces per dwelling for visitor parking where development involves 3 or more dwellings.
Residential Flat Building	Dwelling with 1 or 2 bedrooms (including rooms capable of being used as a bedroom) - 1 space per dwelling.
	Dwelling with 3 or more bedrooms (including rooms capable of being used as a bedroom) - 2 spaces per dwelling, 1 of which is to be covered.
	0.33 spaces per dwelling for visitor parking where development involves 3 or more dwellings.
Row Dwelling where vehicle access is from the primary street	Dwelling with 1 bedroom (including rooms capable of being used as a bedroom) - 1 space per dwelling.
primary outcet	Dwelling with 2 or more bedrooms (including rooms capable of being used as a bedroom) - 2 spaces per dwelling, 1 of which is to be covered.
Row Dwelling where vehicle access is not from the primary street (i.e. rear-loaded)	Dwelling with 1 or 2 bedrooms (including rooms capable of being used as a bedroom) - 1 space per dwelling.
,	Dwelling with 3 or more bedrooms (including rooms capable of being used as a bedroom) - 2 spaces per dwelling, 1 of which is to be covered.
Semi-Detached Dwelling	Dwelling with 1 bedroom (including rooms capable of being used as a bedroom) - 1 space per dwelling.
	Dwelling with 2 or more bedrooms (including rooms capable of being used as a

Page 130 of 141 Printed on 19/09/2022

Aged / Supported Accommodation	bedroom) - 2 spaces per dwelling, 1 of which is to be covered.
Retirement village	Dwelling with 1 or 2 bedrooms (including rooms capable of being used as a bedroom) - 1 space per dwelling. Dwelling with 3 or more bedrooms (including rooms capable of being used as a bedroom) - 2 spaces per dwelling. 0.2 spaces per dwelling for visitor parking.
Supported accommodation	0.3 spaces per bed.
Residential Development (Other)	
Ancillary accommodation	No additional requirements beyond those associated with the main dwelling.
Residential park	Dwelling with 1 or 2 bedrooms (including rooms capable of being used as a bedroom) - 1 space per dwelling. Dwelling with 3 or more bedrooms (including rooms capable of being used as a bedroom) - 2 spaces per dwelling. 0.2 spaces per dwelling for visitor parking.
Student accommodation	0.3 spaces per bed.
Workers' accommodation	0.5 spaces per bed plus 0.2 spaces per bed for visitor parking.
Tourist	
Caravan park / tourist park	Parks with 100 sites or less - a minimum of 1 space per 10 sites to be used for accommodation. Parks with more than 100 sites - a minimum of 1 space per 15 sites used for accommodation. A minimum of 1 space for every caravan (permanently fixed to the ground) or cabin.
Tourist accommodation	1 car parking space per accommodation unit / guest room.
Commercial Uses	
Auction room/ depot	1 space per 100m ² of building floor area plus an additional 2 spaces.
Automotive collision repair	3 spaces per service bay.
Call centre	8 spaces per 100m ² of gross leasable floor area.
Motor repair station	3 spaces per service bay.
Office	4 spaces per 100m ² of gross leasable floor area.

Page 131 of 141 Printed on 19/09/2022

Retail fuel outlet	3 spaces per 100m ² gross leasable floor area.
Service trade premises	2.5 spaces per 100m ² of gross leasable floor area
	1 space per 100m ² of outdoor area used for display purposes.
Shop (no commercial kitchen)	5.5 spaces per 100m ² of gross leasable floor area where not located in an integrated complex containing two or more tenancies (and which may comprise more than one building) where facilities for off-street vehicle parking, vehicle loading and unloading, and the storage and collection of refuse are shared.
	5 spaces per 100m ² of gross leasable floor area where located in an integrated complex containing two or more tenancies (and which may comprise more than one building) where facilities for off-street vehicle parking, vehicle loading and unloading, and the storage and collection of refuse are shared.
Shop (in the form of a bulky goods outlet)	2.5 spaces per 100m ² of gross leasable floor area.
Shop (in the form of a restaurant or involving a commercial kitchen)	Premises with a dine-in service only (which may include a take-away component with no drive-through) - 0.4 spaces per seat.
	Premises with take-away service but with no seats - 12 spaces per 100m ² of total floor area plus a drive-through queue capacity of ten vehicles measured from the pick-up point.
	Premises with a dine-in and drive-through take-away service - 0.3 spaces per seat plus a drive through queue capacity of 10 vehicles measured from the pick-up point.
Community and Civic Uses	
Childcare centre	0.25 spaces per child
Library	4 spaces per 100m ² of total floor area.
Community facility	10 spaces per 100m ² of total floor area.
Hall / meeting hall	0.2 spaces per seat.
Place of worship	1 space for every 3 visitor seats.
Pre-school	1 per employee plus 0.25 per child (drop off/pick up bays)
Educational establishment	For a primary school - 1.1 space per full time equivalent employee plus 0.25 spaces per student for a pickup/set down area either on-site or on the public realm within 300m of the site.
	For a secondary school - 1.1 per full time equivalent employee plus 0.1 spaces per student for a pickup/set down area either on-site or on the public realm within 300m of the site.
Page 132 of 141	Printed on 19/09/2022

Health Related Uses Hospital 4.5 spaces per bed for a public hospital. 1.5 spaces per bed for a public hospital. 1.5 spaces per consulting room excluding ancillary facilities. Recreational and Entertainment Uses Cinema complex 0.2 spaces per seat. Concert hall / theatre 0.2 spaces per seat. Hotel 1 space for every 2m² of total floor area in a public bar plus 1 space for every one² of total floor area for a Fitness Centre 4.5 spaces per 100m² of total floor area. Industry/Employment Uses Fuel depot 1.5 spaces per 100m² of total floor area used for fuel depot activity purposes. Store 0.3 spaces per 100m² of total floor area. Timber yard 1.5 spaces per 100m² of outdoor area used for fuel depot activity purposes. Warehouse 0.5 spaces per 100m² total floor area. 1 space per 100m² of outdoor area used for display purposes. Warehouse 1.5 spaces per 100m² total floor area. 1 space per 100m² of outdoor area used for display purposes. Warehouse 1.5 spaces per 100m² total floor area. 1 space per 100m² of outdoor area used for display purposes. Warehouse 2.5 spaces per 100m² total floor area. 1 space per 100m² of outdoor area used for display purposes. Warehouse 3.5 spaces per 100m² total floor area. 1 space per 100m² total floor area. 5 spaces per 100m² total floor area. 5 spaces per 100m² total floor area. 7 space per 100m² of outdoor area used for display purposes. Warehouse 3.5 spaces per 100m² total floor area. 7 space per 100m² total floor area. 8 spaces per 100m² total floor area. 9 spaces per 100m² total floor area.		
Hospital 4.5 spaces per bed for a public hospital. 1.5 spaces per bed for a private hospital. Consulting room 4 spaces per consulting room excluding ancillary facilities. Recreational and Entertainment Uses Cinema complex 0.2 spaces per seat. Concert hall / theatre 0.2 spaces per seat. Hotel 1 space for every 2m² of total floor area in a public bar plus 1 space for every 6m² of total floor area available to the public in a lounge, beer garden plus 1 space per 2 garning machines, plus 1 space per 3 seats in a restaurant. Indoor recreation facility 0.5 spaces per 100m² of total floor area for a Fitness Centre 4.5 spaces per 100m² of total floor area for all other indoor recreation facilities. Industry/Employment Uses Fuel depot 1.5 spaces per 100m² total floor area for all other indoor recreation facilities. Industry 1.5 spaces per 100m² of total floor area used for fuel depot activity purposes. Industry 1.5 spaces per 100m² of total floor area. Store 0.5 spaces per 100m² of total floor area. 1.5 spaces per 100m² of total floor area. Constitution of total floor area used for display purposes. Warehouse 0.5 spaces per 100m² total floor area. Other Uses Funeral Parlour 1 space per 5 seats in the chapel plus 1 space for each vehicle operated by the parlour.		
Lonsulting room 4 spaces per bed for a private hospital. Consulting room 4 spaces per consulting room excluding ancillary facilities. Recreational and Entertainment Uses Cinema complex 0.2 spaces per seat. Concert hall / theatre 0.2 spaces per seat. Hotel 1 space for every 2m² of total floor area in a public bar plus 1 space for every 6m² of total floor area available to the public in a lounge, beer garden plus 1 space per 2 gaming machines, plus 1 space per 3 seats in a restaurant. Indoor recreation facility 6.5 spaces per 100m² of total floor area for all other Indoor recreation facilities. Industry/Employment Uses Fuel depot 1.5 spaces per 100m² of total floor area 1 spaces per 100m² of total floor area 1 spaces per 100m² of total floor area. Store 0.5 spaces per 100m² of total floor area. 1.5 spaces per 100m² of total floor area 1 spaces per 100m² of total floor area 1 space per 5 seats in the chapel plus 1 space for each vehicle operated by the parlour. Funeral Parlour 1 space per 5 seats in the chapel plus 1 space for each vehicle operated by the parlour.	Health Related Uses	
Consulting room 4 spaces per consulting room excluding ancillary facilities. Recreational and Entertainment Uses Cinema complex 0.2 spaces per seat. Concert hall / theatre 0.2 spaces per seat. Hotel 1 space for every 2m² of total floor area in a public bar plus 1 space for every 6m² of total floor area available to the public in a lounge, beer garden plus 1 space per 2 gaming machines, plus 1 space per 3 seats in a restaurant. Indoor recreation facility 6.5 spaces per 100m² of total floor area for a Fitness Centre 4.5 spaces per 100m² of total floor area for all other Indoor recreation facilities. Industry/Employment Uses Fuel depot 1.5 spaces per 100m² total floor area for all other Indoor recreation facilities. Industry 1.5 spaces per 100m² of outdoor area used for fuel depot activity purposes. Store 0.5 spaces per 100m² of total floor area. Timber yard 1.5 spaces per 100m² of total floor area 1 space per 100m² of total floor area.	Hospital	4.5 spaces per bed for a public hospital.
Recreational and Entertainment Uses Cinema complex 0.2 spaces per seat. Concert hall / theatre 1 space for every 2m² of total floor area in a public bar plus 1 space for every 6m² of total floor area available to the public in a lounge, beer garden plus 1 space per 2 gaming machines, plus 1 space per 3 seats in a restaurant. Indoor recreation facility 6.5 spaces per 100m² of total floor area for a Fitness Centre 4.5 spaces per 100m² of total floor area for all other Indoor recreation facilities. Industry/Employment Uses Fuel depot 1.5 spaces per 100m² of outdoor area used for fuel depot activity purposes. Industry 1.5 spaces per 100m² of total floor area. Store 0.5 spaces per 100m² of total floor area. Timber yard 1.5 spaces per 100m² of total floor area 1 space per 100m² of total floor area 1 space per 100m² of total floor area 0.5 spaces per 100m² of total floor area 1 space per 100m² total floor area 1 space per 100m² total floor area used for display purposes.		1.5 spaces per bed for a private hospital.
Cinema complex 0.2 spaces per seat. Concert hall / theatre 0.2 spaces per seat. Hotel 1 space for every 2m² of total floor area in a public bar plus 1 space for every 6m² of total floor area available to the public in a lounge, beer garden plus 1 space per 2 gaming machines, plus 1 space per 3 seats in a restaurant. Indoor recreation facility 6.5 spaces per 100m² of total floor area for a Fitness Centre 4.5 spaces per 100m² of total floor area for all other Indoor recreation facilities. Industry/Employment Uses Fuel depot 1.5 spaces per 100m² of total floor area 1 spaces per 100m² of outdoor area used for fuel depot activity purposes. Industry 1.5 spaces per 100m² of total floor area. Store 0.5 spaces per 100m² of total floor area. Timber yard 1.5 spaces per 100m² of total floor area 1 space per 100m² of total floor area 2 spaces per 100m² of total floor area 3 spaces per 100m² of total floor area 4 space per 100m² of total floor area 5 spaces per 100m² of total floor area 6 spaces per 100m² of total floor area 7 space per 100m² of total floor area 8 spaces per 100m² of total floor area 9 spaces per 100m² of total floor area 1 space per 100m² of total floor area 1 space per 5 seats in the chapel plus 1 space for each vehicle operated by the parlour.	Consulting room	4 spaces per consulting room excluding ancillary facilities.
Concert half / theatre 0.2 spaces per seat. Hotel 1 space for every 2m² of total floor area in a public bar plus 1 space for every 6m² of total floor area available to the public in a lounge, beer garden plus 1 space per 2 gaming machines, plus 1 space per 3 seats in a restaurant. Indoor recreation facility 6.5 spaces per 100m² of total floor area for a Fitness Centre 4.5 spaces per 100m² of total floor area for all other Indoor recreation facilities. Industry/Employment Uses Fuel depot 1.5 spaces per 100m² total floor area 1 spaces per 100m² of outdoor area used for fuel depot activity purposes. Industry 1.5 spaces per 100m² of total floor area. Store 0.5 spaces per 100m² of total floor area. Timber yard 1.5 spaces per 100m² of total floor area 1 space per 100m² of outdoor area used for display purposes. Warehouse 0.5 spaces per 100m² total floor area. Other Uses Funeral Parlour 1 space per 5 seats in the chapel plus 1 space for each vehicle operated by the parlour.	Recreational and Entertainment Uses	
Hotel 1 space for every 2m² of total floor area in a public bar plus 1 space for every 6m² of total floor area available to the public in a lounge, beer garden plus 1 space per 2 gaming machines, plus 1 space per 3 seats in a restaurant. Indoor recreation facility 6.5 spaces per 100m² of total floor area for a Fitness Centre 4.5 spaces per 100m² of total floor area for all other Indoor recreation facilities. Industry/Employment Uses Fuel depot 1.5 spaces per 100m² total floor area 1 spaces per 100m² of outdoor area used for fuel depot activity purposes. Industry 1.5 spaces per 100m² of total floor area. Store 0.5 spaces per 100m² of total floor area. Timber yard 1.5 spaces per 100m² of total floor area 1 space per 100m² of total floor area 0.5 spaces per 100m² of total floor area 1 space per 100m² of outdoor area used for display purposes. Warehouse 0.5 spaces per 100m² total floor area. Timber yard 1 space per 5 seats in the chapel plus 1 space for each vehicle operated by the parlour.	Cinema complex	0.2 spaces per seat.
Industry Company Com	Concert hall / theatre	0.2 spaces per seat.
4.5 spaces per 100m² of total floor area for all other Indoor recreation facilities. Industry/Employment Uses Fuel depot 1.5 spaces per 100m² total floor area 1 spaces per 100m² of outdoor area used for fuel depot activity purposes. Industry 1.5 spaces per 100m² of total floor area. Store 0.5 spaces per 100m² of total floor area. Timber yard 1.5 spaces per 100m² of total floor area 1 space per 100m² of outdoor area used for display purposes. Warehouse 0.5 spaces per 100m² total floor area. Other Uses Funeral Parlour 1 space per 5 seats in the chapel plus 1 space for each vehicle operated by the parlour.	Hotel	6m ² of total floor area available to the public in a lounge, beer garden plus 1
Industry/Employment Uses Fuel depot 1.5 spaces per 100m² total floor area 1 spaces per 100m² of outdoor area used for fuel depot activity purposes. Industry 1.5 spaces per 100m² of total floor area. Store 0.5 spaces per 100m² of total floor area. Timber yard 1.5 spaces per 100m² of total floor area 1 space per 100m² of total floor area 1 space per 100m² of outdoor area used for display purposes. Warehouse 0.5 spaces per 100m² total floor area. Other Uses Funeral Parlour 1 space per 5 seats in the chapel plus 1 space for each vehicle operated by the parlour.	Indoor recreation facility	
Fuel depot 1.5 spaces per 100m² total floor area 1 spaces per 100m² of outdoor area used for fuel depot activity purposes. Industry 1.5 spaces per 100m² of total floor area. Store 0.5 spaces per 100m² of total floor area. Timber yard 1.5 spaces per 100m² of total floor area 1 space per 100m² of total floor area 1 space per 100m² of outdoor area used for display purposes. Warehouse 0.5 spaces per 100m² total floor area. Other Uses Funeral Parlour 1 space per 5 seats in the chapel plus 1 space for each vehicle operated by the parlour.		4.5 spaces per 100m ² of total floor area for all other Indoor recreation facilities.
1 spaces per 100m² of outdoor area used for fuel depot activity purposes. Industry 1.5 spaces per 100m² of total floor area. Store 0.5 spaces per 100m² of total floor area. Timber yard 1.5 spaces per 100m² of total floor area 1 space per 100m² of outdoor area used for display purposes. Warehouse 0.5 spaces per 100m² total floor area. Other Uses Funeral Parlour 1 space per 5 seats in the chapel plus 1 space for each vehicle operated by the parlour.	Industry/Employment Uses	
Industry 1.5 spaces per 100m² of total floor area. Store 0.5 spaces per 100m² of total floor area. Timber yard 1.5 spaces per 100m² of total floor area 1 space per 100m² of outdoor area used for display purposes. Warehouse 0.5 spaces per 100m² total floor area. Other Uses Funeral Parlour 1 space per 5 seats in the chapel plus 1 space for each vehicle operated by the parlour.	Fuel depot	1.5 spaces per 100m ² total floor area
Store 0.5 spaces per 100m² of total floor area. Timber yard 1.5 spaces per 100m² of total floor area 1 space per 100m² of outdoor area used for display purposes. Warehouse 0.5 spaces per 100m² total floor area. Other Uses Funeral Parlour 1 space per 5 seats in the chapel plus 1 space for each vehicle operated by the parlour.		1 spaces per 100m ² of outdoor area used for fuel depot activity purposes.
Timber yard 1.5 spaces per 100m² of total floor area 1 space per 100m² of outdoor area used for display purposes. Warehouse 0.5 spaces per 100m² total floor area. Other Uses Funeral Parlour 1 space per 5 seats in the chapel plus 1 space for each vehicle operated by the parlour.	Industry	1.5 spaces per 100m ² of total floor area.
1 space per 100m² of outdoor area used for display purposes. Warehouse 0.5 spaces per 100m² total floor area. Other Uses Funeral Parlour 1 space per 5 seats in the chapel plus 1 space for each vehicle operated by the parlour.	Store	0.5 spaces per 100m ² of total floor area.
Warehouse 0.5 spaces per 100m² total floor area. Other Uses Funeral Parlour 1 space per 5 seats in the chapel plus 1 space for each vehicle operated by the parlour.	Timber yard	1.5 spaces per 100m ² of total floor area
Other Uses Funeral Parlour 1 space per 5 seats in the chapel plus 1 space for each vehicle operated by the parlour.		1 space per 100m ² of outdoor area used for display purposes.
Funeral Parlour 1 space per 5 seats in the chapel plus 1 space for each vehicle operated by the parlour.	Warehouse	0.5 spaces per 100m ² total floor area.
parlour.	Other Uses	
Radio or Television Station 5 spaces per 100m ² of total building floor area.	Funeral Parlour	
	Radio or Television Station	5 spaces per 100m ² of total building floor area.

Page 133 of 141 Printed on 19/09/2022

Table 2 - Off-Street Car Parking Requirements in Designated Areas

The following parking rates apply in any zone, subzone or other area described in the 'Designated Areas' column subject to the following:

- (a) the location of the development is unable to satisfy the requirements of Table 2 Criteria (other than where a location is exempted from the application of those criteria)
- (b) the development satisfies Table 2 Criteria (or is exempt from those criteria) and is located in an area where a lawfully established carparking fund operates, in which case the number of spaces are reduced by an amount equal to the number of spaces offset by contribution to the fund.

Class of Development	Car Parking Rate Where a development comprises more than one development type, then the overall car parking rate will be taken to be the sum of the car parking rates for each development type.		Designated Areas
	Minimum number of spaces	Maximum number of spaces	
Development generally			
All classes of development	No minimum.	No maximum except in the Primary Pedestrian Area identified in the Primary Pedestrian Area Concept Plan, where the maximum is: 1 space for each dwelling with a total floor area less than 75 square metres 2 spaces for each dwelling with a total floor area between 75 square metres and 150 square metres 3 spaces for each dwelling with a total floor area greater than 150 square metres. Residential flat building or Residential component of a multi-storey building: 1 visitor space for each 6 dwellings.	Capital City Zone City Main Street Zone City Riverbank Zone Adelaide Park Lands Zone Business Neighbourhood Zone (within the City of Adelaide) The St Andrews Hospital Precinct Subzone and Women's and Children's Hospital Precinct Subzone of the Community Facilities Zone
Non-residential develop	oment		
Non-residential development excluding tourist accommodation	3 spaces per 100m ² of gross leasable floor area.	5 spaces per 100m ² of gross leasable floor area.	City Living Zone Urban Corridor (Boulevard) Zone Urban Corridor (Business) Zone Urban Corridor (Living) Zone Urban Corridor (Main Street) Zone

Page 134 of 141 Printed on 19/09/2022

			Urban Neighbourhood Zone
Non-residential development excluding tourist accommodation	3 spaces per 100m ² of gross leasable floor area.	6 spaces per 100m ² of gross leasable floor area.	Strategic Innovation Zone Suburban Activity Centre Zone Suburban Business Zone Business Neighbourhood Zone Suburban Main Street Zone Urban Activity Centre Zone
Tourist accommodation	1 space for every 4 bedrooms up to 100 bedrooms plus 1 space for every 5 bedrooms over 100 bedrooms	1 space per 2 bedrooms up to 100 bedrooms and 1 space per 4 bedrooms over 100 bedrooms	City Living Zone Urban Activity Centre Zone Urban Corridor (Boulevard) Zone Urban Corridor (Business) Zone Urban Corridor (Living) Zone Urban Corridor (Main Street) Zone Urban Neighbourhood Zone
Residential developmen	t		
Residential component of a multi-storey building	Dwelling with no separate bedroom -0.25 spaces per dwelling 1 bedroom dwelling - 0.75 spaces per dwelling 2 bedroom dwelling - 1 space per dwelling 3 or more bedroom dwelling - 1.25 spaces per dwelling 0.25 spaces per dwelling for visitor parking.	None specified.	City Living Zone Strategic Innovation Zone Urban Activity Centre Zone Urban Corridor (Boulevard) Zone Urban Corridor (Business) Zone Urban Corridor (Living) Zone Urban Corridor (Main Street) Zone Urban Neighbourhood Zone
Residential flat building	Dwelling with no separate bedroom -0.25 spaces per dwelling 1 bedroom dwelling - 0.75 spaces per dwelling 2 bedroom dwelling - 1 space per dwelling 3 or more bedroom dwelling - 1.25 spaces per dwelling 0.25 spaces per dwelling for	None specified.	City Living Zone Urban Activity Centre Zone Urban Corridor (Boulevard) Zone Urban Corridor (Business) Zone Urban Corridor (Living) Zone Urban Corridor (Main Street) Zone Urban Neighbourhood Zone

Page 135 of 141 Printed on 19/09/2022

vicitor parking	
visitor parking.	

Table 2 - Criteria:

The following criteria are used in conjunction with Table 2. The 'Exception' column identifies locations where the criteria do not apply and the car parking rates in Table 2 are applicable.

Criteria	Exceptions
The designated area is wholly located within Metropolitan Adelaide and any part of the development site satisfies one or more of the following:	(a) All zones in the City of Adelaide (b) Strategic Innovation Zone in the following locations: (i) City of Burnside (ii) City of Marion (iii) City of Mitcham
 (a) is within 200 metres of any section of road reserve along which a bus service operates as a high frequency public transit service⁽²⁾ (b) is within 400 metres of a bus interchange⁽¹⁾ (c) is within 400 metres of an O-Bahn interchange⁽¹⁾ (d) is within 400 metres of a passenger rail station⁽¹⁾ (e) is within 400 metres of a passenger tram station⁽¹⁾ (f) is within 400 metres of the Adelaide Parklands. 	(c) Urban Corridor (Boulevard) Zone (d) Urban Corridor (Business) Zone (e) Urban Corridor (Living) Zone (f) Urban Corridor (Main Street) Zone (g) Urban Neighbourhood Zone

[NOTE(S): (1)Measured from an area that contains any platform(s), shelter(s) or stop(s) where people congregate for the purpose waiting to board a bus, tram or train, but does not include areas used for the parking of vehicles. (2) A high frequency public transit service is a route serviced every 15 minutes between 7.30am and 6.30pm Monday to Friday and every 30 minutes at night, Saturday, Sunday and public holidays until 10pm.]

Table 3 - Off-Street Bicycle Parking Requirements

The bicycle parking rates apply within designated areas located within parts of the State identified in the Schedule to Table 3.

Class of Development	Bicycle Parking Rate Where a development comprises more than one development type, then the overall bicycle parking rate will be taken to be the sum of the bicycle parking rates for each development type.
Consulting Room	1 space per 20 employees plus 1 space per 20 consulting rooms for customers.
Educational establishment	For a secondary school - 1 space per 20 full-time time employees plus 10 percent of the total number of employee spaces for visitors. For tertiary education - 1 space per 20 employees plus 1 space per 10 full time students.
Hospital	1 space per 15 beds plus 1 space per 30 beds for visitors.
Indoor recreation facility	1 space per 4 employees plus 1 space per 200m ² of gross leasable floor area for

Page 136 of 141 Printed on 19/09/2022

	visitors.
Licensed Premises	1 per 20 employees, plus 1 per 60 square metres total floor area, plus 1 per 40 square metres of bar floor area, plus 1 per 120 square metres lounge and beer garden floor area, plus 1 per 60 square metres dining floor area, plus 1 per 40 square metres gaming room floor area.
Office	1 space for every 200m ² of gross leasable floor area plus 2 spaces plus 1 space per 1000m ² of gross leasable floor area for visitors.
Pre-school	1 space per 20 full time employees plus 1 space per 40 full time children.
Recreation area	1 per 1500 spectator seats for employees plus 1 per 250 visitor and customers.
Residential flat building	Within the City of Adelaide 1 for every dwelling for residents with a total floor area less than 150 square metres, 2 for every dwelling for residents with a total floor area greater than 150 square metres, plus 1 for every 10 dwellings for visitors, and in all other cases 1 space for every 4 dwellings for residents plus 1 for every 10 dwellings for visitors.
Residential component of a multi-storey building	Within the City of Adelaide 1 for every dwelling for residents with a total floor area less than 150 square metres, 2 for every dwelling for residents with a total floor area greater than 150 square metres, plus 1 for every 10 dwellings for visitors, and in all other cases 1 space for every 4 dwellings for residents plus 1 space for every 10 dwellings for visitors.
Shop	1 space for every 300m ² of gross leasable floor area plus 1 space for every 600m ² of gross leasable floor area for customers.
Tourist accommodation	1 space for every 20 employees plus 2 for the first 40 rooms and 1 for every additional 40 rooms for visitors.

Schedule to Table 3

Designated Area	Relevant part of the State The bicycle parking rate applies to a designated area located in a relevant part of the State described below.
All zones	City of Adelaide
Business Neighbourhood Zone	Metropolitan Adelaide
Strategic Innovation Zone	
Suburban Activity Centre Zone	
Suburban Business Zone	
Suburban Main Street Zone	
Urban Activity Centre Zone	
Urban Corridor (Boulevard) Zone	
Urban Corridor (Business) Zone	

Page 137 of 141 Printed on 19/09/2022

Urban Corridor (Living) Zone	
Urban Corridor (Main Street) Zone	
Urban Neighbourhood Zone	

Waste Treatment and Management Facilities

Assessment Provisions (AP)

	Desired Outcome
DO 1	Mitigation of the potential environmental and amenity impacts of waste treatment and management facilities.

Performance Outcomes (PO) and Deemed-to-Satisfy (DTS) Criteria / Designated Performance Feature (DPF)

Deemed-to-Satisfy Criteria / Designated Performance Feature		
Siting		
DTS/DPF 1.1		
None are applicable.		
Soil and Water Protection		
DTS/DPF 2.1		
None are applicable.		
DTS/DPF 2.2		
Wastewater lagoons are set back 50m or more from watercourse banks.		

Page 138 of 141 Printed on 19/09/2022

Policy24 - Eliquity		
PO 2.3	DTS/DPF 2.3	
Wastewater lagoons are designed and sited to:	None are applicable.	
 (a) avoid intersecting underground waters; (b) avoid inundation by flood waters; (c) ensure lagoon contents do not overflow; (d) include a liner designed to prevent leakage. 		
P0 2.4	DTS/DPF 2.4	
Waste operations areas of landfills and organic waste processing facilities are set back from watercourses to minimise adverse impacts on water resources.	Waste operations areas are set back 100m or more from watercourse banks.	
Am	enity	
PO 3.1	DTS/DPF 3.1	
Waste treatment and management facilities are screened, located and designed to minimise adverse visual impacts on amenity.	None are applicable.	
P0 3.2	DTS/DPF 3.2	
Access routes to waste treatment and management facilities via residential streets is avoided.	None are applicable.	
P0 3.3	DTS/DPF 3.3	
Litter control measures minimise the incidence of windblown litter.	None are applicable.	
P0 3.4	DTS/DPF 3.4	
Waste treatment and management facilities are designed to minimise adverse impacts on both the site and surrounding areas from weed and vermin infestation.	None are applicable.	
Acc	Dess	
P0 4.1	DTS/DPF 4.1	
Traffic circulation movements within any waste treatment or management site are designed to enable vehicles to enter and exit the site in a forward direction.	None are applicable.	
P0 4.2	DTS/DPF 4.2	
Suitable access for emergency vehicles is provided to and within waste treatment or management sites.	None are applicable.	
Fencing a	nd Security	
PO 5.1	DTS/DPF 5.1	
Security fencing provided around waste treatment and management facilities prevents unauthorised access to operations and potential hazard to the public.	Chain wire mesh or pre-coated painted metal fencing 2m or more in height is erected along the perimeter of the waste treatment or waste management facility site.	
Landfill		
PO 6.1	DTS/DPF 6.1	
Landfill gas emissions are managed in an environmentally	None are applicable.	

Page 139 of 141 Printed on 19/09/2022

Policy24 - Enquiry	
acceptable manner.	
P0 6.2	DTS/DPF 6.2
Landfill facilities are separated from areas of environmental significance and land used for public recreation and enjoyment.	Landfill facilities are set back 250m or more from a public open space reserve, forest reserve, national park or Conservation Zone.
PO 6.3	DTS/DPF 6.3
Landfill facilities are located on land that is not subject to land slip.	None are applicable.
P0 6.4	DTS/DPF 6.4
Landfill facilities are separated from areas subject to flooding.	Landfill facilities are set back 500m or more from land inundated in a 1% AEP flood event.
Organic Waste Pr	ocessing Facilities
P0 7.1	DTS/DPF 7.1
Organic waste processing facilities are separated from the coast to avoid potential environment harm.	Organic waste processing facilities are set back 500m or more from the coastal high water mark.
PO 7.2	DTS/DPF 7.2
Organic waste processing facilities are located on land where the engineered liner and underlying seasonal water table cannot intersect.	None are applicable.
P0 7.3	DTS/DPF 7.3
Organic waste processing facilities are sited away from areas of environmental significance and land used for public recreation and enjoyment.	Organic waste processing facilities are set back 250m or more from a public open space reserve, forest reserve, national park or a Conservation Zone.
PO 7.4	DTS/DPF 7.4
Organic waste processing facilities are located on land that is not subject to land slip.	None are applicable.
P0 7.5	DTS/DPF 7.5
Organic waste processing facilities separated from areas subject to flooding.	Organic waste processing facilities are set back 500m or more from land inundated in a 1% AEP flood event.
Major Wastewater	Treatment Facilities
PO 8.1	DTS/DPF 8.1
Major wastewater treatment and disposal systems, including lagoons, are designed to minimise potential adverse odour impacts on sensitive receivers, minimise public and environmental health risks and protect water quality.	None are applicable.
PO 8.2	DTS/DPF 8.2
Artificial wetland systems for the storage of treated wastewater are designed and sited to minimise potential public health risks arising from the breeding of mosquitoes.	None are applicable.
Po 8.1 Major wastewater treatment and disposal systems, including lagoons, are designed to minimise potential adverse odour impacts on sensitive receivers, minimise public and environmental health risks and protect water quality. Po 8.2 Artificial wetland systems for the storage of treated wastewater are designed and sited to minimise potential public health risks	DTS/DPF 8.1 None are applicable. DTS/DPF 8.2

Workers' accommodation and Settlements

Page 140 of 141 Printed on 19/09/2022

Assessment Provisions (AP)

	Desired Outcome
DO 1	Appropriately designed and located accommodation for seasonal and short-term workers in rural areas that minimises environmental and social impacts.

Performance Outcome	Deemed-to-Satisfy Criteria / Designated Performance Feature
PO 1.1	DTS/DPF 1.1
Workers' accommodation and settlements are obscured from scenic routes, tourist destinations and areas of conservation significance or otherwise designed to complement the surrounding landscape.	None are applicable.
PO 1.2	DTS/DPF 1.2
Workers' accommodation and settlements are sited and designed to minimise nuisance impacts on the amenity of adjacent users of land.	None are applicable.
PO 1.3	DTS/DPF 1.3
Workers' accommodation and settlements are built with materials and colours that blend with the landscape.	None are applicable.
PO 1.4	DTS/DPF 1.4
Workers' accommodation and settlements are supplied with service infrastructure such as power, water and effluent disposal sufficient to satisfy the living requirements of workers.	None are applicable.

No criteria applies to this land use. Please check the definition of the land use for further detail.

Page 141 of 141 Printed on 19/09/2022

228 SMART RD ST AGNES SA 5097

Address:

Click to view a detailed interactive SAILIS in SAILIS

To view a detailed interactive property map in SAPPA click on the map below



Property Zoning Details

Local Variation (TNV)

Maximum Building Height (Metres) (Maximum building height is 9m)

Maximum Building Height (Levels) (Maximum building height is 2 levels)

Overlay

Affordable Housing

Hazards (Flooding)

Hazards (Flooding - Evidence Required)

Prescribed Wells Area

Regulated and Significant Tree

Stormwater Management

Traffic Generating Development

Urban Tree Canopy

Water Resources

Zone

Employment

General Neighbourhood

Selected Development(s)

Office

This development may be subject to multiple assessment pathways. Please review the document below to determine which pathway may be applicable based on the proposed development compliances to standards.

development compliances to standards.

If no assessment pathway is shown this mean the proposed development will default to performance assessed. Please contact your local council in this instance. Refer to Part 1 - Rules of Interpretation - Determination of Classes of Development

Property Policy Information for above selection

Office - Code Assessed - Performance Assessed

Page 1 of 28 Printed on 19/09/2022

Part 2 - Zones and Sub Zones

Employment Zone

Assessment Provisions (AP)

Desired Outcome			
DO 1	A diverse range of low-impact light industrial, commercial and business activities that complement the role of other zones accommodating significant industrial, shopping and business activities.		
DO 2	Distinctive building, landscape and streetscape design to achieve high visual and environmental amenity particularly along arterial roads, zone boundaries and public open spaces.		

Performance Outcomes (PO) and Deemed-to-Satisfy (DTS) Criteria / Designated Performance Feature (DPF)

Performance Outcome	Deemed-to-Satisfy Criteria / Designated Performance Feature
Land Use a	nd Intensity
P01.1	DTS/DPF 1.1
A range of employment-generating light industrial, service trade, motor repair and other compatible businesses servicing the local community that do not produce emissions that would detrimentally affect local amenity.	(a) Advertisement (b) Consulting room (c) Indoor recreation facility (d) Light industry (e) Motor repair station (f) Office (g) Place of worship (h) Research facility (i) Retail fuel outlet (j) Service trade premises (k) Shop (l) Store (m) Telecommunications facility (n) Training facility (o) Warehouse.
PO 1.2	DTS/DPF 1.2
Shops provide convenient day-to-day services and amenities to local businesses and workers, support the sale of products manufactured on-site and otherwise complement the role of Activity Centres.	Shop where one of the following applies: (a) with a gross leasable floor area up to 100m² (b) is a bulky goods outlet (c) is a restaurant (d) is ancillary to and located on the same allotment as an industry and primarily involves the sale by retail of goods manufactured by the industry.
Built Form a	nd Character
PO 2.1	DTS/DPF 2.1

Page 2 of 28 Printed on 19/09/2022

Development achieves distinctive building, landscape and streetscape design to achieve high visual and environmental amenity particularly along arterial roads, zone boundaries and public open spaces.	None are applicable.
PO 2.2	DTS/DPF 2.2
Building facades facing a boundary of a zone primarily intended to accommodate residential development, public roads, or publ open space incorporate design elements to add visual interest considering the following:	lic
(a) using a variety of building finishes	
(b) avoiding elevations that consist solely of metal claddin	g
 (c) using materials with a low reflectivity (d) using techniques to add visual interest and reduce large 	
expanses of blank walls including modulation and incorporation of offices and showrooms along elevations visible to a public road.	3
Building he	ight and setbacks
PO 3.1	DTS/DPF 3.1
Buildings are set back from the primary street boundary to contribute to the existing/emerging pattern of street setbacks in	The building line of a building set back from the primary street boundary:
the streetscape.	 (a) at least the average setback to the building line of existing buildings on adjoining sites which face the same primary street (including those buildings that would adjoin the site if not separated by a public road or a vacant allotment) (b) where there is only one existing building on adjoining sites which face the same primary street (including those that would adjoin if not separated by a public road or a vacant allotment), not less than the setback to the building line of that building or (c) not less than 3m where no building exists on an adjoining site with the same primary street frontage.
PO 3.2	DTS/DPF 3.2
Buildings are set back from a secondary street boundary to accommodate the provision of landscaping between buildings and the street to enhance the appearance of land and buildings when viewed from the street.	Building walls are no closer than 2m to the secondary street boundary.
PO 3.3	DTS/DPF 3.3
Buildings are set back from rear access ways to provide adequate manoeuvrability for vehicles to enter and exit the site.	Building walls are set back from the rear access way: (a) where the access way is 6.5m wide or more, no requirement (b) where the access way is less than 6.5m wide, the distance equal to the additional width required to make the access way at least 6.5m wide.
PO 3.4	DTS/DPF 3.4
Buildings are sited to accommodate vehicle access to the rear a site for deliveries, maintenance and emergency purposes.	of Building walls are set back at least 3m from at least one side boundary, unless an alternative means for vehicular access to the

Page 3 of 28 Printed on 19/09/2022

PO 3.5

Building height is consistent with the form expressed in any relevant *Maximum Building Height (Levels) Technical and Numeric Variation* layer, and is otherwise generally low-rise to complement the established streetscape and local character.

rear of the site is available.

DTS/DPF 3.5

Building height is not greater than:

(a) the following:

Maximum Building Height (Levels)

Maximum building height is 2 levels

Maximum Building Height (Metres)

Maximum building height is 9m

(b) in all other cases (i.e. there are blank fields for both maximum building height (metres) and maximum building height (levels)) - 2 building levels up to a height of 9m.

In relation to DTS/DPF 3.5, in instances where:


- (c) more than one value is returned in the same field for DTS/DPF 3.5(a) refer to the Maximum Building Height (Levels) Technical and Numeric Variation layer or Maximum Building Height (Metres) Technical and Numeric Variation layer in the SA planning database to determine the applicable value relevant to the site of the proposed development
- (d) only one value is returned for DTS/DPF 3.1(a) (i.e. there is one blank field), then the relevant height in metres or building levels applies with no criteria for the other.

PO 3.6

Buildings mitigate visual impacts of building massing on residential development within a neighbourhood-type zone.

DTS/DPF 3.6

Buildings are constructed within a building envelope provided by a 45 degree plane, measured from a height of 3m above natural ground level at the boundary of an allotment used for residential purposes in a neighbourhood-type zone as shown in the following diagram, except where the relevant boundary is a southern boundary or where this boundary is the primary street boundary.




PO 3.7

Buildings mitigate overshadowing of residential development within a neighbourhood-type zone.

DTS/DPF 3.7

Buildings on sites with a southern boundary adjoining an allotment used for residential purposes within a neighbourhood-type zone are constructed within a building envelope provided by a 30 degree plane grading north measured from a height of 3m above natural ground level at the southern boundary, as shown in the following diagram:

Page 4 of 28 Printed on 19/09/2022



PO 3.8

Buildings on an allotment fronting a road that is not a State maintained road, and where land on the opposite side of the road is within a neighbourhood-type zone, provides an orderly transition to the built form scale envisaged in the adjacent zone to complement the streetscape character.

DTS/DPF 3.8

None are applicable.

Landscaping

PO 5.1

Landscaping is provided to enhance the visual appearance of development when viewed from public roads and thoroughfares.

DTS/DPF 5.1

Other than to accommodate a lawfully existing or authorised driveway or access point, or an access point for which consent has been granted as part of an application for the division of land, a landscaped area is provided within the development site:

- (a) where a building is set back less than 3m from the street boundary - 1m wide or the area remaining between the relevant building and the street boundary where the building is less than 1m from the street boundary
- (b) in any other case at least 1.5m wide.

PO 5.2

Development incorporates areas for landscaping to enhance the overall amenity of the site and locality.

DTS/DPF 5.2

Landscape areas comprise:

- (a) not less than 10 percent of the site
- (b) a dimension of at least 1.5m.

Concept Plans

PO 7.1

Development is compatible with the outcomes sought by any relevant Concept Plan contained within Part 12 - Concept Plans of the Planning and Design Code to support the orderly development of land through staging of development and provision of infrastructure.

DTS/DPF 7.1

The site of the development is wholly located outside any relevant Concept Plan boundary. The following Concept Plans are relevant:

In relation to DTS/DPF 7.1, in instances where:

- (a) one or more Concept Plan is returned, refer to Part 12 -Concept Plans in the Planning and Design Code to determine if a Concept Plan is relevant to the site of the proposed development. Note: multiple concept plans may be relevant.
- (b) in instances where 'no value' is returned, there is no relevant concept plan and DTS/DPF 7.1 is met.

Page 5 of 28 Printed on 19/09/2022

Table 5 - Procedural Matters (PM) - Notification

The following table identifies, pursuant to section 107(6) of the *Planning, Development and Infrastructure Act 2016*, classes of performance assessed development that are excluded from notification. The table also identifies any exemptions to the placement of notices when notification is required.

Interpretation

Notification tables exclude the classes of development listed in Column A from notification provided that they do not fall within a corresponding exclusion prescribed in Column B.

Where a development or an element of a development falls within more than one class of development listed in Column A, it will be excluded from notification if it is excluded (in its entirety) under any of those classes of development. It need not be excluded under all applicable classes of development.

Where a development involves multiple performance assessed elements, all performance assessed elements will require notification (regardless of whether one or more elements are excluded in the applicable notification table) unless every performance assessed element of the application is excluded in the applicable notification table, in which case the application will not require notification.

Class	of Develo	ppment	Exceptions	
(Column A)			(Column B)	
1.	authori unreas	oment which, in the opinion of the relevant ty, is of a minor nature only and will not onably impact on the owners or occupiers of the locality of the site of the development.	None specified.	
2.	(a) (b) (c) (d) (e) (f) (g)	velopment involving any of the following (or of mbination of any of the following): advertisement air handling unit, air conditioning system or exhaust fan building on railway land carport fence outbuilding retaining wall shade sail solar photovoltaic panels (roof mounted) temporary public service depot verandah water tank.	Except development that exceeds the maximum building height specified in Employment Zone DTS/DPF 3.5 or does not satisfy any of the following: 1. Employment Zone DTS/DPF 3.6 2. Employment Zone DTS/DPF 3.7.	
3.	any cor (a) (b)	relopment involving any of the following (or of mbination of any of the following): consulting room light industry office motor repair station retail fuel outlet store warehouse.	Except where the site of the development is adjacent land to a site (or land) used for residential purposes in a neighbourhood-type zone.	

Page 6 of 28 Printed on 19/09/2022

- ,	• •	
4.	Any development involving any of the following (or of any combination of any of the following): (a) internal building works (b) land division (c) replacement building (d) temporary accommodation in an area affected by bushfire (e) tree damaging activity.	None specified.
5.	Demolition.	 Except any of the following: the demolition of a State or Local Heritage Place the demolition of a building (except an ancillary building) in a Historic Area Overlay.
6.	Shop within any of the following: (a) Retail Activity Centre Subzone (b) Roadside Service Centre Subzone.	Except shop that exceeds the maximum building height specified in Employment Zone DTS/DPF 3.5 or does not satisfy any of the following: 1. Employment Zone DTS/DPF 3.6 2. Employment Zone DTS/DPF 3.7.
7.	Shop.	 where the site of the shop is adjacent land to a site (or land) used for residential purposes in a neighbourhood-type zone or shop that exceeds the maximum building height specified in Employment Zone DTS/DPF 3.5 or shop that does not satisfy Employment Zone DTS/DPF 1.2.
8.	Telecommunications facility.	Except telecommunications facility that does not satisfy Employment Zone DTS/DPF 1.3.

Placement of Notices - Exemptions for Performance Assessed Development

None specified.

Placement of Notices - Exemptions for Restricted Development

None specified.

Part 3 - Overlays

Hazards (Flooding) Overlay

Assessment Provisions (AP)

Page 7 of 28 Printed on 19/09/2022

Desired Outcome

DO 1

Impacts on people, property, infrastructure and the environment from high flood risk are minimised by retaining areas free from development, and minimising intensification where development has occurred.

Performance Outcomes (PO) and Deemed-to-Satisfy (DTS) Criteria / Designated Performance Feature (DPF)

Performance Outcome	Deemed-to-Satisfy Criteria / Designated Performance Feature	
Flood R	esilience	
PO 3.1	DTS/DPF 3.1	
Development avoids the need for flood protection works.	None are applicable.	
PO 3.2	DTS/DPF 3.2	
Development does not cause unacceptable impacts on any adjoining property by the diversion of flood waters or an increase in flood velocity or flood level.	None are applicable.	
PO 3.3	DTS/DPF 3.3	
Development does not impede the flow of floodwaters through the allotment or the surrounding land, or cause an unacceptable loss of flood storage.		
PO 3.4	DTS/DPF 3.4	
Development avoids frequently flooded or high velocity areas, other than where it is part of a flood mitigation scheme to reduce flood impact.	Other than a recreation area, development is located outside of the 5% AEP principal flow path.	
PO 3.5	DTS/DPF 3.5	
Buildings are sited, designed and constructed to prevent the entry of floodwaters in a 1% AEP flood event where the entry of floodwaters is likely to result in undue damage to, or compromise ongoing activities within, buildings.	Buildings comprise one of the following: (a) a porch or portico with at least 2 open sides (b) a verandah with at least 3 open sides (c) a carport or outbuilding with at least 2 open sides (whichever elevations face the direction of the flow) (d) any post construction with open sides (e) a building with a finished floor level that is at least 300mm above the height of a 1% AEP flood event.	
Environment	ral Protection	
PO 4.1	DTS/DPF 4.1	
Buildings and structures used either partly or wholly to contain or store hazardous materials are designed to prevent spills or leaks leaving the confines of the building during a 1% AEP flood event to avoid potential environmental harm.	Development involving the storage or disposal of hazardous materials is wholly located outside of the 1% AEP flood plain or flow path.	
PO 4.2	DTS/DPF 4.2	
Development does not create or aggravate the potential for	None are applicable.	

Page 8 of 28 Printed on 19/09/2022

Policy24 - Enquiry	
erosion or siltation or lead to the destruction of vegetation during a flood.	
Site Ear	thworks
PO 5.1	DTS/DPF 5.1
The depth and extent of filling required to raise the finished floor level of a building does not cause unacceptable impact on any adjoining property by diversion of flood waters, an increase in flood velocity or flood level, or an unacceptable loss of flood storage.	
PO 5.2	DTS/DPF 5.2
Driveways, access tracks and parking areas are designed and constructed to minimise excavation and filling.	Filling for ancillary purposes: (a) does not exceed 300mm above existing ground level (b) is no more than 5m wide.
Acc	cess
PO 6.1	DTS/DPF 6.1
Development does not occur on land:	None are applicable.
(a) from which evacuation to areas not vulnerable to flood risk is not possible during a 1% AEP flood event	
(b) which cannot be accessed by emergency services vehicles or essential utility service vehicles during a 1% AEP flood event.	
PO 6.2	DTS/DPF 6.2
Access driveways and tracks to significant development (i.e. dwellings, places of work, etc.) consist of a safe, all-weather trafficable surface that is accessible during a 1% AEP flood event.	None are applicable.

Procedural Matters (PM) - Referrals

The following table identifies classes of development / activities that require referral in this Overlay and the applicable referral body. It sets out the purpose of the referral as well as the relevant statutory reference from Schedule 9 of the Planning, Development and Infrastructure (General) Regulations 2017.

Class of Development / Activity	Referral Body		Statutory Reference
None	None	None	None

Hazards (Flooding - Evidence Required) Overlay

Assessment Provisions (AP)

Desired Outcome	
DO 1	Development adopts a precautionary approach to mitigate potential impacts on people, property, infrastructure and the environment from potential flood risk through the appropriate siting and design of development.

Performance Outcomes (PO) and Deemed-to-Satisfy (DTS) Criteria / Designated Performance Feature (DPF)

Page 9 of 28 Printed on 19/09/2022

Performance Outcome

Deemed-to-Satisfy Criteria / Designated Performance Feature

Flood Resilience

PO 1.1

Development is sited, designed and constructed to minimise the risk of entry of potential floodwaters where the entry of flood waters is likely to result in undue damage to or compromise ongoing activities within buildings.

DTS/DPF 1.1

Habitable buildings, commercial and industrial buildings, and buildings used for animal keeping incorporate a finished floor level at least 300mm above:

- (a) the highest point of top of kerb of the primary street
- (b) the highest point of natural ground level at the primary street boundary where there is no kerb

Procedural Matters (PM) - Referrals

The following table identifies classes of development / activities that require referral in this Overlay and the applicable referral body. It sets out the purpose of the referral as well as the relevant statutory reference from Schedule 9 of the Planning, Development and Infrastructure (General) Regulations 2017.

Class of Development / Activity	Referral Body	Purpose of Referral	Statutory Reference
None	None	None	None

Traffic Generating Development Overlay

Assessment Provisions (AP)

	Desired Outcome		
DO 1	Safe and efficient operation of Urban Transport Routes and Major Urban Transport Routes for all road users.		
DO 2	Provision of safe and efficient access to and from urban transport routes and major urban transport routes.		

Performance Outcomes (PO) and Deemed to Satisfy (DTS) / Designated Performance Feature (DPF) Criteria

Performance Outcome **Deemed-to-Satisfy Criteria / Designated Performance Feature** Traffic Generating Development PO 1.1 DTS/DPF 1.1 Development designed to minimise its potential impact on the Access is obtained directly from a State Maintained Road where safety, efficiency and functional performance of the State it involves any of the following types of development: Maintained Road network. (a) land division creating 50 or more additional allotments (b) commercial development with a gross floor area of 10,000m2 or more

Page 10 of 28 Printed on 19/09/2022

(c) retail development with a gross floor area of 2,000m2 or more
(d) a warehouse or transport depot with a gross leasable floor area of 8,000m2 or more
(e) industry with a gross floor area of 20,000m2 or more
(f) educational facilities with a capacity of 250 students or more.
DTS/DPF 1.2
Access is obtained directly from a State Maintained Road where it involves any of the following types of development:
(a) land division creating 50 or more additional allotments
(b) commercial development with a gross floor area of 10,000m2 or more
(c) retail development with a gross floor area of 2,000m2 or more
(d) a warehouse or transport depot with a gross leasable floor area of 8,000m2 or more
(e) industry with a gross floor area of 20,000m2 or more
(f) educational facilities with a capacity of 250 students or more.
DTS/DPF 1.3
Access is obtained directly from a State Maintained Road where it involves any of the following types of development:
(a) land division creating 50 or more additional allotments
(b) commercial development with a gross floor area of 10,000m2 or more
(c) retail development with a gross floor area of 2,000m2 or more
(d) a warehouse or transport depot with a gross leasable floor area of 8,000m2 or more
(e) industry with a gross floor area of 20,000m2 or more
(f) educational facilities with a capacity of 250 students or more.

Procedural Matters (PM) - Referrals

The following table identifies classes of development / activities that require referral in this Overlay and the applicable referral body. It sets out the purpose of the referral as well as the relevant statutory reference from Schedule 9 of the Planning, Development and Infrastructure (General) Regulations 2017.

Class of Development / Activity	Referral Body	Purpose of Referral	Statutory Reference
Except where all of the relevant deemed-to-satisfy criteria are met, any of the following classes of development that are proposed within 250m of a State Maintained Road:	Commissioner of Highways.	To provide expert technical assessment and direction to the Relevant Authority on the safe and efficient operation and management of all roads	Development of a class to which Schedule 9 clause 3 item
 (a) land division creating 50 or more additional allotments (b) commercial development with a gross floor area of 10,000m² or more 		relevant to the Commissioner of Highways as described in the Planning and Design Code.	7 of the Planning, Development and

Page 11 of 28 Printed on 19/09/2022

(c) retail development with a gross floor area of 2,000m ² or more	Infrastructure (General)
(d) a warehouse or transport depot with a gross leasable floor area of 8,000m ² or more	Regulations 2017 applies.
(e) industry with a gross floor area of 20,000m² or more (f) educational facilities with a capacity of 250 students or more.	

Water Resources Overlay

Assessment Provisions (AP)

Desired Outcome		
DO 1	Protection of the quality of surface waters considering adverse water quality impacts associated with projected reductions in rainfall and warmer air temperatures as a result of climate change.	
DO 2	Maintain the conveyance function and natural flow paths of watercourses to assist in the management of flood waters and stormwater runoff.	

Performance Outcomes (PO) and Deemed-to-Satisfy (DTS) Criteria / Designated Performance Feature (DPF)

Performance Outcome	Deemed-to-Satisfy Criteria / Designated Performance Feature
Water Co	atchment
PO 1.1	DTS/DPF 1.1
Watercourses and their beds, banks, wetlands and floodplains (1% AEP flood extent) are not damaged or modified and are retained in their natural state, except where modification is required for essential access or maintenance purposes.	None are applicable.
PO 1.2	DTS/DPF 1.2
Development avoids interfering with the existing hydrology or water regime of swamps and wetlands other than to improve the existing conditions to enhance environmental values.	None are applicable.
PO 1.5	DTS/DPF 1.5
Development that increases surface water run-off includes a suitably sized strip of vegetated land on each side of a watercourse to filter runoff to: (a) reduce the impacts on native aquatic ecosystems (b) minimise soil loss eroding into the watercourse.	A strip of land 20m or more wide measured from the top of existing banks on each side of the watercourse is free from development, livestock use and revegetated with locally indigenous vegetation.
PO 1.6	DTS/DPF 1.6
Development resulting in the depositing or placing of an object or solid material in a watercourse or lake occurs only where it involves any of the following:	None are applicable.

Page 12 of 28 Printed on 19/09/2022

 (a) the construction of an erosion control structure (b) devices or structures used to extract or regulate water flowing in a watercourse (c) devices used for scientific purposes (d) the rehabilitation of watercourses. 	
P01.7 Watercourses, floodplains (1% AEP flood extent) and wetlands protected and enhanced by retaining and protecting existing native vegetation.	DTS/DPF 1.7 None are applicable.
PO 1.8 Watercourses, floodplains (1% AEP flood extent) and wetlands are protected and enhanced by stabilising watercourse banks and reducing sediments and nutrients entering the watercourse.	DTS/DPF 1.8 None are applicable.

Procedural Matters (PM) - Referrals

The following table identifies classes of development / activities that require referral in this Overlay and the applicable referral body. It sets out the purpose of the referral as well as the relevant statutory reference from Schedule 9 of the Planning, Development and Infrastructure (General) Regulations 2017.

Class of Development / Activity	Referral Body		Statutory Reference
None	None	None	None

Part 4 - General Development Policies

Clearance from Overhead Powerlines

Assessment Provisions (AP)

	Desired Outcome
DO 1	Protection of human health and safety when undertaking development in the vicinity of overhead transmission powerlines.

Performance Outcome	Deemed-to-Satisfy Criteria / Designated Performance Feature
P0 1.1 Buildings are adequately separated from aboveground powerlines to minimise potential hazard to people and property.	One of the following is satisfied: (a) a declaration is provided by or on behalf of the applicant to the effect that the proposal would not be contrary to the regulations prescribed for the purposes of section 86 of the Electricity Act 1996 (b) there are no aboveground powerlines adjoining the site that are the subject of the proposed development.

Page 13 of 28 Printed on 19/09/2022

Design

Assessment Provisions (AP)

	Desired Outcome		
DO 1	Develo	opment is:	
	(a)	contextual - by considering, recognising and carefully responding to its natural surroundings or built environment and positively contributes to the character of the immediate area	
	(b)	durable - fit for purpose, adaptable and long lasting	
	(c)	inclusive - by integrating landscape design to optimise pedestrian and cyclist usability, privacy and equitable access, and promoting the provision of quality spaces integrated with the public realm that can be used for access and recreation and help optimise security and safety both internally and within the public realm, for occupants and visitors	
	(d)	sustainable - by integrating sustainable techniques into the design and siting of development and landscaping to improve community health, urban heat, water management, environmental performance, biodiversity and local amenity and to minimise energy consumption.	

Performance Outcome

Deemed-to-Satisfy Criteria / Designated Performance Feature

All development

External Appearance

PO 1.4

Plant, exhaust and intake vents and other technical equipment is integrated into the building design to minimise visibility from the public realm and negative impacts on residential amenity by:

- (a) positioning plant and equipment in unobtrusive locations viewed from public roads and spaces
- (b) screening rooftop plant and equipment from view
- (c) when located on the roof of non-residential development, locating the plant and equipment as far as practicable from adjacent sensitive land uses.

DTS/DPF 1.4

Development does not incorporate any structures that protrude beyond the roofline.

PO 1.5

The negative visual impact of outdoor storage, waste management, loading and service areas is minimised by integrating them into the building design and screening them from public view (such as fencing, landscaping and built form) taking into account the form of development contemplated in the relevant zone.

DTS/DPF 1.5

None are applicable.

On-site Waste Treatment Systems

PO 6.1

Dedicated on-site effluent disposal areas do not include any areas to be used for, or could be reasonably foreseen to be used for, private open space, driveways or car parking.

DTS/DPF 6.1

Effluent disposal drainage areas do not:

 encroach within an area used as private open space or result in less private open space than that specified in Design Table 1 - Private Open Space

Page 14 of 28 Printed on 19/09/2022

(b) use an area also used as a driveway (c) encroach within an area used for on-site car parking or result in less on-site car parking than that specified in Transport, Access and Parking Table 1 - General Off-Street Car Parking Requirements or Table 2 - Off-Street Car Parking Requirements in Designated Areas. Carparking Appearance DTS/DPF 7.1 PO 7.1 Development facing the street is designed to minimise the None are applicable. negative impacts of any semi-basement and undercroft car parking on the streetscapes through techniques such as: (a) limiting protrusion above finished ground level (b) screening through appropriate planting, fencing and mounding (c) limiting the width of openings and integrating them into the building structure. PO 7.2 DTS/DPF 7.2 Vehicle parking areas are appropriately located, designed and None are applicable. constructed to minimise impacts on adjacent sensitive receivers through measures such as ensuring they are attractively developed and landscaped, screen fenced and the like. PO 7.3 DTS/DPF 7.3 Safe, legible, direct and accessible pedestrian connections are None are applicable. provided between parking areas and the development. PO 7.4 DTS/DPF 7.4 Street level vehicle parking areas incorporate tree planting to None are applicable. provide shade and reduce solar heat absorption and reflection. PO 7.5 DTS/DPF 7.5 Street level parking areas incorporate soft landscaping to None are applicable. improve visual appearance when viewed from within the site and from public places. PO 7.6 DTS/DPF 7.6 Vehicle parking areas and associated driveways are landscaped None are applicable. to provide shade and positively contribute to amenity. PO 7.7 DTS/DPF 7.7 Vehicle parking areas and access ways incorporate integrated None are applicable. stormwater management techniques such as permeable or porous surfaces, infiltration systems, drainage swales or rain gardens that integrate with soft landscaping. All non-residential development Water Sensitive Design PO 31.1 DTS/DPF 31.1 None are applicable. Development likely to result in significant risk of export of litter, oil or grease includes stormwater management systems

Page 15 of 28 Printed on 19/09/2022

designed to minimise pollutants entering stormwater.	
PO 31.2	DTS/DPF 31.2
Water discharged from a development site is of a physical, chemical and biological condition equivalent to or better than its pre-developed state.	None are applicable.

Infrastructure and Renewable Energy Facilities

Assessment Provisions (AP)

Desired Outcome		
DO 1	Efficient provision of infrastructure networks and services, renewable energy facilities and ancillary development in a manner that minimises hazard, is environmentally and culturally sensitive and manages adverse visual impacts on natural and rural landscapes and residential amenity.	

Performance Outcomes (PO) and Deemed-to-Satisfy (DTS) Criteria / Designated Performance Feature (DPF)

Performance Outcome	Deemed-to-Satisfy Criteria / Designated Performance Feature
Wastewa	nter Services
PO 12.1	DTS/DPF 12.1
Development is connected to an approved common wastewater disposal service with the capacity to meet the requirements of the intended use. Where this is not available an appropriate onsite service is provided to meet the ongoing requirements of the intended use in accordance with the following: (a) it is wholly located and contained within the allotment of the development it will service (b) in areas where there is a high risk of contamination of surface, ground, or marine water resources from on-site disposal of liquid wastes, disposal systems are included to minimise the risk of pollution to those water resources (c) septic tank effluent drainage fields and other wastewater disposal areas are located away from watercourses and flood prone, sloping, saline or poorly drained land to minimise environmental harm.	allotment of development it will service; and (b) the system will comply with the requirements of the South Australian Public Health Act 2011.
PO 12.2	DTS/DPF 12.2
Effluent drainage fields and other wastewater disposal areas are maintained to ensure the effective operation of waste systems and minimise risks to human health and the environment.	Development is not built on, or encroaches within, an area that is, or will be, required for a sewerage system or waste control system.

Interface between Land Uses

Assessment Provisions (AP)

Page 16 of 28 Printed on 19/09/2022

Desired Outcome

DO 1

Development is located and designed to mitigate adverse effects on or from neighbouring and proximate land uses.

Performance Outcomes (PO) and Deemed-to-Satisfy (DTS) Criteria / Designated Performance Feature (DPF)

Performance Outcome

Deemed-to-Satisfy Criteria / Designated Performance Feature

Hours of Operation

PO 2.1

Non-residential development does not unreasonably impact the amenity of sensitive receivers (or lawfully approved sensitive receivers) or an adjacent zone primarily for sensitive receivers through its hours of operation having regard to:

- (a) the nature of the development
- (b) measures to mitigate off-site impacts
- (c) the extent to which the development is desired in the zone
- (d) measures that might be taken in an adjacent zone primarily for sensitive receivers that mitigate adverse impacts without unreasonably compromising the intended use of that land.

DTS/DPF 2.1

Development operating within the following hours:

Class of Development	Hours of operation
Consulting room	7am to 9pm, Monday to Friday 8am to 5pm, Saturday
Office	7am to 9pm, Monday to Friday 8am to 5pm, Saturday
Shop, other than any one or combination of the following:	7am to 9pm, Monday to Friday 8am to 5pm, Saturday and Sunday
(a) restaurant (b) cellar door in the Productive Rural Landscape Zone, Rural Zone or Rural Horticulture Zone	

Overshadowing

PO 3.1

Overshadowing of habitable room windows of adjacent residential land uses in:

- a neighbourhood-type zone is minimised to maintain access to direct winter sunlight
- b. other zones is managed to enable access to direct winter sunlight.

DTS/DPF 3.1

North-facing windows of habitable rooms of adjacent residential land uses in a neighbourhood-type zone receive at least 3 hours of direct sunlight between 9.00am and 3.00pm on 21 June.

PO 3.2

Overshadowing of the primary area of private open space or communal open space of adjacent residential land uses in:

a. a neighbourhood type zone is minimised to maintain access

DTS/DPF 3.2

Development maintains 2 hours of direct sunlight between 9.00 am and 3.00 pm on 21 June to adjacent residential land uses in a neighbourhood-type zone in accordance with the following:

Page 17 of 28 Printed on 19/09/2022

to direct winter sunlight	a. for ground level private open space, the smaller of the
b. other zones is managed to enable access to direct winter	following:
sunlight.	i. half the existing ground level open space
	or
	ii. 35m2 of the existing ground level open space (with at least
	one of the area's dimensions measuring 2.5m)
	b. for ground level communal open space, at least half of the
	existing ground level open space.

Out of Activity Centre Development

Assessment Provisions (AP)

	Desired Outcome	
D01	, , , , , , , , , , , , , , , , , , , ,	
	convenient access to a range of shopping, administrative, cultural, entertainment and other facilities in a single trip is maintained and reinforced.	

Performance Outcome	Deemed-to-Satisfy Criteria / Designated Performance Feature
	DTS/DPF 1.1
•	None are applicable.
as primary locations for shopping, administrative, cultural, entertainment and community services as a focus for regular social and business gatherings	
in contributing to or maintaining a pattern of development that supports equitable community access to services and facilities.	
	DTS/DPF 1.2
•	None are applicable.
that support the needs of local residents and workers, particularly in underserviced locations	
at the edge of Activities Centres where they cannot readily be accommodated within an existing Activity Centre to expand the range of services on offer and support the role of the Activity Centre.	
	sidential development outside Activity Centres of a scale be that does not diminish the role of Activity Centres: as primary locations for shopping, administrative, cultural, entertainment and community services as a focus for regular social and business gatherings in contributing to or maintaining a pattern of development that supports equitable community access to services and facilities. activity centre non-residential development complements of Centres through the provision of services and facilities: that support the needs of local residents and workers, particularly in underserviced locations at the edge of Activities Centres where they cannot readily be accommodated within an existing Activity Centre to expand the range of services on offer and

Transport, Access and Parking

Assessment Provisions (AP)

Desired Outcome

Page 18 of 28 Printed on 19/09/2022

DO 1

A comprehensive, integrated and connected transport system that is safe, sustainable, efficient, convenient and accessible to all users.

Performance Outcomes (PO) and Deemed-to-Satisfy (DTS) Criteria / Designated Performance Feature (DPF)

Deemed-to-Satisfy Criteria / **Performance Outcome Designated Performance Feature** Movement Systems PO 1.4 DTS/DPF 1.4 Development is sited and designed so that loading, unloading All vehicle manoeuvring occurs onsite. and turning of all traffic avoids interrupting the operation of and queuing on public roads and pedestrian paths. Vehicle Access DTS/DPF 3.1 PO 3.1 Safe and convenient access minimises impact or interruption on The access is: the operation of public roads. provided via a lawfully existing or authorised driveway or access point or an access point for which consent has been granted as part of an application for the division of land or (b) not located within 6m of an intersection of 2 or more roads or a pedestrian activated crossing. PO 3.5 DTS/DPF 3.5 Vehicle access to designated car parking spaces satisfy (a) or Access points are located so as not to interfere with street trees, (b): existing street furniture (including directional signs, lighting, (a) is provided via a lawfully existing or authorised access seating and weather shelters) or infrastructure services to point or an access point for which consent has been maintain the appearance of the streetscape, preserve local granted as part of an application for the division of land amenity and minimise disruption to utility infrastructure assets. (b) where newly proposed, is set back: 0.5m or more from any street furniture, street pole, infrastructure services pit, or other stormwater or utility infrastructure unless consent is provided from the asset owner (ii) 2m or more from the base of the trunk of a street tree unless consent is provided from the tree owner for a lesser distance (iii) 6m or more from the tangent point of an intersection of 2 or more roads outside of the marked lines or infrastructure dedicating a pedestrian crossing. PO 3.6 DTS/DPF 3.6 Driveways and access points are separated and minimised in Driveways and access points: number to optimise the provision of on-street visitor parking (where on-street parking is appropriate). (a) for sites with a frontage to a public road of 20m or less, one access point no greater than 3.5m in width is provided (b) for sites with a frontage to a public road greater than 20m:

Page 19 of 28 Printed on 19/09/2022

Policy24 - Enquiry	
	(i) a single access point no greater than 6m in width is provided or (ii) not more than two access points with a width of 3.5m each are provided.
Vehicle Pa	rking Rates
PO 5.1	DTS/DPF 5.1
Sufficient on-site vehicle parking and specifically marked accessible car parking places are provided to meet the needs of the development or land use having regard to factors that may support a reduced on-site rate such as: (a) availability of on-street car parking (b) shared use of other parking areas (c) in relation to a mixed-use development, where the hours of operation of commercial activities complement the residential use of the site, the provision of vehicle parking may be shared (d) the adaptive reuse of a State or Local Heritage Place.	Development provides a number of car parking spaces on-site at a rate no less than the amount calculated using one of the following, whichever is relevant: (a) Transport, Access and Parking Table 1 - General Off-Street Car Parking Requirements (b) Transport, Access and Parking Table 2 - Off-Street Vehicle Parking Requirements in Designated Areas (c) if located in an area where a lawfully established carparking fund operates, the number of spaces calculated under (a) or (b) less the number of spaces offset by contribution to the fund.
Vehicle Par	rking Areas
PO 6.1 Vehicle parking areas are sited and designed to minimise impact on the operation of public roads by avoiding the use of public roads when moving from one part of a parking area to another.	DTS/DPF 6.1 Movement between vehicle parking areas within the site can occur without the need to use a public road.
PO 6.6 Loading areas and designated parking spaces for service vehicles are provided within the boundary of the site.	DTS/DPF 6.6 Loading areas and designated parking spaces are wholly located within the site.
Bicycle Parking in	Designated Areas
PO 9.1	DTS/DPF 9.1
The provision of adequately sized on-site bicycle parking facilities encourages cycling as an active transport mode.	Areas and / or fixtures are provided for the parking and storage of bicycles at a rate not less than the amount calculated using Transport, Access and Parking Table 3 - Off Street Bicycle

Table 1 - General Off-Street Car Parking Requirements

The following parking rates apply and if located in an area where a lawfully established carparking fund operates, the number of spaces is reduced by an amount equal to the number of spaces offset by contribution to the fund.

Parking Requirements.

Class of Development	Car Parking Rate (unless varied by Table 2 onwards) Where a development comprises more than one development type, then the overall car parking rate will be taken to be the sum of the car parking rates for each development type.
Residential Development	
Detached Dwelling	Dwelling with 1 bedroom (including rooms capable of being used as a bedroom) - 1 space per dwelling.

Page 20 of 28 Printed on 19/09/2022

	Dwelling with 2 or more bedrooms (including rooms capable of being used as a bedroom) - 2 spaces per dwelling, 1 of which is to be covered.
Group Dwelling	Dwelling with 1 or 2 bedrooms (including rooms capable of being used as a bedroom) - 1 space per dwelling.
	Dwelling with 3 or more bedrooms (including rooms capable of being used as a bedroom) - 2 spaces per dwelling, 1 of which is to be covered.
	0.33 spaces per dwelling for visitor parking where development involves 3 or more dwellings.
Residential Flat Building	Dwelling with 1 or 2 bedrooms (including rooms capable of being used as a bedroom) - 1 space per dwelling.
	Dwelling with 3 or more bedrooms (including rooms capable of being used as a bedroom) - 2 spaces per dwelling, 1 of which is to be covered.
	0.33 spaces per dwelling for visitor parking where development involves 3 or more dwellings.
Row Dwelling where vehicle access is from the primary street	Dwelling with 1 bedroom (including rooms capable of being used as a bedroom) - 1 space per dwelling.
	Dwelling with 2 or more bedrooms (including rooms capable of being used as a bedroom) - 2 spaces per dwelling, 1 of which is to be covered.
Row Dwelling where vehicle access is not from the primary street (i.e. rear-loaded)	Dwelling with 1 or 2 bedrooms (including rooms capable of being used as a bedroom) - 1 space per dwelling.
	Dwelling with 3 or more bedrooms (including rooms capable of being used as a bedroom) - 2 spaces per dwelling, 1 of which is to be covered.
Semi-Detached Dwelling	Dwelling with 1 bedroom (including rooms capable of being used as a bedroom) - 1 space per dwelling.
	Dwelling with 2 or more bedrooms (including rooms capable of being used as a bedroom) - 2 spaces per dwelling, 1 of which is to be covered.
Aged / Supported Accommodation	
Retirement village	Dwelling with 1 or 2 bedrooms (including rooms capable of being used as a bedroom) - 1 space per dwelling.
	Dwelling with 3 or more bedrooms (including rooms capable of being used as a bedroom) - 2 spaces per dwelling.
	0.2 spaces per dwelling for visitor parking.
Supported accommodation	0.3 spaces per bed.
Residential Development (Other)	
Ancillary accommodation	No additional requirements beyond those associated with the main dwelling.
Residential park	Dwelling with 1 or 2 bedrooms (including rooms capable of being used as a bedroom) - 1 space per dwelling.
	Dwelling with 3 or more bedrooms (including rooms capable of being used as a bedroom) - 2 spaces per dwelling.
	0.2 spaces per dwelling for visitor parking.
	!

Page 21 of 28 Printed on 19/09/2022

Student accommodation 0.3 spaces per bed.		
Workers' accommodation	0.5 spaces per bed plus 0.2 spaces per bed for visitor parking.	
Workers accommodation	0.3 spaces per bed plus 0.2 spaces per bed for visitor parking.	
Tourist		
Caravan park / tourist park	Parks with 100 sites or less - a minimum of 1 space per 10 sites to be used for accommodation.	
	Parks with more than 100 sites - a minimum of 1 space per 15 sites used for accommodation.	
	A minimum of 1 space for every caravan (permanently fixed to the ground) or cabin.	
Tourist accommodation	1 car parking space per accommodation unit / guest room.	
Commercial Uses		
Auction room/ depot	1 space per 100m ² of building floor area plus an additional 2 spaces.	
Automotive collision repair	3 spaces per service bay.	
Call centre	8 spaces per 100m ² of gross leasable floor area.	
Motor repair station	3 spaces per service bay.	
Office	4 spaces per 100m ² of gross leasable floor area.	
Retail fuel outlet	3 spaces per 100m ² gross leasable floor area.	
Service trade premises	2.5 spaces per 100m ² of gross leasable floor area	
	1 space per 100m ² of outdoor area used for display purposes.	
Shop (no commercial kitchen)	5.5 spaces per 100m ² of gross leasable floor area where not located in an integrated complex containing two or more tenancies (and which may comprise more than one building) where facilities for off-street vehicle parking, vehicle loading and unloading, and the storage and collection of refuse are shared.	
	5 spaces per 100m ² of gross leasable floor area where located in an integrated complex containing two or more tenancies (and which may comprise more than one building) where facilities for off-street vehicle parking, vehicle loading and unloading, and the storage and collection of refuse are shared.	
Shop (in the form of a bulky goods outlet)	2.5 spaces per 100m ² of gross leasable floor area.	
Shop (in the form of a restaurant or involving a commercial kitchen)	Premises with a dine-in service only (which may include a take-away component with no drive-through) - 0.4 spaces per seat.	
	Premises with take-away service but with no seats - 12 spaces per 100m ² of	

Page 22 of 28 Printed on 19/09/2022

	total floor area plus a drive-through queue capacity of ten vehicles measured from the pick-up point.
	Premises with a dine-in and drive-through take-away service - 0.3 spaces per seat plus a drive through queue capacity of 10 vehicles measured from the pick-up point.
Community and Civic Uses	
Childcare centre	0.25 spaces per child
Library	4 spaces per 100m ² of total floor area.
Community facility	10 spaces per 100m ² of total floor area.
Hall / meeting hall	0.2 spaces per seat.
Place of worship	1 space for every 3 visitor seats.
Pre-school	1 per employee plus 0.25 per child (drop off/pick up bays)
Educational establishment	For a primary school - 1.1 space per full time equivalent employee plus 0.25 spaces per student for a pickup/set down area either on-site or on the public realm within 300m of the site.
	For a secondary school - 1.1 per full time equivalent employee plus 0.1 spaces per student for a pickup/set down area either on-site or on the public realm within 300m of the site.
	For a tertiary institution - 0.4 per student based on the maximum number of students on the site at any time.
Health Related Uses	
Hospital	4.5 spaces per bed for a public hospital.
	1.5 spaces per bed for a private hospital.
Consulting room	4 spaces per consulting room excluding ancillary facilities.
Recreational and Entertainment Uses	
Cinema complex	0.2 spaces per seat.
Concert hall / theatre	0.2 spaces per seat.
Hotel	1 space for every 2m ² of total floor area in a public bar plus 1 space for every 6m ² of total floor area available to the public in a lounge, beer garden plus 1 space per 2 gaming machines, plus 1 space per 3 seats in a restaurant.

Page 23 of 28 Printed on 19/09/2022

Indoor recreation facility	 6.5 spaces per 100m² of total floor area for a Fitness Centre 4.5 spaces per 100m² of total floor area for all other Indoor recreation facilities. 	
Industry/Employment Uses		
Fuel depot	1.5 spaces per 100m ² total floor area	
	1 spaces per 100m ² of outdoor area used for fuel depot activity purposes.	
Industry	1.5 spaces per 100m ² of total floor area.	
Store	0.5 spaces per 100m ² of total floor area.	
Timber yard	1.5 spaces per 100m ² of total floor area	
	1 space per 100m ² of outdoor area used for display purposes.	
Warehouse	0.5 spaces per 100m ² total floor area.	
Other Uses		
Funeral Parlour	1 space per 5 seats in the chapel plus 1 space for each vehicle operated by the parlour.	
Radio or Television Station	5 spaces per 100m ² of total building floor area.	

Table 2 - Off-Street Car Parking Requirements in Designated Areas

The following parking rates apply in any zone, subzone or other area described in the 'Designated Areas' column subject to the following:

- (a) the location of the development is unable to satisfy the requirements of Table 2 Criteria (other than where a location is exempted from the application of those criteria) or
- (b) the development satisfies Table 2 Criteria (or is exempt from those criteria) and is located in an area where a lawfully established carparking fund operates, in which case the number of spaces are reduced by an amount equal to the number of spaces offset by contribution to the fund.

Class of Development	Car Parking Rate Where a development comprises more than one development type, then the overall car parking rate will be taken to be the sum of the car parking rates for each development type.		Designated Areas
	Minimum number of spaces Maximum number of spaces		
Development generally	Development generally		
All classes of	No minimum.	No maximum except in the	Capital City Zone

Page 24 of 28 Printed on 19/09/2022

development		Primary Pedestrian Area identified in the Primary Pedestrian Area Concept Plan, where the maximum is: 1 space for each dwelling with a total floor area less than 75 square metres 2 spaces for each dwelling with a total floor area between 75 square metres and 150 square metres 3 spaces for each dwelling with a total floor area greater than 150 square metres. Residential flat building or Residential component of a multi-storey building: 1 visitor space for each 6 dwellings.	City Main Street Zone City Riverbank Zone Adelaide Park Lands Zone Business Neighbourhood Zone (within the City of Adelaide) The St Andrews Hospital Precinct Subzone and Women's and Children's Hospital Precinct Subzone of the Community Facilities Zone
Non-residential develop	ment		
Non-residential development excluding tourist accommodation	3 spaces per 100m ² of gross leasable floor area.	5 spaces per 100m ² of gross leasable floor area.	City Living Zone Urban Corridor (Boulevard) Zone Urban Corridor (Business) Zone Urban Corridor (Living) Zone Urban Corridor (Main Street) Zone Urban Neighbourhood Zone
Non-residential development excluding tourist accommodation	3 spaces per 100m ² of gross leasable floor area.	6 spaces per 100m ² of gross leasable floor area.	Strategic Innovation Zone Suburban Activity Centre Zone Suburban Business Zone Business Neighbourhood Zone Suburban Main Street Zone Urban Activity Centre Zone
Tourist accommodation	1 space for every 4 bedrooms up to 100 bedrooms plus 1 space for every 5 bedrooms over 100 bedrooms	1 space per 2 bedrooms up to 100 bedrooms and 1 space per 4 bedrooms over 100 bedrooms	City Living Zone Urban Activity Centre Zone Urban Corridor (Boulevard) Zone Urban Corridor (Business) Zone Urban Corridor (Living) Zone Urban Corridor (Main Street) Zone Urban Neighbourhood Zone

Page 25 of 28 Printed on 19/09/2022

Residential development			
Residential component of a multi-storey building	Dwelling with no separate bedroom -0.25 spaces per dwelling 1 bedroom dwelling - 0.75 spaces per dwelling 2 bedroom dwelling - 1 space per dwelling 3 or more bedroom dwelling - 1.25 spaces per dwelling 0.25 spaces per dwelling for visitor parking.	None specified.	City Living Zone Strategic Innovation Zone Urban Activity Centre Zone Urban Corridor (Boulevard) Zone Urban Corridor (Business) Zone Urban Corridor (Living) Zone Urban Corridor (Main Street) Zone Urban Neighbourhood Zone
Residential flat building	Dwelling with no separate bedroom -0.25 spaces per dwelling 1 bedroom dwelling - 0.75 spaces per dwelling 2 bedroom dwelling - 1 space per dwelling 3 or more bedroom dwelling - 1.25 spaces per dwelling 0.25 spaces per dwelling for visitor parking.	None specified.	City Living Zone Urban Activity Centre Zone Urban Corridor (Boulevard) Zone Urban Corridor (Business) Zone Urban Corridor (Living) Zone Urban Corridor (Main Street) Zone Urban Neighbourhood Zone

Table 2 - Criteria:

The following criteria are used in conjunction with Table 2. The 'Exception' column identifies locations where the criteria do not apply and the car parking rates in Table 2 are applicable.

Criteria		Exceptions
Metro	esignated area is wholly located within politan Adelaide and any part of the opment site satisfies one or more of the ing:	(a) All zones in the City of Adelaide (b) Strategic Innovation Zone in the following locations: (i) City of Burnside (ii) City of Marion (iii) City of Mitcham
(a) (b) (c) (d) (e)	is within 200 metres of any section of road reserve along which a bus service operates as a high frequency public transit service ⁽²⁾ is within 400 metres of a bus interchange ⁽¹⁾ is within 400 metres of an O-Bahn interchange ⁽¹⁾ is within 400 metres of a passenger rail station ⁽¹⁾ is within 400 metres of a passenger	(c) Urban Corridor (Boulevard) Zone (d) Urban Corridor (Business) Zone (e) Urban Corridor (Living) Zone (f) Urban Corridor (Main Street) Zone (g) Urban Neighbourhood Zone

Page 26 of 28 Printed on 19/09/2022

tram station ⁽¹⁾ (f) is within 400 metres of the Adelaide Parklands.

[NOTE(S): (1)Measured from an area that contains any platform(s), shelter(s) or stop(s) where people congregate for the purpose waiting to board a bus, tram or train, but does not include areas used for the parking of vehicles. (2) A high frequency public transit service is a route serviced every 15 minutes between 7.30am and 6.30pm Monday to Friday and every 30 minutes at night, Saturday, Sunday and public holidays until 10pm.]

Table 3 - Off-Street Bicycle Parking Requirements

The bicycle parking rates apply within designated areas located within parts of the State identified in the Schedule to Table 3.

Class of Development	Bicycle Parking Rate
	Where a development comprises more than one development type, then the overall bicycle parking rate will be taken to be the sum of the bicycle parking rates for each development type.
Consulting Room	1 space per 20 employees plus 1 space per 20 consulting rooms for customers.
Educational establishment	For a secondary school - 1 space per 20 full-time time employees plus 10 percent of the total number of employee spaces for visitors. For tertiary education - 1 space per 20 employees plus 1 space per 10 full time students.
Hospital	1 space per 15 beds plus 1 space per 30 beds for visitors.
Indoor recreation facility	1 space per 4 employees plus 1 space per 200m ² of gross leasable floor area for visitors.
Licensed Premises	1 per 20 employees, plus 1 per 60 square metres total floor area, plus 1 per 40 square metres of bar floor area, plus 1 per 120 square metres lounge and beer garden floor area, plus 1 per 60 square metres dining floor area, plus 1 per 40 square metres gaming room floor area.
Office	1 space for every 200m ² of gross leasable floor area plus 2 spaces plus 1 space per 1000m ² of gross leasable floor area for visitors.
Pre-school	1 space per 20 full time employees plus 1 space per 40 full time children.
Recreation area	1 per 1500 spectator seats for employees plus 1 per 250 visitor and customers.
Residential flat building	Within the City of Adelaide 1 for every dwelling for residents with a total floor area less than 150 square metres, 2 for every dwelling for residents with a total floor area greater than 150 square metres, plus 1 for every 10 dwellings for visitors, and in all other cases 1 space for every 4 dwellings for residents plus 1 for every 10 dwellings for visitors.
Residential component of a multi-storey building	Within the City of Adelaide 1 for every dwelling for residents with a total floor area less than 150 square metres, 2 for every dwelling for residents with a total floor area greater than 150 square metres, plus 1 for every 10 dwellings for visitors, and in all other cases 1 space for every 4 dwellings for residents plus 1 space for every 10 dwellings for visitors.

Page 27 of 28 Printed on 19/09/2022

Shop	1 space for every 300m ² of gross leasable floor area plus 1 space for every 600m ² of gross leasable floor area for customers.
Tourist accommodation	1 space for every 20 employees plus 2 for the first 40 rooms and 1 for every additional 40 rooms for visitors.

Schedule to Table 3

Designated Area	Relevant part of the State
	The bicycle parking rate applies to a designated area located in a relevant part of the State described below.
All zones	City of Adelaide
Business Neighbourhood Zone	Metropolitan Adelaide
Strategic Innovation Zone	
Suburban Activity Centre Zone	
Suburban Business Zone	
Suburban Main Street Zone	
Urban Activity Centre Zone	
Urban Corridor (Boulevard) Zone	
Urban Corridor (Business) Zone	
Urban Corridor (Living) Zone	
Urban Corridor (Main Street) Zone	
Urban Neighbourhood Zone	

Page 28 of 28 Printed on 19/09/2022

228 SMART RD ST AGNES SA 5097

Address:

Click to view a detailed interactive SAILIS in SAILIS

To view a detailed interactive property map in SAPPA click on the map below



Property Zoning Details

Local Variation (TNV)

Maximum Building Height (Metres) (Maximum building height is 9m)

Maximum Building Height (Levels) (Maximum building height is 2 levels)

Overlay

Affordable Housing

Hazards (Flooding)

Hazards (Flooding - Evidence Required)

Prescribed Wells Area

Regulated and Significant Tree

Stormwater Management

Traffic Generating Development

Urban Tree Canopy

Water Resources

Zone

Employment

General Neighbourhood

Selected Development(s)

Fence

This development may be subject to multiple assessment pathways. Please review the document below to determine which pathway may be applicable based on the proposed development compliances to standards.

development compliances to standards.

If no assessment pathway is shown this mean the proposed development will default to performance assessed. Please contact your local council in this instance. Refer to Part 1 - Rules of Interpretation - Determination of Classes of Development

Property Policy Information for above selection

Fence - Code Assessed - Performance Assessed

Page 1 of 7 Printed on 19/09/2022

Part 2 - Zones and Sub Zones

General Neighbourhood Zone

Assessment Provisions (AP)

Desired Outcome		
DO 1	Low-rise, low and medium-density housing that supports a range of needs and lifestyles located within easy reach of services and facilities. Employment and community service uses contribute to making the neighbourhood a convenient place to live without compromising residential amenity.	

Table 5 - Procedural Matters (PM) - Notification

The following table identifies, pursuant to section 107(6) of the *Planning, Development and Infrastructure Act 2016*, classes of performance assessed development that are excluded from notification. The table also identifies any exemptions to the placement of notices when notification is required.

Interpretation

Notification tables exclude the classes of development listed in Column A from notification provided that they do not fall within a corresponding exclusion prescribed in Column B.

Where a development or an element of a development falls within more than one class of development listed in Column A, it will be excluded from notification if it is excluded (in its entirety) under any of those classes of development. It need not be excluded under all applicable classes of development.

Where a development involves multiple performance assessed elements, all performance assessed elements will require notification (regardless of whether one or more elements are excluded in the applicable notification table) unless every performance assessed element of the application is excluded in the applicable notification table, in which case the application will not require notification.

Class	of Development	Exceptions (Column B)	
(Colun	nn A)		
1.	Development which, in the opinion of the relevant authority, is of a minor nature only and will not unreasonably impact on the owners or occupiers of land in the locality of the site of the development.	None specified.	
2.	All development undertaken by: (a) the South Australian Housing Trust either individually or jointly with other persons or bodies or (b) a provider registered under the Community Housing National Law participating in a program relating to the renewal of housing endorsed by the South Australian Housing Trust.	 residential flat building(s) of 3 or more building levels the demolition of a State or Local Heritage Place the demolition of a building (except an ancillary building) in a Historic Area Overlay. 	
3.	Any development involving any of the following (or of any combination of any of the following): (a) air handling unit, air conditioning system or exhaust fan (b) ancillary accommodation (c) building work on railway land	Except development that: 1. does not satisfy General Neighbourhood Zone DTS/DPF 4.1 or 2. involves a building wall (or structure) that is proposed to	

Page 2 of 7 Printed on 19/09/2022

- (d) carport
- (e) deck
- (f) dwelling
- (g) dwelling addition
- (h) fence
- (i) outbuilding
- (j) pergola
- (k) private bushfire shelter
- (I) residential flat building
- (m) retaining wall
- (n) retirement facility
- (o) shade sail
- (p) solar photovoltaic panels (roof mounted)
- (q) student accommodation
- (r) supported accommodation
- (s) swimming pool or spa pool
- (t) verandah
- (u) water tank.

be situated on (or abut) an allotment boundary (not being a boundary with a primary street or secondary street or an excluded boundary) and:

- (a) the length of the proposed wall (or structure) exceeds 11.5m (other than where the proposed wall abuts an existing wall or structure of greater length on the adjoining allotment)
- (b) the height of the proposed wall (or post height) exceeds 3m measured from the top of footings (other than where the proposed wall (or post) abuts an existing wall or structure of greater height on the adjoining allotment).

- 4. Any development involving any of the following (or of any combination of any of the following):
 - (a) consulting room
 - (b) office
 - (c) shop.

Except development that:

- 1. does not satisfy any of the following:
 - (a) General Neighbourhood Zone DTS/DPF 1.4
 - (b) General Neighbourhood Zone DTS/DPF 4.1

or

- involves a building wall (or structure) that is proposed to be situated on (or abut) an allotment boundary (not being a boundary with a primary street or secondary street or an excluded boundary) and:
 - (a) the length of the proposed wall (or structure) exceeds 11.5m (other than where the proposed wall abuts an existing wall or structure of greater length on the adjoining allotment)
 - (b) the height of the proposed wall (or post height) exceeds 3m measured from the top of footings (other than where the proposed wall (or post) abuts an existing wall or structure of greater height on the adjoining allotment).
- 5. Any development involving any of the following (or of any combination of any of the following):
 - (a) internal building works
 - (b) land division
 - (c) recreation area
 - (d) replacement building
 - (e) temporary accommodation in an area affected by bushfire
 - (f) tree damaging activity.

None specified.

6. Alteration of or addition to any development involving the following (or of any combination of any of the following):

(a) community facility

Except development that does not satisfy General Neighbourhood Zone DTS/DPF 1.5.

Page 3 of 7 Printed on 19/09/2022

olicy24 - Linquiry		
(b) educational establishment(c) pre-school.		
7. Demolition.	 the demolition of a State or Local Heritage Place the demolition of a building (except an ancillary building) in a Historic Area Overlay. 	
Placement of Notices - Exemptions for Performance Assessed Development		
None specified.		
Placement of Notices - Exemptions for Restricted Development		

Part 3 - Overlays

None specified.

Hazards (Flooding) Overlay

Assessment Provisions (AP)

Desired Outcome		
D		Impacts on people, property, infrastructure and the environment from high flood risk are minimised by retaining areas free from development, and minimising intensification where development has occurred.

Performance Outcomes (PO) and Deemed-to-Satisfy (DTS) Criteria / Designated Performance Feature (DPF)

Performance Outcome	Deemed-to-Satisfy Criteria / Designated Performance Feature	
Flood Resilience		
PO 3.6	DTS/DPF 3.6	
Fences do not unreasonably impede floodwaters.	A post and wire fence (other than a chain mesh fence).	

Procedural Matters (PM) - Referrals

The following table identifies classes of development / activities that require referral in this Overlay and the applicable referral body. It sets out the purpose of the referral as well as the relevant statutory reference from Schedule 9 of the Planning, Development and Infrastructure (General) Regulations 2017.

Class of Development / Activity	Referral Body		Statutory Reference
None	None	None	None

Page 4 of 7 Printed on 19/09/2022

Water Resources Overlay

Assessment Provisions (AP)

Desired Outcome		
DO 1	Protection of the quality of surface waters considering adverse water quality impacts associated with projected reductions in rainfall and warmer air temperatures as a result of climate change.	
DO 2	Maintain the conveyance function and natural flow paths of watercourses to assist in the management of flood waters and stormwater runoff.	

Performance Outcomes (PO) and Deemed-to-Satisfy (DTS) Criteria / Designated Performance Feature (DPF)

Performance Outcome	Deemed-to-Satisfy Criteria / Designated Performance Feature
Water Ca	atchment
PO 1.1	DTS/DPF 1.1
Watercourses and their beds, banks, wetlands and floodplains (1% AEP flood extent) are not damaged or modified and are retained in their natural state, except where modification is required for essential access or maintenance purposes.	None are applicable.
PO 1.4	DTS/DPF 1.4
Watercourses, areas of remnant native vegetation, or areas prone to erosion that are capable of natural regeneration are fenced off to limit stock access.	None are applicable.
PO 1.7	DTS/DPF 1.7
Watercourses, floodplains (1% AEP flood extent) and wetlands protected and enhanced by retaining and protecting existing native vegetation.	None are applicable.

Procedural Matters (PM) - Referrals

The following table identifies classes of development / activities that require referral in this Overlay and the applicable referral body. It sets out the purpose of the referral as well as the relevant statutory reference from Schedule 9 of the Planning, Development and Infrastructure (General) Regulations 2017.

Class of Development / Activity	Referral Body		Statutory Reference
None	None	None	None

Part 4 - General Development Policies

Clearance from Overhead Powerlines

Page 5 of 7 Printed on 19/09/2022

Assessment Provisions (AP)

	Desired Outcome
DO 1	Protection of human health and safety when undertaking development in the vicinity of overhead transmission powerlines.

Performance Outcome	Deemed-to-Satisfy Criteria / Designated Performance Feature
Buildings are adequately separated from aboveground powerlines to minimise potential hazard to people and property.	One of the following is satisfied: (a) a declaration is provided by or on behalf of the applicant to the effect that the proposal would not be contrary to the regulations prescribed for the purposes of section 86 of the Electricity Act 1996 (b) there are no aboveground powerlines adjoining the site that are the subject of the proposed development.

Design in Urban Areas

Assessment Provisions (AP)

Desired Outcome				
DO 1	Development is:			
	(a) (b)	contextual - by considering, recognising and carefully responding to its natural surroundings or built environment and positively contributing to the character of the locality durable - fit for purpose, adaptable and long lasting		
	(c)	inclusive - by integrating landscape design to optimise pedestrian and cyclist usability, privacy and equitable access and promoting the provision of quality spaces integrated with the public realm that can be used for access and recreation and help optimise security and safety both internally and within the public realm, for occupants and visitors		
	(d)	sustainable - by integrating sustainable techniques into the design and siting of development and landscaping to improve community health, urban heat, water management, environmental performance, biodiversity and local amenity and to minimise energy consumption.		

Performance Outcome Designated Performance Feature All Development Fences and walls PO 9.1 Fences, walls and retaining walls of sufficient height maintain privacy and security without unreasonably impacting visual amenity and adjoining land's access to sunlight or the amenity of

Page 6 of 7 Printed on 19/09/2022

	~ 4	_		
Poli	cv24	- E	na	Iuir

public places.	

Page 7 of 7 Printed on 19/09/2022

228 SMART RD ST AGNES SA 5097

Address:

Click to view a detailed interactive SAILIS in SAILIS

To view a detailed interactive property map in SAPPA click on the map below



Property Zoning Details

Local Variation (TNV)

Maximum Building Height (Metres) (Maximum building height is 9m)

Maximum Building Height (Levels) (Maximum building height is 2 levels)

Overlay

Affordable Housing

Hazards (Flooding)

Hazards (Flooding - Evidence Required)

Prescribed Wells Area

Regulated and Significant Tree

Stormwater Management

Traffic Generating Development

Urban Tree Canopy

Water Resources

Zone

Employment

General Neighbourhood

Selected Development(s)

Outbuilding

This development may be subject to multiple assessment pathways. Please review the document below to determine which pathway may be applicable based on the proposed development compliances to standards.

development compliances to standards.

If no assessment pathway is shown this mean the proposed development will default to performance assessed. Please contact your local council in this instance. Refer to Part 1 - Rules of Interpretation - Determination of Classes of Development

Property Policy Information for above selection

Outbuilding - Code Assessed - Performance Assessed

Page 1 of 12 Printed on 19/09/2022

Part 2 - Zones and Sub Zones

General Neighbourhood Zone

Assessment Provisions (AP)

	Desired Outcome		
DO 1	Low-rise, low and medium-density housing that supports a range of needs and lifestyles located within easy reach of services and facilities. Employment and community service uses contribute to making the neighbourhood a convenient place to live without compromising residential amenity.		

Performance Outcomes (PO) and Deemed to Satisfy (DTS) / Designated Performance Feature (DPF) Criteria

Performance Outcome	Deemed-to-Satisfy Criteria / Designated Performance Feature	
	Coverage 	
P0 3.1	DTS/DPF 3.1	
Building footprints allow sufficient space around buildings to limit visual impact, provide an attractive outlook and access to light and ventilation.	The development does not result in site coverage exceeding 60%.	
Ancillary Buildi	ngs and Structures	
PO 11.1	DTS/DPF 11.1	
Residential ancillary buildings are sited and designed to not detract from the streetscape or appearance of primary residential buildings on the site or neighbouring properties.	(a) are ancillary to a dwelling erected on the same site (b) have a floor area not exceeding 60m2 (c) are not constructed, added to or altered so that any part is situated: (i) in front of any part of the building line of the dwelling to which it is ancillary or (ii) within 900mm of a boundary of the allotment with a secondary street (if the land has boundaries on two or more roads) (d) in the case of a garage or carport, the garage or carport (i) is set back at least 5.5m from the boundary of the primary street (ii) have a door / opening not exceeding: A. for dwellings of single building level - 7m in width or 50% of the site frontage whichever is the lesser B. for dwellings comprising two or more building levels at the building line fronting the same public street - 7m in width	
	(e) if situated on a boundary (not being a boundary with a primary street or secondary street), do not exceed a length of 11.5m unless:	

- a longer wall or structure exists on the adjacent site and is situated on the same allotment boundary and
- (ii) the proposed wall or structure will be built along the same length of boundary as the existing adjacent wall or structure to the same or lesser extent
- (f) if situated on a boundary of the allotment (not being a boundary with a primary street or secondary street), all walls or structures on the boundary will not exceed 45% of the length of that boundary
- (g) will not be located within 3m of any other wall along the same boundary unless on an adjacent site on that boundary there is an existing wall of a building that would be adjacent to or about the proposed wall or structure
- (h) have a wall height or post height not exceeding 3m (and not including a gable end)
- (i) have a roof height where no part of the roof is more than 5m above the natural ground level
- (j) if clad in sheet metal, is pre-colour treated or painted in a non-reflective colour
- (k) retains a total area of soft landscaping in accordance with (i) or (ii), whichever is less:
- (i) a total area as determined by the following table:

Dwelling site area (or in the case of residential flat building or group dwelling(s), average site area) (m ²)	Minimum percentage of site
<150	10%
150-200	15%
201-450	20%
>450	25%

the amount of existing soft landscaping prior to the development occurring.

PO 11.2

Ancillary buildings and structures do not impede on-site functional requirements such as private open space provision, car parking requirements or result in over-development of the site.

DTS/DPF 11.2

Ancillary buildings and structures do not result in:

- (a) less private open space than specified in Design in Urban Areas Table 1 Private Open Space
- (b) less on-site car parking than specified in Transport, Access and Parking Table 1 - General Off-Street Car Parking Requirements or Table 2 - Off-Street Car Parking Requirements in Designated Areas.

Table 5 - Procedural Matters (PM) - Notification

The following table identifies, pursuant to section 107(6) of the *Planning, Development and Infrastructure Act 2016*, classes of performance assessed development that are excluded from notification. The table also identifies any exemptions to the placement of

Page 3 of 12 Printed on 19/09/2022

notices when notification is required.

Interpretation

Notification tables exclude the classes of development listed in Column A from notification provided that they do not fall within a corresponding exclusion prescribed in Column B.

Where a development or an element of a development falls within more than one class of development listed in Column A, it will be excluded from notification if it is excluded (in its entirety) under any of those classes of development. It need not be excluded under all applicable classes of development.

Where a development involves multiple performance assessed elements, all performance assessed elements will require notification (regardless of whether one or more elements are excluded in the applicable notification table) unless every performance assessed element of the application is excluded in the applicable notification table, in which case the application will not require notification.

Class of D	pevelopment	Exceptions
(Column A	A)	(Column B)
au un	evelopment which, in the opinion of the relevant athority, is of a minor nature only and will not a nreasonably impact on the owners or occupiers of and in the locality of the site of the development.	None specified.
2. All	I development undertaken by: (a) the South Australian Housing Trust either individually or jointly with other persons or bodies or (b) a provider registered under the Community Housing National Law participating in a program relating to the renewal of housing endorsed by the South Australian Housing Trust.	 residential flat building(s) of 3 or more building levels the demolition of a State or Local Heritage Place the demolition of a building (except an ancillary building) in a Historic Area Overlay.
	ny development involving any of the following (or of my combination of any of the following): (a) air handling unit, air conditioning system or exhaust fan (b) ancillary accommodation (c) building work on railway land (d) carport (e) deck (f) dwelling (g) dwelling addition (h) fence (i) outbuilding (j) pergola (k) private bushfire shelter (l) residential flat building (m) retaining wall (n) retirement facility (o) shade sail (p) solar photovoltaic panels (roof mounted) (q) student accommodation (r) supported accommodation	Except development that: 1. does not satisfy General Neighbourhood Zone DTS/DPF 4.1 or 2. involves a building wall (or structure) that is proposed to be situated on (or abut) an allotment boundary (not being a boundary with a primary street or secondary street or an excluded boundary) and: (a) the length of the proposed wall (or structure) exceeds 11.5m (other than where the proposed wall abuts an existing wall or structure of greater length on the adjoining allotment) or (b) the height of the proposed wall (or post height) exceeds 3m measured from the top of footings (other than where the proposed wall (or post) abuts an existing wall or structure of greater height on the adjoining allotment).

Page 4 of 12 Printed on 19/09/2022

None specified.

Placement of Notices - Exemptions for Restricted Development

Page 5 of 12 Printed on 19/09/2022

None specified.

Part 3 - Overlays

Hazards (Flooding) Overlay

Assessment Provisions (AP)

	Desired Outcome
DO 1	Impacts on people, property, infrastructure and the environment from high flood risk are minimised by retaining areas free from development, and minimising intensification where development has occurred.

Performance Outcomes (PO) and Deemed-to-Satisfy (DTS) Criteria / Designated Performance Feature (DPF)

Performance Outcome	Deemed-to-Satisfy Criteria / Designated Performance Feature
Flood R	esilience
PO 3.1	DTS/DPF 3.1
Development avoids the need for flood protection works.	None are applicable.
PO 3.2	DTS/DPF 3.2
Development does not cause unacceptable impacts on any adjoining property by the diversion of flood waters or an increase in flood velocity or flood level.	None are applicable.
PO 3.3	DTS/DPF 3.3
Development does not impede the flow of floodwaters through the allotment or the surrounding land, or cause an unacceptable loss of flood storage.	None are applicable.
PO 3.4	DTS/DPF 3.4
Development avoids frequently flooded or high velocity areas, other than where it is part of a flood mitigation scheme to reduce flood impact.	Other than a recreation area, development is located outside of the 5% AEP principal flow path.
Environmen	tal Protection
PO 4.1	DTS/DPF 4.1
Buildings and structures used either partly or wholly to contain or store hazardous materials are designed to prevent spills or leaks leaving the confines of the building during a 1% AEP flood event to avoid potential environmental harm.	Development involving the storage or disposal of hazardous materials is wholly located outside of the 1% AEP flood plain or flow path.
PO 4.2	DTS/DPF 4.2
Development does not create or aggravate the potential for	None are applicable.

Page 6 of 12 Printed on 19/09/2022

Policy24 - Enquiry	
erosion or siltation or lead to the destruction of vegetation during a flood.	
Site Ear	thworks
PO 5.1	DTS/DPF 5.1
The depth and extent of filling required to raise the finished floor level of a building does not cause unacceptable impact on any adjoining property by diversion of flood waters, an increase in flood velocity or flood level, or an unacceptable loss of flood storage.	None are applicable.
PO 5.2	DTS/DPF 5.2
Driveways, access tracks and parking areas are designed and constructed to minimise excavation and filling.	Filling for ancillary purposes: (a) does not exceed 300mm above existing ground level (b) is no more than 5m wide.
Acc	cess
P0 6.1	DTS/DPF 6.1
Development does not occur on land:	None are applicable.
 (a) from which evacuation to areas not vulnerable to flood risk is not possible during a 1% AEP flood event (b) which cannot be accessed by emergency services vehicles or essential utility service vehicles during a 1% AEP flood event. 	
P0 6.2	DTS/DPF 6.2
Access driveways and tracks to significant development (i.e. dwellings, places of work, etc.) consist of a safe, all-weather trafficable surface that is accessible during a 1% AEP flood event.	None are applicable.

Procedural Matters (PM) - Referrals

The following table identifies classes of development / activities that require referral in this Overlay and the applicable referral body. It sets out the purpose of the referral as well as the relevant statutory reference from Schedule 9 of the Planning, Development and Infrastructure (General) Regulations 2017.

Class of Development / Activity	Referral Body		Statutory Reference
None	None	None	None

Water Resources Overlay

Assessment Provisions (AP)

	Desired Outcome
DO 1	Protection of the quality of surface waters considering adverse water quality impacts associated with projected reductions in rainfall and warmer air temperatures as a result of climate change.

Page 7 of 12 Printed on 19/09/2022

DO 2

Maintain the conveyance function and natural flow paths of watercourses to assist in the management of flood waters and stormwater runoff.

Performance Outcomes (PO) and Deemed-to-Satisfy (DTS) Criteria / Designated Performance Feature (DPF)

Performance Outcome	Deemed-to-Satisfy Criteria / Designated Performance Feature
Water C	atchment
PO 1.1	DTS/DPF 1.1
Watercourses and their beds, banks, wetlands and floodplains (1% AEP flood extent) are not damaged or modified and are retained in their natural state, except where modification is required for essential access or maintenance purposes.	None are applicable.
PO 1.2	DTS/DPF 1.2
Development avoids interfering with the existing hydrology or water regime of swamps and wetlands other than to improve the existing conditions to enhance environmental values.	None are applicable.
PO 1.5	DTS/DPF 1.5
Development that increases surface water run-off includes a suitably sized strip of vegetated land on each side of a watercourse to filter runoff to: (a) reduce the impacts on native aquatic ecosystems (b) minimise soil loss eroding into the watercourse.	A strip of land 20m or more wide measured from the top of existing banks on each side of the watercourse is free from development, livestock use and revegetated with locally indigenous vegetation.
PO 1.6	DTS/DPF 1.6
Development resulting in the depositing or placing of an object or solid material in a watercourse or lake occurs only where it involves any of the following:	None are applicable.
(a) the construction of an erosion control structure (b) devices or structures used to extract or regulate water flowing in a watercourse (c) devices used for scientific purposes (d) the rehabilitation of watercourses.	
PO 1.7	DTS/DPF 1.7
Watercourses, floodplains (1% AEP flood extent) and wetlands protected and enhanced by retaining and protecting existing native vegetation.	None are applicable.
PO 1.8	DTS/DPF 1.8
Watercourses, floodplains (1% AEP flood extent) and wetlands are protected and enhanced by stabilising watercourse banks and reducing sediments and nutrients entering the watercourse.	None are applicable.

Procedural Matters (PM) - Referrals

The following table identifies classes of development / activities that require referral in this Overlay and the applicable referral body. It

Page 8 of 12 Printed on 19/09/2022

sets out the purpose of the referral as well as the relevant statutory reference from Schedule 9 of the Planning, Development and Infrastructure (General) Regulations 2017.

Class of Development / Activity	Referral Body	-	Statutory Reference
None	None	None	None

Part 4 - General Development Policies

Clearance from Overhead Powerlines

Assessment Provisions (AP)

	Desired Outcome
DO 1	Protection of human health and safety when undertaking development in the vicinity of overhead transmission powerlines.

Performance Outcome	Deemed-to-Satisfy Criteria / Designated Performance Feature
PO 1.1 Buildings are adequately separated from aboveground powerlines to minimise potential hazard to people and property.	One of the following is satisfied: (a) a declaration is provided by or on behalf of the applicant to the effect that the proposal would not be contrary to the regulations prescribed for the purposes of section 86 of the <i>Electricity Act 1996</i> (b) there are no aboveground powerlines adjoining the site that are the subject of the proposed development.

Design in Urban Areas

Assessment Provisions (AP)

	Desired Outcome		
DO 1		Develo	pment is:
		(a)	contextual - by considering, recognising and carefully responding to its natural surroundings or built environment and positively contributing to the character of the locality
		(b)	durable - fit for purpose, adaptable and long lasting
		(c)	inclusive - by integrating landscape design to optimise pedestrian and cyclist usability, privacy and equitable access and promoting the provision of quality spaces integrated with the public realm that can be used for access and recreation and help optimise security and safety both internally and within the public realm, for occupants and visitors
		(d)	sustainable - by integrating sustainable techniques into the design and siting of development and landscaping to improve community health, urban heat, water management, environmental performance, biodiversity and local amenity and to minimise energy consumption.

Page 9 of 12 Printed on 19/09/2022

Performance Outcome

Deemed-to-Satisfy Criteria / Designated Performance Feature

All Development

All Development			
Earthworks and sloping land			
PO 8.1	DTS/DPF 8.1		
Development, including any associated driveways and access tracks, minimises the need for earthworks to limit disturbance to natural topography.	Development does not involve any of the following: (a) excavation exceeding a vertical height of 1m (b) filling exceeding a vertical height of 1m (c) a total combined excavation and filling vertical height of 2m or more.		
PO 8.2	DTS/DPF 8.2		
Driveways and access tracks designed and constructed to allow safe and convenient access on sloping land.	Driveways and access tracks on sloping land (with a gradient exceeding 1 in 8) satisfy (a) and (b): (a) do not have a gradient exceeding 25% (1-in-4) at any point along the driveway (b) are constructed with an all-weather trafficable surface.		
PO 8.3	DTS/DPF 8.3		
Driveways and access tracks on sloping land (with a gradient exceeding 1 in 8):	None are applicable.		
 (a) do not contribute to the instability of embankments and cuttings (b) provide level transition areas for the safe movement of people and goods to and from the development (c) are designed to integrate with the natural topography of the land. 			
PO 8.4	DTS/DPF 8.4		
Development on sloping land (with a gradient exceeding 1 in 8) avoids the alteration of natural drainage lines and includes on site drainage systems to minimise erosion.	None are applicable.		
Residential Development - Low Rise			
Car parking, access and manoeuvrability			

Car parking, access and manoeuvrability

PO 23.3

Driveways and access points are located and designed to facilitate safe access and egress while maximising land available for street tree planting, domestic waste collection, landscaped street frontages and on-street parking.

DTS/DPF 23.3

Driveways and access points satisfy (a) or (b):

- (a) sites with a frontage to a public road of 10m or less, have a width between 3.0 and 3.2 metres measured at the property boundary and are the only access point provided on the site
- (b) sites with a frontage to a public road greater than 10m:
 - have a maximum width of 5m measured at the property boundary and are the only access point provided on the site;
 - (ii) have a width between 3.0 metres and 3.2 metres measured at the property boundary and

Page 10 of 12 Printed on 19/09/2022

	no more than two access points are provided on site, separated by no less than 1m.
PO 23.4	DTS/DPF 23.4
Vehicle access is safe, convenient, minimises interruption to the operation of public roads and does not interfere with street infrastructure or street trees.	Vehicle access to designated car parking spaces satisfy (a) or (b): (a) is provided via a lawfully existing or authorised access point or an access point for which consent has been granted as part of an application for the division of land (b) where newly proposed, is set back: (i) 0.5m or more from any street furniture, street pole, infrastructure services pit, or other stormwater or utility infrastructure unless consent is provided from the asset owner (ii) 2m or more from the base of the trunk of a street tree unless consent is provided from the tree owner for a lesser distance (iii) 6m or more from the tangent point of an intersection of 2 or more roads (iv) outside of the marked lines or infrastructure dedicating a pedestrian crossing.
PO 23.5 Driveways are designed to enable safe and convenient vehicle movements from the public road to on-site parking spaces.	DTS/DPF 23.5 Driveways are designed and sited so that: (a) the gradient from the place of access on the boundary of the allotment to the finished floor level at the front of the garage or carport is not steeper than 1-in-4 on average (b) they are aligned relative to the street so that there is no more than a 20 degree deviation from 90 degrees between the centreline of any dedicated car parking space to which it provides access (measured from the front of that space) and the road boundary. (c) if located so as to provide access from an alley, lane or right of way - the alley, lane or right or way is at least 6.2m wide along the boundary of the allotment / site

Infrastructure and Renewable Energy Facilities

Assessment Provisions (AP)

	Desired Outcome
DO 1	Efficient provision of infrastructure networks and services, renewable energy facilities and ancillary development in a manner that minimises hazard, is environmentally and culturally sensitive and manages adverse visual impacts on natural and rural landscapes and residential amenity.

Performance Outcomes (PO) and Deemed-to-Satisfy (DTS) Criteria / Designated Performance Feature (DPF)

Performance Outcome	Deemed-to-Satisfy Criteria /
	Designated Performance

Page 11 of 12 Printed on 19/09/2022

	Feature
Wastewater Services	
PO 12.2	DTS/DPF 12.2
Effluent drainage fields and other wastewater disposal areas are maintained to ensure the effective operation of waste systems and minimise risks to human health and the environment.	Development is not built on, or encroaches within, an area that is, or will be, required for a sewerage system or waste control system.

Page 12 of 12 Printed on 19/09/2022